





# ISO/IEC17025 Accredited Lab.

Report No: FCC0704092 File reference No: 2007-04-28

Applicant: The Ant Commandos, Inc

Product: Wireless Shredder Guitar

Model No: SHRD-WL-SBBL

Brand Name: TAC

Test Standards: FCC Part 15 Subpart C, Paragraph 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: April 28, 2007

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 0704092 Page 2 of 44

Date: 2007-04-28



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

#### **CNAL-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

# FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

# **IC- Registration No.: IC5205**

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205.

Page 3 of 44

Report No: 0704092 Date: 2007-04-28



# **Test Report Conclusion** Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration	4
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment	5
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition	8
5.5	Conducted Emission Limit.	8
5.6	Test Result	8
6.0	Radiated Emission test	14
6.1	Test Method and Test Procedure.	14
6.2	Configuration of the EUT	14
6.3	EUT Operation Condition.	14
6.4	Radiated Emission Limit	14
6.5	Test Result.	14
7.0	Band Edge	27
7.1	Test Method and Test Procedure.	27
7.2	Radiated Test Setup	27
7.3	Configuration of the EUT	27
7.4	EUT Operating Condition	27
7.5	Band Edge Limit	28
7.6	Band Edge Test Result.	28
8.0	FCC ID Label	33
9.0	Photo of Test Setup and EUT View	34

Date: 2007-04-28



#### 1.0 General Details

#### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205

For 3m & 10 m OATS

#### 1.2 Applicant Details

Applicant: The Ant Commandos, Inc

Address: 3633 Inland Empire Blvd, Suite 670, Ca, Ontario, 91764, USA

Telephone: 1-909-461-0965 Fax: 1-909-466-9886

# 1.3 Description of EUT

Product: Wireless Shredder Guitar Manufacturer: The Ant Commandos, Inc

Brand Name: TAC

Model Number: SHRD-WL-SBBL

Additional Model Name N/A
Additional Trade Name N/A

Rating: DC6.0V, 15mA-25mA

Modulation Type: GFSK

Operation Frequency 2400-2483.5MHz

Number of Channel 74

Antenna Designation A permanent fixed antenna, which is built-in, designed as an indispensable part of

the EUT.

#### 1.4 Submitted Sample

1 Sample

# 1.5 Test Duration

2007-04-20 to 2007-04-28

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 5 of 44

Report No: 0704092 Date: 2007-04-28



1.6 Test Uncertainty

Conducted Emissions Uncertainty =  $\pm 3.0 dB$ 

Radiated Emissions Uncertainty =  $\pm 6.0 dB$ 

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

2.0		Test Equi	pments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2006-12-06	2007-12-05
Absorbing Clamp	ROHDE&SCHWARZ	MDS-21	100126	2006-12-06	2007-12-05
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2006-12-06	2007-12-05
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2006-12-06	2007-12-05
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2006-12-06	2007-12-05
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2007-03-30	2008-03-29
4-WIRE ISN	ROHDE&SCHWARZ	ENY 41	830663/044	2007-02-19	2008-02-18
GG ENY22 Double 2-Wire ISN	ROHDE&SCHWARZ	ENY22	83066/016	2007-02-19	2008-02-18
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2007-02-19	2008-02-18
System Controller	: CT	SC100	-	2007-02-19	2008-02-18
Printer	EPSON	РНОТО ЕХЗ	CFNH234850	2007-02-19	2008-02-18
FM-AM Signal Generator	JUNGJIN	SG-150M	389911177	2007-02-19	2008-02-18
Color TV Pattern Generator	PHILIPS	PM5418	LO621747	2007-02-19	2008-02-18

Page 6 of 44

		THE STATE OF THE S			
Computer	IBM	8434	1S8434KCE99BLX LO*	-	-
Oscillator	KENWOOD	AG-203D	3070002	2007-02-23	2008-02-22
Spectrum Analyzer	HAMEG	HM5012	-	-	-
Power Supply	LW	APS1502	-	-	-
5K VA AC Power Source	California Instruments	5001iX	56060	2007-02-19	2008-02-18
CDN	EM TEST	CDN M2/M3	-	2007-02-19	2008-02-18
Attenuation	EM TEST	ATT6/75	-	2007-02-19	2008-02-18
Resistance	EM TEST	R100	-	2007-02-19	2008-02-18
Electromagnetic Injection Clamp	LITTHI	EM101	35708	2007-02-19	2008-02-18
Inductive Components	EM TEST	MC2630	-	2007-02-19	2008-02-18
Antenna	EM TEST	MS100	-	2007-02-19	2008-02-18
Signal Generator	ROHDE&SCHWARZ	SMT03	100029	2007-02-05	2008-02-04
Power Amplifier	AR	150W1000	300999	2007-02-05	2008-02-04
Field probe	Holaday	HI-6005	105152	2007-02-05	2008-02-04
Bilog Antenna	Chase	CBL6111C	2576	2007-02-05	2008-02-04
Loop Antenna	EMCO	6502	00042960	2007-02-05	2008-02-04
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2007-02-05	2008-02-04
3m OATS			N/A	2007-02-05	2008-02-04

Page 7 of 44

Report No: 0704092 Date: 2007-04-28



#### 3.0 Technical Details

# 3.1 Summary of test results

The EUT has been	n tested accordin	g to the following	specifications:
		A	, 50000

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.207	Conducted Emission Test	N/A	Not Applicable
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	PASS	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	PASS	Complies

#### 3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249


# 4.0 EUT Modification

No modification by Shenzhen Timeway Technology Consulting Co.,Ltd



#### 5. Power Line Conducted Emission Test

#### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

#### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2001. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2001.

#### Block diagram of Test setup



# 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2001. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

One channels are provided to the EUT

#### A. EUT

Device	Manufacturer	Model	FCC ID
Wireless Shredder	The Ant Commandos	SHRD-WL-SBL	U93GUITAR
Guitar			

#### B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

Page 9 of 44

Report No: 0704092 Date: 2007-04-28



# C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

#### 5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2001.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Eraguanay (MHz)	Class A Lir	nits (dB µ V)	Class B Limits (dB µ V)		
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

#### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Note: Due to DC power supply, this test item not conducted

Page 10 of 44

Report No: 0704092 Date: 2007-04-28



#### 6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2001. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2001.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "**QP**" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

# Block diagram of Test setup Distance = 3m Computer Pre -Amplifier EUT Turn-table Receiver

- 6.2 Configuration of The EUT

  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

Page 11 of 44

Report No: 0704092 Date: 2007-04-28



#### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

#### A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Ī	Fundamental Frequency	Field Strength of Fundamental (3m)			Field S	trength of Harmo	onics (3m)
	(MHz)	mV/m	dBuV/m		uV/m	dBu	V/m
	2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)

Note:

- 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

# B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage  $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT

Report No: 0704092 Page 12 of 44

Date: 2007-04-28



#### 6.5 Test result

#### **Fundamental & Harmonics Radiated Emission Data** $\mathbf{A}$

Product:	Wireless Shredder Guitar	Test Mode:	Low Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	6VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2409.965	69.8/50.6	Н	114/94	44.2/43.4
2409.965	75.7/55.5	V	114/94	38.3/38.5
4820		H/V	74/54	
7230		H/V	74/54	
9640		H/V	74/54	
12050		H/V	74/54	
14460		H/V	74/54	
16870		H/V	74/54	
19280		H/V	74/54	
21690		H/V	74/54	
24100		H/V	74/54	

Page 13 of 44

Product:	Wireless Shredder Guitar	Test Mode:	Middle Channel		
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃		
Test Voltage:	6VDC	Humidity:	56%		
Test Result:	Pass				

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2440.087	78.2/54.3	Н	114/94	35.8/39.7
2440.087	85.6/62.4	V	114/94	28.4/31.6
4880		H/V	74/54	
7320		H/V	74/54	
9760		H/V	74/54	
12200		H/V	74/54	
14640		H/V	74/54	
17080		H/V	74/54	
19520		H/V	74/54	
21960		H/V	74/54	
24400		H/V	74/54	

Page 14 of 44

Report No: 0704092 Date: 2007-04-28

Product:	Wireless Shredder Guitar	Test Mode:	High Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	6VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2469.136	81.1/56.9	Н	114/94	32.9/37.1
2469.136	87.9/62.8	V	114/94	26.1/31.2
4940		H/V	74/54	
7410		H/V	74/54	
9880		H/V	74/54	
12350		H/V	74/54	
14820		H/V	74/54	
17290		H/V	74/54	
19760		H/V	74/54	
22230		H/V	74/54	
24700		H/V	74/54	

Note: (1) PK= Peak, AV= Average


- (2) Emission Level = Reading Level + Probe Factor + Cable Loss.
- (3)Margin=Emission-Limits
- (4)According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) Due to measured PK value less than the AV limit, the measured AV value must be less than AV limit



# Test Figure above 1G

Low Channel

#### **Horizontal**




The report refers only to the sample tested and does not apply to the bulk.



# Low Channel

#### Vertical




The report refers only to the sample tested and does not apply to the bulk.



# **Middle Channel**

# Horizontal




The report refers only to the sample tested and does not apply to the bulk.



# **Middle Channel**

#### Vertical




The report refers only to the sample tested and does not apply to the bulk.



# **High Channel**

#### Horizontal



The report refers only to the sample tested and does not apply to the bulk.


Page 20 of 44

Report No: 0704092 Date: 2007-04-28



# **High Channel**

#### Vertical



The report refers only to the sample tested and does not apply to the bulk.

Page 21 of 44

Report No: 0704092 Date: 2007-04-28




# B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Mode: Low Channel


**Results:** Pass

Please refer to following diagram for individual



Report No: 0704092 Page 22 of 44

Date: 2007-04-28



**EUT** set Condition: Keep Tx transmitting

Mode: Low Channel

**Results: Pass** 

Please refer to following diagram for individual



Frequency (MHz)	Level@3m (dB $\mu$ V/m)	Antenna Polarity	Limit@3m (dB $\mu$ V/m)
809.981	41.95	V	46.00
575.762	40.46	V	46.00



# **General Radiated Emission Data** Radiated Emission In Horizontal (30MHz----1000MHz)

**EUT** set Condition: Keep Tx transmitting Mode: Middle Channel

**Results: Pass** 


589.820

260.001

364.007

Please refer to following diagram for individual

#### Radiated Emission Measurement



Η Η

Η

46.00

46.00

41.21

35.53

37.12

Report No: 0704092 Page 24 of 44

Date: 2007-04-28




# Radiated Emission In Horizontal (30MHz----1000MHz)

**EUT** set Condition: Keep Tx transmitting Mode: Middle Channel

**Results: Pass** 

Please refer to following diagram for individual



Report No: 0704092 Page 25 of 44

Date: 2007-04-28




EUT set Condition: Keep Tx transmitting

Mode: High Channel

**Results:** Pass

Please refer to following diagram for individual



Report No: 0704092 Page 26 of 44

Date: 2007-04-28




# Radiated Emission In Horizontal (30MHz----1000MHz)

**EUT** set Condition: Keep Tx transmitting

Mode: Low Channel

**Results: Pass** 

Please refer to following diagram for individual



Frequency (MHz)	Level@3m (dB $\mu$ V/m)	Antenna Polarity	Limit@3m (dB $\mu$ V/m)
809.976	40.08	V	46.00
589.815	39.21	V	46.00




# 7. Band Edge

#### 7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.4 –2001. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (5) The antenna polarization : Vertical polarization and Horizontal polarization.

#### 7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

# 7.3 Configuration of The EUT

Same as section 5.3 of this report

#### 7.4 EUT Operating Condition

Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No: 0704092 Page 28 of 44

Date: 2007-04-28



# 7.5 Band Edge Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50dB below that in the 100kHz, bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Page 29 of 44

Stop 2.415 GHz


Report No: 0704092 Date: 2007-04-28



# **7.6** Band Edge Test Result

Product:	Wireless Shredder Guitar	Test Mode:	Low Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	6VDC	Humidity:	56%
Test Result:	Pass	Detector	PK

#### **Test Figure:**



Date: 29.APR.2007 05:47:34

#### Note (Peak)

-120

Start 2.38 GHz

The band edge emission plot on the following first page shows 28.59dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of Low channel is 75.7dBuV/m (Peak), so the maximum field strength in restrict band is 75.7-28.59=47.11dBuV/m which is under 74dBuV/m limit.

3.5 MHz/

The report refers only to the sample tested and does not apply to the bulk.

Page 30 of 44


Report No: 0704092 Date: 2007-04-28



# **7.6** Band Edge Test Result

Product:	Wireless Shredder Guitar	Test Mode:	Low Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	6VDC	Humidity:	56%
Test Result:	Pass	Detector	AV

# **Test Figure:**



Date: 29.APR.2007 05:20:32

#### Note (Average):

The band edge emission plot on the following second page shows 13.39dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 is 55.5dBuV/m (Average), so the maximum field strength in restrict band is 55.5-13.39=42.11dBuV/m which is under 54dBuV/m limit.

The report refers only to the sample tested and does not apply to the bulk.

Page 31 of 44

Stop 2.52 GHz


Report No: 0704092 Date: 2007-04-28



#### **7.6** Band Edge Test Result

Product:	Wireless Shredder Guitar	Test Mode:	High Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	6VDC	Humidity:	56%
Test Result:	Pass	Detector	PK

#### **Test Figure:**



Date: 29.APR.2007 05:29:12

#### Note (Peak)

-120

Start 2.46 GHz

The band edge emission plot on the following first page shows 23.72dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 is 87.9dBuV/m (Peak), so the maximum field strength in restrict band is 87.9-23.72=64.18dBuV/m which is under 74dBuV/m limit.

6 MHz/

The report refers only to the sample tested and does not apply to the bulk.

Page 32 of 44


Report No: 0704092 Date: 2007-04-28



# **7.6** Band Edge Test Result

Product:	Wireless Shredder Guitar	Test Mode:	High Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	6VDC	Humidity:	56%
Test Result:	Pass	Detector	AV

# **Test Figure:**



Date: 29.APR.2007 05:36:14

#### Note (Average):

The band edge emission plot on the following second page shows 14.3dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 is 62.8dBuV/m (Average), so the maximum field strength in restrict band is 62.8-14.3=48.5dBuV/m which is under 54dBuV/m limit.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 0704092 Page 33 of 44

Date: 2007-04-28




#### 8.0 FCC ID Label

#### FCC ID: U93GUITAR

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### **Mark Location:**



Page 34 of 44

Report No: 0704092 Date: 2007-04-28



# Photo of testing

9.1 Conducted test View--N/A

9.2 Radiated emission test view



Page 35 of 44

Report No: 0704092 Date: 2007-04-28



#### 9.3 Photo for the EUT





Page 36 of 44






Page 37 of 44





Page 38 of 44






Page 39 of 44




Interior View




Page 40 of 44





Page 41 of 44






Page 42 of 44




Interior View



Page 43 of 44




Interior View



Page 44 of 44

Report No: 0704092 Date: 2007-04-28





-- End of the report--