KP337-TX BOM

| Date | : | 20-N | Iarch | -2007 |
|------|---|------|-------|-------|
|------|---|------|-------|-------|

| No. | Part No. | | Description | Qty | Location | Remark |
|-----|----------|------------|---|-----|---------------|--------|
| 1 | | Resistor | 240Ω 1/10W +-5% 0805 SMD | 1 | R3 | |
| 2 | | | 22KΩ 1/10W +-5% 0805 SMD | 2 | R2,R4 | |
| 3 | | | 47KΩ 1/10W +-5% 0805 SMD | 1 | R1 | |
| 4 | | | 430KΩ 1/10W +-5% 0805 SMD | 1 | R8 | |
| 5 | | Ceramic | 8pF NPO 0805 SMD | 1 | C2 | |
| 6 | | Capacitor | 3.3pF NPO 0805 SMD | 1 | C1 | |
| 7 | | Transistor | KTC3121 SOT-23 SMD | 1 | Q3 | |
| 8 | | | 8050D SOT-23 SMD | 2 | Q4,Q1 | |
| 9 | | Diode | LED 3mm Red 0805 SMD | 1 | D5 | |
| 10 | | | RLS4148 0805 SMD | 6 | D7~D8,D10~D13 | |
| 11 | | Coil | 2.5T 0.7X2.9X4.5-R-N | 1 | L2 | |
| 12 | | | 7.5T 0.7X2.9X7.5-L-N | 1 | L1 | _ |
| 13 | | | 45T 0.8X2.9X45-R-N | 1 | ANT | |
| 14 | | Switch | Tact swi TS-1187B 5.1mmX6.4mm | 7 | | |
| 15 | | | 6 Pos Swi Pitch 1.27mm SMD | 1 | | |
| 16 | | SAW Filter | 433MHz TO-39 | 1 | TX1 | |
| 17 | | Encode IC | PT2260- R4S SOP-16 | 1 | U1 | |
| 18 | | Battery | 3V 2032 | 1 | | |
| 19 | | Flat Cable | 6Pin 28mm Pitch 2mm | 1 | | |
| 20 | | Lead Wire | 35mm 7 X 0.8 Red | 1 | | · |
| 21 | | | 35mm 7 X 0.8 Black | 1 | | |
| 22 | | | 35mm 7 X 0.8 White | 1 | | |
| 23 | | PCB | 18.5X18.4mm 1mm,FR4,golden, Dauble Side | 1 | RF | |
| 24 | | | Ø45.8mm 1mm,FR4,golden, Dauble Side | 1 | KB | |
| 25 | | | Ø43.5mm 1mm,FR4,golden, Dauble Side | 1 | MB | |

KP337-TX BOM

| Date | e · 20-March-200/ | | | | |
|------|-------------------|--|---|--|--|
| | | | | | |
| | | | 1 | | |
| | | | 1 | | |

| 26 | Fiber W | asher 0.9 X 5.5 X | 10mm 1 | |
|----|---------|-------------------|--------|--|
| 27 | Battery | Plate Positive | 1 | |
| 28 | | Negative | 1 | |