4   FCC §2.1091, §15.407(f) & ISEDC RSS-102 - RF Exposure

4.1   Applicable Standards

According to FCC §15.247(i), §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* ($180/f^2$)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz
* = Plane-wave equivalent power density

Before equipment certification is granted, the procedure of ISED RSS-102 must be followed concerning the exposure of humans to RF field

According to ISED RSS-102 Issue 5:

2.5.2   Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz[6] and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

4.2   MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density
P = power input to antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna

4.3   FCC MPE Results

5.2GHz band:

Maximum average output power at antenna input terminal (dBm):	14.49
Maximum average output power at antenna input terminal (mW):	28.12
Prediction distance (cm):	20
Prediction frequency (MHz):	5200
Maximum Antenna Gain, typical (dBi):	3
Maximum Antenna Gain (numeric):	1.995
Power density of prediction frequency at 20.0 cm (mW/cm^2):	0.0112
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

5.8GHz band:

Maximum average output power at antenna input terminal (dBm):	13.23
Maximum average output power at antenna input terminal (mW):	21.04
Prediction distance (cm):	20
Prediction frequency (MHz):	5825
Maximum Antenna Gain, typical (dBi):	3
Maximum Antenna Gain (numeric):	1.995
Power density of prediction frequency at 20.0 cm (mW/cm^2):	0.0084
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

2.4GHz Bluetooth/BLE:

Maximum average output power at antenna input terminal (dBm):	10.52
Maximum average output power at antenna input terminal (mW):	11.272
Prediction distance (cm):	20
Prediction frequency (MHz):	2402
Maximum Antenna Gain, typical (dBi):	2
Maximum Antenna Gain (numeric):	1.585
Power density of prediction frequency at 40 cm (mW/cm^2):	0.0036
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

Multi Transmitter MPE Evaluation

$0.0112/1.0+0.0036/1.0 = 0.0148 \leq 1.0$

Conclusion

The device is compliant with the requirement MPE limit for uncontrolled exposure. All transceiver modules must be installed with a separation distance of no less than **20** cm from all persons.

4.4   RF exposure evaluation exemption for IC

5.2 GHz band: $14.49 + 3$ dBi $= 17.49$ dBm $< 1.31 \times 10^{-2} f^{0.6834} = 4.537$ W $= 36.57$ dBm

5.8 GHz band: $13.23 + 3$ dBi $= 16.23$ dBm $< 1.31 \times 10^{-2} f^{0.6834} = 4.903$ W $= 36.90$ dBm

2.4 GHz Bluetooth/BLE: $10.52 + 2$ dBi $= 12.52$ dBm $< 1.31 \times 10^{-2} f^{0.6834} = 2.676$ W $= 34.27$ dBm

Multi Transmitter MPE Evaluation

$0.056W(17.49$ dBm$) + 0.018W(12.52$ dBm$) = 0.074$ W < 2.676 W

Conclusion

Therefore the RF exposure is not required. All transceiver modules must be installed with a separation distance of no less than **20** cm from all persons.