



## ***Test Report for Part 15***

---

**Report number:** STD-FCC-06007

**Type of EUT:** 17" TFT LCD Monitor

**Model number:** GT170M

**Applicant:** GENESIS TECH CO., LTD.

**Applied standards:** FCC Part 15 Subpart B(Class B)

The above mentioned EUT had been tested by EMC Laboratory of Standard Engineering Company in order to confirm the compliance with the requirements of FCC rules and this test was executed in accordance with the measurement method specified in ANSI C63.4-2003

I hereby certify that the accuracy of test-data is true and correct with my best knowledge and belief. Also I prove this measurement was performed by qualified person.

***Date of tested:*** 2006-05-26

***Date of Issued:*** 2006-05-27

***Tested by:***   
SM Kim / Test Engineer

***Approved by:***   
SS Seo / Senior Researcher



# Contents

---

## **1. General information**

- 1.1 Product information
- 1.2 Client information

## **2. Information of EMC Laboratory**

## **3. Procedure of measurement**

- 3.1 Conducted emission
  - 3.1.1 Configuration of measurement
  - 3.1.2 Detector function selection and bandwidth
  - 3.1.3 Frequency range to be scanned
  - 3.1.4 Line impedance stabilization network (LISN)
- 3.2 Radiated emission
  - 3.2.1 Configuration of measurement
  - 3.2.2 Detector function selection and bandwidth
- 3.3 Method of calculation

## **4. Environment of measurement**

- 4.1 Condition of environment
- 4.2 Measurement uncertainty
- 4.3 List of Test equipments
- 4.4 List of peripherals and cables
- 4.5 Configuration of EUT
- 4.6 Rating and Physical Characteristics

## **5. Result of measurement**

- 5.1 Conducted emission
  - 5.1.1 Test data
  - 5.1.2 Result
- 5.2 Radiated emission
  - 5.2.1 Test data
  - 5.2.2 Result



## **6. Attachment**

- 6.1 Sample Label
- 6.2 Photographs of Set-up
- 6.3 Photographs of EUT
- 6.4 Conducted emission data
- 6.5 Block Diagram/Circuit
- 6.6 User's Manual





## 1. General Information

---

### 1.1 Product information

Description of EUT : 17" TFT LCD Monitor

Model number : GT170M

Specification : Adaptor Input : AC100-240V, 50/60Hz  
Adaptor Output : DC12V, 4.12A

Applied Standard : FCC Part 15 subpart B (Class B)

Test method : ANSI C63.4 - 2003

### 1.2 Client information

Applicant : GENESIS TECH CO., LTD.

Address : #611 C-dong, Woolim Lion's Valley 425, Cheongcheon- dong,  
Bupyeong-gu, Incheon Korea

Phone No. : +82-32-623-7900

Fax. No. : +82-32-623-7988

Contact person : JunHyeong Cho/Assistant Manager

Manufacturer : GENESIS TECH CO., LTD.

Address : #611 C-dong, Woolim Lion's Valley 425, Cheongcheon- dong,  
Bupyeong-gu, Incheon Korea

Phone No.: +82-32-623-7900

Fax. No.: +82-32-623-7988



## 2. Information of EMC Laboratory

---

### Name of test laboratory

Standard Engineering Co., Ltd.

### Location

377-11 Sinjang-Ri, Eumam-Myeon, Seosan-Si Chungnam, Korea

Phone No. : +82-41-663-9436~7

Fax. No. : +82-41-663-9434

### FCC Filing Number : 624439

### Environment of Laboratory

This location can keep accuracy in measuring more than anywhere because surrounding noise ambient is low and silent excellently to be suitable in EMI's measuring.

### Map



### 3. Procedure of measurement

---

#### 3.1 Conducted emissions

##### **3.1.1 Configuration of measurement**

This measurement executed in shield-room and EUT was tested on 0.8m height wooden table located on the floor with 0.1m distance from the reference ground plane.

EUT's rear part had a distance from VCP(Vertical Conducted Plane) with 0.4m length and LISN placed on the grounded plane with 1m distance from EUT's side part .

Excess power cord and cables fixed in bundle style of 30~40cm length with non-inductive material, and power line was connected to power source through LISN to detect maximum EMI without external RFI from aux. instruments.

For the measurement, 'H' scroll pattern was applied to the EUT with maximum resolution (1280x1024) in order to detect maximum electromagnetic disturbance from the EUT.

Measuring equipments and EUT confirmed that warming-up was performed during enough time and calibration of antenna as well as calibration of measuring equipment also completed beforehand.

This measurement was performed on condition of worst-case emission.

##### **3.1.2 Detector function selection and bandwidth**

During conducted emission measurement, a radio noise meter that has a CISPR quasi-peak detector with 10 kHz IF bandwidth of 6 dB was utilized.

##### **3.1.3 Frequency range to be scanned**

For conducted emissions measurement, frequency range of 150 kHz to 30 MHz included, was investigated.

##### **3.1.4 Line impedance stabilization network (LISN)**

A LISN with characteristics that conform to the requirements of ANSI C63.4-1992 was used for the measurement of conducted power-line radio noise; (50 micro-henries / 50 ohms). Chassis and earth-points for grounding of the LISN were earth-grounded.



## **3.2 Radiated Emissions**

### **3.2.1 Configuration of measurement**

Preliminary measurement was performed in 3 meter semi-anechoic chamber to detect correct EMI frequency. For detecting the EMI frequency in semi-anechoic chamber, TRILOG antenna used on 30-1000MHz band.

Final measurement was executed at 3 meters OATS(Open Area Test Site) using Quasi-peak detector and TRILOG antenna.

EUT was placed on 0.8m height wooden table located on the floor with 0.1m distance from the reference ground plane.

Excess power cord and other excess cables fixed in bundle style of 30~40cm length with non-inductive material to detect maximum EMI emission from EUT.

For the measurement, 'H' scroll pattern was applied to the EUT with maximum resolution (1280x1024) in order to detect maximum electromagnetic disturbance from the EUT.

Measuring equipments and EUT confirmed that warming-up was performed during enough time and calibration of antenna as well as calibration of measuring equipment also completed beforehand.

Measurement antenna height was varied 1 to 4 meters and set position in both horizontal and vertical plane to search maximum EMI emission frequency.

### **3.2.2 Detector function selection and bandwidth**

In radiated emissions measurement, a field strength meter that has a CISPR quasi-peak detector was used. The 6 dB bandwidth of the detector of instrument is 120 kHz over frequency range of 30 to 1000 MHz.

---

### **3.3 Method of Calculations**

#### **3.3.1 Unit of Conducted emission measurement**

Conducted Emission Test results for conducted emissions are reported in micro-volts.

#### **3.3.2 Unit of Radiated emission measurement**

Test results of radiated emissions measurement are reported in micro-volts per meter at the specific distance. Using the unit of dBuV on the test instrument, the indication unit was converted to field strength unit of uV/m as following method;

$$F (uV/m) = 10^{(R+CL+AF)/20} (uV/m)$$

F: Field Strength in uV/m, R: Meter Reading Level in dB(uV),

CL: Cable Loss from antenna to meter in dB,

AF: Antenna Factor of receiving antenna in dB(/m)

#### **Sample calculation (Radiated emission)**

Emission level is calculated as follows;

Emission Level(dBuV/m)

= Reading Level + Ant. Factor + Cable Loss – Amp Gain

Margin Level is calculated as follows;

Margin(dBuV) = Limit Level – Emission Level

Example) Standard limit = 40 dBuV/m,

Reading Level = 10 dBuV,

Ant. Factor = 15 dB,

Cable Loss= 1 dB

External Amp Gain= 0 dB

**Emission Level(dBuV/m) = 10 + 15 + 1 - 0 = 26 (dBuV/m)**

**Margin(dBuV) = 40 – 26 = 14 (dBuV)**



## 4. Environments of measurement

---

### 4.1 Conditions of environment

Shield room	Temperature	29 °C
	Humidity	38 %
	Pressure	1014 hPa
OATS	Temperature	26 °C
	Humidity	34 %
	Pressure	1014 hPa

### 4.2 Measurement uncertainty

All measurements, especially EUT's measurement includes uncertain level that can happen for the reason as following;

Variation of antenna factor by changes of height, center, polarization, directivity.

Uncertainty factor by change of measurement distance, site's imperfection.

Radiated emissions measurements:  $\pm 4$  dB

Power line conducted emission measurements:  $\pm 3$  dB

The measurement uncertainty describes the overall uncertainty of the given measured value during the operation of the EUT in the above mentioned way.

The measurement uncertainty was calculated in accordance with NAMAS NIS 81 : The treatment of uncertainty in EMC measurement.”

The measurement uncertainty was given with a confidence of 95%.


#### 4.3 List of Test equipments

Used	Equipment	Maker	Model No.	S/No.	Cal.due date.
<input checked="" type="checkbox"/>	EMI Test Receiver	Rhode & Schwarz	ESIB7	100119	05/24/2007
<input checked="" type="checkbox"/>	Spectrum Analyzer	ADVANTEST	R3132	130300485	09/15/2006
<input type="checkbox"/>	Artificial Mains	Rhode & Schwarz	ESH2-Z5	100064	09/22/2006
<input checked="" type="checkbox"/>	Artificial Mains	Rhode & Schwarz	ESH3-Z5	100204	09/22/2006
<input type="checkbox"/>	Signal Generator	Rhode & Schwarz	SML03	101003	01/27/2007
<input type="checkbox"/>	Absorbing Clamp	Rhode & Schwarz	MDS-21	100076	09/21/2006
<input checked="" type="checkbox"/>	TRILOG Antenna	Schwarzbeck	VULB9163	164	05/24/2007
<input type="checkbox"/>	2 Wire ISN	Rhode & Schwarz	ENY22	10086	N/A
<input type="checkbox"/>	4 Wire ISN	Rhode & Schwarz	ENY41	100095	N/A
<input checked="" type="checkbox"/>	Pulse Limiter	Rhode & Schwarz	ESH3-Z2	100137	N/A
<input type="checkbox"/>	Attenuator	Rhode & Schwarz	DNF	100041	N/A
<input type="checkbox"/>	Attenuator	Rhode & Schwarz	MDS-2	100274	N/A
<input type="checkbox"/>	Ferrite Clamp	Rhode & Schwarz	EZ-24	100002	N/A

#### 4.4 List of Peripherals & Cables

Used	Descriptions	Maker	Type	S/No.	Approval
<input checked="" type="checkbox"/>	Reference PC set	JOOYONTECH	JTET320	JT03ZAB01ZDC146	Class B CE/FCC MIC/VCCI
<input checked="" type="checkbox"/>	Reference Printer	EPSON	P730A	60H0187628	
<input type="checkbox"/>	Reference Printer	HP	Deskjet 540	US52M1B0NF	
<input type="checkbox"/>	DC Power Supply	HP	6574A	US36340515	CE
<input checked="" type="checkbox"/>	M/W Cable/2GHz 5m	H+Suhner	SF104/2x11BNC	14354	
<input type="checkbox"/>	M/W Cable/2GHz10m	“	“	14353	
<input type="checkbox"/>	M/W Cable/18GHz18m	“	SF104/2x11N	6025	
<input checked="" type="checkbox"/>	M/W Cable/18GHz18m	“	“	6026	
<input type="checkbox"/>	M/W Cable/18GHz10m	“	“	6027	
<input checked="" type="checkbox"/>	M/W Cable/2GHz43m	Thermax	MS-P400		
<input type="checkbox"/>	Color monitor/composit	Samsung	SCM-14		
<input type="checkbox"/>	Function Generator	HP	3311A	1244A25104	
<input type="checkbox"/>	CCD Color Camera	Sung Eun	PSS-C5327		

#### 4.5 Configuration of EUT



#### Used Peripherals

Descriptions	Maker	Type	S/No.	Remarks
EUT	GENESIS TECH CO., LTD	GT170M	N/A	
Adapter	LISHIN INTERNATIONAL	LSE0107A1240	B12018-A703	
PC	JOORYONTECH CO., LTD.	JTET320	JT03ZAB01ZDC146	
Mouse	DELL	MO56UD	337000527	
Key-board	DELL	SK-8100	3BH-1735	
Printer	EPSON	P730A	60H0187628	

#### 4.6 Rating and Physical Characteristics

Model	GT170M
Panel	17"
Resolution	1280 x 1024
Active area	338mm x 270mm
Pixel pitch	0.264mm x 0.264mm
Contrast	700:1
Brightness	300 cd/m <sup>2</sup>
Response time	8ms
Display colors	16.2 M
Viewing angle CR <sub>≥10</sub>	H:150°V:135°
H-Frequency	57~82 KHz
V-Frequency	55~77 Hz
Input signal	Analog / Digital
Video Input connector	15 pins D-Sub /DVI
Audio input connector	1 Stereo input
Built-in speakers	2 x 2 W
Maximum power cons.	<40 W
Stand-by power cons.	<5 W
Off mode power cons.	<2 W
Power supply for adapter	100 V-240 VAC 50/60Hz
Power supply for monitor	12 VDC 4.12 A
Power saving control	Yes
Atmosphere pressure	86kpa~104kpa
Storage temperature and humidity	-20°C~+55°C, 5%-95%
Operating temperature	5°C~40°C
Humidity	10%~85%
Unpacking dimension	393 x 150 x 390 mm
Packing dimension	455 x 165 x 440 mm
Net weight	4.8 kg
Gross weight	6.0 kg

## 5. Result of Measurement

### 5.1 Conducted Emission

#### 5.1.1 Test data

Frequency [MHz]	Line	Limit[dBuV]		Result[dBuV]		Factor [dB]	Margin[dBuV]	
		QP	AV	QP	AV		QP	AV
D-Sub Mode								
0.190	N	64.04	54.04	44.95	37.63	13.48	19.09	16.41
0.195	L	63.82	53.82	51.32	45.24	13.46	12.50	8.58
0.260	L	61.43	51.43	44.87	41.19	13.24	16.56	10.24
0.520	L	56.00	46.00	39.27	37.09	12.31	16.73	8.91
0.585	L	56.00	46.00	43.59	40.96	12.08	12.41	5.04
0.650	L	56.00	46.00	42.52	40.54	11.86	13.48	5.46
3.640	N	56.00	46.00	37.55	32.95	10.86	18.45	13.05
3.645	L	56.00	46.00	36.81	32.31	10.86	19.19	13.69
4.420	N	56.00	46.00	38.42	35.46	10.92	17.58	10.54
DVI Mode								
0.195	L	63.82	53.82	50.97	45.19	13.46	12.85	8.63
0.260	L	61.43	51.43	44.57	41.28	13.24	16.86	10.15
0.585	L	56.00	46.00	43.73	41.00	12.08	12.27	5.00
0.650	L	56.00	46.00	42.68	40.11	11.86	13.32	5.89
0.975	L	56.00	46.00	40.40	39.61	10.72	15.60	6.39
3.255	N	56.00	46.00	39.28	35.04	10.85	16.72	10.96
4.035	L	56.00	46.00	40.30	35.03	10.90	15.70	10.97
4.815	N	56.00	46.00	39.17	36.55	10.96	16.83	9.45

\* Detector function was set into Quasi-peak & Average mode.

\* Factor = LISN Factor + Cable loss + Pulse Limiter

#### 5.1.2 Result

Complied

## 5.2 Radiated Emission

### 5.2.1 Test data

Frequency [MHz]	Polarization [Ver/Hor]	Limit [dBuV/m]	Result [dBuV/m]	Factor [dB]	Margin [dBuV/m]
<b>D-Sub Mode</b>					
38.34	V	40.00	32.63	13.60	7.37
87.60	V	40.00	28.84	10.50	11.16
336.00	H	46.00	41.26	16.65	4.74
351.18	V	46.00	41.30	17.22	4.70
364.92	H	46.00	39.39	17.41	6.61
966.06	V	53.90	39.19	27.18	14.71
<b>DVI Mode</b>					
39.54	V	40.00	35.95	13.87	4.05
336.00	H	46.00	39.40	16.65	6.60
351.18	V	46.00	41.69	17.22	4.31
432.00	V	46.00	41.89	18.36	4.11
600.00	V	46.00	40.92	22.32	5.08
964.14	V	53.90	38.93	27.18	14.97

\* Detector function was set into Quasi-peak mode.

\* Factor = Antenna factor + Cable loss

\* External Amp Gain : 0 dB


### 5.2.1 Result

Complied



## 6. Attachments

### 6.1 Sample Label



Labeling Requirements per section 2.925 & 15.19

The label shown shall be permanently affixed at a conspicuous location on the device and be readily visible to the user at the time of purchase.



## 6.2 Photographs of Set-up

**Conducted emission test (Front)**



**Conducted emission test (Rear)**



**Radiated Emission (Front)**



**Radiated Emission (Rear)**





### 6.3 Photographs of EUT

**Front View**



### Rear View



**Inside View**






### Main Board Front




**Main Board Rear**






### Inverter Board Front



**Inverter Board Rear**





## 6.4 Data sheet of Conducted Emission


*Standard Engineering Co., Ltd.*

*Conducted Emission Measurement*

EUT: GT170M (D-Sub Mode)  
 Manufacturer: GENESIS TECH CO., LTD.  
 Operating Condition: Normal  
 Test Site: Shield Room  
 Operator: SM Kim  
 Test Specification: Conducted Emission Fcc Part 15 Subpart B / Class B  
 Comment: Phase N

### SCAN TABLE: "ZFCCCEB"

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	5.0 kHz	MaxPeak Average	1.0 ms	9 kHz	ESH3-Z2






**Standard Engineering Co., Ltd.**  
**Conducted Emission Measurement**

EUT: GT170M (D-Sub Mode)  
 Manufacturer: GENESIS TECH CO., LTD.  
 Operating Condition: Normal  
 Test Site: Shield Room  
 Operator: SM Kim  
 Test Specification: Conducted Emission Fcc Part 15 Subpart B / Class B  
 Comment: Phase L

**SCAN TABLE: "ZFCCCEB"**

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	5.0 kHz	MaxPeak Average	1.0 ms	9 kHz	ESH3-Z2




**Standard Engineering Co., Ltd.**  
**Conducted Emission Measurement**

EUT: GT170M (DVI Mode)  
 Manufacturer: GENESIS TECH CO., LTD.  
 Operating Condition: Normal  
 Test Site: Shield Room  
 Operator: SM Kim  
 Test Specification: Conducted Emission Fcc Part 15 Subpart B / Class B  
 Comment: Phase N

**SCAN TABLE: "ZFCCCEB"**

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	5.0 kHz	MaxPeak Average	1.0 ms	9 kHz	ESH3-Z2




**Standard Engineering Co., Ltd.**  
**Conducted Emission Measurement**

EUT: GT170M (DVI Mode)  
Manufacturer: GENESIS TECH CO., LTD.  
Operating Condition: Normal  
Test Site: Shield Room  
Operator: SM Kim  
Test Specification: Conducted Emission Fcc Part 15 Subpart B / Class B  
Comment: Phase L

**SCAN TABLE: "ZFCCCEB"**

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	5.0 kHz	MaxPeak Average	1.0 ms	9 kHz	ESH3-Z2





## **6.5 Block Diagram/Circuit**

**Attached**

---

## **6.6 User's Manual**

**Attached**

