FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to FCC §15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

   f = frequency in MHz;
 * = Plane-wave equivalent power density;

MPE Calculation

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm^2);
        P = power input to the antenna (in appropriate units, e.g., mW);
        G = power gain of the antenna in the direction of interest relative to an isotropic radiator
        R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm^2)	MPE Limit (mW/cm^2)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412	14	25.12	11.01	12.62	265	0.00036	1.0
802.11g	2412	14	25.12	9.37	8.65	265	0.00025	1.0
802.11n20	2412	14	25.12	9.57	9.06	265	0.00026	1.0
802.11n40	2422	14	25.12	10.07	10.16	265	0.00029	1.0

Note: The antenna has 14 dBi gain and needs to be installed professionally, the manufacture specified the minimum distance of 8.7 feet (265 cm) in the manual.

Result: The device meets FCC MPE limit at 8.7 feet distance.