

### 850 Body Towards Phantom Middle with GPRS

Date/Time: 2007-1-16 15:25:04

Electronics: DAE3 Sn536

Medium: 850 Body

Medium parameters used (interpolated):  $\sigma = 1.00$  mho/m;  $\epsilon_r = 53.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 GPRS Frequency: 836.6 MHz Duty Cycle: 1:4

Probe: ET3DV6 - SN1736 ConvF(6.45, 6.45, 6.45)

**Toward Phantom Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.120 mW/g

**Toward Phantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.0 V/m; Power Drift = 0.007 dB

Peak SAR (extrapolated) = 0.149 W/kg

**SAR(1 g) = 0.111 mW/g; SAR(10 g) = 0.077 mW/g**

Maximum value of SAR (measured) = 0.118 mW/g





Fig. 39 850 MHz CH190



**Fig. 40 Z-Scan at power reference point (850 MHz CH190)**

### 850 Body Towards Phantom Low with GPRS

Date/Time: 2007-1-16 15:53:39

Electronics: DAE3 Sn536

Medium: 850 Body

Medium parameters used (interpolated):  $\sigma = 1.00$  mho/m;  $\epsilon_r = 53.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 GPRS Frequency: 824.2 MHz Duty Cycle: 1:4

Probe: ET3DV6 - SN1736 ConvF(6.45, 6.45, 6.45)

**Toward Phantom Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.092 mW/g

**Toward Phantom Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.56 V/m; Power Drift = 0.114 dB

Peak SAR (extrapolated) = 0.117 W/kg

**SAR(1 g) = 0.086 mW/g; SAR(10 g) = 0.061 mW/g**

Maximum value of SAR (measured) = 0.093 mW/g





Fig. 41 850 MHz CH128



**Fig. 42 Z-Scan at power reference point (850 MHz CH128)**

### 850 Body Towards Ground High with GPRS

Date/Time: 2007-1-16 17:09:43

Electronics: DAE3 Sn536

Medium: 850 Body

Medium parameters used (interpolated):  $\sigma = 1.00$  mho/m;  $\epsilon_r = 53.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 GPRS Frequency: 848.8 MHz Duty Cycle: 1:4

Probe: ET3DV6 - SN1736 ConvF(6.45, 6.45, 6.45)

**Toward Ground High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.441 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.5 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 0.557 W/kg

**SAR(1 g) = 0.409 mW/g; SAR(10 g) = 0.287 mW/g**

Maximum value of SAR (measured) = 0.432 mW/g





Fig. 43 850 MHz CH251



**Fig. 44 Z-Scan at power reference point (850 MHz CH251)**

### 850 Body Towards Ground Middle with GPRS

Date/Time: 2007-1-16 16:40:35

Electronics: DAE3 Sn536

Medium: 850 Body

Medium parameters used (interpolated):  $\sigma = 1.00$  mho/m;  $\epsilon_r = 53.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 GPRS Frequency: 836.6 MHz Duty Cycle: 1:4

Probe: ET3DV6 - SN1736 ConvF(6.45, 6.45, 6.45)

**Toward Ground Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.317 mW/g

**Toward Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.3 V/m; Power Drift = 0.030 dB

Peak SAR (extrapolated) = 0.401 W/kg

**SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.210 mW/g**

Maximum value of SAR (measured) = 0.315 mW/g





Fig. 45 850 MHz CH190



**Fig. 46 Z-Scan at power reference point (850 MHz CH190)**



### 850 Body Towards Ground Low with GPRS

Date/Time: 2007-1-16 16:17:46

Electronics: DAE3 Sn536

Medium: 850 Body

Medium parameters used (interpolated):  $\sigma = 1.00$  mho/m;  $\epsilon_r = 53.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 GPRS Frequency: 824.2 MHz Duty Cycle: 1:4

Probe: ET3DV6 - SN1736 ConvF(6.45, 6.45, 6.45)

**Toward Ground Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.264 mW/g

**Toward Ground Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.9 V/m; Power Drift = 0.058 dB

Peak SAR (extrapolated) = 0.327 W/kg

**SAR(1 g) = 0.248 mW/g; SAR(10 g) = 0.177 mW/g**

Maximum value of SAR (measured) = 0.261 mW/g





Fig. 47 850 MHz CH128



**Fig. 48 Z-Scan at power reference point (850 MHz CH128)**

### 1900 Left Cheek High

Date/Time: 2007-1-17 08:43:52

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Cheek High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.308 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.8 V/m; Power Drift = -0.035 dB

Peak SAR (extrapolated) = 0.427 W/kg

**SAR(1 g) = 0.278 mW/g; SAR(10 g) = 0.164 mW/g**

Maximum value of SAR (measured) = 0.295 mW/g





Fig. 49 1900 MHz CH810



**Fig. 50 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Left Cheek Middle

Date/Time: 2007-1-17 08:57:52

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Cheek Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.250 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 0.314 W/kg

**SAR(1 g) = 0.215 mW/g; SAR(10 g) = 0.128 mW/g**

Maximum value of SAR (measured) = 0.229 mW/g





Fig. 51 1900 MHz CH661



**Fig. 52 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Left Cheek Low

Date/Time: 2007-1-17 09:11:52

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Cheek Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.154 mW/g

**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.24 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 0.199 W/kg

**SAR(1 g) = 0.133 mW/g; SAR(10 g) = 0.079 mW/g**

Maximum value of SAR (measured) = 0.140 mW/g





Fig. 53 1900 MHz CH512



**Fig. 54 Z-Scan at power reference point (1900 MHz CH512)**



### 1900 Left Tilt High

Date/Time: 2007-1-17 09:59:54

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Tilt High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.316 mW/g

**Tilt High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.5 V/m; Power Drift = -0.061 dB

Peak SAR (extrapolated) = 0.462 W/kg

**SAR(1 g) = 0.271 mW/g; SAR(10 g) = 0.152 mW/g**

Maximum value of SAR (measured) = 0.292 mW/g





Fig.55 1900 MHz CH810



**Fig. 56 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Left Tilt Middle

Date/Time: 2007-1-17 09:44:31

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Tilt Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.239 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.8 V/m; Power Drift = -0.105 dB

Peak SAR (extrapolated) = 0.353 W/kg

**SAR(1 g) = 0.206 mW/g; SAR(10 g) = 0.117 mW/g**

Maximum value of SAR (measured) = 0.225 mW/g





Fig.57 1900 MHz CH661



**Fig. 58 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Left Tilt Low

Date/Time: 2007-1-17 09:27:52

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Tilt Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.141 mW/g

**Tilt Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.82 V/m; Power Drift = 0.040 dB

Peak SAR (extrapolated) = 0.198 W/kg

**SAR(1 g) = 0.121 mW/g; SAR(10 g) = 0.069 mW/g**

Maximum value of SAR (measured) = 0.133 mW/g





Fig. 59 1900 MHz CH512



**Fig. 60 Z-Scan at power reference point (1900 MHz CH512)**

### 1900 Right Cheek High

Date/Time: 2007-1-17 10:08:50

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Cheek High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.292 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.9 V/m; Power Drift = -0.017 dB

Peak SAR (extrapolated) = 0.402 W/kg

**SAR(1 g) = 0.259 mW/g; SAR(10 g) = 0.154 mW/g**

Maximum value of SAR (measured) = 0.282 mW/g





Fig. 61 1900 MHz CH810



**Fig. 62 Z-Scan at power reference point (1900 MHz CH810)**



### 1900 Right Cheek Middle

Date/Time: 2007-1-17 10:25:49

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Cheek Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.233 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.8 V/m; Power Drift = -0.025 dB

Peak SAR (extrapolated) = 0.309 W/kg

**SAR(1 g) = 0.206 mW/g; SAR(10 g) = 0.123 mW/g**

Maximum value of SAR (measured) = 0.225 mW/g





Fig. 63 1900 MHz CH661



**Fig. 64 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Right Cheek Low

Date/Time: 2007-1-17 10:43:46

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Cheek Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.143 mW/g

**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.86 V/m; Power Drift = 0.030 dB

Peak SAR (extrapolated) = 0.196 W/kg

**SAR(1 g) = 0.130 mW/g; SAR(10 g) = 0.079 mW/g**

Maximum value of SAR (measured) = 0.138 mW/g





Fig. 65 1900 MHz CH512



**Fig. 66 Z-Scan at power reference point (1900 MHz CH512)**

### 1900 Right Tilt High

Date/Time: 2007-1-16 11:39:21

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Tilt High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.332 mW/g

**Tilt High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.7 V/m; Power Drift = -0.183 dB

Peak SAR (extrapolated) = 0.472 W/kg

**SAR(1 g) = 0.280 mW/g; SAR(10 g) = 0.158 mW/g**

Maximum value of SAR (measured) = 0.306 mW/g





Fig. 67 1900 MHz CH810



**Fig. 68 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Right Tilt Middle

Date/Time: 2007-1-17 11:18:46

Electronics: DAE3 Sn536

Medium: 1900 Head

Medium parameters used:  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(5.4, 5.4, 5.4)

**Tilt Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.323 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.7 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 0.514 W/kg

**SAR(1 g) = 0.282 mW/g; SAR(10 g) = 0.156 mW/g**

Maximum value of SAR (measured) = 0.304 mW/g




Fig.69 1900 MHz CH661