



# **RADIO TEST REPORT**

**Test Report No. : 10636726H-H-R2**

**Applicant** : **Panasonic Mobile Communications Development of Europe Ltd**

**Type of Equipment** : **Digital Camera**

**Model No.** : **DMC-CM1**

**FCC ID** : **UCE314062A**

**Test regulation** : **FCC Part 15 Subpart E: 2015 (DFS test only)**


**Test Result** : **Complied**

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
7. This report is a revised version of 10636726H-H-R1. 10636726H-H-R1 is replaced with this report.

**Date of test:**

February 9, 2015

**Representative test engineer:**

  
Kazuya Yoshioka  
Engineer

Consumer Technology Division

**Approved by:**

  
Takayuki Shimada  
Engineer

Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address,  
<http://www.ul.com/japan/jpn/pages/services/emc/about/mark1/index.jsp#nvlap>

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429

Facsimile : +81 596 24 8124

<b><u>CONTENTS</u></b>	<b><u>PAGE</u></b>
<b>SECTION 1: Customer information.....</b>	<b>4</b>
<b>SECTION 2: Equipment under test (E.U.T.).....</b>	<b>4</b>
<b>SECTION 3: Scope of Report.....</b>	<b>6</b>
<b>SECTION 4: Test specification, procedures &amp; results.....</b>	<b>6</b>
<b>SECTION 5: Operation of E.U.T. during testing.....</b>	<b>11</b>
<b>SECTION 6: Channel Move Time, Channel Closing Transmission Time.....</b>	<b>18</b>
<b>SECTION 7: Non-Occupancy Period .....</b>	<b>20</b>
<b>APPENDIX 1: Test instruments .....</b>	<b>22</b>
<b>APPENDIX 2: Photographs of test setup .....</b>	<b>23</b>

## **SECTION 1: Customer information**

Company Name	:	Panasonic Mobile Communications Development of Europe Ltd
Address	:	Willoughby Road, Bracknell Berkshire RG12 8FP, UK
Telephone Number	:	+44 (0) 1344 706774
Facsimile Number	:	+44 (0) 1344 706796
Contact Person	:	Andrew James

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment	:	Digital Camera
Model No.	:	DMC-CM1
Serial No.	:	Refer to Section 4, Clause 4.2
Rating	:	AC120V/60Hz (AC Adaptor) DC3.8V (Battery)
Receipt Date of Sample	:	January 7, 2015
Country of Mass-production	:	China
Condition of EUT	:	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT	:	No Modification by the test lab

### **2.2 Product Description**

#### **General Specification**

Power Supply (radio part input)	:	Cellular PA: 3.0V-4.2V (Depend on Battery voltage) Cellular other RF part: 1.3V, 1.8V, 2.05V, 2.7V (Regulated voltage) WLAN 5GHz Front-end module: 3.0V-4.2V (Depend on Battery voltage) WLAN/BT other RF part: 1.3V, 1.8V, 3.0V (Regulated voltage)
Clock frequency(ies) in the system	:	2.26GHz (Max) See below table for other clock frequencies

Frequency	Device
32.768kHz	MSM8974AB
32.768kHz (X'tal)	BUYD2206
27.0MHz	TC358764AXBG, XO2-256-64UCBGA, BUYD2206
48.0MHz (X'tal)	WCN3680
24.0MHz	MSM8974AB, Sub Camera
19.2MHz	WTR1625L, MSM8974AB
19.2MHz (X'tal)	PM8941
9.6MHz	WCD9320
72MHz	Main Camera
27.12MHz	NFC IC

Hardware / Software version	:	Rev. PR / QRCT Version 3.0.32.0
-----------------------------	---	---------------------------------

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Radio Specification

	IEEE802.11b	IEEE802.11g/n (20 M band)	IEEE802.11a/n/ac (20 M band)	IEEE802.11n/ac (40 M band)	IEEE802.11ac (80 M band)
Frequency of operation	2412-2462MHz	2412-2462MHz	5180-5240MHz 5260-5320MHz *1) 5500-5700MHz *1) 5745-5825MHz	5190-5230MHz 5270-5310MHz *1) 5510-5670MHz *1) 5755-5795MHz	5210MHz 5290MHz *1) 5530-5610MHz *1) 5775MHz
Type of modulation	DSSS (CCK, DQPSK, DBPSK)	OFDM-CCK (64QAM, 16QAM, QPSK, BPSK)	OFDM (64QAM, 16QAM, QPSK, BPSK)		OFDM (64QAM, 16QAM, QPSK, BPSK, 256QAM)
Channel spacing	5MHz		20MHz	40MHz	80MHz
Antenna type	Monopole				
Antenna Connector type	Spring type				
Antenna Gain	2.4GHz: -5.40dBi W52: -3.0dBi, W53: -3.5dBi, W56: -1.5dBi, W58: -1.8dBi				

\*1) 11a, 11n, 11ac (5260-5320MHz and 5500-5700MHz) are applied for this test report.

	Bluetooth Ver.4.0 with EDR function	GSM	W-CDMA	LTE
Frequency of operation	2402-2480MHz	[Up Link] GSM850: 824 – 849MHz PCS: 1850 – 1910MHz [Down Link] GSM850: 869 – 894MHz PCS: 1930 – 1990MHz	[Up Link] Band II: 1850 – 1910MHz Band IV: 1710 – 1755MHz Band V: 824 – 849MHz [Down Link] Band II: 1930 – 1990MHz Band IV: 2110 – 2155MHz Band V: 869 – 894MHz	[Up Link] Band II: 1850 – 1910MHz Band IV: 1710 – 1755MHz Band V: 824 – 849MHz Band VII: 2500 – 2570MHz Band X VII: 704 – 716MHz [Down Link] Band II: 1930 – 1990MHz Band IV: 2110 – 2155MHz Band V: 869 – 894MHz Band VII: 2620 – 2690MHz Band X VII: 734 – 746MHz
Type of modulation	BT: FHSS (GFSK, $\pi/4$ -DQPSK, 8-DPSK) LE: GFSK	GMSK, 8PSK	QPSK	QPSK, 16QAM
Channel spacing	BT: 1MHz LE: 2MHz	200kHz	200kHz	100kHz
Antenna type	Monopole	Monopole	Main: Monopole Sub: Monopole	
Antenna Connector type	Spring type	Spring type	Main: Spring type Sub: Spring type	
Antenna Gain	-5.40dBi	GSM850: -0.9dBi PCS: 0.5dBi	Band II: 0.5dBi Band IV: 0.6dBi Band V: -0.9dBi	Band II: 0.5dBi Band IV: 0.6dBi Band V: -0.9dBi Band VII: -0.2dBi Band X VII: -1.5dBi

	NFC	GPS/GLONASS
Frequency of operation	13.56MHz	GPS: 1575.42MHz GLONASS: 1597.55-1605.89MHz
Type of modulation	ASK	GPS: BPSK GLONASS: BPSK
Channel spacing	-	GLONASS: 0.5625MHz
Antenna type	Loop	Monopole
Antenna Connector type	Spring type	Spring type
Antenna Gain	N/A	-2.9dBi

\*This test report applies for WLAN (IEEE802.11a/11n-20/11n-40/11ac-20/11ac-40/11ac-80 [5GHz band]).

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### **SECTION 3: Scope of Report**

This report only covers DFS requirement, as specified by the following referenced procedures.

### **SECTION 4: Test specification, procedures & results**

#### **4.1 Test Specification**

Test Specification	:	FCC Part 15 Subpart E: 2015, final revised on January 21, 2015
Title	:	FCC 47CFR Part15 Radio Frequency Device Subpart E Unlicensed National Information Infrastructure Devices Section 15.407 General technical requirements
Test Specification	:	KDB905462 D02 UNII DFS Compliance Procedures New Rules v01r01
Title	:	COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED- NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN THE 5250-5350MHz AND 5470-5725MHz BANDS INCORPORATING DYNAMIC FREQUENCY SELECTION
Test Specification	:	KDB905462 D03 Client Without DFS New Rules v01r01
Title	:	U-NII CLIENT DEVICES WITHOUT RADAR DETECTION CAPABILITY

#### **FCC 15.31 (e)**

The EUT is a battery-operated device and test was performed with the full-charged battery.  
During the test, the battery was charged from AC Adaptor.  
Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

## 4.2 Procedures and results

**Table 1: Applicability of DFS Requirements**

Requirement	Operating Mode	Test Procedures & Limits	Deviation	Results
	Client without Radar Detection			
U-NII Detection Bandwidth	Not required	KDB905462 D02 UNII DFS Compliance Procedures New Rules v01r01	N/A	N/A
Initial Channel Availability Check Time	Not required	FCC15.407 (h)	N/A	N/A
		KDB905462 D02 UNII DFS Compliance Procedures New Rules v01r01		
		RSS-210 A9.3		
Radar Burst at the Beginning of the Channel Availability Check Time	Not required	FCC15.407 (h)	N/A	N/A
		KDB905462 D02 UNII DFS Compliance Procedures New Rules v01r01		
		RSS-210 A9.3		
Radar Burst at the End of the Channel Availability Check Time	Not required	FCC15.407 (h)	N/A	N/A
		KDB905462 D02 UNII DFS Compliance Procedures New Rules v01r01		
		RSS-210 A9.3		
In-Service Monitoring for Channel Move Time, Channel Closing Transmission Time	Yes	FCC15.407 (h)	N/A	Complied
		KDB905462 D02 UNII DFS Compliance Procedures New Rules v01r01		
		RSS-210 A9.3		
In-Service Monitoring for Non-Occupancy period	Yes	FCC15.407 (h)	N/A	Complied
		KDB905462 D02 UNII DFS Compliance Procedures New Rules v01r01		
		RSS-210 A9.3		
Statistical Performance Check	Not required	FCC15.407 (h)	N/A	N/A
		KDB905462 D02 UNII DFS Compliance Procedures New Rules v01r01		

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

**Table 2 DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection**

Maximum Transmit Power	Value (See Notes 1,2, and 3)
≥ 200 milliwatt	-64 dBm
< 200 milliwatt and power spectral density < 10dBm/MHz	-62 dBm
< 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
<p>Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.</p> <p>Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.</p> <p>Note 3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.</p>	

**Table 3 DFS Response Requirement Values**

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth See Note 3
<p><b>Note 1:</b> Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.</p> <p><b>Note 2:</b> The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signal will not count quiet periods in between transmissions.</p> <p><b>Note 3:</b> During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.</p>	

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124



**Table 4 Short Pulse Radar Test Waveform**

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A	Roundup $\{(1/360) * (19 * 10^6 / \text{PRI}_{\text{μsec}})\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Rader Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

**Table 5 Long Pulse Radar Test Waveform**

Radar Type	Pulse Width (μsec)	Chip Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Burst	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

**Table 6 Frequency Hopping Radar Test Waveform**

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulse per Hop (kHz)	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Number of Trials
6	1	333	9	0.333	300	70%	30

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

#### 4.3 Test Location

UL Japan, Inc. Ise EMC Lab. \*NVLAP Lab. code: 200572-0  
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.0 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

#### 4.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.  
Time Measurement uncertainty for this test was: ( $\pm$ ) 0.012%

#### 4.5 Data of DFS test, Test instruments of DFS, Test set up

Refer to APPENDIX.

## **SECTION 5: Operation of E.U.T. during testing**

### **5.1 Operating Modes**

The EUT, which is a Client Device without Radar detection capability, operates over the 11a, 11n, 11ac (5260-5320MHz and 5500-5700MHz).

Power level of the EUT[dBm]

Band	Output Power (Min)	Output Power(Max)
W53	8.58	12.22
W56	8.51	12.13

\*Refer to 10636726H-C-R1, FCC Part 15E (FCC 15.407) report for other parts than DFS.

The channel-loading of approximately 17% or greater was used for testing, and its test data was transferred from the Master Device to the Client Device for all test configurations.

The EUT utilizes the 802.11ac, with 20MHz and 80MHzbandwidth.

The FCC ID for the Master Device used with EUT for DFS testing is LDK102087.

The rated output power of the Master unit is >200mW(23dBm). Therefore the required interference threshold level is -64 dBm. After correction for antenna gain and procedural adjustments, the required conducted threshold at the antenna port is  $-64 + 1 + 0 = -63.0$  dBm (threshold level + additional 1dB + antenna gain ).

It is impossible for users to change DFS control, because the DFS function is written on the firmware and users cannot access it.

The EUT was set by the software as follows:  
Software name & version: iPerf version 2.0.6

---

**UL Japan, Inc.**


**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## 5.2 Configuration and peripherals



■ : Standard Ferrite Core

### Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Digital Camera	DMC-CM1	004401221416072	Panasonic	EUT
B	Wireless LAN access point	AIR-CAP3702E-A-K9	FTX18227609	Cisco Systems	-
C	AC Adaptor	AA25480L	ALD02510FEW	Cisco Systems	-
D	Laptop PC	FMV-A8260	R8800679	FUJITSU	-
E	AC Adaptor	ADP-80NBA	10268063C	FUJITSU	-

### List of cables used

No.	Name	Length (m)	Shield	
			Cable	Connector
1	DC Cable	0.3	Unshielded	Unshielded
2	DC Cable	1.8	Unshielded	Unshielded
3	AC Cable	1.8	Unshielded	Unshielded
4	LAN Cable	1.0	Unshielded	Unshielded
5	DC Cable	1.9	Unshielded	Unshielded
6	AC Cable	1.8	Unshielded	Unshielded

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 5.3 Test and Measurement System

#### **SYSTEM OVERVIEW**

The measurement system is based on a conducted test method.


The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution. The short pulse types 0, 1, 2, 3, and 4, the long pulse type 5, and the frequency hopping type 6 parameters are randomized at run-time.

The signal monitoring equipment consists of a spectrum analyzer with the capacity to display 8001 bins on the horizontal axis. A time-domain resolution of 2 msec/bin is achievable with a 16 second sweep time, meeting the 10 seconds short pulse reporting criteria. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection. A time-domain resolution of 3 msec/bin is achievable with a 24 second sweep time, meeting the 22 second long pulse reporting criteria and allowing a minimum of 10 seconds after the end of the long pulse waveform.

#### **FREQUENCY HOPPING RADAR WAVEFORM GENERATING SUBSYSTEM**

The first 100 frequencies are selected out of the hopping sequence of the randomized 475 hop frequencies. Only a *Burst* that has the frequency falling within the receiver bandwidth of the tested U-NII device is selected among those frequencies. (Frequency-domain simulation). The radar waveform generated at the start time of the selected *Burst* (Time-domain simulation) is download to the Signal Generator. If all of the randomly selected 100 frequencies do not fall within the receiver bandwidth of the U-NII device, the radar waveform is not used for the test.

## CONDUCTED METHODS SYSTEM BLOCK DIAGRAM



## MEASUREMENT SYSTEM FREQUENCY REFERENCE

Lock the signal generator and the spectrum analyzer to the same reference sources as follows: Connect the 10MHz OUT on the signal generator to the 10MHz IN on the spectrum analyzer and set the spectrum analyzer 10MHz In to On.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SYSTEM CALIBRATION**

**Step 1:** Set the system as shown in Figure 3 of KDB905462 7.2.2.

**Step 2:** Adjust each attenuator to fulfill the following three conditions:

- WLAN can be communicated, and
- Rader detection threshold level is bigger than Client Device traffic level on the spectrum analyzer

**Step 3:** Terminate 50 ohm at B , C and D points, and connect the spectrum analyzer to the point A. (See the figure on page 14)

At the point A, adjust the signal generator and spectrum analyzer to the center frequency of the channel to be measured.

Download the applicable radar waveforms to the signal generator. Select the radar waveform, trigger a burst manually and measure the amplitude on the spectrum analyzer. Readjust the amplitude of the signal generator as required so that the peak level of the waveform is at a displayed level equal to the required or desired interference detection threshold.

Separate signal generator amplitude settings are determined as required for each radar type.

**Step 4:** Without changing any of the instrument settings, restore the system setting to Step 2 and adjust the Reference Level Offset of the spectrum analyzer to the level at Step 3.

By taking the above steps 1 to 4, the spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device.

See Clause 5.4 for Plots of Noise, Rader Waveforms, and WLAN signals.

5.4 Plots of Noise, Rader Waveforms, and WLAN signals

Test place

Report No.

Date

Temperature/ Humidity

Engineer

Mode

Ise EMC Lab. No.6 Semi Anechoic Chamber


10636726H

02/09/2015


21deg. C / 41% RH

Kazuya Yoshioka

11ac-20 / 11ac-80







## **SECTION 6: Channel Move Time, Channel Closing Transmission Time**

### **6.1 Test Procedure**

Transmit the data from the Master Device to the Client Device on the test Channel for the entire period of the test. The Radar Waveform generator sends a Burst of pulses for Radar Types 0 at levels defined , on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel for duration greater than 10 seconds.

### **6.2 Test data**

Test place	Ise EMC Lab. No.6 Semi Anechoic Chamber
Report No.	10636726H
Date	02/09/2015
Temperature/ Humidity	21deg. C / 41% RH
Engineer	Kazuya Yoshioka
Mode	11ac-20 / 11ac-80

#### **11ac-20**

Test Item	Unit	Measurement Time	Limit	Results
Channel Move Time *1)	[sec]	0.198	10.000	Pass
Channel Closing Transmission Time *2)	[msec]	0	60	Pass

\*1) Channel Move Time is calculated as follows:

(Channel Move Time) = (End of Transmission) - (End of Burst) = 3.330-3.132

\*2) Channel Closing Transmission Time is calculated from (End of Burst + 200msec) to (End of Burst + 10sec )

(Channel Closing Transmission Time) = (Number of analyzer bins showing transmission) × (dwell time per bin)  
= 0 × 2[msec]

#### **11ac-80**

Test Item	Unit	Measurement Time	Limit	Results
Channel Move Time *1)	[sec]	0.064	10.000	Pass
Channel Closing Transmission Time *2)	[msec]	0	60	Pass

\*1) Channel Move Time is calculated as follows:

(Channel Move Time) = (End of Transmission) - (End of Burst) = 4.554-4.490

\*2) Channel Closing Transmission Time is calculated from (End of Burst + 200msec) to (End of Burst + 10sec )

(Channel Closing Transmission Time) = (Number of analyzer bins showing transmission) × (dwell time per bin)  
= 0 × 2[msec]

**UL Japan, Inc.**

**Ise EMC Lab.**


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999


Facsimile : +81 596 24 8124

### Radar Type 0

#### 11ac-20




#### 11ac-80




Marker 1 : End of Burst , Marker 2 : End of Transmission

#### 11ac-20



#### 11ac-80



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 7: Non-Occupancy Period**

### **7.1 Test Procedure**

The following two tests are performed:

1) Transmit the data from the Master Device to the Client Device on the test Channel for the entire period of the test. The Radar Waveform generator sends a Burst of pulses for Radar Types 0 at levels defined on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors. Observe the transmissions of the EUT after the Channel Move Time on the Operating Channel for duration greater than 30 minutes.

2) Transmit the data from the Master Device to the Client Device on the test Channel for the entire period of the test. Observe the transmissions of the EUT on the Operating Channel for duration greater than 30 minutes after the Master Device is shut off.

\* This product is client device in DFS band. Two client devices cannot communicate directly with each other.

---

**UL Japan, Inc.**

**Ise EMC Lab.**


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## 7.2 Test data

Test place	Ise EMC Lab. No.6 Semi Anechoic Chamber
Report No.	10636726H
Date	02/09/2015
Temperature/ Humidity	21deg. C / 41% RH
Engineer	Kazuya Yoshioka
Mode	11ac-20 Tx / 11ac-80 Tx



## **APPENDIX 1: Test instruments**

### **EMI Test Equipment**

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MSA-13	Spectrum Analyzer	Agilent	E4440A	MY46185823	DFS	2014/06/06 * 12
MCC-137	Microwave cable	HUBER+SUHNER	SUCOFLEX 102	37954/2	DFS	2014/10/02 * 12
MCC-95	Microwave Cable 1G-40GHz	Suhner	SUCOFLEX102	30816/2	DFS	2014/05/16 * 12
MCC-96	Microwave Cable 1G-40GHz	Suhner	SUCOFLEX102	30817/2	DFS	2014/05/16 * 12
MCC-97	Microwave Cable 1G-40GHz	Suhner	SUCOFLEX102	30818/2	DFS	2014/05/16 * 12
MCC-138	Microwave cable	HUBER+SUHNER	SUCOFLEX 102	37953/2	DFS	2014/10/02 * 12
MAT-24	Attenuator(10dB)(above 1GHz)	Agilent	8493C	71389	DFS	2014/06/12 * 12
MAT-57	Attenuator(10dB)	Suhner	6810.19.A	-	DFS	2015/01/08 * 12
MAT-57	Attenuator(10dB)	Suhner	6810.19.A	-	DFS	2015/01/08 * 12
MAT-61	Attenuator(20dB)	Suhner	6820.19.A	-	DFS	Pre Check
MAT-59	Attenuator(20dB)	Suhner	6820.19.A	-	DFS	Pre Check
EST-48 *1)	Signal Generator	Agilent	E4438C	MY45090353	DFS	2014/12/19 * 12
COTS-MDFS-01	Signal Studio Software for DFS	Agilent	N7620A-101	5010-7739	DFS	-
MPD-01	PowerDivider DC to 26.5GHz	Agilent	11636B	52258	DFS	2014/03/24 * 12
MPSC-04	Power Splitters/Combiners	Mini-Circuit	ZFSC-2-10G	0326	DFS	2014/09/26 * 12

**\*1) Signal generator is only used to generate radar test signal, and the wave form is confirmed with spectrum analyzer every time before the test.**

**The expiration date of the calibration is the end of the expired month.**

**All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.**

**As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.**

**DFS: Dynamic Frequency Selection**

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124