NF-TA-R080011

NEX1 Future Co., Ltd.

FCC TEST REPORT

The Reputation of LG Defense Industry Continues with NEX1 Future.

Locations & Offices



April 22, 2008

NEX 1 Future Co., Ltd.



NF-TA-R080011

NEX1 Future Co., Ltd.

TEST REPORT CERTIFICATION

Applicant : Dreamtech Co., Ltd.

Address : 340-4, Yangdang-ri, jiksan-eup, Cheonan, Chungnam, 330-810,

Korea

EUT Name : Mono Headset

Model No. : DT100

Serial No. : Engineering Sample

FCCID : UD5DT100

Testing location : Nex1 Future Co., Ltd.

133, Kongdan-Dong, Gumi-City, Kyeongsangbuk-Do, 730-030, R.O.K

Applied : FCC Part 15

specification

Test result : The above mentioned test item passed.

Test Date April 22, 2008 Review Date April 22, 2008

Tested by Hyo-Jeung, Cho Reviewed by Jeong-Hi, Jin

Title Engineer Title EMC Manager

Signature // Signature

I HEREBY CERTIFY THAT the data shown in this report were made in accordance with the procedures given in the applied specification and I assume full responsibility for accuracy and completeness of these data.

Note: This test report relates to the a.m. test item. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products.



NF-TA-R080011

NEX1 Future Co., Ltd.

Contents

1. GENERAL INFORMATION	5
1.1 Product Description	5
1.2 Project data	5
1.3 APPLICANT	5
1.4 Manufacturer	5
2. EUT INFORMATION	6
2.1 GENERAL EUT INFORMATION	6
2.2 CENTER FREQUENCY OF TESTED CHANNEL	6
2.3 Test Environment	6
2.4 ACCESSORIES AND ANCILLARY EQUIPMENT	6
3. TESTING FACILITIES	7
4. EUT DESCRIPTION AND OPERATIONAL DESCRIPTION	7
5. Test Set-up	8
5.1 PRINCIPLE OF CONFIGURATION	8
5.2 OPERATIONAL MODES	8
5.3 APPLIED SPECIFICATION	8
6. TEST REPORT SUMMARY	9
7. TEST RESULTS	10
7.1 ANTENNA CONNECTOR REQUIREMENTS	10
7.2 AC CONNECTED EMISSION	11
7.3 CARRIER FREQUENCY SEPARATION	12
7.4 TIME OF OCCUPANCY(DWELL TIME)	14
7.5 20dB Bandwidth	16
7.6 NUMBER OF HOPPING FREQUENCIES REQUIREMENTS	20
7.7 PSEUDORANDOM FHS AND EQUAL HOPPING FREQUENCY USE REQUIREMENTS	22
7.8 RECEIVER INPUT BANDWIDTH REQUIREMENTS	23



NF-TA-R080011

NEX1 Future Co., Ltd.

7.9 PEAK OUTPUT POWER	. 24
7.10 BAND-EDGE COMPLIANCE	. 28
7.11 FIELD STRENGTH MEASUREMENT FOR BAND-EDGE COMPLIANCE	. 31
7.12 Spurious Conducted emissions	. 36
7.13 Spurious Radiated emissions	. 47
3. LIST OF TEST AND MEASUREMENT INSTRUMENTS	. 50
9. Notes	. 50



NF-TA-R080011

NEX1 Future Co., Ltd.

1. General Information

1.1 Product Description

Product Name : Mono Headset

Product ID : DT100
Serial No. : Prototype
FCC ID : UD5DT100

1.2 Project data

Receipt of EUT : April 10, 2008

Date of Test : April 22, 2008

Data of report : April 22, 2008

1.3 Applicant

Company Name : Dreamtech Co., Ltd.

Address : 340-4, Yangdang-ri, jiksan-eup, Cheonan, Chungnam,

330-810,Korea

Contact Person : Mr. JAE-HO KANG

1.4 Manufacturer

Company Name : Dreamtech Co., Ltd.

Address : 340-4, Yangdang-ri, jiksan-eup, Cheonan, Chungnam,

330-810.Korea

Contact Person : Mr. JAE-HO KANG



NF-TA-R080011

NEX1 Future Co., Ltd.

2. EUT Information

2.1 General EUT Information

Туре	Transmitter Receiver			
FCC Classification	FHSS Sequence Spread	FHSS Sequence Spread		
	Spectrum (FHSS) Spectrum (FHSS)			
Operating frequency range	2402 – 2480 MHz	2402 – 2480 MHz		
Bands of operation	2.400 - 2.4835 GHz	2.400 – 2.4835 GHz		
Number of Channels	79	79		
Channel Separation	1MHz	1MHz		
Type of Antenna	Chip Antenna	Chip Antenna		
Power Supply	DC 3.7 V Li-Polymer DC 3.7 V Li-Polymer			
	Battery	Battery		

2.2 Center Frequency of Tested Channel

Frequency	Tx (MHz)	Rx (MHz)
Lowest	2402	2402
Middle	2441	2441
Highest	2480	2480

2.3 Test Environment

Temperature	25°C		
Relative Humidity	30 ~ 60%		
DC Voltage	DC 3.7V		

2.4 Accessories and Ancillary Equipment

Equipment	Model No. Serial Number		Maker
Laptop PC	PS428L-OE142	30014068J	Toshiba



NF-TA-R080011

NEX1 Future Co., Ltd.

3. Testing Facilities

Nex1 Future Co., Ltd.

133, Kongdan-Dong, Gumi-City, Kyeongsangbuk-Do, 730-030, R.O.K

4. EUT Description and Operational Description

Your headset is compatible with most Bluetooth phones that are compliant with Bluetooth version 2.0 and support the headset and/or hands-free profile(s). Ensure that your phone has Bluetooth capability by visiting your phone manufacturer's web site.

2. Features

Item	Description
Bluetooth Specification	V2.0
Supported Profile	Handsfree /
	Headset profile
Power Control?	No
Normal operation during battery charging?	No
Serial Number if any	N/A
Hardware Version	VER 1.0
Software Version	VER 2.0
Voltage (Min, Nom , Max)	3.0, 3.7, 4.1
Temperature (Min, Nom , Max)	-10, 25, 50
Power supply Type	TA (100~240 VAC 50~60
	HZ 0.15A) DTH (5.0V
	DC)
Battery Type if any (ex. Lithium Ion)	Li-ion Battery Polymer
Antenna Gain (maximum)	-1 dBi
Antenna Type (ex. Surface mounting type)	PCB soldering type
LSP(Largest supported packet)?	DH5



NF-TA-R080011

NEX1 Future Co., Ltd.

5. Test Set-up

5.1 Principle of configuration

Conducted: The equipment under test (EUT) was configured with a temporary SMA Connector and EUT transmits the related packet type with PRBS 9 as payload.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes and test settings were adapted accordingly in reference to the instructions for use.

For details, please refer to the Operation mode in chapter 7.

5.2 Operational Modes

Page Scan, Inquiry Scan Hopping Mode Fixed mode (2402Mhz, 2441Mhz and 2480Mhz)

5.3 Applied Specification

FCC Part 15



NF-TA-R080011

NEX1 Future Co., Ltd.

6. Test Report Summary

Related	Test Cases	FCC Part	Result
Clause		Sections	(Note1)
7.1	Antenna Connector Requirements	15.203	С
		15.204	
7.2	AC Connected Emission	15.207	N/A
7.3	Carrier Frequency Separation	15.247	Pass
7.4	Time of Occupancy(Dwell time)	15.247	Pass
7.5	20dB Bandwidth	15.247	Pass
7.6	Number of Hopping Frequencies	15.247	С
	Requirements		
7.7	Pseudorandom Frequency Hopping	15.247	С
	Sequence and Equal Hopping		
	Frequency use Requirements		
7.8	Receiver Input Bandwidth	15.247	С
	Requirements		
7.9	Peak Output Power	15.247	Pass
7.10	Band-edge Compliance	15.247	Pass
7.11	Field Strength measurement	15.247	Pass
7.12	Spurious Conducted emissions	15.247	Pass
7.13	Spurious Radiated emissions	15.247	Pass

^{*} Note1: C: Complies, Pass: Passed, Fail : Failed and NA : Not Applicable



NF-TA-R080011

NEX1 Future Co., Ltd.

7. Test Results

7.1 Antenna Connector Requirements

Requirements

Subclause 15.203 and 15.204(c)

According to the Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. And according to the Part 15.204(c), only the antenna with which an intentional radiator is authorized may be used with the intentional radiator.

Test results

RESULT: Complies

The antenna is permanently attached on the PCB.

The EUT has a Printed Chip Antenna soldered to the circuit board.

For more information on the antenna:

Antenna gain : -1 dBi

Manufacturer : SE KWANG.
Model No. : SKQ601-0000AA

Type : Printed Chip Antenna



NF-TA-R080011

NEX1 Future Co., Ltd.

7.2 AC Connected Emission

Test Mode and conditions

The power is supplied by a DC 3.7 V Li-ion Polymer and EUT doesn't operate during charging.

Requirements

Subclause15.207(a)

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency of Emission (M	Conducted Limit (dBµV)		
Hz)	Quasi-peak	Average	
0.15-0.5	66-56*	56-46*	
0.5-5	56	46	
5-30	60	50	

^{*} Decreases with the logarithm of the frequency.

Test results

N/A



NF-TA-R080011

NEX1 Future Co., Ltd.

7.3 Carrier Frequency Separation

Test Mode and conditions

Mode of operation : Tx mode (hopping on), DH1 packet with PRBS9 payload

Measurement Method: Conducted

Detector : PK

Trace : Max hold

RBW/VBW : 100kHz/300kHz

Requirements

Subclause 15.247(a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

Test results


Reference frequency	Channel Separation	Limit	Results
(MHz)	(kHz)		
2441.000	996.0	Minimum of 25kHz or	Pass
		the 20dB bandwidth	



NF-TA-R080011

NEX1 Future Co., Ltd.

Carrier Frequency Separation Plot



Date: 13.APR.2008 11:46:45



NF-TA-R080011

NEX1 Future Co., Ltd.

7.4 Time of Occupancy(Dwell time)

Test Mode and conditions

Mode of operation : Hopping on , DH5 packet with PRBS9 payload

Measurement Method: Conducted

Detector : PK

Trace : Max hold RBW/VBW : 1MHz/3MHz

Requirements

Subclause 15.247(a)(1)(iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 75 hopping frequencies. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

Test results

The system makes 1600 hops per second or has a length of 625us.

Let take DH5 packet in worst case. A DH5 packet has 5 slots for transmitting and 1 slot for receiving. It means it can have maximum 266.67 (=1600/6) hops per second.

Therefore it has 3.38 hops(=266.67/79) per second for each channel.

And it has 106.81hops appearance for 31.6 seconds (= 0.4x79channels).


Length per	Number slots	Dwell Time	Limit	Results
slot(L)	(N)	(=L*N)		
2.928ms	106.81	312.73968ms	0.4 seconds	Pass



NF-TA-R080011

NEX1 Future Co., Ltd.

Time of Occupancy Plot



Date: 13.APR.2008 11:49:41



NF-TA-R080011

NEX1 Future Co., Ltd.

7.5 20dB Bandwidth

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz),

DH5 packet with PRBS9 payload

Measurement Method: Conducted

Detector : PK

Trace : Max hold

RBW/VBW : 30kHz/100kHz

Requirements Subclause 15.247(a)(1)

It is mentioned implicitly as the maximum 20dB bandwidth of the hopping channel is 1Mhz.

Test results


Operating frequency (MHz)	20dB Bandwidth (MHz)	Limit	Results
2402	0.936	< 1 Mhz	Pass
2441	0.924	< 1 Mhz	Pass
2480	0.936	< 1 Mhz	Pass



NF-TA-R080011

NEX1 Future Co., Ltd.

20dB Bandwidth Plot - 2402Mhz




Date: 13.APR.2008 11:52:35



NF-TA-R080011

NEX1 Future Co., Ltd.

20dB Bandwidth Plot - 2441Mhz




Date: 13.APR.2008 11:55:36



NF-TA-R080011

NEX1 Future Co., Ltd.

20dB Bandwidth Plot - 2480Mhz



Date: 13.APR.2008 11:57:17



NF-TA-R080011

NEX1 Future Co., Ltd.

7.6 Number of Hopping Frequencies Requirements

Test Mode and conditions

Mode of operation : Hopping, DH1 with PRBS9 payload

Measurement Method: Conducted

Detector : PK

Trace : Max hold

RBW/VBW : 100kHz/300kHz

Requirements 15.247(a)(1)(iii)

Frequency hopping systems in the 2400-2483.5 Mhz band shall use at least 15 non-overlapping Channels.

Test results


Operating frequency (MHz)	Number of Hopping	Limit	Results
2402~2480	79	≥ 15	Pass



NF-TA-R080011

NEX1 Future Co., Ltd.

Number of Hopping Frequencies Plot



Date: 13.APR.2008 11:58:57

NF-TA-R080011

NEX1 Future Co., Ltd.

7.7 Pseudorandom FHS and Equal Hopping Frequency use Requirements

Requirements


Subclause 15.247 (a)(1)

The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter.

<u>RESULT</u> Complies

The channel is represented by a pseudo-random hopping sequence hopping throug h the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. For details, refer to the figure 1. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto thehop frequencies.

The algorism in the Bluetooth specifications shows the each of its hoping channels Is used equally on average also.



< Figure 1 : Block diagram of hop selection kernel for 79 hop system >



NF-TA-R080011

NEX1 Future Co., Ltd.

7.8 Receiver Input Bandwidth Requirements

Requirements

Subclause 15.247 (a)(1)

The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in the synchronization with the transmitted signals.

<u>RESULT</u> Complies

The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth is indirectly verified during Bluetooth RF conformance testing.



NF-TA-R080011

NEX1 Future Co., Ltd.

7.9 Peak Output Power

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz),

DH1 packet with PRBS 9 payload

Measurement Method: Conducted

Detector : PK

Trace : Max hold RBW/VBW : 1MHz/3MHz

Requirements

Subclause 15.247(b)(1)

For frequency hopping systems operating in the 2400~2483.5 Mhz band employing at least 75hopping channels, the maximum output power of the intentional radiator shall not exceeded 1 watt.

Test results


Operating	Reading	Cable	Actual	Limit	Results
Frequency	(dBm)	attenuation	Value	(W)	
(MHz)		(dB)	(W)		
2402	-1.54	1.80	0.001061696	<1.0	Pass
2441	-1.36	1.83	0.001114300	<1.0	Pass
2480	-0.81	1.85	0.001270574	<1.0	Pass



NF-TA-R080011

NEX1 Future Co., Ltd.

Peak Output Power Plot - 2402




Date: 13.APR.2008 12:01:04



NF-TA-R080011

NEX1 Future Co., Ltd.

Peak Output Power Plot - 2441




Date: 13.APR.2008 12:01:40



NF-TA-R080011

NEX1 Future Co., Ltd.

Peak Output Power Plot - 2480



Date: 13.APR.2008 12:02:35



NF-TA-R080011

NEX1 Future Co., Ltd.

7.10 Band-edge Compliance

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet

Measurement Method: Conducted

Detector : PK

Trace : Max hold

RBW/VBW : 300kHz/1.0MHz

Requirements

Subclause 15.247(c)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100k Hz bandwidth within the band that contains the highest level of the desired power, b ased on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Test results

There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency.


Tx Frequency (MHz)	RF power outside 100kHz BW (MHz)	Limit	Results
2402	No peak above 20dB	20dB below	Pass
2480	No peak above 20dB	20dB below	Pass



NF-TA-R080011

NEX1 Future Co., Ltd.

Band-edge Compliance Plot - 2402




Date: 13.APR.2008 12:11:53



NF-TA-R080011

NEX1 Future Co., Ltd.

Band-edge Compliance Plot - 2480



Date: 13.APR.2008 12:15:50

NF-TA-R080011

NEX1 Future Co., Ltd.

7.11 Field Strength measurement for Band-edge Compliance

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2480MHz), DH1 packet

Trace : Max hold

Measurement Method : Radiated- Enclosure

Measurement Distance : 3m

RB/VB in Restricted band : 1 MHz/1MHz for Peak, 1MHz/10Hz for Average

RB/VB in Non-Restricted band : 100KHz/100KHz for Peak

Requirements Subclause 15.247(c)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100k Hz bandwidth within the band that contains the highest level of the desired power, b ased on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Test results


Frequ-	Polari	Corr.	Re	sult	L	imit	Mar	gin	Table	Ant.
ency	z-	Factor	(dBu	V/m)	(dBu	ıV/m)	(dB)		Angle	Height
(MHz)	ation	(dB)	Α	Р	Α	Р	Α	Р	(Deg.)	(m)
	(H/V)									
Operating frequency: 2402Mhz										
2390	V	16.1	42.22	54.52	54	74	11.78	19.48	150	1.4
2390	Н	16.1	42.25	54.57	54	74	11.75	19.43	230	1.2
Operating frequency: 2480Mhz										
2483.5	V	16.1	42.51	54.44	54	74	11.49	19.56	150	1.4
2483.5	Н	16.1	42.32	54.76	54	74	11.68	19.24	230	1.2



NF-TA-R080011

NEX1 Future Co., Ltd.

Band-edge emissions plot- 2402 (Vertical)






NF-TA-R080011

NEX1 Future Co., Ltd.

Band-edge emissions plot- 2402 (Horizontal)




Date: 22.APR.2008 00:01:16



NF-TA-R080011

NEX1 Future Co., Ltd.

Band-edge emissions plot- 2480 (Vertical)




Date: 22.APR.2008 00:19:32



NF-TA-R080011

NEX1 Future Co., Ltd.

Band-edge emissions plot- 2480 (Peak /Horizontal)



Date: 22.APR.2008 00:05:03



NF-TA-R080011

NEX1 Future Co., Ltd.

7.12 Spurious Conducted emissions

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet

Measurement Method: Conducted

Detector : PK

Trace : Max hold

RBW/VBW : 100kHz/300kHz

Requirements Subclause 15.247(c)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100k Hz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Test results

Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)			
Operating frequency : 2402MHz								
4795.66	-49.72	3.6	-46.12	-20.360	25.76			
9621.14	-56.01	4.6	-51.41	-20.360	31.05			
17100	-51.8	6.0	-45.8	-20.360	25.44			
24100	-50.48	6.7	-43.78	-20.360	23.42			



NF-TA-R080011

NEX1 Future Co., Ltd.

Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
	(Operating frequ	iency : 2441Mi	Hz	
4875.42	-50.89	3.6	-47.29	-20.010	27.28
7328.04	-55.13	4.6	-50.53	-20.010	30.52
17100	-52.21	6.0	-46.21	-20.010	26.2
24090	-49.8	6.7	-43.1	-20.010	23.09


Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
	(Operating frequ	iency : 2480Mi	Hz	
4955.18	-55.68	3.6	-52.08	-19.480	32.6
7447.68	-55.34	4.6	-50.74	-19.480	31.26
17100	-51.51	6.0	-45.51	-19.480	26.03
24030	-50.09	6.7	-43.39	-19.480	23.91



NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2402 (30MHz~10GHz)




Date: 13.APR.2008 12:20:02



NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2402 (10GHz~20GHz)




Date: 13.APR.2008 12:22:36

NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2402 (20GHz~25GHz)




Date: 13.APR.2008 12:26:27



NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2441 (30MHz~10GHz)




Date: 13.APR.2008 12:29:12



NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2441 (10GHz~20GHz)




Date: 13.APR.2008 12:35:17



NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2441 (20GHz~25GHz)




Date: 13.APR.2008 12:37:43



NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2480 (30MHz~10GHz)




Date: 13.APR.2008 12:40:51



NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2480 (10GHz~20GHz)




Date: 13.APR.2008 12:43:44



NF-TA-R080011

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2480 (20GHz~25GHz)



Date: 13.APR.2008 12:46:03



NF-TA-R080011

NEX1 Future Co., Ltd.

7.13 Spurious Radiated emissions

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz),

DH1 packet

Detector : PK

Trace : Max hold

Measurement Method : Radiated- Enclosure

Measurement Distance: 3m

Measurement BW : 1 MHz for $f \ge 1$ GHz, 100kHz for f < 1 GHz

Requirements

Subclause 15.247(c)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to Section 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency	Field strength	Field strength	Measurement
(MHz)	(microvolts/meter)	(dBμV/m)	distance
			(meters)
30-88	100**	$20*\log(100) = 40.0$	3
88-216	150**	$20*\log(150) = 43.5$	3
216-960	200	20*log(200) = 46.0	3
960-2500	500	$20*\log(500) = 54.0$	3

^{**} Except as provided in paragraph(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72Mhz, 76-88Mhz, 174-216Mhz or 470-806Mhz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241. According to section 15.35(b), on any frequency or frequencies above 1000 MHz the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurements are specified in this part, including emission measurements below



NF-TA-R080011

NEX1 Future Co., Ltd.

1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated

Test results

Frequ-	Polariz-	Corr.	Re	sult	Lir	nit	Ма	rgin	Table	Ant.
ency	ation	Factor	(dBu	V/m)	(dBuV	/m)	(d	B)	Angle	Height
(MHz)	(H/V)	(dB)	Α	Р	Α	Р	Α	Р	(Deg.)	(m)
			Inoroti	na fra	au on ov	. 240	L 2Mhz			
			operati	ng ned	quency	. 240			T	
4804	V	16.3	49.8	64.9	54	74	4.2	9.1	1.5	150
4804	Н	16.3	46.7	61.9	54	74	7.3	12.1	1.2	230

Frequ-	Polariz-	Corr.	Re	sult	Lir	mit	Ма	Margin		Ant.
ency	ation	Factor	(dBu	V/m)	(dBuV	/m)	(dB)		Angle	Height
(MHz)	(H/V)	(dB)	Α	Р	Α	Р	Α	Р	(Deg.)	(m)
		(Operati	ng fred	quency	: 244	1Mhz	•		
4882	V	16.4	48.9	635	54	74	5.1	10.5	1.5	150
4882	Н	16.4	46.1	60.8	54	74	7.9	13.2	1.3	230



NF-TA-R080011

NEX1 Future Co., Ltd.

Frequ- ency	Polariz- ation	Corr. Factor		sult V/m)	Lir (dBuV	mit /m)	Ma (d	rgin B)	Table Angle	Ant. Height
(MHz)	(H/V)	(dB)	A	P	A	P	Α	P	(Deg.)	(m)
		(Operati	ng free	quency	: 248	80Mhz			
4960	V	16.4	49.3	64.1	54	74	4.7	9.9	1.4	150
4960	Н	16.4	47.1	62.8	54	74	6.9	11.2	1.2	230

Note:

- 1. Remark "*" means that the emission frequency is produced by local oscillator.
- 2. Remark"- " means that the emission level is too low to be measured.
- 3. The measurement uncertainty of the radiated emission test is $\pm 3dB$
- 4. "A" and "P" mean average and peak measurement respectively.
- 5. There are no spurious emissions found between the lowest internal oscillating frequency and 30 MHz.



NF-TA-R080011

NEX1 Future Co., Ltd.

8. List of Test and Measurement Instruments

	Kind of Equipment	Туре	Manufacturer	S/N	Calibration	Expiration
					date	date
	EMI Test Receiver	ESI26	R/S	8340.0010.02	'07.07.23	'08.07.23
	Spectrum Analyzer	FSP30	R/S	1093.4495.30	'07.07.23	'08.07.23
	Tracking Generator	ESMI-B1	R/S	1033.3240.52	'07.07.23	'07.07.23
	Spectrum Analyzer	E4407B	HP	MY41310181	'07.05.22	'08.05.22
	LISN	3825/2	EMCO	9502-2334	'06.12.18	'07.12.18
	Turn Table	2081	EMCO		'07.01.24	'09.01.24
	Antenna Tower	1072-5	EMCO	9202-1651	'07.01.24	'09.01.24
	Positioning	1090	EMCO		'07.01.24	'09.01.24
	Controller					
	Signal Generator	2023	MARCONI	112246067	'07.04.24	'08.04.24
	10dB Attenuator	23-10-34	Weinschel co	BD4316	'07.04.25	'09.04.25
	10dB Attenuator	33-10-34	Weinschel co	BB9784	'07.04.25	'09.04.25
\boxtimes	Loop Antenna	6507	EMCO	9408-1327	'07.05.16	'09.05.16
	Antenna	3142	EMCO	9710-1220	'07.05.18	'09.05.18
	Antenna	3115	EMCO	9202-3820	'07.02.15	'09.02.15
	Antenna	3160-08	EMCO	1168	'07.02.16	'09.02.16
\boxtimes	Antenna	3160-09	EMCO	1304	'07.02.16	'09.02.16
\boxtimes	Amplifier	HP8447F	HP	3113A06911	'07.09.12	'08.09.12
\boxtimes	Amplifier	HP83006	HP	3104A00611	'07.09.12	'08.09.12
\boxtimes	Amplifier	HP8449B	HP	3008A00859	'07.09.12	'08.09.12

9. Notes

N/A