

# RF Test Report

Test in accordance with  
Federal Communications Commission(FCC)  
CFR TITLE 47, Parts 2, 22, 24  
&  
Industry Canada (IC), RSS-GEN, 132,133

Product Name : GSM/WCDMA Module

Model No. : SIM5360A

FCC : UDV-SIM5360A

IC : 8460A-SIM5360A

Applicant : Shanghai Simcom Ltd.

Address : Building A, SIM Technology Building No.633,  
Jinzhong Road, Changning Disdriect, Shanghai P.R.  
China

Date of Receipt : 2014-07-02

Test Date : 2014-07-02~2014-07-08

Issued Date : 2014-07-08

Report No. : UL15820140702FCC/IC30-2

Report Version : V1.0

**Notes:**

The test results only relate to these samples which have been tested.

Partly using this report will not be admitted unless been allowed by Unilab.

Unilab is only responsible for the complete report with the reported stamp of Unilab.

## Test Report Certification

Issued Date : 2014-07-08  
Report No. : UL20140702FCC/IC30

Product Name : GSM/WCDMA Module  
Applicant : Shanghai Simcom Ltd.  
Address : Building A, SIM Technology Building No.633, Jinzhong Road, Changning  
Disdriect, Shanghai P.R. China  
Manufacturer : Shanghai Simcom Ltd.  
Address : Building A, SIM Technology Building No.633, Jinzhong Road, Changning  
Disdriect, Shanghai P.R. China  
Model No. : SIM5360A  
EUT Voltage : MIN: 3.4V, NOR: 3.8V, MAX: 4.2V  
Brand Name : SIMCom  
FCC: UDV-SIM5360A  
IC: 8460A-SIM5360A  
Applicable Standard : ANSI/TIA-603-C-2004; FCC CFR Title 47 Part 2;  
FCC CFR Title 47 Part 22 Subpart H;  
FCC CFR Title 47 Part24 Subpart E;  
RSS-GEN Issue 2; Industry Canada RSS-132, Issue 3;  
Industry Canada RSS-133, Issue 6;  
Test Result : Complied  
Performed Location : Unilab (Shanghai) Co., Ltd.  
FCC 2.948 register number is 714465  
IC register number is 11025A-1  
No. 1350, Lianxi Rd. Pudong New District, Shanghai, China  
TEL: +86-21-50275125 FAX: +86-21-50275126


Documented By :

  
(Technical Engineer: Andy Wei)

Reviewed By :

  
(Senior Engineer: Forest Cao)

Approved By :

  
(Supervisor: Eva Wang)

## TABLE OF CONTENTS

SUMMARY OF TEST RESULT .....	5
1. General Information .....	6
1.1. EUT Description .....	6
1.2. Mode of Operation .....	7
1.3. Tested System Details .....	8
1.4. Configuration of Tested System.....	9
1.5. EUT Exercise Software .....	9
2. Technical Test.....	10
2.1. Test Environment .....	10
3. Peak Output Power .....	11
3.1. Test Equipment .....	11
3.2. Test Setup.....	11
3.3. Limit.....	12
3.4. Test Procedure .....	13
3.5. Uncertainty .....	13
3.6. Test Result .....	14
4. Occupied Bandwidth .....	19
4.1. Test Equipment .....	19
4.2. Test Setup .....	19
4.3. Limit.....	20
4.4. Test Procedure .....	20
4.5. Uncertainty .....	20
4.6. Test Result .....	21
5.Spurious Emission At Antenna Terminals (+/- 1MHz) .....	33
5.1. Test Equipment .....	33
5.2. Test Setup .....	33
5.3. Limit.....	34
5.4. Test Procedure .....	34
5.5. Uncertainty .....	34
5.6. Test Result .....	35
6.Spurious Emission.....	41
6.1. Test Equipment .....	41
6.2. Test Setup .....	42
6.3. Limit.....	43
6.4. Test Procedure .....	43
6.5. Uncertainty .....	44
6.6. Test Result .....	45
7. Frequency Stability Under Temperature & Voltage Variations.....	60
7.1. Test Equipment .....	60
7.2. Test Setup .....	60
7.3. Limit.....	61
7.4. Test Procedure .....	61
7.5. Uncertainty .....	61
7.6. Test Result .....	62
8. Peak to Average .....	68
8.1. Test Equipment .....	68
8.2. Test Setup .....	68
8.3. Limit.....	68
8.4. Test Procedure .....	68
8.5. Uncertainty .....	69
8.6. Test Result .....	69
9.Receiver Spurious Emission for RSS 132/133 .....	72

9.1. Test Equipment ..... 72

9.2. Test Setup ..... 72

9.3. Limit..... 73

9.4. Test Procedure ..... 73

9.5. Uncertainty ..... 74

9.6. Test Result ..... 74

10.Attachment ..... 98

## SUMMARY OF TEST RESULT

Report Section	SPECIFICATION		Description	Limit	Result
	FCC CFR 47	IC			
3	part2.1046	N/A	Conducted Output Power	N/A	PASS
3	part 22.913(a)(2)	RSS-132, 5.4	Effective Radiated Power	<7 Watts	PASS
3	part 24.232(c)	RSS-133, 6.4	Equivalent Isotropic Radiated Power	<2 Watts	PASS
4	part 2.1046	RSS-132, 5.2 RSS-133, 6.2 RSS-139, 6.2	Modulation Characteristic	N/A	PASS
4	part 2.1049 part 22.917(a) part 24.238(a)	RSS-GEN, 4.6	Occupied Bandwidth	N/A	PASS
5	part 2.1051 part 22.917(a) part 24.238(a)	RSS-132, 5.5 RSS-133, 6.5 RSS-139, 6.5	Band Edge Measurement	<43+10lg(P[Watts])	PASS
6	part 2.1051 part 22.917(a) part 24.238(a)	RSS-GEN, 4.9 RSS-132, 5.5 RSS-133, 6.5 RSS-139, 6.5	Conducted Spurious Emission	<43+10lg(P[Watts])	PASS
6	part 2.1053 part 22.917(a) part 24.238(a)	RSS-GEN, 4.9 RSS-132, 5.5 RSS-133, 6.5 RSS-139, 6.5	Field Strength of Spurious Radiation	<43+10lg(P[Watts])	PASS
7	part 2.1055 part 22.355 part 24.235	RSS-132, 5.3 RSS-133, 6.3 RSS-139, 6.3	Frequency Stability for Temperature & Voltage	<2.5 ppm	PASS
8	part 24.232(d)	RSS-133,6.4	Peak-to-Average	<13dB	PASS
9	/	RSS-132,5.6 RSS-133,6.6	Receiver Spurious Emission	See section 9.3	PASS

## 1.General Information

### 1.1. EUT Description

Product Name:	GSM/WCDMA Module
Model Name:	SIM5360A
Hardware Version:	V1.03
Software Version:	SIM5360A_V3.5
RF Exposure Environment:	Uncontrolled
<b>GSM/ EDGE</b>	
Support Band:	GSM850/PCS1900
GPRS Class:	12
Tx Frequency Range:	GSM 850: 824.2MHz to 848.8MHz PCS 1900: 1850.2MHz to 1909.8MHz
Rx Frequency Range:	GSM 850: 869.2MHz to 893.8MHz PCS 1900: 1930.2MHz to 1989.8MHz
Type of modulation:	GSM/GPRS for GMSK EDGE for 8PSK
Antenna Type:	Connector
Antenna Peak Gain:	GSM 850/PCS 1900: 1dBi
<b>WCDMA</b>	
Support Band:	WCDMA Band II
Tx Frequency Range:	WCDMA Band II : 1850MHz ~1910MHz
Rx Frequency Range:	WCDMA Band II : 1930MHz ~1990MHz
Type of modulation:	WCDMA(UMTS): QPSK
Antenna Type:	Connector
Antenna Peak Gain:	WCDMA Band II : 1dBi
Support Band:	WCDMA Band V
Tx Frequency Range:	WCDMA Band V: 824MHz ~849MHz
Rx Frequency Range:	WCDMA Band V: 869MHz ~894MHz
Type of modulation:	WCDMA(UMTS): QPSK
Antenna Type:	Connector
Antenna Peak Gain:	WCDMA Band V: 1dBi
<b>Component</b>	
AC Adapter:	Model Name:DSA-0131F-06 EU 12
	Input: AC 100-240V ~50/60Hz 0.3A
	Output: DC 6V/2.0A

## 1.2. Mode of Operation

Unilab has verified the construction and function in typical operation. EUT is inlink mode with base station emulator at maximum power level. All the test modes were carried out with the EUT in normal operation, which was shown in this test report is the worst test mode and defined as:

Test Mode		
Band	Radiated TCs	Conducted TCs
GSM 850	GSM Link EDGE 8 Link	GSM Link EDGE 8 Link
GSM1900	GSM Link EDGE 8 Link	GSM Link EDGE 8 Link
WCDMA Band V	RMC 12.2Kbps Link	RMC 12.2Kbps Link
WCDMA Band II	RMC 12.2Kbps Link	RMC 12.2Kbps Link

Note:

1. Regards to the frequency band operation: the lowest、middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. The maximum power levels are GSM for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA Band V and RMC 12.2Kbps mode for WCDMA Band II, only these modes were used for all tests.
3. For the ERP/EIRP and radiated emission test, every axis (X, Y, Z) was verified, and show the worst (Z axis) result on this report.

**The conducted power table is as follows:**

Conducted Power (Unit: dBm)						
Band	GSM 850			GSM 1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM (GMSK, 1 Tx slot) CS1	33.18	33.17	33.17	29.93	29.83	30.06
GPRS (GMSK, 1 Tx slot) CS1	33.17	33.15	33.14	29.88	29.81	29.77
GPRS (GMSK, 2 Tx slot) CS1	31.25	30.84	30.75	27.33	27.25	27.23
GPRS (GMSK, 3 Tx slot) CS1	28.35	28.44	28.51	26.37	26.45	24.50
GPRS (GMSK, 4 Tx slot) CS1	26.36	26.51	26.47	24.84	24.76	24.72
EDGE (8-PSK, 1 Tx slot) CS1	26.57	26.45	26.34	25.06	25.02	24.89
EDGE (8-PSK, 2 Tx slot) CS1	25.22	25.34	25.51	24.24	24.52	24.10
EDGE(8-PSK, 3 Tx slot) CS1	24.13	24.32	24.02	23.41	23.33	23.20
EDGE(8-PSK, 4 Tx slot) CS1	23.02	23.11	22.92	22.61	22.35	22.22

Band	WCDMA V			WCDMA II		
TX Channel	4132	4182	4233	9262	9400	9538
RX Channel	4357	4407	4458	9662	9800	9938
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2Kbps	23.38	23.02	23.53	22.70	22.77	22.70
AMC 12.2Kbps	23.31	23.11	23.05	22.64	22.53	22.58
HSDPA Subtest-1	23.34	22.96	23.42	22.28	22.36	22.19
HSDPA Subtest-2	22.42	22.31	22.45	21.42	21.38	22.21
HSDPA Subtest-3	21.54	21.43	22.03	21.22	21.37	22.19
HSDPA Subtest-4	21.58	21.49	21.31	21.28	21.43	21.56
HSUPA Subtest-1	23.23	23.31	23.57	22.54	22.32	22.45
HSUPA Subtest-2	22.89	22.78	22.72	21.68	21.58	21.89
HSUPA Subtest-3	21.56	21.62	21.35	21.45	21.65	22.28
HSUPA Subtest-4	21.68	21.59	21.46	21.43	21.58	21.66

### 1.3. Tested System Details


The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model	Serial No.	Power Cord
1 Agilent8960	Agilent	E5515C	GB46581718	N/A



**1.4. Configuration of Tested System**

Connection Diagram



**1.5. EUT Exercise Software**

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of all equipment.
3	EUT Communicate with E5515C, then select channel to test.

**2. Technical Test**

**2.1. Test Environment**

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	22
Humidity (%RH)	25-75	54
Barometric pressure (mbar)	860-1060	950-1000

### 3. Peak Output Power


#### 3.1. Test Equipment


Instrument	Manufacturer	Model	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	N9038A	MY51210142	2015.07.27
Radio Communication Tester	Agilent	E5515C	GB46581718	2014.10.24
Signal Generator	Agilent	N5183A	MY50140938	2015.01.03
Preamplifier	CEM	EM30180	3008A0245	2015.02.28
DC Power Supply	Agilent	6612C	MY43002989	2015.03.03
Bilog Antenna	Schwarzbeck	VULB9160	9160-3316	2015.07.19
VHF-UHF-Biconical Antenna	Schwarzbeck	VUBA9117	9117-263	2015.07.19
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-942	2015.07.19
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-943	2015.07.19

The measure equipment had been calibrated once a year.


#### 3.2. Test Setup

Conducted Power Measurement:





Radiated Spurious Measurement: above 1GHz



### 3.3. Limit

**For FCC Part 22.913(a)(2):**

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

**For FCC Part 24.232(c):**

The EIRP of mobile transmitters and auxiliary test transmitters must not exceed 2 Watts.

### 3.4. Test Procedure

#### **Conducted Power Measurement:**

- a. Place the EUT on a bench and set it in transmitting mode.
- b. Connect a low loss RF cable from the antenna port to a spectrum analyzer and E5515C by a Directional Couple.
- c. EUT Communicate with E5515C, then selects a channel for testing.
- d. Add a correction factor to the display of spectrum, and then test.

#### **Radiated Power Measurement:**

- a. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c. The output of the test antenna shall be connected to the measuring receiver.
- d. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h. The maximum signal level detected by the measuring receiver shall be noted.
- i. The transmitter shall be replaced by a substitution antenna.
- j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k. The substitution antenna shall be connected to a calibrated signal generator.
- l. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q. Test site anechoic chamber refer to ANSI C63.4: 2009.

### 3.5. Uncertainty

The measurement uncertainty is defined as for Conducted Power Measurement  $\pm 1.1$  dB,  
for Radiated Power Measurement  $\pm 3.1$  dB

### 3.6. Test Result

The following table shows the conducted power measured:

Table 1

GSM850				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)
GSM850 (GSM)	128(Low)	824.2	33.18	2.08
	189(Mid)	836.4	33.17	2.07
	251(High)	848.8	33.17	2.07
GSM850 (EDGE 8)	128(Low)	824.2	26.57	0.45
	189(Mid)	836.4	26.45	0.44
	251(High)	848.8	26.34	0.43

Table 2

GSM1900				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)
GSM1900 (GSM)	512(Low)	1850.2	29.93	0.98
	661(Mid)	1880.0	29.83	0.96
	810(High)	1909.8	30.06	1.01
GSM1900 (EDGE 8)	512(Low)	1850.2	25.06	0.32
	661(Mid)	1880.0	25.02	0.32
	810(High)	1909.8	24.89	0.31

Table 3

WCDMA				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)
WCDMA Band V	4132(Low)	826.4	22.70	0.19
	4182(Mid)	836.4	22.77	0.19
	4233(High)	846.6	22.70	0.19
WCDMA Band II	9262(Low)	1852.4	23.38	0.22
	9400(Mid)	1880.0	23.02	0.20
	9538(High)	1907.6	23.53	0.23

The following table shows the Radiated power measured :

GSM850 (GSM Link)

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	ERP (W)
Low Channel 128 (824.20MHz)						
824.2	H	39.38	3.83	-2.99	32.56	1.80
824.2	V	36.15	3.83	-2.99	29.33	0.86
Middle Channel 189 (836.40MHz)						
836.4	H	39.61	3.96	-3.04	32.61	1.82
836.4	V	36.43	3.96	-3.04	29.43	0.88
High Channel 251 (848.80MHz)						
848.8	H	39.49	3.97	-3.10	32.42	1.75
848.8	V	36.45	3.97	-3.10	29.38	0.87

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	ERP (W)
Low Channel 128 (824.20MHz)						
824.2	H	33.12	3.83	-2.99	26.30	0.43
824.2	V	31.48	3.83	-2.99	24.66	0.29
Middle Channel 189 (836.40MHz)						
836.4	H	33.12	3.96	-3.04	26.12	0.41
836.4	V	31.98	3.96	-3.04	24.98	0.31
High Channel 251 (848.80MHz)						
848.8	H	33.35	3.97	-3.10	26.28	0.42
848.8	V	31.58	3.97	-3.10	24.51	0.28

GSM1900 (GSM Link)

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	EIRP (W)
Low Channel 512(1850.20MHz)						
1850.2	H	33.78	6.26	10.40	29.64	0.92
1850.2	V	30.29	6.26	10.40	26.15	0.41
Middle Channel 661 (1880.00MHz)						
1880.0	H	34.11	6.19	10.43	29.87	0.97
1880.0	V	30.21	6.19	10.43	25.97	0.40
High Channel 810 (1909.80MHz)						
1909.8	H	34.03	6.15	10.44	29.74	0.94
1909.8	V	30.17	6.15	10.44	25.88	0.39



GSM1900 (EDGE 8 Link)

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	EIRP (W)
Low Channel 512(1850.20MHz)						
1850.2	H	28.89	6.26	10.40	24.75	0.30
1850.2	V	27.53	6.26	10.40	23.39	0.22
Middle Channel 661 (1880.00MHz)						
1880.0	H	29.10	6.19	10.43	24.86	0.31
1880.0	V	27.68	6.19	10.43	23.44	0.22
High Channel 810 (1909.80MHz)						
1909.8	H	28.81	6.15	10.44	24.52	0.28
1909.8	V	27.80	6.15	10.44	23.51	0.22

WCDMA Band V

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	ERP (W)
Low Channel 4132(826.4MHz)						
826.4	H	29.77	3.83	-2.99	22.95	0.20
826.4	V	28.05	3.83	-2.99	21.23	0.13
Middle Channel 4182 (836.4MHz)						
836.4	H	30.16	3.96	-3.04	23.16	0.21
836.4	V	28.02	3.96	-3.04	21.02	0.13
High Channel 4233 (846.6MHz)						
846.6	H	30.11	3.97	-3.10	23.04	0.20
846.6	V	28.51	3.97	-3.10	21.44	0.14

WCDMA Band II

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	EIRP (W)
Low Channel 9262(1852.40MHz)						
1850.2	H	26.74	6.26	10.40	22.60	0.18
1850.2	V	25.15	6.26	10.40	21.01	0.13
Middle Channel 9400 (1880.00MHz)						
1880.0	H	26.81	6.19	10.43	22.57	0.18
1880.0	V	25.40	6.19	10.43	21.16	0.13
High Channel 9538 (1907.60MHz)						
1909.8	H	26.64	6.15	10.44	22.35	0.17
1909.8	V	25.40	6.15	10.44	21.11	0.13

4. Occupied Bandwidth


4.1. Test Equipment

Occupied Bandwidth

Instrument	Manufacturer	Model	Serial No	Cal. Date
Radio Communication Tester	Agilent	E5515C	GB46581718	2014.10.24
Spectrum Analyzer	Agilent	N9038A	MY51210142	2015.07.27
DC Power Supply	Agilent	6612C	MY43002989	2015.03.03

The measure equipment had been calibrated once a year.

4.2. Test Setup



#### **4.3. Limit**

N/A

#### **4.4. Test Procedure**

Using Occupied Bandwidth measurement function of spectrum analyzer, and setting as follows:

For GSM850/1900 test --- RBW = 3 kHz and VBW = 10 kHz

For WCDMA Band V/II test --- RBW = 100 kHz and VBW = 300 kHz


#### **4.5. Uncertainty**

The measurement uncertainty is defined as  $\pm 10$  Hz


GSM850 (GSM Link)

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
128	824.20	350.5	287.3
189	836.40	346.1	285.0
251	848.80	338.5	280.6


GSM850 (GSM Link), Channel 128



GSM850 (GSM Link), Channel 189




GSM850 (GSM Link), Channel 251




GSM850 (EDGE 8 Link)

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
128	824.20	346.4	285.4
189	836.40	344.3	286.7
251	848.80	347.1	282.5


GSM850 (EDGE 8 Link), Channel 128



GSM850 (EDGE 8 Link), Channel 189



GSM850 (EDGE 8 Link), Channel 251







GSM 1900 (GSM Link)

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
512	1850.20	338.1	274.3
661	1880.00	332.2	271.1
810	1909.80	342.6	278.8


GSM1900 (GSM Link), Channel 512



GSM1900 (GSM Link), Channel 661




GSM1900 (GSM Link), Channel 810




GSM1900 (EDGE 8 Link)

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
512	1850.20	329.7	272.7
661	1880.00	337.8	275.7
810	1909.80	335.2	274.0


GSM1900 (EDGE 8 Link), Channel 512



GSM1900 (EDGE 8 Link), Channel 661




GSM1900 (EDGE 8 Link), Channel 810




WCDMA Band V

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
4132	826.40	4.673	4.239
4182	836.40	4.672	4.227
4233	846.40	4.699	4.213


WCDMA Band V, Channel 4132



WCDMA Band V, Channel 4182




WCDMA Band V, Channel 4233




WCDMA Band II

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
9262	1852.4	4.652	4.183
9400	1880.0	4.675	4.229
9538	1907.6	4.672	4.188


WCDMA Band II, Channel 9262



WCDMA Band II, Channel 9400



WCDMA Band II, Channel 9538






## 5.Spurious Emission At Antenna Terminals (+/- 1MHz)

### 5.1. Test Equipment

Instrument	Manufacturer	Model	Serial No	Cal. Date
Radio Communication Tester	Agilent	E5515C	GB46581718	2014.10.24
Spectrum Analyzer	Agilent	N9038A	MY51210142	2015.07.27
DC Power Supply	Agilent	6612C	MY43002989	2015.03.03

The measure equipment had been calibrated once a year.

### 5.2. Test Setup



### **5.3. Limit**

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10\log(P)$  dB.

### **5.4. Test Procedure**


In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

### **5.5. Uncertainty**

The measurement uncertainty is defined as  $\pm 1.2$  dB.




GSM850 (EDGE 8 Link), Channel 128



GSM850 (EDGE 8 Link), Channel 251




GSM 1900 (GSM Link), Channel 512



GSM 1900 (GSM Link), Channel 810




GSM1900 (EDGE 8 Link), Channel 512




GSM1900 (EDGE 8 Link), Channel 810






WCDMA Band V, Channel 4233





WCDMA Band II, Channel 9538





## 6.Spurious Emission


### 6.1. Test Equipment

Instrument	Manufacturer	Model	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	N9038A	MY51210142	2015.07.27
Radio Communication Tester	Agilent	E5515C	GB46581718	2014.10.24
Signal Generator	Agilent	N5183A	MY50140938	2015.01.03
Preamplifier	CEM	EM30180	3008A0245	2015.02.28
Loop Antenna	Schwarzbeck	FMZB1519	1519-020	2015.03.26
Bilog Antenna	Schwarzbeck	VULB9160	9160-3316	2015.07.19
VHF-UHF-Biconical Antenna	Schwarzbeck	VUBA9117	9117-263	2015.07.19
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-942	2015.07.19
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-943	2015.07.19


The measure equipment had been calibrated once a year.

## 6.2. Test Setup


Conducted Spurious Emission Measurement:




Radiated Spurious Measurement: below 30MHz



Radiated Spurious Measurement: 30MHz to 1GHz



### Radiated Spurious Measurement: above 1GHz



### 6.3. Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10\log(P)$  dB.

### 6.4. Test Procedure

#### Conducted Spurious Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and E5515C by a Directional Coupler.
- EUT Communicate with E5515C, then select a channel for testing.
- Add a correction factor to the display of spectrum, and then test.
- The resolution bandwidth of the spectrum analyzer was set at 1 MHz, sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.

#### Radiated Spurious Measurement:

- The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- The output of the test antenna shall be connected to the measuring receiver. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- The transmitter shall then be rotated through  $360^\circ$  in the horizontal plane, until the maximum signal level is detected by the measuring receiver.

- f. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h. The maximum signal level detected by the measuring receiver shall be noted.
- i. The transmitter shall be replaced by a substitution antenna.
- j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k. The substitution antenna shall be connected to a calibrated signal generator.
- l. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q. The frequency range was checked up to 10<sup>th</sup> harmonic.
- r. Test site anechoic chamber refer to ANSI/TIA-603-C-2004.



## 6.5. Uncertainty

The measurement uncertainty is defined as 3.2 dB for Radiated Power Measurement.


## 6.6. Test Result

### Conducted Spurious Measurement:


GSM850 (GSM Link), Channel 189




Note: The signal at point 1 is carrier





GSM850 (EDGE 8 Link), Channel 189







GSM 1900 (GSM Link), Channel 661











Note: The signal at point 1 is carrier










Note: The signal at point 1 is carrier






WCDMA Band II, Channel 9400:






Note: The signal at point 1 is carrier





Note: The signal at point 1 is carrier



### Radiated Spurious Measurement:

#### GSM850 (GSM Link), 9KHz to 30MHz

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line, and that was not reported per 2.1057 (c).

#### GSM850 (GSM Link), 30MHz to 1GHz

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Antenna Factor (dBm)	ERP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 189 (836.40MHz)							
778.8	H	-93.42	3.81	40.05	-49.56	-13.00	-36.56
276.4	H	-94.36	2.21	26.56	-65.59	-13.00	-52.59
778.8	V	-94.99	3.81	32.23	-58.94	-13.00	-45.94
276.4	V	-96.39	2.21	24.11	-70.07	-13.00	-57.07

#### GSM850 (GSM Link), Above 1GHz

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 189 (836.40MHz)							
1673.4	H	-41.38	6.00	-2.35	-37.73	-13.00	-24.73
7282.8	H	-64.60	12.64	-8.99	-42.95	-13.00	-29.95
1673.4	V	-46.43	6.00	-2.35	-42.78	-13.00	-29.78
7282.8	V	-64.12	12.64	-8.99	-42.47	-13.00	-29.47

#### GSM850 (EDGE 8 Link), 9KHz to 30MHz

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line, and that was not reported per 2.1057 (c).

#### GSM850 (EDGE 8 Link), 30MHz to 1GHz

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Antenna Factor (dBm)	ERP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 189 (836.40MHz)							
778.8	H	-89.11	3.81	40.05	-45.25	-13.00	-32.25
276.4	H	-92.30	2.21	26.56	-63.53	-13.00	-50.53
778.8	V	-90.79	3.81	32.23	-54.74	-13.00	-41.74
276.4	V	-93.17	2.21	24.11	-66.85	-13.00	-53.85



**GSM850 (EDGE 8 Link), Above 1GHz**

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 189 (836.40MHz)							
1673.4	H	-37.42	6.00	2.35	-33.77	-13.00	-20.77
4818.0	H	-64.58	10.37	-4.88	-49.31	-13.00	-36.31
1673.4	V	-45.61	6.00	2.35	-41.96	-13.00	-28.96
4818.0	V	-63.12	10.37	-4.88	-47.85	-13.00	-34.85

**GSM1900 (GSM Link), 9KHz to 30MHz**

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line, and that was not reported per 2.1057 (c).

**GSM 1900 (GSM Link), 30MHz to 1GHz**

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Antenna Factor (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 661 (1880.00MHz)							
256.9	H	-95.72	2.17	26.41	-67.14	-13.00	-54.14
779.8	H	-95.67	3.82	40.01	-51.84	-13.00	-38.84
256.9	V	-96.64	2.17	23.20	-71.17	-13.00	-58.17
779.8	V	-95.10	3.82	32.23	-59.05	-13.00	-46.05

**GSM 1900 (GSM Link), Above 1GHz**

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 661 (1880.00MHz)							
1821.8	H	-50.74	6.22	1.61	-46.13	-13.00	-33.13
3757.2	H	-62.90	8.95	-3.16	-50.79	-13.00	-37.79
1821.8	V	-43.17	6.22	1.61	-38.56	-13.00	-25.56
3757.2	V	-56.64	8.95	-3.16	-44.53	-13.00	-31.53

**GSM1900 (EDGE 8 Link), 9KHz to 30MHz**

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line, and that was not reported per 2.1057 (c).

**GSM1900 (EDGE 8 Link), 30MHz to 1GHz**

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Antenna Factor (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 661 (1880.00MHz)							
256.9	H	-93.62	2.17	26.41	-65.04	-13.00	-52.04
779.8	H	-91.17	3.82	40.01	-47.34	-13.00	-34.34
256.9	V	-92.64	2.17	23.20	-67.17	-13.00	-54.17
779.8	V	-90.03	3.82	32.23	-53.98	-13.00	-40.98

**GSM1900 (EDGE 8 Link), Above 1GHz**

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 661 (1880.00MHz)							
1823.2	H	-51.00	6.22	1.61	-46.39	-13.00	-33.39
3757.2	H	-62.42	8.95	-3.16	-50.31	-13.00	-37.31
1823.2	V	-43.72	6.22	1.61	-57.29	-13.00	-44.29
3757.2	V	-56.26	8.95	-3.16	-39.11	-13.00	-26.11

**WCDMA Band V 9KHz to 30MHz**

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line, and that was not reported per 2.1057 (c).

**WCDMA Band V 30MHz to 1GHz**

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Antenna Factor (dBm)	ERP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 4182 (836.40MHz)							
438.87	H	-102.65	2.85	33.10	-66.70	-13.00	-53.70
438.87	V	-102.67	2.85	28.22	-71.60	-13.00	-58.60

**WCDMA Band V Above 1GHz**

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 4182 (836.40MHz)							
1669.2	H	-62.40	5.95	2.53	-58.98	-13.00	-45.98
8718.0	H	-68.57	13.48	-8.85	-46.24	-13.00	-33.24
1669.2	V	-58.53	5.95	2.53	-55.11	-13.00	-42.11
8718.0	V	-70.74	13.48	-8.85	-48.41	-13.00	-35.41

### WCDMA Band II 9KHz to 30MHz

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line, and that was not reported per 2.1057 (c).

### WCDMA Band II 30MHz to 1GHz

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Antenna Factor (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 9400 (1880MHz)							
948.6	H	-102.88	4.15	43.17	-55.56	-13.00	-42.56
948.6	V	-105.16	4.15	35.75	-65.26	-13.00	-52.26

### WCDMA Band II Above 1GHz

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Middle Channel 9400 (1880MHz)							
3913.2	H	-69.08	9.18	-3.37	-56.53	-13.00	-43.53
3913.2	V	-66.88	9.18	-3.37	-54.33	-13.00	-41.33


## 7. Frequency Stability Under Temperature & Voltage Variations

### 7.1. Test Equipment

Instrument	Manufacturer	Model	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	N9038A	MY51210142	2015.07.27
Radio Communication Tester	Agilent	E5515C	GB46581718	2014.10.24
DC Power Supply	Agilent	6612C	MY43002989	2015.03.03
Temperature Chamber	WEISS	DU/20/40	58226017340050	2015.01.03

The measure equipment had been calibrated once a year.

### 7.2. Test Setup



The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Limit	< $\pm 2.5$ ppm
-------	-----------------

## 7.4. Test Procedure

### Frequency Stability Under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

### Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.

## 7.5. Uncertainty

The measurement uncertainty is defined as  $\pm 10$  Hz.

## 7.6. Test Result

### GSM850 (GSM Link):

#### Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation	Limit (Hz)
		(Hz)	
-20	836.40	-25.24	± 2091
-10	836.40	-23.89	± 2091
0	836.40	-18.11	± 2091
10	836.40	-12.17	± 2091
20	836.40	-10.25	± 2091
30	836.40	-24..51	± 2091
40	836.40	-33.12	± 2091
50	836.40	-33.42	± 2091

#### Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.4	836.40	-17.50	± 2091
3.8	836.40	-20.32	± 2091
4.2	836.40	-26.84	± 2091

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation	Limit (Hz)
		(Hz)	
-20	836.40	-30.42	± 2091
-10	836.40	-26.35	± 2091
0	836.40	-20.40	± 2091
10	836.40	-17.33	± 2091
20	836.40	-11.84	± 2091
30	836.40	-22.30	± 2091
40	836.40	-25.47	± 2091
50	836.40	-32.01	± 2091

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.4	836.40	-19.35	± 2091
3.8	836.40	-15.21	± 2091
4.2	836.40	-36.20	± 2091

**GSM 1900 (GSM Link):**

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-20	1880.00	28.32	±4700
-10	1880.00	25.21	±4700
0	1880.00	12.01	±4700
10	1880.00	5.34	±4700
20	1880.00	10.88	±4700
30	1880.00	22.31	±4700
40	1880.00	30.24	±4700
50	1880.00	38.95	±4700

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.4	1880.00	27.21	±4700
3.8	1880.00	15.84	±4700
4.2	1880.00	28.61	±4700



**GSM1900 (EDGE 8 Link):**

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-20	1880.00	25.21	±4700
-10	1880.00	21.30	±4700
0	1880.00	14.98	±4700
10	1880.00	11.56	±4700
20	1880.00	5.98	±4700
30	1880.00	15.63	±4700
40	1880.00	14.85	±4700
50	1880.00	32.09	±4700
60	1880.00	31.84	±4700

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.4	1880.00	21.35	±4700
3.8	1880.00	10.20	±4700
4.2	1880.00	26.55	±4700

**WCDMA Band V:**

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit(Hz)	Result
-20	836.40	15.30	$\pm 2091$	PASS
-10	836.40	11.02	$\pm 2091$	
0	836.40	-15.33	$\pm 2091$	
10	836.40	-18.27	$\pm 2091$	
20	836.40	-27.20	$\pm 2091$	
30	836.40	-14.89	$\pm 2091$	
40	836.40	15.87	$\pm 2091$	
50	836.40	19.88	$\pm 2091$	

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit(Hz)	Result
3.4	836.40	20.47	$\pm 2091$	PASS
3.8	836.40	13.24	$\pm 2091$	
4.2	836.40	27.70	$\pm 2091$	

## WCDMA Band II:

### Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit(Hz)	Result
-20	1880.00	13.24	$\pm 4700$	PASS
-10	1880.00	15.38	$\pm 4700$	
0	1880.00	-12.89	$\pm 4700$	
10	1880.00	-20.67	$\pm 4700$	
20	1880.00	-14.56	$\pm 4700$	
30	1880.00	-16.25	$\pm 4700$	
40	1880.00	-17.74	$\pm 4700$	
50	1880.00	18.33	$\pm 4700$	

### Frequency Stability under Voltage


DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit(Hz)	Result
3.4	1880.00	-21.30	$\pm 4700$	PASS
3.8	1880.00	-19.47	$\pm 4700$	
4.2	1880.00	-27.56	$\pm 4700$	

## 8. Peak to Average

### 8.1. Test Equipment

Instrument	Manufacturer	Model	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	N9038A	MY51210142	2014.12.20
Radio Communication Tester	Agilent	E5515C	GB46581718	2014.10.24
Signal Generator	Agilent	N5183A	MY50140938	2015.01.03
Preamplifier	CEM	EM30180	3008A0245	2015.02.28
DC Power Supply	Agilent	6612C	MY43002989	2015.03.03

### 8.2. Test Setup



### 8.3. Limit

In addition, the transmitter's peak-to-average power ratio (PAPR) shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

### 8.4. Test Procedure

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function(CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given a bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at

or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Procedure:


- a. Place the EUT on a bench and set it in transmitting mode.
- b. Connect a low loss RF cable from the antenna port to a spectrum analyzer and E5515C by a Directional Couple.
- c. EUT Communicate with E5515C, then select a channel for testing.
- d. Add a correction factor to the display of spectrum, and then test.
- e. The resolution bandwidth of the spectrum analyzer was set at 1 MHz.

## 8.5. Uncertainty


The measurement uncertainty is defined as  $\pm 1.2$  dB.


## 8.6. Test Result

Band	Channel No.	Limit (dB)	Result (dB)
PCS 1900	661	< 13	0.06
EDGE 1900	661	< 13	0.01
WCDMA BAND II	9800	< 13	3.55



For EDGE 1900, channel 661





## 9.Receiver Spurious Emission for RSS 132/133


### 9.1. Test Equipment

Instrument	Manufacturer	Model	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	N9038A	MY51210142	2014.12.20
Radio Communication Tester	Agilent	E5515C	GB46581718	2014.10.24
Signal Generator	Agilent	N5183A	MY50140938	2015.01.03
Preamplifier	CEM	EM30180	3008A0245	2015.02.28
Loop Antenna	Schwarzbeck	FMZB1519	1519-020	2015.03.26
Bilog Antenna	Schwarzbeck	VULB9160	9160-3316	2015.07.19
VHF-UHF-Biconical Antenna	Schwarzbeck	VUBA9117	9117-263	2015.07.19
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-942	2015.07.19
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-943	2015.07.19

The measure equipment had been calibrated once a year.


### 9.2. Test Setup

Below 1GHz Test Setup





### Above 1GHz Test Setup



### 9.3. Limit

According to Standard RSS132/133 refer to RSS-Gen Issu 3.

Field Strength micro-volts/m at 3 meters		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) =  $20 \log E$  field strength (uV/m).

### 9.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated on radiated measurement. On any frequency or frequencies below or equal to 1000 MHz, the radiated limits shown are based on measuring equipment employing a quasi-peak detector function and above 100MHz, the radiated limits shown are based measuring equipment employing an average detector function.

When average radiated emission measurement are included emission measurement Above 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

**Note:** When measurement above 1GHz, the horn antenna will bend down a little (as horn antenna have the narrow beamwidth) in order to find the maximum emission of EUT.


## 9.5. Uncertainty

The measurement uncertainty is defined as 3.1 dB for Radiated Power Measurement.

## 9.6. Test Result


No significant emissions measurable. Plots reported here represent the worse case emissions.

Prob : VULB9160(30M-1G)	Polarity: Horizontal
GSM 850 Idle	




NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	572.23 MHz	8.09 dBuV	28.27 dB/m	3.23 dB	0.00 dB	39.59 dBuV/m	46.00 dBuV/m	-6.41 dB	QP

Prob : VULB9160(30M-1G)	Polarity: Vertical
GSM 850 Idle	




NO	Freq	Read Level	Atenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	761.38 MHz	-3.15 dBuV	40.33 dB/m	3.70 dB	0.00 dB	40.88 dBuV/m	46.00 dBuV/m	-5.12 dB	QP

Prob : BBHA9120D(1G-18G)	Polarity: Horizontal
GSM 850 Idle	




NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
1	10911 MHz	39.09 dBuV	40.28 dB/m	15.65 dB	38.94 dB	48.07 dBuV/m	74.00 dBuV/m	-17.92 dB	Peak
2	10911 MHz	20.08 dBuV	40.28 dB/m	15.65 dB	38.94 dB	37.07 dBuV/m	54.00 dBuV/m	-16.93 dB	AV
3	14600 MHz	14.54 dBuV	42.43 dB/m	18.66 dB	38.11 dB	37.52 dBuV/m	54.00 dBuV/m	-16.48 dB	AV
4	14600 MHz	35.55 dBuV	42.43 dB/m	18.66 dB	38.11 dB	58.53 dBuV/m	74.00 dBuV/m	-15.47 dB	Peak

Prob : BBHA9120D(1G-18G)	Polarity: Vertical
GSM 850 Idle	




NO	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	8701 MHz	45.40 dBuV	36.90 dB/m	13.40 dB	40.77 dB	54.93 dBuV/m	74.00 dBuV/m	-19.07 dB	Peak
2	8701 MHz	23.38 dBuV	36.90 dB/m	13.40 dB	40.77 dB	32.91 dBuV/m	54.00 dBuV/m	-21.09 dB	AV
3	14362 MHz	14.58 dBuV	42.43 dB/m	19.06 dB	38.34 dB	37.73 dBuV/m	54.00 dBuV/m	-16.27 dB	AV
4	14362 MHz	34.86 dBuV	42.43 dB/m	19.06 dB	38.34 dB	58.01 dBuV/m	74.00 dBuV/m	-15.99 dB	Peak

Prob : VULB9160(30M-1G)	Polarity: Horizontal
EDGE 850 Idle	




NO.	Freq	Read Level	Atenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	719.6 7MHz	-4.03 dBuV	38.58 dB/m	3.70 dB	0.00 dB	38.25dB uV/m	46.00 dBuV/m	-7.75 dB	QP

Prob : VULB9160(30M-1G)	Polarity: Vertical
EDGE 850 Idle	



NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	499.48 MHz	5.53 dBuV	28.79 dB/m	3.03 dB	0.00 dB	37.35 dBuV/m	46.00 dBuV/m	-8.65 dB	QP


Prob : BBHA9120D(1G-18G)	Polarity: Horizontal
EDGE 850 Idle	



NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
1	11165.10 MHz	31.02 dBuV	40.00 dB/m	15.76 dB	38.98 dB	47.80 dBuV/m	54.00 dBuV/m	-6.20 dB	AV
2	11165.00 MHz	37.67 dBuV	40 dB/m	15.76 dB	38.98 dB	54.45 dBuV/m	74.00 dBuV/m	-19.55 dB	Peak




Prob : BBHA9120D(1G-18G)	Polarity: Vertical
EDGE 850 Idle	




NO	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	14311.80 MHz	25.24 dBuV	42.34 dB/m	18.96 dB	38.39 dB	48.15 dBuV/m	54.00 dBuV/m	-5.85 dB	AV
2	14311.00 MHz	32.48 dBuV	42.34 dB/m	18.96 dB	38.39 dB	55.39 dBuV/m	74.00 dBuV/m	-18.61 dB	Peak

Prob : VULB9160(30M-1G)	Polarity: Horizontal
GSM 1900 Idle	




NO.	Freq	Read Level	Atenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
2	546.0 4 MHz	5.00 dBuV	28.27 dB/m	3.15 dB	0.00 dB	36.42 dBuV/m	46.00 dBuV/m	-9.58 dB	QP

Prob : VULB9160(30M-1G)	Polarity: Vertical
GSM 1900 Idle	




NO	Freq	Read Level	Atenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
2	763.32 MHz	-4.07 dBuV	40.33 dB/m	3.70 dB	0.00 dB	39.35 dBuV/m	46.00 dBuV/m	-6.65 dB	QP

Prob : BBHA9120D(1G-18G)	Polarity: Horizontal
GSM 1900 Idle	




NO	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	10979 MHz	28.33 dBuV	40.30 dB/m	15.71 dB	38.91 dB	45.43 dBuV/m	74.00 dBuV/m	-28.57 dB	Peak
2	10979 MHz	9.21 dBuV	40.30 dB/m	15.71 dB	38.91 dB	26.31 dBuV/m	54.00 dBuV/m	-27.69 dB	AV
3	14532 MHz	19.98 dBuV	42.52 dB/m	18.80 dB	38.17 dB	43.13 dBuV/m	54.00 dBuV/m	-10.87 dB	AV
4	14532 MHz	40.21 dBuV	42.52 dB/m	18.80 dB	38.17 dB	46.14 dBuV/m	74.00 dBuV/m	-27.86 dB	Peak

Prob : BBHA9120D(1G-18G)	Polarity: Vertical
GSM 1900 Idle	




NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
1	8701 MHz	45.40 dBuV	36.90 dB/m	13.40 dB	40.77 dB	54.93 dBuV/m	74.00 dBuV/m	-19.07 dB	Peak
2	8701 MHz	26.24 dBuV	36.90 dB/m	13.40 dB	40.77 dB	35.77 dBuV/m	54.00 dBuV/m	-18.23 dB	AV
3	14412 MHz	17.01 dBuV	42.50 dB/m	18.71 dB	38.29 dB	39.92 dBuV/m	54.00 dBuV/m	-14.08 dB	AV
4	14413 MHz	36.14 dBuV	42.50 dB/m	18.71 dB	38.29 dB	59.06 dBuV/m	74.00 dBuV/m	-14.94 dB	Peak

Prob : VULB9160(30M-1G)	Polarity: Horizontal
EDGE 1900 Idle	




NO	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	601.33 MHz	-1.64 dBuV	36.60 dB/m	3.34 dB	0.00 dB	38.30 dBuV/m	46.00 dBuV/m	-7.70 dB	QP

Prob : VULB9160(30M-1G)	Polarity: Vertical
EDGE 1900 Idle	



NO	Freq	Read Level	Atenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	519.85 MHz	2.88 dBuV	29.09 dB/m	3.10 dB	0.00 dB	35.07 dBuV/m	46.00 dBuV/m	-10.93 dB	QP


Prob : BBHA9120D(1G-18G)	Polarity: Horizontal
EDGE 1900 IDLE	



NO	Freq	Read Level	Atenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	10587.30 MHz	30.55d BuV	39.66 dB/m	15.50 dB	39.10 dB	46.61 dBuV/m	54.00 dBuV/m	-7.39 dB	AV
2	10587.00 MHz	38.78d BuV	39.66 dB/m	15.50 dB	39.10 dB	54.84 dBuV/m	74.00 dBuV/m	-19.16 dB	Peak




Prob : BBHA9120D(1G-18G)	Polarity: Vertical
EDGE 1900 IDLE	




NO	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
1	9840.90 MHz	34.08 dBuV	38.70 dB/m	14.79 dB	39.68 dB	47.89 dBuV/m	54.00 dBuV/m	-6.11 dB	AV
2	9840.00 MHz	40.97 dBuV	38.70 dB/m	14.79 dB	39.68 dB	54.78 dBuV/m	74.00 dBuV/m	-19.22 dB	Peak

Prob : VULB9160(30M-1G)	Polarity: Horizontal
WCDMA BAND II Idle	




NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
1	572.23 MHz	8.33 dBuV	28.27 dB/m	3.23 dB	0.00 dB	39.74 dBuV/m	46.00 dBuV/m	-6.26 dB	QP

Prob : VULB9160(30M-1G)	Polarity: Vertical
WCDMA BAND II Idle	




NO	Freq	Read Level	Atenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	761.38 MHz	-4.49 dBuV	40.33 dB/m	3.70 dB	0.00 dB	39.54 dBuV/m	46.00 dBuV/m	-6.46 dB	QP

Prob : BBHA9120D(1G-18G)	Polarity: Horizontal
WCDMA BAND II Idle	




NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
1	10911 MHz	39.09 dBuV	40.28 dB/m	15.65 dB	38.94 dB	48.07 dBuV/m	74.00 dBuV/m	-17.92 dB	Peak
2	10911 MHz	20.08 dBuV	40.28 dB/m	15.65 dB	38.94 dB	37.07 dBuV/m	54.00 dBuV/m	-16.93 dB	AV
3	14600 MHz	14.54 dBuV	42.43 dB/m	18.66 dB	38.11 dB	37.52 dBuV/m	54.00 dBuV/m	-16.48 dB	AV
4	14600 MHz	35.55 dBuV	42.43 dB/m	18.66 dB	38.11 dB	58.53 dBuV/m	74.00 dBuV/m	-15.47 dB	Peak

Prob : BBHA9120D(1G-18G)	Polarity: Vertical
WCDMA BAND II Idle	




NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	8701 MHz	45.40 dBuV	36.90 dB/m	13.40 dB	40.77 dB	54.93 dBuV/m	74.00 dBuV/m	-19.07 dB	Peak
2	8701 MHz	23.38 dBuV	36.90 dB/m	13.40 dB	40.77 dB	32.91 dBuV/m	54.00 dBuV/m	-21.09 dB	AV
3	14362 MHz	14.58 dBuV	42.43 dB/m	19.06 dB	38.34 dB	37.73 dBuV/m	54.00 dBuV/m	-16.27 dB	AV
4	14362 MHz	34.86 dBuV	42.43 dB/m	19.06 dB	38.34 dB	58.01 dBuV/m	74.00 dBuV/m	-15.99 dB	Peak

Prob : VULB9160(30M-1G)	Polarity: Horizontal
WCDMA BAND V Idle	




NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	601.33 MHz	-1.64 dBuV	36.60 dB/m	3.34 dB	0.00 dB	38.30 dBuV/m	46.00 dBuV/m	-7.70 dB	QP

Prob : VULB9160(30M-1G)	Polarity: Vertical
WCDMA BAND V Idle	



NO.	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
1	519.85 MHz	2.88 dBuV	29.09 dB/m	3.10 dB	0.00 dB	35.07 dBuV/m	46.00 dBuV/m	-10.93 dB	QP


Prob : BBHA9120D(1G-18G)	Polarity: Horizontal
WCDMA BAND V IDLE	



NO	Freq	Read Level	Atenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	14684.20 MHz	25.37 dBUV	42.29 dB/m	18.44 dB	38.02 dB	48.08 dBUV/m	54.00 dBUV/m	-5.92 dB	AV
2	14685.00 MHz	33.85 dBUV	42.29 dB/m	18.44 dB	38.02 dB	56.56 dBUV/m	74.00 dBUV/m	-17.44 dB	Peak



Prob : BBHA9120D(1G-18G)	Polarity: Vertical
WCDMA BAND V Idle	



NO	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
1	11777.10 MHz	31.50 dBuV	39.46 dB/m	16.45 dB	39.29 dB	48.12 dBuV/m	54.00 dBuV/m	-5.88 dB	AV
2	11778.00 MHz	38.82 dBuV	39.46 dB/m	16.45 dB	39.29 dB	55.44 dBuV/m	74.00 dBuV/m	-18.56 dB	Peak

## **10.Attachment**

### **PHOTOGRAPHS OF TEST SETUP**

Please refer to the file named “RF Setup Photos”.

### **PHOTOGRAPHS OF EUT**

Please refer to the two files named “SIM5360A\_EUT Photos”.

----End of the report----