

**47 CFR PART 22 SUBPART H & 24 SUBPART E**

# **TEST REPORT**

of

**GSM/GPRS 850/900/1800/1900 Module**

Model Name: SIM340E  
Brand Name: SIMCOM  
Report No.: SH08060012E01  
FCC ID: UDV-0606020080701

*prepared for*

**Shanghai Simcom Ltd.**

SIM Technology Building, 700 Yishan Rd., Shanghai 200233

*prepared by*

**Shenzhen Electronic Product Quality Testing Center**

**Morlab Laboratory**

3/F, Electronic Testing Building, Shahe Road, Xili,  
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



**NOTE:** This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.



<b>1.</b>	<b>TEST CERTIFICATION .....</b>	<b>4</b>
<b>2.</b>	<b>GENERAL INFORMATION .....</b>	<b>5</b>
<b>2.1</b>	<b>EUT Description .....</b>	<b>5</b>
<b>2.2</b>	<b>Test Standards and Results .....</b>	<b>6</b>
<b>2.3</b>	<b>Facilities and Accreditations .....</b>	<b>7</b>
2.3.1	Facilities .....	7
2.3.2	Test Environment Conditions .....	7
<b>3.</b>	<b>47 CFR PART 2, PART 22H REQUIREMENTS .....</b>	<b>8</b>
<b>3.1</b>	<b>Frequencies .....</b>	<b>8</b>
3.1.1	Requirement .....	8
3.1.2	Test Description .....	8
3.1.3	Test Result .....	9
<b>3.2</b>	<b>Conducted RF Output Power .....</b>	<b>12</b>
3.2.1	Requirement .....	12
3.2.2	Test Description .....	12
3.2.3	Test Result .....	12
<b>3.3</b>	<b>20dB Occupied Bandwidth .....</b>	<b>16</b>
3.3.1	Definition .....	16
3.3.2	Test Description .....	16
3.3.3	Test Verdict .....	16
<b>3.4</b>	<b>Frequency Stability .....</b>	<b>20</b>
3.4.1	Requirement .....	20
3.4.2	Test Description .....	20
3.4.3	Test Verdict .....	20
<b>3.5</b>	<b>Conducted Out of Band Emissions .....</b>	<b>22</b>
3.5.1	Requirement .....	22
3.5.2	Test Description .....	22
3.5.3	Test Result .....	22
<b>3.6</b>	<b>Band Edge .....</b>	<b>29</b>
3.6.1	Requirement .....	29
3.6.2	Test Description .....	29
3.6.3	Test Result .....	29

<b>3.7</b>	<b>Transmitter Radiated Power (EIRP/ERP)</b>	<b>32</b>
3.7.1	Requirement	32
3.7.2	Test Description	32
3.7.3	Test Result	33
<b>3.8</b>	<b>Radiated Out of Band Emissions</b>	<b>37</b>
3.8.1	Requirement	37
3.8.2	Test Description	37
3.8.3	Test Result	37
<b>Appendix I:</b>	<b>Photograph of the Test Setup</b>	<b>39</b>
<b>Appendix II:</b>	<b>Photograph of the EUT</b>	<b>40</b>





Report No.: SH08060012E01

## 1. TEST CERTIFICATION

Equipment under Test: GSM/GPRS 850/900/1800/1900 Module

Brand Name: SIMCOM

Model Name: SIM340E

FCC ID: UDV-0606020080701

Applicant: Shanghai Simcom Ltd.

SIM Technology Building, 700 Yishan Rd., Shanghai 200233

Manufacturer: Shanghai Simcom Ltd.

SIM Technology Building, 700 Yishan Rd., Shanghai 200233

Test Standards: 47 CFR Part 2

47 CFR Part 22 Subpart H

47 CFR Part 24 Subpart E

Test Date(s): June 25, 2008 – June 31, 2008

Test Result: PASS

### \* We Hereby Certify That:

The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by:

*Lou Qin Chao*

Lou Qin Chao

Dated:

08.07.01

Reviewed by:

*Zhang Jun*

Zhang Jun

Dated:

08.07.01

Approved by:

*Su Feng*

Su Feng

Dated:

08.07.01





## 2. GENERAL INFORMATION

### 2.1 EUT Description

EUT Type.....: GSM/GPRS 850/900/1800/1900 Module  
Model Name .....: SIM340E  
Serial No.....: MP0608190000058  
IMEI .....: 359586015544351  
Hardware Version .....: SIM300\_V8.01  
Software Version .....: TTPCom 10.0  
Frequency Range.....: GSM 850MHz:  
Tx: 824.20 - 848.80MHz (at intervals of 200kHz);  
Rx: 869.20 - 893.80MHz (at intervals of 200kHz)  
GSM 1900MHz:  
Tx: 1850.20 - 1909.80MHz (at intervals of 200kHz);  
Rx: 1930.20 - 1989.80MHz (at intervals of 200kHz)  
Modulation Type.....: GMSK  
Emission Designators .....: 300KGXW  
Ancillary Equipments.....: AC Adapter  
Model Name: DSA-0131F-06EU12  
Brand Name: DEEVAN  
Serial No.: (n.a. marked #1 by test site)  
Rated Input: ~100-240V, 0.3A, 50/60Hz  
Rated Output: = 6V, 2A  
Manufacturer: DEEVAN ELECTRONICS(JIAXING) CO.,LTD  
Wire Length: 185cm

*Note 1:* The transmitter (Tx) frequency arrangement of the Cellular 850MHz band used by the EUT can be represented with the formula  $F(n)=824.2+0.2*(n-128)$ ,  $128 \leq n \leq 251$ ; the lowest, middle, highest channel numbers (ARFCHs) used and tested in this report are separately 128 (824.2MHz), 190 (836.6MHz) and 251 (848.8MHz).

*Note 2:* The transmitter (Tx) frequency arrangement of the PCS 1900MHz band used by the EUT can be represented with the formula  $F(n)=1850.2+0.2*(n-512)$ ,  $512 \leq n \leq 810$ ; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 512 (1850.2MHz), 661 (1880.0MHz) and 810 (1909.8MHz).

*Note 3:* For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22 and Part 24 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-05 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-05 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-05 Edition)	Personal Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	2.106 22.905 24.229	Frequencies	PASS
2	2.1046	Conducted RF Output Power	PASS
3	2.1049	20dB Occupied Bandwidth	PASS
4	2.1055 22.355 24.235	Frequency Stability	PASS
5	2.1051 2.1057 22.917 24.238	Conducted Out of Band Emissions	PASS
6	2.1051 2.1057 22.917 24.238	Band Edge	PASS
7	22.913 24.232	Transmitter Radiated Power (EIPR/ERP)	PASS
8	2.1053 2.1057 22.917 24.238	Radiated Out of Band Emissions	PASS

## **2.3 Facilities and Accreditations**

### **2.3.1 Facilities**

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Board for Laboratories (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

### **2.3.2 Test Environment Conditions**

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 - 25
Relative Humidity (%):	40 - 60
Atmospheric Pressure (kPa):	960

### 3. 47 CFR PART 2, PART 22H REQUIREMENTS

#### 3.1 Frequencies

##### 3.1.1 Requirement

According to FCC section 22.905, the frequency blocks assignment for the cellular radiotelephone service is listed as below:


- (a) Channel Block A:  
Mobile 824 - 835MHz, Base 869 - 880MHz;  
Mobile 845 - 846.5MHz, Base 890 - 891.5MHz
- (b) Channel Block B:  
Mobile 835 - 845 MHz, Base 880 - 890MHz;  
Mobile 846.5 - 849 MHz, Base 891.5 - 894MHz

According to FCC section 24.229, the frequencies available in the Broadband PCS services are listed as below, in accordance with the frequency allocations table of FCC section 2.106.

- (a) The following frequency blocks are available for assignment on an MTA basis:  
Block A: 1850 - 1865MHz paired with 1930 - 1945MHz;  
Block B: 1870 - 1885MHz paired with 1950 - 1965MHz.
- (b) The following frequency blocks are available for assignment on a BTA basis:  
Block C: 1895 - 1910 MHz paired with 1975 - 1990MHz;  
Block D: 1865 - 1870 MHz paired with 1945 - 1950MHz;  
Block E: 1885 - 1890 MHz paired with 1965 - 1970MHz;  
Block F: 1890 - 1895 MHz paired with 1970 - 1975MHz.

##### 3.1.2 Test Description

###### 1. Test Setup:



The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna



terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

## 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Rohde&Schwarz	CMU200	105571	2007.06	1year
Spectrum Analyzer	Agilent	E7405A	US44210471	2007.07	1year
Power Splitter	Weinschel	1506A	NW521	(n.a.)	(n.a.)
Attenuator 1	Resnet	20dB	(n.a.)	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)	(n.a.)

### 3.1.3 Test Result


The Tx frequency arrangement of the Cellular 850MHz band employed by the EUT should be from 824.2MHz to 848.8MHz (the corresponding frequency block is from 824MHz to 849MHz), and Tx frequency arrangement of the PCS 1900MHz band employed by the EUT should be from 1850.2MHz to 1909.8MHz (the corresponding frequency block is from 1850MHz to 1910MHz). Here the lowest and highest channels are tested to verify the EUT's using the frequency block required.

#### 1. Test Verdict:

The required frequency block is employed legally, the verdict is PASS.


Band	Channel	Frequency (MHz)	Measured Carrier (dBm)	Refer to Plot
GSM 850MHz	128	824.2	20.77	Plot A
	251	848.8	20.52	Plot B
GSM 1900MHz	512	1850.2	16.46	Plot C
	810	1909.8	16.32	Plot D

#### 2. Test Plot:




Date: 24.JUN.2008 08:07:30

(Plot A: GSM 850MHz Channel = 128)




Date: 24.JUN.2008 08:09:13

(Plot B: GSM 850MHz Channel = 251)



Date: 24.JUN.2008 10:37:49

(Plot C: GSM 1900MHz Channel = 512)



Date: 24.JUN.2008 10:34:35

(Plot D: GSM 1900MHz Channel = 810)

## 3.2 Conducted RF Output Power

### 3.2.1 Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

### 3.2.2 Test Description

See section 3.1.2 of this report.

### 3.2.3 Test Result


Here the lowest, middle and highest channels are selected to perform testing to verify the conducted RF output power of the EUT. For the GSM 850MHz operates at PCL=5 (where Power Class is 4), the rated conducted RF output power is 33dBm within the tolerance of  $\pm 3$ dB, and For the GSM 1900MHz operates at PCL=0 (where Power Class is 1), the rated conducted RF output power is 30dBm within the tolerance of  $\pm 3$ dB.

#### 1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Output Power		Rated Output Power		Verdict
			dBm	Refer to Plot	dBm	Tolerance (dB)	
GSM 850MHz	128	824.2	27.70	Plot A	33	$\pm 3$	PASS
	190	836.6	27.87	Plot B			PASS
	251	848.8	27.91	Plot C			PASS
GSM 1900MHz	512	1850.2	23.22	Plot D	30	$\pm 3$	PASS
	661	1880.0	23.60	Plot E			PASS
	810	1909.8	23.70	Plot F			PASS


#### 2. Test Plot:






Date: 24.JUN.2008 08:20:12

(Plot A: GSM 850MHz Channel = 128)




Date: 24.JUN.2008 08:23:10

(Plot B: GSM 850MHz Channel = 190)




Date: 24.JUN.2008 08:25:00

(Plot C: GSM 850MHz Channel = 251)




Date: 24.JUN.2008 10:40:07

(Plot D: GSM 1900MHz Channel = 512)



Date: 24.JUN.2008 10:41:06

(Plot E: GSM 1900MHz Channel = 661)



Date: 24.JUN.2008 10:41:53

(Plot F: GSM 1900MHz Channel = 810)

### 3.3 20dB Occupied Bandwidth

#### 3.3.1 Definition

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Occupied bandwidth is also known as the 99% emission bandwidth, or 20dB bandwidth ( $10 \cdot \log 1\% = 20\text{dB}$ ) taking the total RF output power as reference.

#### 3.3.2 Test Description

See section 3.1.2 of this report.

#### 3.3.3 Test Verdict


Here the lowest, middle and highest channels are tested to record the 20dB occupied bandwidth, it's about 300kHz.

1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured 20dB Occupied Bandwidth (kHz)	Refer to Plot
GSM 850MHz	128	824.2	276.0	Plot A
	190	836.6	276.0	Plot B
	251	848.8	276.0	Plot C
GSM 1900MHz	512	1850.2	270.0	Plot D
	661	1880.0	276.0	Plot E
	810	1909.8	282.0	Plot F


2. Test Plot:






Date: 24.JUN.2008 09:49:53

(Plot A: GSM 850MHz Channel = 128)




Date: 24.JUN.2008 09:55:51

(Plot B: GSM 850MHz Channel = 190)




Date: 24.JUN.2008 10:03:17

(Plot C: GSM 850MHz Channel = 251)




Date: 24.JUN.2008 10:46:36

(Plot D: GSM 1900MHz Channel = 512)



Date: 24.JUN.2008 10:48:09

(Plot E: GSM 1900MHz Channel = 661)



Date: 24.JUN.2008 10:50:07

(Plot F: GSM 1900MHz Channel = 810)

### 3.4 Frequency Stability


#### 3.4.1 Requirement

According to FCC section 22.355 and FCC section 24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- The temperature is varied from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  at intervals of not more than  $10^{\circ}\text{C}$ .
- For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

#### 3.4.2 Test Description

##### 1. Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.

##### 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Agilent	E5515C	GB43130131	2007.06	1year
DC Power Supply	Good Will	GPS-3030DD	EF920938	2007.06	2year
Temperature Chamber	YinHe Experimental Equip.	HL4003T	(n.a.)	2007.03	1year

#### 3.4.3 Test Verdict

The nominal, highest and lowest extreme voltages are separately 3.7VDC, 4.2VDC and 3.6VDC, which are specified by the applicant; the normal temperature here used is  $25^{\circ}\text{C}$ . The frequency



deviation limit is  $\pm 2.5$ ppm.

Band	Test Conditions		Frequency Deviation						Verdict
	Power (VDC)	Temperature (°C)	Channel = 128 (824.2MHz)		Channel = 190 (836.6MHz)		Channel = 251 (848.8MHz)		
			Hz	Limit	Hz	Limit	Hz	Limit	
GSM 850MHz	4.0	-30	-14.25	±2060.5	13.52	±2091.5	-16.57	±2122.0	PASS
		-20	12.23		-12.37		-10.36		
		-10	13.35		10.01		16.51		
		0	-13.25		11.25		16.25		
		+10	-15.63		12.56		10.54		
		+20	-12.52		-11.63		15.60		
		+30	11.25		10.21		13.55		
		+40	-11.15		-12.59		13.95		
		+50	-12.74		-19.73		12.34		
	4.4	+25	-11.02	-13.57	13.46				
	3.6	+25	-14.12	-17.51	12.38				
GSM 1900MHz	4.0	-30	24.65	±1550.2	-32.47	±1550.0	25.64	±1707.5	PASS
		-20	16.35		15.20		12.55		
		-10	-13.42		7.21		-11.35		
		0	13.75		10.47		-16.56		
		+10	10.21		5.75		15.16		
		+20	17.21		26.11		-20.22		
		+30	-11.76		-12.47		-10.62		
		+40	-15.77		13.25		14.06		
		+50	13.62		21.90		-12.24		
	4.4	+25	-12.56	-7.57	-15.53				
	3.6	+25	-5.67	-17.07	15.53				

### 3.5 Conducted Out of Band Emissions

#### 3.5.1 Requirement

According to FCC section 22.717(a) and FCC section 24.235(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

#### 3.5.2 Test Description

See section 3.1.2 of this report.

#### 3.5.3 Test Result


The measurement frequency range is from 30MHz to the 10<sup>th</sup> harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.

##### 1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	824.2	-29.49	Plot A.1/A.2	-13	PASS
	190	836.6	-29.96	Plot B.1/B.2		PASS
	251	848.8	-30.89	Plot C.1/C.2		PASS
GSM 1900MHz	512	1850.2	---	Plot D.1/D.2	-13	PASS
	661	1880.0	---	Plot E.1/E.2		PASS
	810	1909.8	---	Plot F.1/F.2		PASS


##### 2. Test Plot for the Whole Measurement Frequency Range:

Note: the power of the EUT transmitting frequency should be ignored.




Date: 25.JUN.2008 09:57:40

(Plot A.1:GSM 850MHz Channel = 128, 30MHz to 1GHz)




Date: 25.JUN.2008 09:53:29

(Plot A.2: GSM 850MHz Channel = 190, 30MHz to 1GHz)



Date: 25.JUN.2008 09:58:51


(Plot B.1: GSM 850MHz Channel = 190, 1GHz to 9GHz)



Date: 24.JUN.2008 11:21:41


(Plot B.2: GSM 850MHz Channel = 190, 1GHz to 9GHz)






Date: 24.JUN.2008 09:21:23

(Plot C.1:GSM 850MHz Channel = 251, 30MHz to 1GHz)




Date: 25.JUN.2008 09:55:48

(Plot C.2:GSM 850MHz Channel = 251, 1GHz to 9GHz)




Date: 24.JUN.2008 10:54:01

(Plot D.1:GSM 1900MHz Channel = 512, 30MHz to 2GHz)




Date: 24.JUN.2008 10:57:09

(Plot D.2:GSM 1900MHz Channel = 512, 2GHz to 20GHz)




Date: 25.JUN.2008 10:02:33

(Plot E.1:GSM 1900MHz Channel = 661, 30MHz to 2GHz)




Date: 25.JUN.2008 10:04:37

(Plot E.2:GSM 1900MHz Channel = 661, 2GHz to 20GHz)



Date: 25.JUN.2008 11:05:53

(Plot F.1:GSM 1900MHz Channel = 810, 30MHz to 2GHz)



Date: 25.JUN.2008 11:07:35

(Plot F.2:GSM 1900MHz Channel = 810, 2GHz to 20GHz)

### 3.6 Band Edge

#### 3.6.1 Requirement

According to FCC section 22.717(b) and FCC section 24.235(b), in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth (26dB emission bandwidth) of the fundamental emission of the transmitter may be employed.

#### 3.6.2 Test Description

See section 3.1.2 of this report.

#### 3.6.3 Test Result


The lowest and highest channels are tested to verify the band edge emissions.

##### 1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Band Edge Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	824.2	-18.03	Plot A	-13	PASS
	251	848.8	-16.45	Plot B		PASS
GSM 1900MHz	512	1850.2	-22.69	Plot C	-13	PASS
	810	1909.8	-20.45	Plot D		PASS


##### 2. Test Plot:






Date: 25.JUN.2008 10:16:12

(Plot A: GSM 850MHz Channel = 128)




Date: 25.JUN.2008 10:08:13

(Plot B: GSM 850MHz Channel = 251)



Date: 25.JUN.2008 10:10:59

(Plot C: GSM 1900MHz Channel = 512)



Date: 24.JUN.2008 11:07:14

(Plot D: GSM 1900MHz Channel = 810)


### 3.7 Transmitter Radiated Power (EIRP/ERP)

#### 3.7.1 Requirement

According to FCC section 22.713, the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7Watts, and FCC section 24.232, the broadband PCS mobile station is limited to 2Watts e.i.r.p. peak power.

#### 3.7.2 Test Description

##### 1. Test Setup:



The EUT, which is powered by the Battery charged with the AC Adapter, is located in a 3m Full-Anechoic Chamber; the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. GSM550MHz band Power Control Level (PCL) = 5 and Power Class = 4 and GSM1700MHz band Power Control Level (PCL) = 0 and Power Class = 1. A call is established between the EUT and the SS via a Common Antenna.

The Test Antenna is a Bi-Log one (used for 30MHz to 1GHz) or a Horn one (used for above 3GHz), and it's located at the same height as the EUT. The Filters consists of Notch Filters and High Pass Filter.

##### 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Agilent	E5515C	GB43130131	2006.06	1year

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E7405A	US44210471	2006.07	1year
Full-Anechoic Chamber	Albatross	7m*6m*6m	(n.a.)	2006.05	2year
Test Antenna - Bi-Log	Schwarzbeck	VULB 7163	7163-274	2006.07	1year
Test Antenna - Horn	Schwarzbeck	BBHA 7120C	7120C-354	2006.07	1year


### 3.7.3 Test Result

The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested.

#### 1. Test Verdict:


Band	Channel	Frequency (MHz)	Measured ERP			Limit		Verdict
			dBm	W	Refer to Plot	dBm	W	
GSM 850MHz	128	824.2	20.29	0.106	Plot A	35.45	7	PASS
	190	836.6	20.14	0.103	Plot B			PASS
	251	848.8	20.01	0.100	Plot C			PASS
GSM 1900MHz	512	1850.2	11.70	0.014	Plot D	33	2	PASS
	661	1880.0	11.06	0.012	Plot E			PASS
	810	1909.8	10.07	0.010	Plot F			PASS

#### 2. Test Plot:




Date: 24.JUN.2008 11:40:48

(Plot A: GSM 850MHz Channel = 128)




Date: 24.JUN.2008 11:38:52

(Plot B: GSM 850MHz Channel = 190)




Date: 24.JUN.2008 11:39:47

(Plot C: GSM 850MHz Channel = 251)




Date: 25.JUN.2008 10:32:31

(Plot D: GSM 1900MHz Channel = 512)



Date: 25.JUN.2008 10:38:22

(Plot E: GSM 1900MHz Channel = 661)



Date: 25.JUN.2008 10:56:55

(Plot F: GSM 1900MHz Channel = 810)

### 3.8 Radiated Out of Band Emissions

#### 3.8.1 Requirement

According to FCC section 22.717(a) and section 24.235(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

#### 3.8.2 Test Description

See section 3.7.2 of this report.

#### 3.8.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

##### 1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)		Refer to Plot	Limit (dBm)	Verdict
			Test Antenna Horizontal	Test Antenna Vertical			
GSM 850MHz	128	824.2	< -30	< -30	Plot A.1/A.2	-13	PASS
	190	836.6	< -30	< -30	Plot B.1/B.2		PASS
	251	848.8	< -30	< -30	Plot C.1/C.2		PASS
GSM 1900MHz	512	1850.2	< -25	< -25	Plot D.1/D.2	-13	PASS
	661	1880.0	< -25	< -25	Plot E.1/E.2		PASS
	810	1909.8	< -25	< -25	Plot F.1/F.2		PASS




## Appendix I: Photograph of the Test Setup

### 1. Conducted RF Test




### 2. Radiated RF Test




**Appendix II: Photograph of the EUT**

## 1. Appearance of the MS module






2. Inside of the MS module



3. Appearance of MS base







#### 4. Appearance of the Charge



5. Inside of the Charge





6. Cable



\*\* END OF REPORT \*\*