

RF Exposure Report

Report No.: SA180704E02I

FCC ID: UDX-60083010

Test Model: MR55-HW

Received Date: Oct. 18, 2018

Test Date: Oct. 18, 2018 to Jan. 02, 2019

Issued Date: Mar. 12, 2019

Applicant: Cisco Systems, Inc.

Address: 170 West Tasman Drive, San Jose, CA 95134 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA180704E02I	Original release.	Mar. 12, 2019

1 Certificate of Conformity

Product: 8x8 802.11a/b/g/n/ac/ax Access Point

Brand: Cisco

Test Model: MR55-HW

Sample Status: ENGINEERING SAMPLE

Applicant: Cisco Systems, Inc.

Test Date: Oct. 18, 2018 to Jan. 02, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Phoenix Huang

Date:

Mar. 12, 2019

Phoenix Huang / Specialist

Approved by :

May Chen

Date:

Mar. 12, 2019

May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 34cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WLAN Directional gain table – 8TX

Frequency range (GHz)	Directional Antenna Gain (dBi)	Antenna Type	Antenna Connector
5.15 ~ 5.25	9.29	PIFA	i-pex(MHF)
5.25 ~ 5.35	9.34		
5.47 ~ 5.725	8.88		
5.725 ~ 5.85	9.2		

WLAN Directional gain table – 4TX

Frequency range (GHz)	Antenna Combine Type	Directional Antenna Gain (dBi)	Antenna Type	Antenna Connector
2.4 ~ 2.4835	Dual_1+Dual_2+Dual_3+Dual_4	5.43	PIFA	i-pex(MHF)
5.15 ~ 5.25	Single_1+Single_2+Single_3+Single_4	10.73		
5.25 ~ 5.35		10.71		
5.47 ~ 5.725		10.33		
5.725 ~ 5.85		10.68		

WLAN Directional gain table – 2TX

Frequency range (GHz)	Antenna Combine Type	Directional Antenna Gain (dBi)	Antenna Type	Antenna Connector
2.4 ~ 2.4835	Dual_1+Dual_3	6.33	PIFA	i-pex(MHF)
5.15 ~ 5.25	Dual_2+Dual_3	8.47		
5.25 ~ 5.35		8.92		
5.47 ~ 5.725		8.16		
5.725 ~ 5.85		8.59		

Bluetooth antenna spec.

Antenna Net Gain (dBi)	Frequency range (GHz)	Antenna Type	Antenna Connector
3.61	2.4~2.4835	PIFA	i-pex(MHF)

Note: More detailed information, please refer to operating description.

2.5 Calculation Result of Maximum Conducted Power

For 2.4GHz, 5GHz (U-NII-1 & UNII-3 band) and Bluetooth data was copied from the original test report (Report No.: SA180704E02)

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz (4TX)	2437	864.55	5.43	34	0.20779	1
WLAN 2.4GHz (2TX)	2437	456.82	6.33	34	0.13508	1
WLAN 2.4GHz (1TX)	2437	204.174	5.54	34	0.05033	1
WLAN U-NII-1 (8TX)	5180	432.724	9.29	34	0.25295	1
WLAN U-NII-1 (4TX)	5230	430.677	10.73	34	0.35074	1
WLAN U-NII-1 (2TX)	5200	376.099	8.47	34	0.18203	1
WLAN U-NII-1 (1TX)	5200	224.905	6.2	34	0.06454	1
WLAN U-NII-2A (8TX)	5290	112.582	9.34	34	0.06657	1
WLAN U-NII-2A (4TX)	5270	156.395	10.71	34	0.12678	1
WLAN U-NII-2A (2TX)	5270	224.418	8.92	34	0.12047	1
WLAN U-NII-2A (1TX)	5300	110.662	6.44	34	0.03356	1
WLAN U-NII-2C (8TX)	5550	127.845	8.88	34	0.06800	1
WLAN U-NII-2C (4TX)	5610	238.486	10.33	34	0.17713	1
WLAN U-NII-2C (2TX)	5670	227.318	8.16	34	0.10244	1
WLAN U-NII-2C (1TX)	5580	110.662	5.8	34	0.02896	1
WLAN U-NII-3 (8TX)	5825	412.219	9.2	34	0.23603	1
WLAN U-NII-3 (4TX)	5825	902.442	10.68	34	0.72653	1
WLAN U-NII-3 (2TX)	5745	440.884	8.59	34	0.21936	1
WLAN U-NII-3 (1TX)	5745	238.781	6.39	34	0.07159	1
BT-LE	2402	4.508	3.61	34	0.00071	1

Note:

1. The Max. Power = Max. tune up power including tolerance.
2. 2.4GHz (4TX): The directional gain = 5.43dBi
2.4GHz (2TX): The directional gain = 6.33dBi
2.4GHz (1TX): The max. gain = 5.54dBi
5GHz:
U-NII-1 (8TX): The directional gain = 9.29dBi
U-NII-1 (4TX): The directional gain = 10.73dBi
U-NII-1 (2TX): The directional gain = 8.47dBi
U-NII-1 (1TX): The max. gain = 6.2dBi
U-NII-2A (8TX): The directional gain = 9.34dBi
U-NII-2A (4TX): The directional gain = 10.71dBi
U-NII-2A (2TX): The directional gain = 8.92dBi
U-NII-2A (1TX): The max. gain = 6.44dBi
U-NII-2C (8TX): The directional gain = 8.88dBi
U-NII-2C (4TX): The directional gain = 10.33dBi
U-NII-2C (2TX): The directional gain = 8.16dBi
U-NII-2C (1TX): The max. gain = 5.8dBi
U-NII-3 (8TX): The directional gain = 9.2dBi
U-NII-3 (4TX): The directional gain = 10.68dBi
U-NII-3 (2TX): The directional gain = 8.59dBi
U-NII-3 (1TX): The max. gain = 6.39dBi

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$WLAN\ 2.4GHz + WLAN\ 5GHz + Bluetooth = 0.20779 / 1 + 0.72653 / 1 + 0.00071 / 1 = 0.93503$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---