

Report No.: FR831635C



## **FCC RADIO TEST REPORT**

FCC ID : UDX-60076027

Equipment : LTE & Wi-Fi Router

Brand Name : CISCO

Model name : MX68CW-HW-NA

Applicant : Cisco Systems, Inc.

170 West Tasman Drive, San Jose,

CA 95134

Standard : FCC Part 15 Subpart E §15.407

The product was received on Mar. 16, 2018 and testing was started from Mar. 29, 2018 and completed on Aug. 02, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 31 FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## **Table of Contents**

Report No.: FR831635C

His	tory o	of this test report	3
Sur	nmary	y of Test Result	4
1	Gene	eral Description	5
	1.1	Product Feature of Equipment Under Test	5
	1.2	Modification of EUT	5
	1.3	Testing Location	6
	1.4	Applicable Standards	6
2	Test	Configuration of Equipment Under Test	7
	2.1	Carrier Frequency and Channel	7
	2.2	Test Mode	8
	2.3	Connection Diagram of Test System	9
	2.4	Support Unit used in test configuration and system	9
	2.5	EUT Operation Test Setup	10
	2.6	Measurement Results Explanation Example	10
3	Test	Result	11
	3.1	6dB and 26dB and 99% Occupied Bandwidth Measurement	11
	3.2	Maximum Conducted Output Power Measurement	14
	3.3	Power Spectral Density Measurement	15
	3.4	Unwanted Emissions Measurement	18
	3.5	AC Conducted Emission Measurement	24
	3.6	Automatically Discontinue Transmission	26
	3.7	Antenna Requirements	27
4	List	of Measuring Equipment	29
5	Unce	rtainty of Evaluation	31
App	pendi	x A. Conducted Test Results	
App	endi	x B. AC Conducted Emission Test Result	
App	endi	x C. Radiated Spurious Emission	
App	endi	x D. Radiated Spurious Emission Plots	
App	endi	x E. Duty Cycle Plots	
App	endi	x F. Setup Photographs	

TEL: 886-3-327-3456 Page Number : 2 of 31 FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018 : 01

Report Version

Report Template No.: BU5-FR15EWLB4 AC MA Version 2.1

## History of this test report

Report No.: FR831635C

Report No.	Version	Description	Issued Date
FR831635C	01	Initial issue of report	Sep. 05, 2018

TEL: 886-3-327-3456 Page Number : 3 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## **Summary of Test Result**

Report No.: FR831635C

Report Clause	lest Items		Result (PASS/FAIL)	Remark
3.1	15.403 (i)	6dB & 26dB Bandwidth	Pass	
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407 (a)	Maximum Conducted Output Power	Pass	-
3.3	15.407 (a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	Under limit 1.13 dB at 5649.000 MHz
3.5	15.207	AC Conducted Emission	Pass	Under limit 21.24 dB at 19.415 MHz
3.6	15.407 (c)	Automatically Discontinue Transmission	Pass	-
3.7	15.203 & 15.407 (a)	Antenna Requirement	Pass	-

Reviewed by: Joseph Lin Report Producer: Fish Liu

TEL: 886-3-327-3456 Page Number : 4 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 1 General Description

## 1.1 Product Feature of Equipment Under Test

GSM/ WCDMA/LTE, Wi-Fi 2.4GHz 802.11b/g/n/ac, Wi-Fi 5GHz 802.11a/n/ac.

<u> </u>					
Pr	Product Specification subjective to this standard				
	WWAN:  Main: Dipole Antenna				
Antenna Type	Aux.: Dipole Antenna WLAN:				
	Ant. 1: Dipole Antenna				
	Ant. 2: Dipole Antenna				

Report No.: FR831635C

### 1.2 Modification of EUT

No modifications are made to the EUT during all test items.

TEL: 886-3-327-3456 Page Number : 5 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Report No.: FR831635C

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978			
Test Site No.	Sporton	Site No.		
rest site No.	TH05-HY	CO05-HY		

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH10-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

## 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2013

#### Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

TEL: 886-3-327-3456 Page Number : 6 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

Report No.: FR831635C

b. AC power line Conducted Emission was tested under maximum output power.

## 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	149	5745	157	5785
5725-5850 MHz Band 4	151*	5755	159*	5795
(U-NII-3)	153	5765	161	5805
(8 1111 8)	155#	5775	165	5825

#### Note:

- 1. The above Frequency and Channel in "\*" were 802.11n HT40 and 802.11ac VHT40.
- 2. The above Frequency and Channel in "#" were 802.11ac VHT80.

TEL: 886-3-327-3456 Page Number : 7 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

#### **MIMO Mode**

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0

Report No.: FR831635C

#### **TXBF Mode (Power Only)**


Modulation	Data Rate
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0

	Test Cases						
AC Conducted Emission	Mode 1: RJ-45 (LAN) Link + RJ-45 (WAN) Link + USB Link + Adapter + POE + WLAN (5GHz) Link						

Ch. #		Band IV:5725-5850 MHz				
	Cn. #	802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80	
L	Low	149	149	151	-	
M	Middle	157	157	-	155	
Н	High	165	165	159	-	

TEL: 886-3-327-3456 Page Number : 8 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 2.3 Connection Diagram of Test System



Report No.: FR831635C

## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	ASUS	P2430U	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	USB Flash Drive	Transcend	N/A	FCC DoC	N/A	N/A

TEL: 886-3-327-3456 Page Number : 9 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 2.5 EUT Operation Test Setup

The RF test items, utility "QRCT" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

Report No.: FR831635C

### 2.6 Measurement Results Explanation Example

#### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

#### Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 4.2 + 10 = 14.2 (dB)

TEL: 886-3-327-3456 Page Number : 10 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

### 3 Test Result

## 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

#### 3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz. 26dB and 99% Occupied bandwidth are reporting only.

### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.1.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
 Section C) Emission bandwidth for the band 5.725-5.85GHz

Report No.: FR831635C

- 2. Set RBW = 100kHz.
- 3. Set the VBW  $\geq$  3 x RBW.
- 4. Detector = Peak.
- 5. Trace mode = max hold
- 6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
- 7. Measure and record the results in the test report.

#### 3.1.4 Test Setup




#### 3.1.5 Test Result of 6dB Bandwidth


Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 11 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018







Report No.: FR831635C



TEL: 886-3-327-3456 Page Number : 12 of 31 FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018 : 01





**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

TEL: 886-3-327-3456 Page Number : 13 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 3.2 Maximum Conducted Output Power Measurement

#### 3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

Report No.: FR831635C

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

- 1. Measurement is performed using a wideband RF power meter.
- 2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
- 3. Measure the average power of the transmitter, and the average power is corrected with duty factor,  $10 \log(1/x)$ , where x is the duty cycle.

#### 3.2.4 Test Setup



#### 3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 14 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 3.3 Power Spectral Density Measurement

### 3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

Report No.: FR831635C

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

#### # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(500kHz/RBW) to the test result.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

TEL: 886-3-327-3456 Page Number : 15 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

- 1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
- 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.


Report No.: FR831635C

3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add 10 log(N<sub>ANT</sub>) dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity  $10 \log(N_{ANT})$  dB is added to each spectrum value before comparing to the emission limit. The addition of  $10 \log(N_{ANT})$  dB serves to apportion the emission limit among the  $N_{ANT}$  outputs so that each output is permitted to contribute no more than  $1/N_{ANT}$  th of the PSD limit.


#### 3.3.4 Test Setup




#### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 16 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018



Report No.: FR831635C



TEL: 886-3-327-3456 Page Number : 17 of 31 FAX: 886-3-328-4978 : Sep. 05, 2018 Issued Date : 01

Report Version Report Template No.: BU5-FR15EWLB4 AC MA Version 2.1

#### 3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

Report No.: FR831635C

#### 3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band: 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

**Note:** The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3}$$
 µV/m, where P is the eirp (Watts)

TEL: 886-3-327-3456 Page Number : 18 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.3

Report No.: FR831635C

#### (3) KDB789033 D02 v02r01 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.<sup>3</sup>
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.<sup>4</sup>
- **Note 3:** An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.
- **Note 4:** Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

#### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

TEL: 886-3-327-3456 Page Number : 19 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

#### 3.4.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

Report No.: FR831635C

- (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
  - RBW = 120 kHz
  - VBW = 300 kHz
  - Detector = Peak
  - Trace mode = max hold
- (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
  - RBW = 1 MHz
  - VBW ≥ 3 MHz
  - Detector = Peak
  - Sweep time = auto
  - Trace mode = max hold
- (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
  - RBW = 1 MHz
  - VBW = 10 Hz, when duty cycle is no less than 98 percent.
  - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

TEL: 886-3-327-3456 Page Number : 20 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.


Report No.: FR831635C

: 01

- 3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- 4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
- 5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
- 6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR guasi-peak method and reported.
- 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


#### 3.4.4 Test Setup

#### For radiated emissions below 30MHz




TEL: 886-3-327-3456 Page Number : 21 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

#### For radiated emissions from 30MHz to 1GHz



Report No.: FR831635C

#### For radiated emissions above 1GHz



TEL: 886-3-327-3456 Page Number : 22 of 31 FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018 : 01

Report Version

Report Template No.: BU5-FR15EWLB4 AC MA Version 2.1

#### 3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Report No.: FR831635C

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### 3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

#### 3.4.7 Duty Cycle

Please refer to Appendix E.

### 3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

TEL: 886-3-327-3456 Page Number : 23 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

#### 3.5 AC Conducted Emission Measurement

#### 3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR831635C

Frequency of emission (MHz)	Conducted limit (dBμV)			
	Quasi-peak	Average		
0.15-0.5	66 to 56*	56 to 46*		
0.5-5	56	46		
5-30	60	50		

<sup>\*</sup>Decreases with the logarithm of the frequency.

#### 3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

#### 3.5.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

TEL: 886-3-327-3456 Page Number : 24 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

### 3.5.4 Test Setup



Report No.: FR831635C

AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

### 3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

TEL: 886-3-327-3456 Page Number : 25 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 3.6 Automatically Discontinue Transmission

#### 3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

Report No.: FR831635C

#### 3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

TEL: 886-3-327-3456 Page Number : 26 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

### 3.7 Antenna Requirements

#### 3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Report No.: FR831635C

#### 3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

#### 3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = GANT + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = 10 log(NANT/NSS=1) dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with

GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain  $G_{ANT}$  is set equal to the antenna having the highest gain, i.e., F(2)f(i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<cdd mod<="" th=""><th>les&gt;</th><th></th><th></th><th></th><th></th><th></th></cdd>	les>					
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 1	Ant. 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	4.32	5.84	5.84	8.12	0.00	2.12

Power Limit Reduction = DG(Power) - 6dBi, ( min = 0 )

 $PSD \ Limit \ Reduction = DG(PSD) - 6dBi, \ (min = 0)$ 

TEL: 886-3-327-3456 Page Number : 27 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

#### **TXBF modes**

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

$$Directional Gain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^{2}}{N_{ANT}} \right]$$

Report No.: FR831635C

where

Each antenna is driven by no more than one spatial stream;

 $N_{SS}$  = the number of independent spatial streams of data;

 $N_{ANT}$  = the total number of antennas

 $g_{j,k} = 10^{G_k/20}$  if the kth antenna is being fed by spatial stream j, or zero if it is not;  $G_k$  is the gain in dBi of the kth antenna.

The EUT supports beamforming for 802.11ac modes.

The directional gain calculation is following F)2)e)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	4.32	5.84	8.12	8.12	2.12	2.12

Power Limit Reduction = DG(Power) - 6dBi, (min = 0)

 $PSD \ Limit \ Reduction = DG(PSD) - 6dBi, \ (min = 0)$ 

TEL: 886-3-327-3456 Page Number : 28 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	DTM-303A	TP157075	N/A	Mar. 06, 2018	Mar. 29, 2018~ Aug. 02, 2018	Mar. 05, 2019	Conducted (TH05-HY)
Power Meter	Anritsu	ML2495A	1240001	N/A	Sep. 07, 2017	Mar. 29, 2018~ Aug. 02, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207349	300MHz~40GHz	Sep. 07, 2017	Mar. 29, 2018~ Aug. 02, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9kHz ~ 30GHz	Nov. 13, 2017	Mar. 29, 2018~ Aug. 02, 2018	Nov. 12, 2018	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Mar. 01, 2018	Mar. 29, 2018~ Aug. 02, 2018	Feb. 28, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 23, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	3.6GHz	Dec. 08, 2017	Jul. 23, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Jul. 23, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 23, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Jul. 23, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Jul. 23, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 19, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 18, 2018	Radiation (03CH10-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Apr. 12, 2018~ Jun. 06, 2018	Jul. 17, 2018	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D&0080 0N1D01N-06	35413&02	30MHz~1GHz	Dec. 18, 2017	Apr. 12, 2018~ Jun. 06, 2018	Dec. 17, 2018	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1325	1GHz ~ 18GHz	Sep. 27, 2017	Apr. 12, 2018~ Jun. 06, 2018	Sep. 26, 2018	Radiation (03CH10-HY)
Hygrometer	TECPEL	DTM-303B	TP140320	N/A	Oct. 12, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 11, 2018	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY53270078	1GHz~26.5GHz	Oct. 25, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 24, 2018	Radiation (03CH10-HY)
Preamplifier	Jet-Power	JPA0010180 0-30-10P	1601180002	1GHz~18GHz	Jul. 31, 2017	Apr. 12, 2018~ Jun. 06, 2018	Jul .30, 2018	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Oct. 31, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 30, 2018	Radiation (03CH10-HY)

Report No.: FR831635C

TEL: 886-3-327-3456 Page Number : 29 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Apr. 12, 2018~ Jun. 06, 2018	N/A	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500 -B	N/A	1~4m	N/A	Apr. 12, 2018~ Jun. 06, 2018	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Apr. 12, 2018~ Jun. 06, 2018	N/A	Radiation (03CH10-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Apr. 12, 2018~ Jun. 06, 2018	N/A	Radiation (03CH10-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Apr. 12, 2018~ Jun. 06, 2018	Nov. 22, 2018	Radiation (03CH10-HY)
Filter	Woken	WHKX8-587 2.5-6750-18 000-40ST	SN3	6.75G High Pass	Sep. 18, 2017	Apr. 12, 2018~ Jun. 06, 2018	Sep. 17, 2018	Radiation (03CH10-HY)
Filter	Wainwright	WHKX12-27 00-3000-180 00-60ST	SN2	3 GHz Highpas s	Jul. 17, 2017	Apr. 12, 2018~ Jun. 06, 2018	Jul. 18, 2018	Radiation (03CH10-HY)
Filter	Wainwright	WLKS1200- 12SS	SN2	1.2G Low Pass	Jul. 17, 2017	Apr. 12, 2018~ Jun. 06, 2018	Jul. 16, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4,M Y28655/4	9K-30M	Jan. 02, 2018	Apr. 12, 2018~ Jun. 06, 2018	Jan. 01, 2019	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	30M-1G	Nov. 14, 2017	Apr. 12, 2018~ Jun. 06, 2018	Nov. 13, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	1G-18G	Nov. 14, 2017	Apr. 12, 2018~ Jun. 06, 2018	Nov. 13, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40G	Oct. 17, 2017	Apr. 12, 2018~ Jun. 06, 2018	Oct. 16, 2018	Radiation (03CH10-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY53290053	20Hz to 26.5GHz	Jan. 16, 2018	Apr. 12, 2018~ Jun. 06, 2018	Jan. 15, 2019	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Apr. 12, 2018~ Jun. 06, 2018	Nov. 26, 2018	Radiation (03CH10-HY)

Report No. : FR831635C

TEL: 886-3-327-3456 Page Number : 30 of 31
FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## 5 Uncertainty of Evaluation

#### <u>Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)</u>

Measuring Uncertainty for a Level of Confidence	2.70
of 95% (U = 2Uc(y))	<u> </u>

Report No.: FR831635C

#### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence	5.60
of 95% (U = 2Uc(y))	5.60

#### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	5.90
of 95% (U = 2Uc(y))	5.90

#### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	
of 95% (U = 2Uc(y))	5.20

TEL: 886-3-327-3456 Page Number : 31 of 31 FAX: 886-3-328-4978 Issued Date : Sep. 05, 2018

## **Appendix A. Test Result of Conducted Test Items**

#### <CDD Mode>

Test Engineer:	Allen Lin/Shiming Liu	Temperature:	21~25	°C
Test Date:	2018/3/29~2018/8/2	Relative Humidity:	51~54	%

### TEST RESULTS DATA 6dB and 26dB EBW and 99% OBW

Band IV															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)		Pass/Fail		
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2			
11a	6Mbps	2	149	5745	18.05	17.45	34.15	31.80	16.25	15.90	0.5		Pass		
11a	6Mbps	2	157	5785	18.20	17.70	33.80	32.60	16.30	16.30	0.5		Pass		
11a	6Mbps	2	165	5825	19.65	17.85	39.70	34.35	16.25	16.30	0.5		0.5		Pass
HT20	MCS0	2	149	5745	18.70	18.45	35.50	29.15	16.20	15.95	0.5		Pass		
HT20	MCS0	2	157	5785	18.65	18.45	32.95	25.05	17.15	17.55	0.5		0.5		Pass
HT20	MCS0	2	165	5825	18.90	18.60	36.40	28.75	17.50	17.50	0.5		0.5		Pass
HT40	MCS0	2	151	5755	36.90	36.60	63.16	51.26	35.10	35.10	0.5		Pass		
HT40	MCS0	2	159	5795	37.00	36.70	74.54	65.20	35.10	35.10	0.5		Pass		
VHT80	MCS0	2	155	5775	75.96	75.84	83.52	83.72	75.84	76.30	0.5		Pass		

## TEST RESULTS DATA Average Power Table

	Band IV																					
Mod	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail								
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2									
11a	6Mbps	2	149	5745	0.17	0.15	20.66	20.55	23.61	30.00		5.84		Pass								
11a	6Mbps	2	157	5785	0.17	0.15	20.86	20.73	23.80	30.00		5.84		Pass								
11a	6Mbps	2	165	5825	0.17	0.15	21.10	20.95	24.03	30.00		5.84		Pass								
HT20	MCS0	2	149	5745	0.10	0.10	20.55	20.33	23.45	30.00		5.84		Pass								
HT20	MCS0	2	157	5785	0.10	0.10	20.51	20.50	23.52	30.00		5.8	34	Pass								
HT20	MCS0	2	165	5825	0.10	0.10	20.92	20.60	23.78	30.00		5.8	34	Pass								
HT40	MCS0	2	151	5755	0.11	0.11	20.71	20.47	23.60	30.00		30.00		5.8	34	Pass						
HT40	MCS0	2	159	5795	0.11	0.11	20.84	20.71	23.78	30.00		30.00		30.00		5.8	34	Pass				
VHT20	MCS0	2	149	5745	0.10	0.10	20.54	20.32	23.44	30.00		30.00		30.00		30.00 5.84		Pass				
VHT20	MCS0	2	157	5785	0.10	0.10	20.50	20.47	23.50	30.00		30.00		30.00		30.00		30.00		5.84		Pass
VHT20	MCS0	2	165	5825	0.10	0.10	20.90	20.55	23.74	30.00		5.8	34	Pass								
VHT40	MCS0	2	151	5755	0.14	0.14	21.09	20.99	24.05	30.00		30.00		30.00		5.8	34	Pass				
VHT40	MCS0	2	159	5795	0.14	0.14	20.79	20.70	23.76	30.00		30.00		5.8	34	Pass						
VHT80	MCS0	2	155	5775	0.26	0.26	16.84	16.86	19.86	30.00		30.00		5.8	34	Pass						

Power Setting
20.5
21
21
21
21
21
21
21
21
21
21
21
21
17.5

# TEST RESULTS DATA Power Spectral Density

	Band IV															
Mod	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)		Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail	
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	0.17	0.15	2.22		8.93	8.39	11.94	27.88		8.	12	Pass
11a	6Mbps	2	157	5785	0.17	0.15	2.22		8.66	8.31	11.67	27.88		8.12		Pass
11a	6Mbps	2	165	5825	0.17	0.15	2.22		9.22	8.72	12.23	27.88		8.	12	Pass
HT20	MCS0	2	149	5745	0.10	0.10	2.22		8.19	8.13	11.20	27.88		8.	12	Pass
HT20	MCS0	2	157	5785	0.10	0.10	2.22		7.94	7.72	10.95	27.88		8.	12	Pass
HT20	MCS0	2	165	5825	0.10	0.10	2.22		2.22 8.44 7.93 11.45 27.88 8		27.88		8.	12	Pass	
HT40	MCS0	2	151	5755	0.11	0.11	2.22		5.89	5.75	8.90	27.88		8.	12	Pass
HT40	MCS0	2	159	5795	0.11	0.11	2.22		5.74	5.32	8.75	27.88		8.	12	Pass
VHT80	MCS0	2	155	5775	0.26	0.26	2.22		-1.49	-1.93	1.52	27.88		8.	12	Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

#### <TXBF Mode>

Test Engineer:	Allen Lin/Shiming Liu	Temperature:	21~25	°C
Test Date:	2018/3/29~2018/8/2	Relative Humidity:	51~54	%

Report Number : FR831635C

### <u>TEST RESULTS DATA</u> <u>Average Power Table</u>

							Ва	and IV						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Fac	uty ctor B)		Average conducte Power (dBm)		Cond Powe	CC ucted r Limit Bm)		G Bi)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HT20	MCS0	2	149	5745	0.10	0.10	17.54	17.32	20.44	27.	.88	8.	12	Pass
HT20	MCS0	2	157	5785	0.10	0.10	17.50	17.49	20.51	27.	.88	8.	12	Pass
HT20	MCS0	2	165	5825	0.10	0.10	17.91	17.59	20.77	27.	.88	8.	12	Pass
HT40	MCS0	2	151	5755	0.11	0.11	17.70	17.46	20.59	27.	.88	8.	12	Pass
HT40	MCS0	2	159	5795	0.11	0.11	17.83	17.70	20.77	27.	.88	8.	12	Pass
VHT20	MCS0	2	149	5745	0.10	0.10	17.53	17.31	20.43	27.	.88	8.	12	Pass
VHT20	MCS0	2	157	5785	0.10	0.10	17.49	17.46	20.49	27.	.88	8.	12	Pass
VHT20	MCS0	2	165	5825	0.10	0.10	17.89	17.54	20.73	27.	.88	8.	12	Pass
VHT40	MCS0	2	151	5755	0.14	0.14	18.08	17.98	21.04	27.	.88	8.	12	Pass
VHT40	MCS0	2	159	5795	0.14	0.14	17.78	17.69	20.75	27.	.88	8.	12	Pass
VHT80	MCS0	2	155	5775	0.26	0.26	13.83	13.85	16.85	27.	.88	8.	12	Pass

Power Setting
18
18
18
18
18
18
18
18
18
18
14.5

# **Appendix B. AC Conducted Emission Test Results**

Toot Engineer	Kai Chun Chu	Temperature :	<b>25~27</b> ℃
Test Engineer :	Kai-Chun Chu	Relative Humidity :	50~52%

Report No. : FR831635C

TEL: 886-3-327-3456 Page Number : B1 of B

# **EUT Information**


 Report NO :
 831635

 Test Mode :
 Mode 1

 Test Voltage :
 120Vac/60Hz

Phase: Line

### Full Spectrum




### **Final Result**

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
0.156750		21.63	55.63	34.00	L1	OFF	19.5
0.156750	34.35		65.63	31.28	L1	OFF	19.5
0.246750		27.55	51.87	24.32	L1	OFF	19.5
0.246750	28.64	-	61.87	33.23	L1	OFF	19.5
0.368250		16.89	48.54	31.65	L1	OFF	19.5
0.368250	18.58		58.54	39.96	L1	OFF	19.5
0.501000		20.10	46.00	25.90	L1	OFF	19.5
0.501000	22.09		56.00	33.91	L1	OFF	19.5
1.680000		15.44	46.00	30.56	L1	OFF	19.6
1.680000	18.10		56.00	37.90	L1	OFF	19.6
19.695750		28.75	50.00	21.25	L1	OFF	19.8
19.695750	33.85		60.00	26.15	L1	OFF	19.8

# **EUT Information**

Report NO: 831635
Test Mode: Mode 1
Test Voltage: 120Vac/60Hz
Phase: Neutral

Full Spectrum



### **Final Result**

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
0.163500		22.90	55.28	32.38	N	OFF	19.5
0.163500	33.00		65.28	32.28	N	OFF	19.5
0.233250		27.20	52.33	25.13	N	OFF	19.5
0.233250	28.57	-	62.33	33.76	N	OFF	19.5
0.368250		16.58	48.54	31.96	N	OFF	19.5
0.368250	18.42		58.54	40.12	N	OFF	19.5
0.505500		16.58	46.00	29.42	N	OFF	19.5
0.505500	19.00		56.00	37.00	N	OFF	19.5
1.637250		16.22	46.00	29.78	N	OFF	19.6
1.637250	18.70	-	56.00	37.30	N	OFF	19.6
19.414500		28.76	50.00	21.24	N	OFF	19.9
19.414500	33.80		60.00	26.20	N	OFF	19.9

# Appendix C. Radiated Spurious Emission

Test Engineer :	Daniel Lee and JC Liang	Temperature :	18 ~ 22°C
rest Engineer .		Relative Humidity :	48 ~ 52%

Report No.: FR831635C

<CDD Mode>

# Band 4 - 5725~5850MHz

# WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	( dBµV/m )	(dB)	( dBµV/m )	(dBµV)	( dB/m )	(dB)	(dB)	( cm )	(deg)	(P/A)	(H/V)
		5646.4	59.42	-8.78	68.2	50.96	32.24	8.77	32.55	248	25	Р	Н
		5696.6	65.36	-37.33	102.69	56.75	32.29	8.89	32.57	248	25	Р	Н
		5717	77.29	-32.67	109.96	68.61	32.31	8.95	32.58	248	25	Р	Н
		5722.2	81.92	-33.9	115.82	73.17	32.32	9.01	32.58	248	25	Р	Н
	*	5745	118.18	-	-	109.36	32.34	9.07	32.59	248	25	Р	Н
	*	5745	110.38	-	-	101.56	32.34	9.07	32.59	248	25	Α	Н
000 44 5													Н
802.11a													Н
CH 149 5745MHz		5642.4	64.59	-3.61	68.2	56.2	32.24	8.7	32.55	300	345	Р	V
3743WITIZ		5697.8	71.25	-32.33	103.58	62.64	32.29	8.89	32.57	300	345	Р	V
		5716.6	84.27	-25.58	109.85	75.59	32.31	8.95	32.58	300	345	Р	V
		5722.6	87.13	-29.6	116.73	78.38	32.32	9.01	32.58	300	345	Р	V
	*	5745	122.95	-	-	114.13	32.34	9.07	32.59	300	345	Р	V
	*	5745	115.24	-	-	106.42	32.34	9.07	32.59	300	345	Α	V
													V
													V

TEL: 886-3-327-3456 Page Number : C1 of C16



# FCC RADIO TEST REPORT

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1+2		( MHz )	( dBµV/m )	Limit	Line ( dBµV/m )	Level	Factor ( dB/m )	Loss (dB)	Factor	Pos	Pos ( deg )	Avg.	/UAA
1+2		5645.8	<u>( аврулп )</u> 50.27	-17.93	68.2	41.81	32.24	8.77	(dB) 32.55	( cm ) 236	21	(P/A)	(п/v) Н
		5695.6	62.49	-39.47	101.96	53.88	32.29	8.89	32.57	236	21	P	н
		5719.6	52.96	-57.73	110.69	44.21	32.32	9.01	32.58	236	21	P	Н
		5721.4	51.77	-62.22	113.99	43.02	32.32	9.01	32.58	236	21	Р	Н
	*	5785	116.66	-02.22	-	107.69	32.38	9.2	32.61	236	21	' Р	Н
	*	5785	109.8	_	-	107.09	32.38	9.2	32.61	236	21	A	Н
						43.34			32.63	236	21	Р	Н
		5850	52.31	-69.89	122.2		32.44	9.16					
		5873.8	61.35	-44.19	105.54	52.38	32.48	9.13	32.64	236	21	Р	Н
		5877.8	63.79	-39.33	103.12	54.82	32.48	9.13	32.64	236	21	Р	Н
		5934	50.32	-17.88	68.2	41.43	32.53	9.01	32.65	236	21	Р	Н
802.11a													Н
CH 157													Н
5785MHz		5601.2	53.41	-14.79	68.2	45.17	32.2	8.58	32.54	298	352	Р	V
370311112		5696.6	65.24	-37.45	102.69	56.63	32.29	8.89	32.57	298	352	Р	V
		5711.4	54.9	-53.49	108.39	46.22	32.31	8.95	32.58	298	352	Р	٧
		5723	53.36	-64.28	117.64	44.61	32.32	9.01	32.58	298	352	Р	٧
	*	5785	120.26	-	-	111.29	32.38	9.2	32.61	298	352	Р	V
	*	5785	112.41	-	-	103.44	32.38	9.2	32.61	298	352	Α	V
		5853.2	53.4	-61.5	114.9	44.43	32.44	9.16	32.63	298	352	Р	٧
		5874.4	64.39	-40.98	105.37	55.42	32.48	9.13	32.64	298	352	Р	٧
		5879.2	64.38	-37.7	102.08	55.41	32.48	9.13	32.64	298	352	Р	V
		5927	51.02	-17.18	68.2	42.1	32.53	9.04	32.65	298	352	Р	V
													٧
													٧
<u> </u>			<u>I</u>		l				1	[		1	1

Report No. : FR831635C

TEL: 886-3-327-3456 Page Number : C2 of C16



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1+2		( MHz )	( dBµV/m )	Limit (dB)	Line ( dBµV/m )	Level ( dBµV )	Factor ( dB/m )	Loss (dB)	Factor ( dB )	Pos ( cm )	Pos ( deg )	Avg. (P/A)	(H/V
	*	5825	117.82	-	-	108.78	32.43	9.23	32.62	241	22	Р	Н
	*	5825	110.11	-	-	101.07	32.43	9.23	32.62	241	22	Α	Н
		5851.4	74.89	-44.12	119.01	65.92	32.44	9.16	32.63	241	22	Р	Н
		5855.8	72.19	-38.39	110.58	63.2	32.46	9.16	32.63	241	22	Р	Н
		5917.8	61.44	-12.07	73.51	52.54	32.51	9.04	32.65	241	22	Р	Н
		5927.6	59.62	-8.58	68.2	50.7	32.53	9.04	32.65	241	22	Р	Н
													Н
802.11a													Н
CH 165	*	5825	120.51	-	-	111.47	32.43	9.23	32.62	305	352	Р	V
5825MHz	*	5825	112.06	-	-	103.02	32.43	9.23	32.62	305	352	Α	V
		5852.4	76.36	-40.37	116.73	67.39	32.44	9.16	32.63	305	352	Р	V
		5856.8	70.81	-39.49	110.3	61.82	32.46	9.16	32.63	305	352	Р	V
		5924	63.03	-5.91	68.94	54.11	32.53	9.04	32.65	305	352	Р	V
		5925.2	60.27	-7.93	68.2	51.35	32.53	9.04	32.65	305	352	Р	V
													V
													V
													V

2. All results are PASS against Peak and Average limit line.

TEL: 886-3-327-3456 Page Number : C3 of C16

### Band 4 5725~5850MHz

Report No.: FR831635C

# WIFI 802.11a (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol
1+2		(MHz)	( dBµV/m )		( dBµV/m )	(dBµV)	(dB/m)	(dB)	(dB)	(cm)		(P/A)	(H/\
		11490	44.89	-29.11	74	58.55	39.81	12.74	66.21	100	0	Р	Н
		17235	45.85	-22.35	68.2	54.09	41.02	16.76	66.02	100	0	Р	Н
802.11a													Н
													Н
CH 149 5745MHz		11490	44.6	-29.4	74	58.26	39.81	12.74	66.21	100	0	Р	٧
3743WITZ		17235	45.37	-22.83	68.2	53.61	41.02	16.76	66.02	100	0	Р	V
													V
													V
		11570	45.88	-28.12	74	54.71	39.69	13.08	61.6	100	0	Р	Н
		17355	48.71	-19.49	68.2	50.89	41.58	17.23	60.99	100	0	Р	Н
802.11a													Н
CH 157													Н
5785MHz		11570	46.29	-27.71	74	55.12	39.69	13.08	61.6	100	0	Р	V
37 03WH 12		17355	49.86	-18.34	68.2	52.04	41.58	17.23	60.99	100	0	Р	V
													V
													V
		11650	45.23	-28.77	74	54.1	39.58	13.15	61.6	100	0	Р	Н
		17475	48.8	-19.4	68.2	50.24	42.14	17.34	60.92	380	0	Р	Н
802.11a													Н
CH 165													Н
5825MHz		11650	45.22	-28.78	74	54.09	39.58	13.15	61.6	100	0	Р	V
		17475	48.55	-19.65	68.2	49.99	42.14	17.34	60.92	100	0	Р	V
													V
							_						V

- Remark

  1. No other spurious found.
  2. All results are PASS against Peak and Average limit line.

TEL: 886-3-327-3456 : C4 of C16 Page Number

# Band 4 5725~5850MHz WIFI 802.11n HT20 (Band Edge @ 3m)

Report No.: FR831635C

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	( dBµV/m )	(dB)	( dBµV/m )	(dB <sub>µ</sub> V)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
		5648	59.57	-8.63	68.2	51.11	32.24	8.77	32.55	217	18	Р	Н
		5699.4	65.56	-39.2	104.76	56.95	32.29	8.89	32.57	217	18	Р	Н
		5719	77.41	-33.11	110.52	68.66	32.32	9.01	32.58	217	18	Р	Н
		5724.4	82.33	-38.5	120.83	73.58	32.32	9.01	32.58	217	18	Р	Н
	*	5745	116.73	-	-	107.91	32.34	9.07	32.59	217	18	Р	Τ
	*	5745	109.13	-	-	100.31	32.34	9.07	32.59	217	18	Α	Н
802.11n													Н
HT20													Н
CH 149		5647.8	66.74	-1.46	68.2	58.28	32.24	8.77	32.55	297	352	Р	V
5745MHz		5699.8	70.43	-34.62	105.05	61.76	32.29	8.95	32.57	297	352	Р	V
		5719.6	82.57	-28.12	110.69	73.82	32.32	9.01	32.58	297	352	Р	V
		5722.2	87.88	-27.94	115.82	79.13	32.32	9.01	32.58	297	352	Р	V
	*	5745	122.43	-	-	113.61	32.34	9.07	32.59	297	352	Р	V
	*	5745	114.73	-	-	105.91	32.34	9.07	32.59	297	352	Α	V
													٧
													٧

TEL: 886-3-327-3456 Page Number : C5 of C16



WIFI Note Over Limit Read Antenna Path Ant Table Peak Pol. Frequency Level Preamp Ant. Limit Line Level **Factor** Loss **Factor** Pos Pos Avg. ( deg ) (P/A) (H/V) 1+2 (MHz) (dBµV/m) (dB)  $(dB\mu V/m)$ (dBµV) ( dB/m ) (dB) (dB) ( cm ) 5642.6 50.85 -17.35 68.2 42.46 32.24 8.7 32.55 235 21 Ρ Н 5696.8 60.75 -42.09 102.84 52.14 32.29 8.89 32.57 235 21 Ρ Н 5719.4 52.81 -57.82 110.63 44.06 32.32 9.01 32.58 235 21 Ρ Н 5722.2 42.83 32.32 32.58 235 Ρ Н 51.58 -64.24 115.82 9.01 21 Р 5785 108.14 32.38 117.11 9.2 32.61 235 21 Η \* 5785 109.01 100.04 32.38 9.2 32.61 235 21 Α Н 51.15 42.18 32.44 Ρ 5852.6 -65.12 116.27 9.16 32.63 235 21 Η Ρ 5873.6 60.56 -45.03 105.59 51.59 32.48 9.13 32.64 235 21 Н Ρ 5888.8 60.87 -34.09 94.96 51.91 32.5 9.1 32.64 235 21 Η 5946 235 Р 50.42 -17.78 68.2 41.52 32.55 9.01 32.66 21 Н Н 802.11n HT20 Н CH 157 5601.2 53.84 -14.36 68.2 45.6 32.2 8.58 32.54 304 339 Ρ ٧ 5785MHz ٧ 5696.6 64.9 -37.79 102.69 56.29 32.29 8.89 32.57 304 339 Ρ ٧ 5712.6 -55.57 108.73 44.48 32.31 8.95 32.58 304 339 53.16 55.52 32.32 9.01 32.58 304 339 Р ٧ 5724.8 -66.22 121.74 46.77 \* ٧ 5785 118.93 109.96 32.38 9.2 32.61 304 339 Ρ \* 5785 111.81 102.84 32.38 9.2 32.61 304 339 ٧ Α 5853 54.99 -60.37115.36 46.02 32.44 9.16 32.63 304 339 ٧ Ρ 5874.8 66.2 -39.06 105.26 57.23 32.48 9.13 32.64 304 339 ٧ 5889 61.02 -33.79 94.81 52.06 32.5 32.64 304 339 Ρ ٧ 9.1 5932.4 51.62 -16.58 68.2 42.7 32.53 9.04 32.65 304 339 Ρ ٧ ٧ ٧

Report No.: FR831635C

TEL: 886-3-327-3456 Page Number : C6 of C16



WIFI Limit Table Peak Pol. Note **Frequency** Level Over Read Antenna Path Preamp Ant Ant. Limit Line Level **Factor** Loss Factor Pos Pos Avg. (dBµV/m) (deg) (P/A) (H/V) 1+2 (MHz) (dB)  $(dB\mu V/m)$ (dB<sub>µ</sub>V) ( dB/m ) (dB) (dB) ( cm ) \* Р 5825 118.03 108.99 32.43 9.23 32.62 219 20 Н 5825 109.18 100.14 32.43 9.23 32.62 219 20 Α Н 5850 81.3 -40.9 122.2 72.33 32.44 9.16 32.63 219 20 Ρ Н Ρ 5855 68.69 -42.11 110.8 59.7 32.46 9.16 32.63 219 20 Н Р 5913.4 59.28 -17.48 76.76 50.35 32.51 9.07 32.65 219 20 Н 5927.4 58.29 -9.91 68.2 49.37 32.53 9.04 32.65 219 20 Ρ Н Н 802.11n HT20 Н CH 165 109.98 5825 119.02 32.43 9.23 32.62 312 338 Ρ ٧ 5825MHz 312 5825 112.05 103.01 32.43 9.23 32.62 338 Α ٧ \_ 5850.6 80.84 -39.99 120.83 71.87 32.44 9.16 32.63 312 338 Ρ ٧ 5857.8 74.1 -35.91 110.01 65.12 32.46 9.16 32.64 312 338 ٧ 5914.8 65.25 -10.47 75.72 56.32 32.51 9.07 32.65 312 338 Ρ ٧ 5928.6 58.7 68.2 49.78 32.53 9.04 32.65 312 338 Ρ ٧ -9.5 ٧ ٧

Report No.: FR831635C

### Remark

1. No other spurious found.

2. All results are PASS against Peak and Average limit line.

TEL: 886-3-327-3456 Page Number: C7 of C16

### Band 4 5725~5850MHz

Report No.: FR831635C

# WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	( dBµV/m )	(dB)	( dBµV/m )	(dBµV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V
		11490	45.62	-28.38	74	54.39	39.81	13.02	61.6	100	0	Р	Н
		17235	47.76	-20.44	68.2	50.68	41.02	17.12	61.06	100	0	Р	Н
802.11n													Н
HT20													Н
CH 149		11490	45.53	-28.47	74	54.3	39.81	13.02	61.6	100	0	Р	V
5745MHz		17235	47.18	-21.02	68.2	50.1	41.02	17.12	61.06	100	0	Р	٧
													V
													V
		11570	45.51	-28.49	74	54.34	39.69	13.08	61.6	100	0	Р	Н
		17355	48.89	-19.31	68.2	51.07	41.58	17.23	60.99	100	0	Р	Н
802.11n													Н
HT20													Н
CH 157		11570	45.04	-28.96	74	53.87	39.69	13.08	61.6	100	0	Р	V
5785MHz		17355	49.54	-18.66	68.2	51.72	41.58	17.23	60.99	100	0	Р	V
													V
													V
		11650	44.04	-29.96	74	52.91	39.58	13.15	61.6	100	0	Р	Н
		17475	49.15	-19.05	68.2	50.59	42.14	17.34	60.92	100	0	Р	Н
802.11n													Н
HT20													Н
CH 165		11650	45.13	-28.87	74	54	39.58	13.15	61.6	100	0	Р	V
5825MHz		17475	48.73	-19.47	68.2	50.17	42.14	17.34	60.92	100	0	Р	٧
													٧
													V

- Remark

  1. No other spurious found.
  2. All results are PASS against Peak and Average limit line.

: C8 of C16 TEL: 886-3-327-3456 Page Number

# Band 4 5725~5850MHz WIFI 802.11n HT40 (Band Edge @ 3m)

Report No.: FR831635C

Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant		Peak	Pol.
	( MU= )	/ dBuV/m \	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
	•		, ,				•		. ,		,	(n/v) H
											•	Н
											•	Н
												- '' H
*											-	
											•	Н
*												Н
	5854.8	61.61	-49.65		52.62	32.46	9.16	32.63	100	296	Р	Н
	5860.4	62.69	-46.6	109.29	53.71	32.46	9.16	32.64	100	296	Р	Н
	5876.4	57.31	-46.85	104.16	48.34	32.48	9.13	32.64	100	296	Р	Н
	5928.8	50.54	-17.66	68.2	41.62	32.53	9.04	32.65	100	296	Р	Н
												Н
												Н
	5649	67.07	-1.13	68.2	58.61	32.24	8.77	32.55	324	17	Р	V
	5689	77.52	-19.57	97.09	68.91	32.29	8.89	32.57	324	17	Р	V
	5718.8	89.46	-21	110.46	80.71	32.32	9.01	32.58	324	17	Р	V
	5723.6	91.35	-27.66	119.01	82.6	32.32	9.01	32.58	324	17	Р	V
*	5755	118.08	-	-	109.17	32.36	9.14	32.59	324	17	Р	V
*	5755	110.5	-	-	101.59	32.36	9.14	32.59	324	17	Α	V
	5850.2	66.45	-55.29	121.74	57.48	32.44	9.16	32.63	324	17	Р	V
	5858.4	66.99	-42.86	109.85	58.01	32.46	9.16	32.64	324	17	Р	V
	5884	59.92	-38.6	98.52	50.98	32.48	9.1	32.64	324	17	Р	V
	5937.4	51.73	-16.47	68.2	42.85	32.53	9.01	32.66	324	17	Р	V
												V
												V
	*	(MHz) 5648.6 5698 5719.8 5723 * 5755 * 5755 5854.8 5860.4 5876.4 5928.8  5649 5689 5718.8 5723.6 * 5755 * 5755 * 5850.2 5858.4 5884	(MHz) (dBµV/m)  5648.6 62.07  5698 76.22  5719.8 82.36  5723 86.68  * 5755 114.43  * 5755 106.07  5854.8 61.61  5860.4 62.69  5876.4 57.31  5928.8 50.54   5649 67.07  5689 77.52  5718.8 89.46  5723.6 91.35  * 5755 118.08  * 5755 110.5  5850.2 66.45  5858.4 66.99  5884 59.92	(MHz)         (dBμV/m)         Limit (dB)           5648.6         62.07         -6.13           5698         76.22         -27.51           5719.8         82.36         -28.38           5723         86.68         -30.96           *         5755         114.43         -           *         5755         106.07         -           5854.8         61.61         -49.65           5860.4         62.69         -46.6           5876.4         57.31         -46.85           5928.8         50.54         -17.66           5649         67.07         -1.13           5689         77.52         -19.57           5718.8         89.46         -21           5723.6         91.35         -27.66           *         5755         118.08         -           *         5755         110.5         -           5850.2         66.45         -55.29           5858.4         66.99         -42.86           5884         59.92         -38.6	(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m)           5648.6         62.07         -6.13         68.2           5698         76.22         -27.51         103.73           5719.8         82.36         -28.38         110.74           5723         86.68         -30.96         117.64           *         5755         114.43         -         -           *         5755         106.07         -         -           5854.8         61.61         -49.65         111.26           5860.4         62.69         -46.6         109.29           5876.4         57.31         -46.85         104.16           5928.8         50.54         -17.66         68.2           5689         77.52         -19.57         97.09           5718.8         89.46         -21         110.46           5723.6         91.35         -27.66         119.01           *         5755         118.08         -         -           *         5755         110.5         -         -           *         5755         10.5         -         -           *         5755         12.74 <td>(MHz)         Limit (dB)         Line (dBµV/m)         Level (dBµV)           5648.6         62.07         -6.13         68.2         53.61           5698         76.22         -27.51         103.73         67.61           5719.8         82.36         -28.38         110.74         73.61           5723         86.68         -30.96         117.64         77.93           *         5755         114.43         -         -         105.52           *         5755         106.07         -         97.16           5854.8         61.61         -49.65         111.26         52.62           5860.4         62.69         -46.6         109.29         53.71           5876.4         57.31         -46.85         104.16         48.34           5928.8         50.54         -17.66         68.2         41.62           5649         67.07         -1.13         68.2         58.61           5689         77.52         -19.57         97.09         68.91           5718.8         89.46         -21         110.46         80.71           5723.6         91.35         -27.66         119.01         82.6           <t< td=""><td>(MHz)         (dBµV/m)         Limit (dB)         Line (dBµV/m)         Level (dBµV/m)         Factor (dBµN)           5648.6         62.07         -6.13         68.2         53.61         32.24           5698         76.22         -27.51         103.73         67.61         32.29           5719.8         82.36         -28.38         110.74         73.61         32.32           5723         86.68         -30.96         117.64         77.93         32.32           * 5755         114.43         -         -         105.52         32.36           * 5755         106.07         -         -         97.16         32.36           5860.4         62.69         -46.6         109.29         53.71         32.46           5876.4         57.31         -46.85         104.16         48.34         32.48           5928.8         50.54         -17.66         68.2         41.62         32.53           5649         67.07         -1.13         68.2         58.61         32.24           5689         77.52         -19.57         97.09         68.91         32.29           5718.8         89.46         -21         110.46         80.71</td><td>(MHz)         (dBμV/m)         Limit (dBμV/m)         Line (dBμV/m)         Level (dBμV)         Factor (dB/m)         Loss (dB)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77           5698         76.22         -27.51         103.73         67.61         32.29         8.89           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01           5723         86.68         -30.96         117.64         77.93         32.32         9.01           * 5755         114.43         -         -         105.52         32.36         9.14           * 5755         106.07         -         -         97.16         32.36         9.14           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16           5876.4         57.31         -46.85         104.16         48.34         32.48         9.13           5928.8         50.54         -17.66         68.2         41.62         32.32         9.04           5718.8<td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m)         Level (dBμV/m)         Factor (dB/m)         Loss (dB)         Factor (dB/m)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58           * 5755         114.43         -         -         105.52         32.36         9.14         32.59           * 5755         106.07         -         -         97.16         32.36         9.14         32.59           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64           5928.8         50.54         -17.66         68.2         41.62         32.33         9.04         <t< td=""><td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m) (dBμV)         Eactor (dB/m)         Loss (dB)         Factor (dB)         Pos (cm)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64         100</td><td>(MHz)         (dBμV/m)         Limit (dB)         Livel (dBμV/m)         Factor (dB/m)         Loss (dBμ)         Factor (dB)         Pos (deg)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100         296           5876.4         57.31         -46.85         104</td><td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμVm)         Level (dBμV)         Factor (dB)         Cos (dB)         Pos (cm)         Avg. (deg)         (P/A)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296         P           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296         P           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296         P           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296         P           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296         P           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296         P           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16</td></t<></td></td></t<></td>	(MHz)         Limit (dB)         Line (dBµV/m)         Level (dBµV)           5648.6         62.07         -6.13         68.2         53.61           5698         76.22         -27.51         103.73         67.61           5719.8         82.36         -28.38         110.74         73.61           5723         86.68         -30.96         117.64         77.93           *         5755         114.43         -         -         105.52           *         5755         106.07         -         97.16           5854.8         61.61         -49.65         111.26         52.62           5860.4         62.69         -46.6         109.29         53.71           5876.4         57.31         -46.85         104.16         48.34           5928.8         50.54         -17.66         68.2         41.62           5649         67.07         -1.13         68.2         58.61           5689         77.52         -19.57         97.09         68.91           5718.8         89.46         -21         110.46         80.71           5723.6         91.35         -27.66         119.01         82.6 <t< td=""><td>(MHz)         (dBµV/m)         Limit (dB)         Line (dBµV/m)         Level (dBµV/m)         Factor (dBµN)           5648.6         62.07         -6.13         68.2         53.61         32.24           5698         76.22         -27.51         103.73         67.61         32.29           5719.8         82.36         -28.38         110.74         73.61         32.32           5723         86.68         -30.96         117.64         77.93         32.32           * 5755         114.43         -         -         105.52         32.36           * 5755         106.07         -         -         97.16         32.36           5860.4         62.69         -46.6         109.29         53.71         32.46           5876.4         57.31         -46.85         104.16         48.34         32.48           5928.8         50.54         -17.66         68.2         41.62         32.53           5649         67.07         -1.13         68.2         58.61         32.24           5689         77.52         -19.57         97.09         68.91         32.29           5718.8         89.46         -21         110.46         80.71</td><td>(MHz)         (dBμV/m)         Limit (dBμV/m)         Line (dBμV/m)         Level (dBμV)         Factor (dB/m)         Loss (dB)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77           5698         76.22         -27.51         103.73         67.61         32.29         8.89           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01           5723         86.68         -30.96         117.64         77.93         32.32         9.01           * 5755         114.43         -         -         105.52         32.36         9.14           * 5755         106.07         -         -         97.16         32.36         9.14           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16           5876.4         57.31         -46.85         104.16         48.34         32.48         9.13           5928.8         50.54         -17.66         68.2         41.62         32.32         9.04           5718.8<td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m)         Level (dBμV/m)         Factor (dB/m)         Loss (dB)         Factor (dB/m)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58           * 5755         114.43         -         -         105.52         32.36         9.14         32.59           * 5755         106.07         -         -         97.16         32.36         9.14         32.59           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64           5928.8         50.54         -17.66         68.2         41.62         32.33         9.04         <t< td=""><td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m) (dBμV)         Eactor (dB/m)         Loss (dB)         Factor (dB)         Pos (cm)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64         100</td><td>(MHz)         (dBμV/m)         Limit (dB)         Livel (dBμV/m)         Factor (dB/m)         Loss (dBμ)         Factor (dB)         Pos (deg)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100         296           5876.4         57.31         -46.85         104</td><td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμVm)         Level (dBμV)         Factor (dB)         Cos (dB)         Pos (cm)         Avg. (deg)         (P/A)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296         P           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296         P           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296         P           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296         P           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296         P           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296         P           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16</td></t<></td></td></t<>	(MHz)         (dBµV/m)         Limit (dB)         Line (dBµV/m)         Level (dBµV/m)         Factor (dBµN)           5648.6         62.07         -6.13         68.2         53.61         32.24           5698         76.22         -27.51         103.73         67.61         32.29           5719.8         82.36         -28.38         110.74         73.61         32.32           5723         86.68         -30.96         117.64         77.93         32.32           * 5755         114.43         -         -         105.52         32.36           * 5755         106.07         -         -         97.16         32.36           5860.4         62.69         -46.6         109.29         53.71         32.46           5876.4         57.31         -46.85         104.16         48.34         32.48           5928.8         50.54         -17.66         68.2         41.62         32.53           5649         67.07         -1.13         68.2         58.61         32.24           5689         77.52         -19.57         97.09         68.91         32.29           5718.8         89.46         -21         110.46         80.71	(MHz)         (dBμV/m)         Limit (dBμV/m)         Line (dBμV/m)         Level (dBμV)         Factor (dB/m)         Loss (dB)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77           5698         76.22         -27.51         103.73         67.61         32.29         8.89           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01           5723         86.68         -30.96         117.64         77.93         32.32         9.01           * 5755         114.43         -         -         105.52         32.36         9.14           * 5755         106.07         -         -         97.16         32.36         9.14           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16           5876.4         57.31         -46.85         104.16         48.34         32.48         9.13           5928.8         50.54         -17.66         68.2         41.62         32.32         9.04           5718.8 <td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m)         Level (dBμV/m)         Factor (dB/m)         Loss (dB)         Factor (dB/m)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58           * 5755         114.43         -         -         105.52         32.36         9.14         32.59           * 5755         106.07         -         -         97.16         32.36         9.14         32.59           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64           5928.8         50.54         -17.66         68.2         41.62         32.33         9.04         <t< td=""><td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m) (dBμV)         Eactor (dB/m)         Loss (dB)         Factor (dB)         Pos (cm)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64         100</td><td>(MHz)         (dBμV/m)         Limit (dB)         Livel (dBμV/m)         Factor (dB/m)         Loss (dBμ)         Factor (dB)         Pos (deg)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100         296           5876.4         57.31         -46.85         104</td><td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμVm)         Level (dBμV)         Factor (dB)         Cos (dB)         Pos (cm)         Avg. (deg)         (P/A)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296         P           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296         P           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296         P           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296         P           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296         P           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296         P           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16</td></t<></td>	(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m)         Level (dBμV/m)         Factor (dB/m)         Loss (dB)         Factor (dB/m)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58           * 5755         114.43         -         -         105.52         32.36         9.14         32.59           * 5755         106.07         -         -         97.16         32.36         9.14         32.59           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64           5928.8         50.54         -17.66         68.2         41.62         32.33         9.04 <t< td=""><td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m) (dBμV)         Eactor (dB/m)         Loss (dB)         Factor (dB)         Pos (cm)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64         100</td><td>(MHz)         (dBμV/m)         Limit (dB)         Livel (dBμV/m)         Factor (dB/m)         Loss (dBμ)         Factor (dB)         Pos (deg)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100         296           5876.4         57.31         -46.85         104</td><td>(MHz)         (dBμV/m)         Limit (dB)         Line (dBμVm)         Level (dBμV)         Factor (dB)         Cos (dB)         Pos (cm)         Avg. (deg)         (P/A)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296         P           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296         P           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296         P           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296         P           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296         P           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296         P           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16</td></t<>	(MHz)         (dBμV/m)         Limit (dB)         Line (dBμV/m) (dBμV)         Eactor (dB/m)         Loss (dB)         Factor (dB)         Pos (cm)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16         32.64         100	(MHz)         (dBμV/m)         Limit (dB)         Livel (dBμV/m)         Factor (dB/m)         Loss (dBμ)         Factor (dB)         Pos (deg)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296           5854.8         61.61         -49.65         111.26         52.62         32.46         9.16         32.63         100         296           5876.4         57.31         -46.85         104	(MHz)         (dBμV/m)         Limit (dB)         Line (dBμVm)         Level (dBμV)         Factor (dB)         Cos (dB)         Pos (cm)         Avg. (deg)         (P/A)           5648.6         62.07         -6.13         68.2         53.61         32.24         8.77         32.55         100         296         P           5698         76.22         -27.51         103.73         67.61         32.29         8.89         32.57         100         296         P           5719.8         82.36         -28.38         110.74         73.61         32.32         9.01         32.58         100         296         P           5723         86.68         -30.96         117.64         77.93         32.32         9.01         32.58         100         296         P           * 5755         114.43         -         -         105.52         32.36         9.14         32.59         100         296         P           * 5755         106.07         -         -         97.16         32.36         9.14         32.59         100         296         P           5860.4         62.69         -46.6         109.29         53.71         32.46         9.16

TEL: 886-3-327-3456 Page Number : C9 of C16



WIFI Preamp Note Level Over Limit Read Antenna Path Ant **Table** Peak Pol. Frequency Ant. Limit Line Level **Factor** Loss **Factor** Pos Pos Avg. ( deg ) (P/A) (H/V) 1+2 (MHz) (dBµV/m) (dB)  $(dB\mu V/m)$ (dBµV) ( dB/m ) (dB) (dB) ( cm ) 5646.6 51.38 -16.82 68.2 42.92 32.24 8.77 32.55 245 22 Ρ Н 5687.6 60.45 -35.6 96.05 51.84 32.29 8.89 32.57 245 22 Н 5703 60.9 -45.14 106.04 52.21 32.31 8.95 32.57 245 22 Ρ Н 5723 57.78 32.32 32.58 245 22 Н 66.53 -51.11 117.64 9.01 Р 32.39 5795 116.42 107.38 9.26 32.61 245 22 Η \* 5795 107.92 98.88 32.39 9.26 32.61 245 22 Α Н 32.44 5853 69.38 -45.98 115.36 60.41 9.16 32.63 245 22 Η Ρ 5863.8 67.29 -41.04 108.33 58.34 32.46 9.13 32.64 245 22 Н 5882.6 22 Ρ 62.72 -36.84 99.56 53.78 32.48 9.1 32.64 245 Η 5931 50.3 32.65 22 Р -17.9 68.2 41.38 32.53 9.04 245 Н Н 802.11n **HT40** Н **CH 159** 5605 52.55 -15.65 68.2 44.31 32.2 8.58 32.54 293 354 Ρ ٧ 5795MHz ٧ 5685.8 62.68 -32.04 94.72 54.07 32.29 8.89 32.57 293 354 Ρ ٧ 5719.8 66.63 -44.11 110.74 57.88 32.32 9.01 32.58 293 354 32.32 9.01 32.58 293 354 Р ٧ 5723.8 68.27 -51.19 119.46 59.52 ٧ 5795 118.02 108.98 32.39 9.26 32.61 293 354 Ρ 5795 110.49 101.45 32.39 9.26 32.61 293 354 ٧ Α 5850.4 68.07 -53.22121.29 59.1 32.44 9.16 32.63 293 354 ٧ Ρ 5862.4 70.54 -38.19 108.73 61.59 32.46 9.13 32.64 293 354 ٧ 5881.2 65.73 -34.86 100.59 56.79 32.48 32.64 293 354 Ρ ٧ 9.1 5937.2 51.88 -16.32 68.2 43 32.53 9.01 32.66 293 354 Ρ ٧ ٧ ٧

Report No.: FR831635C

### Remark

TEL: 886-3-327-3456 Page Number: C10 of C16

No other spurious found.

<sup>2.</sup> All results are PASS against Peak and Average limit line.

### Band 4 5725~5850MHz

Report No.: FR831635C

# WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol
1+2		(MHz)	( dBµV/m )	(dB)	( dBµV/m )	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	( deg )	(P/A)	(H/V
		11510	45.62	-28.38	74	54.39	39.8	13.03	61.6	100	0	Р	Н
		17265	49.05	-19.15	68.2	51.76	41.18	17.15	61.04	100	0	Р	Н
802.11n													Н
HT40													Н
CH 151		11510	47.09	-26.91	74	55.86	39.8	13.03	61.6	100	0	Р	V
5755MHz		17265	48.93	-19.27	68.2	51.64	41.18	17.15	61.04	100	0	Р	V
													٧
													V
		11590	45.96	-28.04	74	54.81	39.66	13.09	61.6	100	0	Р	Н
		17385	48.4	-19.8	68.2	50.37	41.74	17.26	60.97	100	0	Р	Н
802.11n													Н
HT40													Н
CH 159		11590	45.53	-28.47	74	54.38	39.66	13.09	61.6	100	0	Р	V
5795MHz		17385	47.91	-20.29	68.2	49.88	41.74	17.26	60.97	100	0	Р	V
													٧
													V

TEL: 886-3-327-3456 Page Number : C11 of C16

Remark

2. All results are PASS against Peak and Average limit line.

# Band 4 5725~5850MHz WIFI 802.11ac VHT80 (Band Edge @ 3m)

Report No.: FR831635C

WIFI Ant. 1+2	Note	Frequency ( MHz )	Level	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Avg.	
		5646	63.28	-4.92	68.2	54.82	32.24	8.77	32.55	100	298	Р	Н
		5666.6	68.52	-12	80.52	59.98	32.27	8.83	32.56	100	298	Р	Н
		5702.6	68.04	-37.89	105.93	59.35	32.31	8.95	32.57	100	298	Р	Н
		5721.2	66.47	-47.07	113.54	57.72	32.32	9.01	32.58	100	298	Р	Н
	*	5775	106.87	-	-	97.89	32.38	9.2	32.6	100	298	Р	Н
	*	5775	98.89	-	-	89.91	32.38	9.2	32.6	100	298	Α	Н
		5852.2	66.36	-50.82	117.18	57.39	32.44	9.16	32.63	100	298	Р	Н
		5871	68.74	-37.58	106.32	59.77	32.48	9.13	32.64	100	298	Р	Н
		5876.8	67.01	-36.85	103.86	58.04	32.48	9.13	32.64	100	298	Р	Н
		5926.6	57.03	-11.17	68.2	48.11	32.53	9.04	32.65	100	298	Р	Н
802.11ac													Н
VHT80													Н
CH 155		5643	66.08	-2.12	68.2	57.69	32.24	8.7	32.55	339	28	Р	V
5775MHz		5683.8	70.27	-22.98	93.25	61.66	32.29	8.89	32.57	339	28	Р	V
		5718.2	69.18	-41.12	110.3	60.43	32.32	9.01	32.58	339	28	Р	V
		5722.8	68.69	-48.49	117.18	59.94	32.32	9.01	32.58	339	28	Р	V
	*	5775	111.42	-	-	102.44	32.38	9.2	32.6	339	28	Р	V
	*	5775	104	-	-	95.02	32.38	9.2	32.6	339	28	Α	V
		5852.2	69.6	-47.58	117.18	60.63	32.44	9.16	32.63	339	28	Р	V
		5871.2	72.38	-33.88	106.26	63.41	32.48	9.13	32.64	339	28	Р	V
		5881.4	70.81	-29.64	100.45	61.87	32.48	9.1	32.64	339	28	Р	٧
		5925	59.87	-8.33	68.2	50.95	32.53	9.04	32.65	339	28	Р	٧
													٧
													V

### Remark

- 1. No other spurious found.
- 2. All results are PASS against Peak and Average limit line.

TEL: 886-3-327-3456 Page Number: C12 of C16

### Band 4 5725~5850MHz

Report No.: FR831635C

# WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency ( MHz )	Level	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Avg.	
		11550	45.38	-28.62	74	54.2	39.72	13.06	61.6	100	0	Р	Н
		17325	48.08	-20.12	68.2	50.47	41.42	17.2	61.01	100	0	Р	Н
802.11ac													Н
VHT80													Н
CH 155		11550	44.99	-29.01	74	53.81	39.72	13.06	61.6	100	0	Р	V
5775MHz		17325	48.43	-19.77	68.2	50.82	41.42	17.2	61.01	100	0	Р	V
													V
													V

### Remark

. No other spurious found.

2. All results are PASS against Peak and Average limit line.

TEL: 886-3-327-3456 Page Number : C13 of C16

### **Emission below 1GHz**

Report No.: FR831635C

# 5GHz WIFI 802.11n HT20 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	( dBµV/m )	(dB)	( dBµV/m )	(dBµV)	( dB/m )	( dB )	( dB )	( cm )	(deg)	(P/A)	(H/\
		30.54	21.32	-18.68	40	29.35	24.07	0.68	32.78			Р	Н
		125.04	29.28	-14.22	43.5	42.84	17.71	1.42	32.69			Р	Н
		282.18	27.63	-18.37	46	39.28	18.78	2.17	32.6			Р	Н
		374.9	43.7	-2.3	46	52.94	20.93	2.43	32.6	100	4	QP	Н
		500.2	41.5	-4.5	46	47.43	23.86	2.85	32.64			Р	Н
		699.7	38.64	-7.36	46	41.42	26.62	3.38	32.78			Р	Н
													Н
													Н
													Н
													Н
5GHz													Н
802.11n													Н
HT20		75.63	22.67	-17.33	40	41.3	12.94	1.16	32.73			Р	V
LF		125.04	23.73	-19.77	43.5	37.29	17.71	1.42	32.69			Р	V
		300	35.57	-10.43	46	46.81	19.13	2.22	32.59			Р	V
		500.2	44.54	-1.46	46	50.47	23.86	2.85	32.64	100	341	QP	V
		624.8	41.39	-4.61	46	44.98	26.01	3.21	32.81			Р	V
		699.7	39.29	-6.71	46	42.07	26.62	3.38	32.78			Р	V
													V
													V
													V
													V
													V
													V

2. All results are PASS against limit line.

TEL: 886-3-327-3456 Page Number : C14 of C16

# Note symbol

Report No. : FR831635C

*	Fundamental Frequency which can be ignored. However, the level of any
	unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	Peak or Average
H/V	Horizontal or Vertical

TEL: 886-3-327-3456 Page Number : C15 of C16

### A calculation example for radiated spurious emission is shown as below:

Report No.: FR831635C

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	( dBµV/m )	(dB)	( dBµV/m )	(dBµV)	( dB/m )	( dB )	(dB)	( cm )	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

- 1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
- 2. Level(dBµV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- 3. Over Limit(dB) = Level(dB $\mu$ V/m) Limit Line(dB $\mu$ V/m)

### For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

### For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB) = Level(dB $\mu$ V/m) Limit Line(dB $\mu$ V/m)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

TEL: 886-3-327-3456 Page Number : C16 of C16

# Appendix D. Radiated Spurious Emission

Test Engineer :		Temperature :	18 ~ 22°C
rest Engineer .	Daniel Lee and JC Liang	Relative Humidity :	48 ~ 52%

Report No.: FR831635C

### <CDD Mode>


# **Note symbol**

-L	Low channel location
-R	High channel location


TEL: 886-3-327-3456 Page Number: D1 of D29

# Band 4 - 5725~5850MHz WIFI 802.11a (Band Edge @ 3m)


Report No.: FR831635C



TEL: 886-3-327-3456 Page Number : D2 of D29




TEL: 886-3-327-3456 Page Number: D3 of D29




TEL: 886-3-327-3456 Page Number : D4 of D29


ST REPORT Report No.: FR831635C



TEL: 886-3-327-3456 Page Number: D5 of D29




TEL: 886-3-327-3456 Page Number: D6 of D29




TEL: 886-3-327-3456 Page Number: D7 of D29

# Band 4 5725~5850MHz WIFI 802.11n HT20 (Band Edge @ 3m)


Report No.: FR831635C



TEL: 886-3-327-3456 Page Number: D8 of D29




TEL: 886-3-327-3456 Page Number: D9 of D29




TEL: 886-3-327-3456 Page Number : D10 of D29






TEL: 886-3-327-3456 Page Number : D11 of D29




TEL: 886-3-327-3456 Page Number : D12 of D29



TEL: 886-3-327-3456 Page Number : D13 of D29


# Band 4 5725~5850MHz WIFI 802.11n HT40 (Band Edge @ 3m)

Report No.: FR831635C




TEL: 886-3-327-3456 Page Number : D14 of D29

Report No.: FR831635C Band 4 5725~5850MHz Band Edge @ 3m




TEL: 886-3-327-3456 Page Number : D15 of D29





TEL: 886-3-327-3456 Page Number : D16 of D29







TEL: 886-3-327-3456 Page Number : D17 of D29

## Band 4 5725~5850MHz WIFI 802.11ac VHT80 (Band Edge @ 3m)

Report No.: FR831635C




TEL: 886-3-327-3456 Page Number : D18 of D29




TEL: 886-3-327-3456 Page Number : D19 of D29

## Band 4 - 5725~5850MHz WIFI 802.11a (Harmonic @ 3m)


Report No.: FR831635C



TEL: 886-3-327-3456 Page Number : D20 of D29




TEL: 886-3-327-3456 Page Number : D21 of D29




TEL: 886-3-327-3456 Page Number : D22 of D29

## Band 4 5725~5850MHz WIFI 802.11n HT20 (Harmonic @ 3m)

Report No.: FR831635C



TEL: 886-3-327-3456 Page Number: D23 of D29




TEL: 886-3-327-3456 Page Number : D24 of D29

Report No.: FR831635C


TEL: 886-3-327-3456 Page Number: D25 of D29

## Band 4 5725~5850MHz WIFI 802.11n HT40 (Harmonic @ 3m)

Report No.: FR831635C




TEL: 886-3-327-3456 Page Number : D26 of D29



TEL: 886-3-327-3456 Page Number : D27 of D29

## Band 4 5725~5850MHz WIFI 802.11ac VHT80 (Harmonic @ 3m)


Report No.: FR831635C



TEL: 886-3-327-3456 Page Number: D28 of D29

## Emission below 1GHz 5GHz WIFI 802.11n HT20 (LF)

Report No.: FR831635C



TEL: 886-3-327-3456 Page Number : D29 of D29

# **Appendix E. Duty Cycle Plots**


Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1+2	802.11a for Ant. 1	96.27	2064	0.48	1kHz	0.17
1+2	802.11a for Ant. 2	96.63	2064	0.48	1kHz	0.15
1+2	5GHz 802.11n HT20 for Ant. 1	97.66	5000	0.20	300Hz	0.10
1+2	5GHz 802.11n HT20 for Ant. 2	97.64	4960	0.20	300Hz	0.10
1+2	5GHz 802.11n HT40 for Ant. 1	97.60	2440	0.41	1kHz	0.11
1+2	5GHz 802.11n HT40 for Ant. 2	97.60	2440	0.41	1kHz	0.11
1+2	5GHz 802.11ac VHT20 for Ant. 1	97.66	5000	0.20	300Hz	0.10
1+2	5GHz 802.11ac VHT20 for Ant. 2	97.66	5000	0.20	300Hz	0.10
1+2	5GHz 802.11ac VHT40 for Ant. 1	96.83	2440	0.41	1kHz	0.14
1+2	5GHz 802.11ac VHT40 for Ant. 2	96.81	2430	0.41	1kHz	0.14
1+2	5GHz 802.11ac VHT80 for Ant. 1	94.26	1150	0.87	1kHz	0.26
1+2	5GHz 802.11ac VHT80 for Ant. 2	94.26	1150	0.87	1kHz	0.26

Report No.: FR831625C

TEL: 886-3-327-3456 Page Number : E-1 of 7

#### MIMO <Ant. 1>


### 802.11a



Report No.: FR831625C

Date: 29.MAR.2018 03:04:17

### 802.11n HT20




Date: 29.MAR.2018 05:09:40

FAX: 886-3-328-4978

TEL: 886-3-327-3456 Page Number : E-2 of 7


#### \_\_\_\_\_



Report No.: FR831625C

Date: 29.MAR.2018 06:36:11


### 802.11ac VHT20



Date: 29.MAR.2018 06:26:09

TEL: 886-3-327-3456 Page Number : E-3 of 7


### 802.11ac VHT40



Report No.: FR831625C

Date: 29.MAR.2018 06:41:50

### 802.11ac VHT80




Date: 29.MAR.2018 07:52:23

TEL: 886-3-327-3456 Page Number : E-4 of 7

### C RADIO TEST REPORT Report No. : FR831625C


#### MIMO <Ant. 2>





Date: 29.MAR.2018 03:06:08

### 802.11n HT20




Date: 29.MAR.2018 05:10:18

FAX: 886-3-328-4978


TEL: 886-3-327-3456 Page Number : E-5 of 7






Date: 29.MAR.2018 06:43:05


### 802.11ac VHT20



Date: 29.MAR.2018 06:28:21


TEL: 886-3-327-3456 Page Number : E-6 of 7





Date: 29.MAR.2018 06:43:05

### 802.11ac VHT80



Date: 29.MAR.2018 07:52:59

TEL: 886-3-327-3456 Page Number : E-7 of 7