Transmitter
Model: MemoTec-915

FCC PART 15, SUBPART B and C TEST REPORT

for

TRANSMITTER

MODEL: MemoTec-915

Prepared for

ELERO USA, INC. 10827 ALDER CIRCLE DALLAS, TEXAS 75238

Prepared by: ____

Fajimoto

KYLE FUJIMOTO

Approved by: Jomes Rom

JAMES ROSS

COMPATIBLE ELECTRONICS INC. 114 OLINDA DRIVE BREA, CALIFORNIA 92823 (714) 579-0500

DATE: APRIL 11, 2006

	REPORT		APPENDICES			TOTAL	
	BODY	A	В	C	D	E	
PAGES	16	2	2	2	12	5	39

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.

Transmitter
Model: MemoTec-915

TABLE OF CONTENTS

Section	n / Title	PAGE
GENEI	RAL REPORT SUMMARY	4
SUMM.	ARY OF TEST RESULTS	4
1.	PURPOSE	5
2.	ADMINISTRATIVE DATA	6
2.1	Location of Testing	6
2.2	Traceability Statement	6
2.3	Cognizant Personnel	6
2.4	Date Test Sample was Received	6
2.5	Disposition of the Test Sample	6
2.6	Abbreviations and Acronyms	6
3.	APPLICABLE DOCUMENTS	7
4.	DESCRIPTION OF TEST CONFIGURATION	8
4.1	Description Of Test Configuration - EMI	8
4.1.1	Cable Construction and Termination	9
5.	LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1	EUT and Accessory List	10
5.2	EMI Test Equipment	11
6.	TEST SITE DESCRIPTION	12
6.1	Test Facility Description	12
6.2	EUT Mounting, Bonding and Grounding	12
7.	TEST PROCEDURES	13
7.1	Conducted Emissions Test	13
7.2	Radiated Emissions (Spurious and Harmonics) Test	14
7.3	Radiated Emissions (Spurious and Harmonics) Test (continued)	15
8	CONCLUSIONS	16

Model: MemoTec-915

LIST OF APPENDICES

APPENDIX	TITLE		
A	Laboratory Recognitions		
В	Modifications to the EUT		
С	Additional Models Covered Under This Report		
D	Diagrams, Charts, and Photos		
	Test Setup Diagrams		
	Radiated Emissions Photos		
	Antenna and Effective Gain Factors		
Е	Data Sheets		

LIST OF FIGURES

FIGURE	TITLE
1	Plot Map And Layout of Radiated Site

Transmitter

Model: MemoTec-915



GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used to claim product endorsement by NVLAP, NIST or any other agency of the U.S. Government.

Device Tested: Transmitter

Model: MemoTec-915

S/N: N/A

Product Description: See Expository Statement

Modifications: The EUT was not modified in order to meet the specifications.

Manufacturer: Elero USA, Inc.

10827 Alder Circle Dallas, Texas 75238

Test Date: March 17, 2006

Test Specifications: EMI requirements

CFR Title 47, Part 15 Subpart B; and Subpart C, Sections 15.205, 15.209 and 15.249

Test Procedure: ANSI C63.4

Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 150 kHz - 30 MHz	This test was not performed because the EUT is battery powered only and does not connect to the AC public mains.
2	Radiated RF Emissions, 10 kHz - 9300 MHz	Complies with the Class B limits of CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.



Model: MemoTec-915

1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the Transmitter Model: MemoTec-915. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the **Class B** specification limits defined by CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.

Model: MemoTec-915

2. ADMINISTRATIVE DATA

2.1 Location of Testing

The EMI tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Elero USA, Inc.

David Harned

Compatible Electronics, Inc.

Kyle Fujimoto Test Engineer James Ross Test Engineer

2.4 Date Test Sample was Received

The test sample was received on March 1, 2006

2.5 Disposition of the Test Sample

The sample has not yet been returned to Elero USA, Inc. as of April 11, 2006.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF Radio Frequency

EMI Electromagnetic Interference

EUT Equipment Under Test

P/N Part Number S/N Serial Number HP Hewlett Packard

ITE Information Technology Equipment

CML Corrected Meter Limit

LISN Line Impedance Stabilization Network

Model: MemoTec-915

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this EMI Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

Transmitter Model: MemoTec-915

4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description Of Test Configuration - EMI

Setup and operation of the equipment under test.

Specifics of the EUT and Peripherals Tested

The Transmitter Model: MemoTec-915 (EUT) was tested as a stand alone unit and continuously transmitting. The EUT's antenna was hard wired onto the PCB.

After the transmitter is activated by pressing the button, the transmission will cease operation once the button is released.

The final radiated data was taken in the mode above. Please see Appendix E for the data sheets.

Transmitter
Model: MemoTec-915

4.1.1 Cable Construction and Termination

There are no external cables connected to the EUT.





Transmitter
Model: MemoTec-915

5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT

5.1 EUT and Accessory List

EQUIPMENT	MANU- FACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
TRANSMITTER (EUT)	ELERO USA, INC.	MemoTec-915	N/A	UFJ283000902

Transmitter
Model: MemoTec-915

5.2 EMI Test Equipment

EQUIPMENT TYPE	MANU- FACTURER	MODEL NUMBER	SERIAL NUMBER	CALIBRATION DATE	CALIBRATION DUE DATE
	GENERAL TEST I	EQUIPMENT U	SED FOR ALL I	RF EMISSIONS TEST	S
Spectrum Analyzer – Main Section	Hewlett Packard	8566B	3638A08784	June 10, 2005	June 10, 2006
Spectrum Analyzer – Display Section	Hewlett Packard	85662A	3701A22279	June 10, 2005	June 10, 2006
Quasi-Peak Adapter	Hewlett Packard	85650A	2430A00424	June 11, 2005	June 11, 2006
Computer	Hewlett Packard	4530	US91912319	N/A	N/A
EMI Receiver	Rohde & Schwarz	ESIB40	100172	October 28, 2004	October 28, 2006
Monitor	Hewlett Packard	D5258A	TW74500641	N/A	N/A
	RF RA	DIATED EMIS	SIONS TEST EQ	QUIPMENT	
Radiated Emissions Data Capture Program	Compatible Electronics	2.0	N/A	N/A	N/A
Preamplifier	Com Power	PA-103	1582	January 19, 2006	Jan. 19, 2007
Biconical Antenna	Com Power	AB-900	15251	March 9, 2006	March 9, 2007
Log Periodic Antenna	Com Power	AL-100	16247	August 22, 2005	Aug. 22, 2006
Loop Antenna	Com Power	AL-130	17089	September 21, 2005	Sept. 21, 2006
Horn Antenna	Com Power	AH-118	10067	July 27, 2004	July 27, 2006
Microwave Preamplifier	Com Power	PA-122	181917	January 20, 2006	Jan. 20, 2007
Antenna Mast	Com Power	AM-100	N/A	N/A	N/A

Model: MemoTec-915

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 and 7.1 of this report for EMI test location.

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

The EUT was not grounded.

Model: MemoTec-915

7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 Conducted Emissions Test

The spectrum analyzer was used as a measuring meter. The data was collected with the spectrum analyzer in the peak detect mode with the "Max Hold" feature activated. The quasi-peak was used only where indicated in the data sheets. A 10 dB attenuation pad was used for the protection of the spectrum analyzer input stage, and the offset was adjusted accordingly to read the actual data measured. The LISN output was measured using the spectrum analyzer. The output of the second LISN was terminated by a 50 ohm termination. The effective measurement bandwidth used for this test was 9 kHz

Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI C63.4: 2001. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by the Compatible Electronics conducted emissions software in several overlapping sweeps by running the spectrum analyzer at a minimum scan rate of 10 seconds per octave. The final qualification data is located in Appendix E.

Test Results:

This test was not performed because the EUT is battery powered only and does not connect to the AC public mains.

Model: MemoTec-915

7.2 Radiated Emissions (Spurious and Harmonics) Test

The spectrum analyzer was used as a measuring meter along with the quasi-peak adapter. Amplifiers were used to increase the sensitivity of the instrument. The Com-Power Preamplifier Model: PA-103 was used for frequencies from 30 MHz to 1 GHz, and the Com-Power Microwave Preamplifier Model: PA-122 was used for frequencies from 1 GHz to 9.3 GHz. The spectrum analyzer was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps.

For the peak readings below 1000 MHz that were within 3 dB of the spec limit or higher, the quasi-peak adapter was used to quasi-peak the readings.

For the peak readings above 1000 MHz that were within 3 dB of the spec limit or higher, the readings were averaged manually by narrowing the video filter down to 10 Hz and slowing the sweep time to keep the amplitude reading calibrated.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER	
9 kHz to 150 kHz	200 Hz	Active Loop Antenna	
150 kHz to 30 MHz	9 kHz	Active Loop Antenna	
30 MHz to 300 MHz	120 kHz	Biconical Antenna	
300 MHz to 1 GHz	120 kHz	Log Periodic Antenna	
1 GHz to 9.3 GHz	1 MHz	Horn Antenna	

The open field test site of Compatible Electronics, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.4. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna in order to ensure accurate results. The loop antenna was also rotated in the horizontal and vertical axis in order to ensure accurate results.

The presence of ambient signals was verified by turning the EUT off. In case an ambient signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the ambient signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance to obtain final test data. The final qualification data sheets are located in Appendix E.

Model: MemoTec-915

7.3 Radiated Emissions (Spurious and Harmonics) Test (continued)

Test Results:

The EUT complies with the **Class B** limits of CFR Title 47, Part 15, Subpart B; and CFR Title 47, Part 15, Subpart C, sections 15.205, 15.209, and 15.249.



Transmitter
Model: MemoTec-915

8. CONCLUSIONS

The Transmitter Model: MemoTec-915 meets all of the **Class B** specification limits defined in CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.



Transmitter
Model: MemoTec-915

APPENDIX A

LABORATORY RECOGNITIONS

Model: MemoTec-915

LABORATORY RECOGNITIONS

Compatible Electronics has the following agency accreditations:

National Voluntary Laboratory Accreditation Program - Lab Code: 200528-0

Voluntary Control Council for Interference - Registration Numbers: R-983, C-1026, R-984 and C-1027

Bureau of Standards and Metrology Inspection - Reference Number: SL2-IN-E-1031

Conformity Assessment Body for the EMC Directive Under the US/EU MRA Appointed by NIST

Compatible Electronics is recognized or on file with the following agencies:

Federal Communications Commission

Industry Canada

Radio-Frequency Technologies (Competent Body)

Transmitter Model: MemoTec-915

APPENDIX B

MODIFICATIONS TO THE EUT

MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC 15.249 or FCC Class B specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made during testing.



APPENDIX C

ADDITIONAL MODELS COVERED UNDER THIS REPORT

ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Transmitter Model: MemoTec-915

S/N: N/A

There were no additional models covered under this report.



Transmitter Model: MemoTec-915

APPENDIX D


DIAGRAMS, CHARTS, AND PHOTOS

ELECTRONICS

FIGURE 1: PLOT MAP AND LAYOUT OF RADIATED SITE

OPEN LAND > 15 METERS

OPEN LAND > 15 METERS



OPEN LAND > 15 METERS

X = GROUND RODS = GROUND SCREEN

D = TEST DISTANCE (meters) = WOOD COVER

COM-POWER AB-900

BICONICAL ANTENNA

S/N: 15251

CALIBRATION DATE: MARCH 9, 2006

FREQUENCY	FACTOR	FREQUENCY	FACTOR
(MHz)	(dB)	(MHz)	(dB)
30	11.27	120	13.04
35	10.29	125	12.67
40	9.72	140	11.91
45	11.45	150	11.61
50	13.34	160	13.67
60	11.44	175	15.97
70	8.41	180	16.64
80	6.21	200	16.54
90	7.50	250	16.96
100	11.65	300	17.48

Model: MemoTec-915

COM-POWER AL-100

LOG PERIODIC ANTENNA

S/N: 16247

CALIBRATION DATE: AUGUST 22, 2005

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
300	12.70	700	19.72
400	13.19	800	20.59
500	14.99	900	21.10
600	15.95	1000	24.35

COM-POWER PA-103

PREAMPLIFIER

S/N: 1582

CALIBRATION DATE: JANUARY 19, 2006

FREQUENCY	FACTOR	FREQUENCY	FACTOR
(MHz)	(dB)	(MHz)	(dB)
30	32.7	300	32.4
40	32.6	350	32.4
50	32.6	400	32.1
60	32.8	450	32.1
70	32.7	500	31.8
80	32.7	550	31.8
90	32.7	600	32.0
100	32.6	650	31.9
125	32.6	700	31.5
150	32.5	750	31.7
175	32.4	800	31.4
200	32.5	850	31.6
225	32.5	900	30.8
250	32.3	950	31.1
275	32.4	1000	30.9

COM-POWER PA-122

PREAMPLIFIER

S/N: 181917

CALIBRATION DATE: JANUARY 20, 2006

FREQUENCY	FACTOR	FREQUENCY	FACTOR
(GHz)	(dB)	(GHz)	(dB)
1.0	34.697	10.0	36.558
1.5	33.817	10.5	35.048
2.0	33.587	11.0	33.258
2.5	33.804	11.5	32.960
3.0	33.850	12.0	33.312
3.5	33.943	12.5	33.836
4.0	34.399	13.0	34.178
4.5	34.847	13.5	34.197
5.0	35.172	14.0	33.769
5.5	35.383	14.5	33.392
6.0	35.539	15.0	33.387
6.5	34.802	15.5	34.038
7.0	33.793	16.0	34.884
7.5	33.511	16.5	35.740
8.0	33.910	17.0	35.341
8.5	34.907	17.5	34.729
9.0	36.036	18.0	33.760
9.5	36.661		

COM POWER AH-118

HORN ANTENNA

S/N: 10067

CALIBRATION DATE: JULY 27, 2004

FREQUENCY	FACTOR	FREQUENCY	FACTOR
(GHz)	(dB)	(GHz)	(dB)
1.0	25.0	10.0	37.8
1.5	27.9	10.5	39.4
2.0	31.5	11.0	39.4
2.5	31.1	11.5	40.6
3.0	30.6	12.0	40.8
3.5	30.5	12.5	40.5
4.0	30.6	13.0	41.2
4.5	31.4	13.5	42.0
5.0	33.7	14.0	43.1
5.5	33.8	14.5	43.4
6.0	34.7	15.0	39.2
6.5	35.0	15.5	38.8
7.0	35.9	16.0	40.1
7.5	38.1	16.5	40.2
8.0	38.2	17.0	43.4
8.5	37.7	17.5	46.6
9.0	37.7	18.0	45.8
9.5	38.4		

COM-POWER AL-130

LOOP ANTENNA

S/N: 17089

CALIBRATION DATE: SEPTEMBER 21, 2005

FREQUENCY	MAGNETIC	ELECTRIC
(MHz)	(dB/m)	(dB/m)
0.009	-42.84	8.66
0.01	-41.93	9.57
0.02	-41.29	10.21
0.05	-42.37	9.13
0.07	-41.8	9.7
0.1	-41.83	9.67
0.2	-44.13	7.37
0.3	-41.73	9.77
0.5	-41.8	9.7
0.7	-41.53	9.97
1	-41.46	10.04
2	-41.14	10.36
3	-41.26	10.24
4	-41.46	10.04
5	-41.10	10.40
10	-40.83	10.67
15	-41.47	10.03
20	-35.44	16.06
25	-42.37	9.13
30	-42.94	8.56



FRONT VIEW

ELERO USA, INC. TRANSMITTER MODEL: MemoTec-915

FCC SUBPART B AND FCC SUBPART C - RADIATED EMISSIONS - LAB A



REAR VIEW

ELERO USA, INC. TRANSMITTER MODEL: MemoTec-915

FCC SUBPART B AND FCC SUBPART C - RADIATED EMISSIONS - LAB A



FRONT VIEW

ELERO USA, INC.
TRANSMITTER
MODEL: MemoTec-915

FCC SUBPART B AND FCC SUBPART C - RADIATED EMISSIONS - LAB B



REAR VIEW

ELERO USA, INC. TRANSMITTER MODEL: MemoTec-915

FCC SUBPART B AND FCC SUBPART C - RADIATED EMISSIONS - LAB B

Transmitter
Model: MemoTec-915

APPENDIX E

DATA SHEETS

RADIATED EMISSIONS

DATA SHEETS

FCC 15.249

Elero USA, Inc. Date: 03-17-06
Transmitter Labs: A and B

Model: MemoTec-915 Tested By: Kyle Fujimoto

					Peak /	Ant.	Table	
Freq.	Level				QP/	Height	Angle	
(MHz)	(dBuV)	Pol (v/h)	Limit	Margin	Avg	(m)	(deg)	Comments
915.25	86.81	V	94	-7.19	Peak	1.25	90	
1830.4	48.99	V	74	-25.01	Peak	1.38	135	
1830.4	44.53	V	54	-9.47	Avg	1.38	135	
2745.8	42.82	V	74	-31.18	Peak	1.63	135	
2745.8	30.6	V	54	-23.4	Avg	1.63	135	
3660.9	48.25	V	74	-25.75	Peak	2.26	135	
3660.9	44.64	V	54	-9.36	Avg	2.26	135	
4576.3	42.12	V	74	-31.88	Peak	2.54	180	
4576.3	30.01	V	54	-23.99	Avg	2.54	180	
5491.5	49.36	V	74	-24.64	Peak	2.17	135	
5491.5	38.98	V	54	-15.02	Avg	2.17	135	
6406.8	47.25	V	74	-26.75	Peak	1.85	135	
6406.8	34.27	V	54	-19.73	Avg	1.85	135	
7322		V	80.8	-80.8	Peak			No Emissions Detected
7322		V	60.8	-60.8	Avg			No Emissions Detected
8237.3		V	74	-74	Peak			No Emissions Detected
8237.3		V	54	-54	Avg			No Emissions Detected
9152.5		V	74	-74	Peak			No Emissions Detected
9152.5		V	54	-54	Avg			No Emissions Detected

FCC 15.249

Elero USA, Inc. Transmitter

Model: MemoTec-915

Date: 03-17-06 Labs: A and B

Tested By: Kyle Fujimoto

F					Peak /	Ant.	Table	
Freq.	Level	5 1 ((1)	,		QP /	Height	Angle	
(MHz)	(dBuV)	Pol (v/h)		Margin	Avg	(m)	(deg)	Comments
915.25	83.11	Н	94	-10.89	Peak	1.25	0	
1830.4	49.46	Н	74	-24.54	Peak	2.44	180	
1830.4	46.22	Н	54	-7.78	Avg	2.44	180	
2745.8	41.66	Н	74	-32.34	Peak	2.05	135	
2745.8	26.77	Н	54	-27.23	Avg	2.05	135	
3660.9	48.83	Н	74	-25.17	Peak	2.78	135	
3660.9	44.86	Н	54	-9.14	Avg	2.78	135	
4576.3	43.82	Н	74	-30.18	Peak	2.78	135	
4576.3	29.05	Н	54	-24.95	Avg	2.78	135	
5491.5	51.78	Н	74	-22.22	Peak	2.17	135	
5491.5	46.08	Н	54	-7.92	Avg	2.17	135	
0.400.0			7.4	7.4	Б			
6406.8		H	74	-74	Peak			No Emissions Detected
6406.8		Н	54	-54	Avg			No Emissions Detected
7222		- 11	74	7.4	Dools			No Emissions Datastad
7322		H	74	-74	Peak			No Emissions Detected
7322		П	54	-54	Avg			No Emissions Detected
8237.3		Н	74	-74	Peak			No Emissions Detected
8237.3		H	54	-74 -54	Avg			No Emissions Detected
0201.0		- ' '	UT	J-7	, wg			140 Emissions Detected
9152.5		Н	74	-74	Peak			No Emissions Detected
9152.5		Н	54	-54	Avg			No Emissions Detected

FCC 15.249

Elero USA, Inc. Date: 03-17-06
Transmitter Labs: A and B

Model: MemoTec-915 Tested By: Kyle Fujimoto

Digital Portion 10 kHz - 9300 MHz

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
								No Emissions Detected
								from 10 kHz to 9300 MHz
								in either Polarization
								for the Digital Portion
								and the non-harmonic
								emissions of the Transmitter.