







ISO/IEC17025Accredited Lab.

Report No: FCC 1104204-01 File reference No: 2011-07-20

Applicant: Gajah International (HK) Co., Ltd

Product: MID

Model No: M7003

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: July 20, 2011

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District, Shenzhen,CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1104204-01 Page 2 of 78

Date: 2011-07-20



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC- Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.

Page 3 of 78

Report No: 1104204-01

Date: 2011-07-20



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	5
3.0	Technical Details	8
3.1	Summary of Test Results	8
3.2	Test Standards	8
4.0	EUT Modification.	8
5.0	Power Line Conducted Emission Test.	9
5.1	Schematics of the Test.	9
5.2	Test Method and Test Procedure.	9
5.3	Configuration of the EUT	9
5.4	EUT Operating Condition.	10
5.5	Conducted Emission Limit.	10
5.6	Test Result.	10
6.0	Radiated Emission test	13
5.1	Test Method and Test Procedure.	13
5.2	Configuration of the EUT	13
5.3	EUT Operation Condition.	13
5.4	Radiated Emission Limit.	14
7.0	6dB Bandwidth Measurement	33
8.0	Maximum Peak Output Power	42
9.0	Power Spectral Density Measurement.	44
10.0	Out of Band Measurement	52
11.0	Antenna Requirement.	65
12.0	RF Exposure	66
13.0	FCC ID Label	67
14.0	Photo of Test Setup and EUT View	68

Report No: 1104204-01 Page 4 of 78

Date: 2011-07-20



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-01

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Gajah International (HK) Co., Ltd

Address: 9A, Block Yinxing, Huamaoxin Garden, 7001 Hongli W, Shenzhen, Guangdong, China

Telephone: 86-755-82970307 Fax: 86-755-82970571

1.3 Description of EUT

Product: MID

Manufacturer: Gajah International (HK) Co., Ltd

Brand Name: N/A
Model Number: M7003
Additional model number: N/A

Power Source Adapter Model: PS12K0901500; Input: 100-240V AC, 50/60Hz, 0.35A; Output: DC9V,

1.5A

Type of Modulation IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK)

IEEE 802.11g: OFDM(64QAM, 16AQM, QPSK, BPSK)

Frequency range IEEE 802.11b/g: 2412-2462MHz

Channel Spacing IEEE 802.11b/g: 5MHz

Air Data Rate IEEE 802.11b: 11 long, 11 short, 5.5 long, 5.5 short, 2 long, 2 short, 1 long Mbps

IEEE 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps

Frequency Selection By software

Channel Number IEEE 802.11b/g: 11 Channels

Report No: 1104204-01 Page 5 of 78

TIMEWAY

1.4 Submitted Sample: 2 Sample

1.5 Test Duration 2011-07-01 to 2011-07-19

Date: 2011-07-20

1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 78

Report No: 1104204-01

Date: 2011-07-20



6.0	Test Equipments						
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date		
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2011-04-26	2012-04-25		
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2011-04-26	2012-04-25		
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2011-04-26	2012-04-25		
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2011-04-26	2012-04-25		
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2011-04-26	2012-04-25		
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2011-04-26	2012-04-25		
System Controller	CT	SC100	-	2011-04-26	2012-04-25		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850	2011-04-26	2012-04-25		
Computer	IBM	8434	1S8434KCE99BLXL O*	-	-		
Loop Antenna	EMCO	6502	00042960	2011-04-26	2012-04-25		
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2011-04-26	2012-04-25		
3m OATS			N/A	2011-04-26	2012-04-25		
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2011-04-26	2012-04-25		
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2011-04-26	2012-04-25		
Power meter	Anritsu	ML2487A	6K00003613	2011-04-26	2012-04-25		
Power sensor	Anritsu	MA2491A	32263	2011-04-26	2012-04-25		
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2011-04-26	2012-04-25		
LISN	AFJ	LS16C	10010947251	2011-04-26	2012-04-25		
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2011-04-26	2012-04-25		
9*6*6 Anechoic			N/A	2011-04-26	2012-04-25		
EMI Test Receiver	RS	ESCS30	100139	2011-04-26	2012-04-25		
LISN	AFJ	LS16C	10010947251	2011-04-26	2012-04-25		
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2011-04-26	2012-04-25		

Report No: 1104204-01 Page 7 of 78

Date: 2011-07-20



3. DESCRIPTION OF TEST MODES

IEEE 802.11b, 802.11g mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) were chosen for full testing. IEEE 802.11g mode: 6Mbps data rate (worst case) were chosen for full testing.

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes.

Page 8 of 78

Report No: 1104204-01 Date: 2011-07-20



3.0 **Technical Details**

Summary of test results 3.1

The EUT has been tested ac	ccording to the following speci	fications:	
Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107 & 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 **EUT Modification**


No modification by Shenzhen Timeway Technology Consulting Co.,Ltd

Page 9 of 78

Report No: 1104204-01 Date: 2011-07-20 TIMEWAY IN THE PROPERTY OF THE

5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2009. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2009.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID
MID	Gajah International (HK) Co., Ltd	M7003	UFKM7003

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1104204-01 Page 10 of 78

Date: 2011-07-20



C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
U-disk	Netac	U208	FCC DOC	
Earphone				Data cable of 1.0m length
SD Card	Kingston			
PC	IBM	R400	FCC DOC	
Keyboard	DELL		FCC DOC	Data cable of 1.0m length
Mouse	DELL		FCC DOC	Data cable of 1.0m length

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107

	Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)		
	(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
0.1	5 ~ 0.50	79.0	66.0	66.0~56.0*	56.0~46.0*	
0.5	$50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.0	00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Note: the worse cases was selected to conducted the test

Date: 2011-07-20




A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Keep EUT Transmitting under WIFI mode, Read SD card, Play USB

And Run EMC test program

Results: Pass

Please refer to following diagram for individual



Frequency		Reading	Limi	t		
	Neutral		Line		(dB µ V)	
(MHz)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.1773			36.30	27.04	64.61	54.61
0.3570			37.00	23.50	58.80	48.80
0.6734			37.88	25.49	56.00	46.00
1.4430			35.51	23.58	56.00	46.00
2.7828			35.97	25.01	56.00	46.00
11.1327			36.35	25.65	56.00	46.00

Date: 2011-07-20




B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Keep EUT Transmitting under WIFI mode, Read SD card, Play USB

And Run EMC test program

Results: Pas

Please refer to following diagram for individual



Frequency		Reading	Limi	t		
	Neutral		Line		(dB µ V)	
(MHz)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.1812	40.47	29.87			64.43	54.43
0.2594	39.34	20.50			61.45	51.45
0.3608	40.89	26.98			58.71	48.71
0.6656	41.38	26.27			56.00	46.00
1.3844	40.15	28.31			56.00	46.00
2.6773	42.09	29.18			56.00	46.00

Report No: 1104204-01 Page 13 of 78

Date: 2011-07-20




6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2009. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "**QP**" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Test Voltage: 120V~, 60Hz

Block diagram of Test setup



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition

 Same as section 5.4 of this report.

Report No: 1104204-01 Page 14 of 78

Date: 2011-07-20



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

	1	8 1
Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. For Radiated emissions below 30MHz, the emission level is much less than the limit value and meet the rule requirement.

Report No: 1104204-01 Page 15 of 78

Date: 2011-07-20



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep EUT Transmitting under WIFI mode, Read SD card, Play USB And Run

EMC test program, Full Load

Results: Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
107.7553	37.51	Н	43.50
45.5510	33.20	Н	40.00
142.7692	37.35	Н	43.50
125.2505	37.13	Н	43.50
187.4550	37.24	Н	43.50
539.2985	40.31	Н	46.00
613.1662	40.29	Н	46.00
323.5271	37.99	Н	46.00
828.9380	40.55	Н	46.00
45.5511	36.23	V	40.00
125.2505	38.67	V	43.50
191.3427	34.72	V	43.50
467.3747	33.39	V	46.00
613.1662	33.59	V	46.00
323.5271	31.41	V	46.00
136.9138	37.10	V	43.50


Report No: 1104204-01


Date: 2011-07-20



Test Figure:

H





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104204-01 Page 17 of 78

Date: 2011-07-20



Operation Mode: Keep Transmitting in CH01 at 6Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)	
2412.00	86.64 (PK)	V	Fundamental Eraguanay	
2412.00	81.21 (PK)	Н	Fundamental Frequency	
4824.00	42.02 (PK)	V	74(Peak)/ 54(AV)	
4824.00	1	Н	74(Peak)/ 54(AV)	
7236.00		H/V	74(Peak)/ 54(AV)	
9648.00		H/V	74(Peak)/ 54(AV)	
12060		H/V	74(Peak)/ 54(AV)	
14472		H/V	74(Peak)/ 54(AV)	
16884		H/V	74(Peak)/ 54(AV)	
19296		H/V	74(Peak)/ 54(AV)	
21708		H/V	74(Peak)/ 54(AV)	
24120	24120		74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6Mbps

Date: 2011-07-20



Operation Mode: Keep Transmitting in CH06 at 6Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB μ V/m)	
2437.00	82.12 (PK)	Н	Fundamental Frequency	
2437.00	88.19 (PK))	V	Fundamental Frequency	
4874.00		Н	74(Peak)/ 54(AV)	
4874.00	43.86	V	74(Peak)/ 54(AV)	
7311.00		H/V	74(Peak)/ 54(AV)	
9748.00		H/V	74(Peak)/ 54(AV)	
12185	12185		74(Peak)/ 54(AV)	
14622		H/V	74(Peak)/ 54(AV)	
17059	17059		74(Peak)/ 54(AV)	
19496	19496		74(Peak)/ 54(AV)	
21933	21933		74(Peak)/ 54(AV)	
24370	24370		74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6Mbps

Operation Mode: Keep Transmitting in CH11 at 6Mbps

	<u> </u>			
Frequency (MHz)	quency (MHz) Level@3m (dB \mu V/m)		Limit@3m (dB \(\mu \)V/m)	
2462.00	87.08 (PK)	V	Fundamental Frequency	
2462.00	80.43 (PK)	Н	Tundamental Prequency	
4924	-	Н	74(Peak)/ 54(AV)	
4924	43.82	V	74(Peak)/ 54(AV)	
7368		H/V	74(Peak)/ 54(AV)	
9848	-	H/V	74(Peak)/ 54(AV)	
12310	12310		74(Peak)/ 54(AV)	
14772	-1	H/V	74(Peak)/ 54(AV)	
17234	17234		74(Peak)/ 54(AV)	
19696	19696		74(Peak)/ 54(AV)	
22158	22158		74(Peak)/ 54(AV)	
24650	24650		74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 6Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No: 1104204-01

Date: 2011-07-20



Please refer to the following test plots for details:

CH01 at 6Mbps: Horizontal



13200.00


Page 20 of 78

Report No: 1104204-01

Date: 2011-07-20



CH01 at 6Mbps: Vertical



11600.00

12400.00

14000.00

14800.00

16400.00

15600.00

13200.00


Page 21 of 78

Report No: 1104204-01

Date: 2011-07-20



CH06 at 6Mbps: Horizontal




Page 22 of 78

Report No: 1104204-01

Date: 2011-07-20



CH06 at 6Mbps: Vertical



11600.00

12400.00

14000.00

14800.00

15600.00

16400.00


Page 23 of 78

Report No: 1104204-01

Date: 2011-07-20



CH11 at 6Mbps: Horizontal




Page 24 of 78

Report No: 1104204-01

Date: 2011-07-20



CH11at 6Mbps: Vertical



Note: For the radiated emissions from 18GHz-25GHz, it is the floor noise that meets the requirement of FCC rule.

Date: 2011-07-20



Operation Mode: Keep Transmitting in CH01 at 11Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)	
2412.00	86.86 (PK)	V	Fundamental Frequency	
2412.00	80.10 (PK)	Н	Tundamental Prequency	
4824.00	43.26	Н	74(Peak)/ 54(AV)	
4824.00	45.63	V	74(Peak)/ 54(AV)	
7236.00		H/V	74(Peak)/ 54(AV)	
9648.00		H/V	74(Peak)/ 54(AV)	
12060	12060		74(Peak)/ 54(AV)	
14472		H/V	74(Peak)/ 54(AV)	
16684	16684		74(Peak)/ 54(AV)	
19296	19296		74(Peak)/ 54(AV)	
21708	21708		74(Peak)/ 54(AV)	
24120	24120		74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Operation Mode: Keep Transmitting in CH06 at 11Mbps

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)	
2437.00	84.71(PK)	Н	- 1	
2437.00	87.77 (PK)	V	Fundamental Frequency	
4874.00		Н	74(Peak)/ 54(AV)	
4874.00	46.88	V	74(Peak)/ 54(AV)	
7311.00		H/V	74(Peak)/ 54(AV)	
9748.00		H/V	74(Peak)/ 54(AV)	
12185		H/V	74(Peak)/ 54(AV)	
14622		H/V	74(Peak)/ 54(AV)	
17059		H/V	74(Peak)/ 54(AV)	
19496		H/V	74(Peak)/ 54(AV)	
21933		H/V	74(Peak)/ 54(AV)	
24370	24370		74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode **11Mbps**

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104204-01 Page 26 of 78

Date: 2011-07-20



Operation Mode: Keep Transmitting in CH11 at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)	
2462.00	82.02(PK)	Н	Fundamental Frequency	
2462.00	89.88(PK)	V	Fundamental Frequency	
4924		Н	74(Peak)/ 54(AV)	
4924	43.26	V	74(Peak)/ 54(AV)	
7368	-	H/V	74(Peak)/ 54(AV)	
9848		H/V	74(Peak)/ 54(AV)	
12310		H/V	74(Peak)/ 54(AV)	
14772		H/V	74(Peak)/ 54(AV)	
17234		H/V	74(Peak)/ 54(AV)	
19696		H/V	74(Peak)/ 54(AV)	
22158	22158		74(Peak)/ 54(AV)	
24650	24650		74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at **11Mbps**

Page 27 of 78


Report No: 1104204-01

Date: 2011-07-20



Please refer to the following test plots for details:

CH01 at 11Mbps: Horizontal



11600.00

12400.00

13200.00

10000.000 10800.00

14000.00

14800.00

15600.00

16400.00

18000.00 MHz


Page 28 of 78

Report No: 1104204-01

Date: 2011-07-20



CH01 at 11Mbps: Vertical



11600.00

12400.00

13200.00

10000.000 10800.00

14000.00

14800.00

15600.00

16400.00

18000.00 MHz


Page 29 of 78

Report No: 1104204-01

Date: 2011-07-20



CH06 at 11Mbps: Horizontal




Page 30 of 78

Report No: 1104204-01

Date: 2011-07-20



CH06 at 11Mbps: Vertical




Page 31 of 78

Report No: 1104204-01

Date: 2011-07-20



CH11 at 11Mbps: Horizontal




Page 32 of 78

Report No: 1104204-01

Date: 2011-07-20



CH11 at 11Mbps: Vertical



Note: For the radiated emissions from 18GHz-25GHz, it is the floor noise that meet the requirement of FCC rule.


Report No: 1104204-01 Page 33 of 78

Date: 2011-07-20



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500kHz

7.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator.

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW for 802.11b/g mode; The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

7.4 Test Result

Report No: 1104204-01 Page 34 of 78

Date: 2011-07-20




EUT			MID		Model		M7003	
Mode		8	02.11b Input Volta		age 120V		<i>I~</i>	
Temperat	ure	24	4 deg. C,		Humidity		56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)				num Limit MHz)	Pass/ Fail
1		2412	1	10	.04		0.5	Pass
6		2437	1	10.04			0.5	Pass
11		2462	1	10	.12		0.5	Pass

Report No: 1104204-01 Page 35 of 78

Date: 2011-07-20



1. 802.11b at 1Mbps of CH01




Date: 16.JUL.2011 14:02:59

Report No: 1104204-01 Page 36 of 78

Date: 2011-07-20



2. 802.11b at 1Mbps of CH06




Date: 16.JUL.2011 14:04:39

Report No: 1104204-01 Page 37 of 78

Date: 2011-07-20



3. 802.11b at 1Mbps of CH11



Date: 16.JUL.2011 14:05:40

Report No: 1104204-01 Page 38 of 78

Date: 2011-07-20



EUT		MID		Model		M7003		
Mode		8	302.11g		Input Vol	tage	120V	/~
Temperat	ure	24	4 deg. C,		Humidity		56%]	RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		andwidth Hz)		num Limit MHz)	Pass/ Fail
1		2412	6	16	.60		0.5	Pass
6		2437	6	16	.56		0.5	Pass
11		2462	6	16	.60		0.5	Pass


Report No: 1104204-01 Page 39 of 78

Date: 2011-07-20



Test Plots:

1. 802.11g at 6Mbps of CH01




Date: 16.JUL.2011 14:09:34

Report No: 1104204-01 Page 40 of 78

Date: 2011-07-20



2. 802.11g at 6Mbps of CH06




Date: 16.JUL.2011 14:08:40

Report No: 1104204-01 Page 41 of 78

Date: 2011-07-20



3. 802.11g at 6Mbps of CH11



Date: 16.JUL.2011 14:07:10


Report No: 1104204-01 Page 42 of 78

Date: 2011-07-20



8. Maximum Peak Output Power

8.1 Test Setup



8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

8.4Test Results

EUT		MII	D Model		Model		M7003		
Mode		802.11b		Input Voltage		Input Voltage 1		20V~	
Temperati	ure	24 deg	24 deg. C, Hum		g. C, Humidity 50		Humidity		6% RH
Channel	Cha	hannel Frequency Peak Power (MHz) (dBm)		Output	Peak P Lin (dB	nit	Pass/ Fail		
1		2412	11.05		30)	Pass		
6		2437	10.79		30)	Pass		
11		2462	11.29		30)	Pass		

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

Report No: 1104204-01 Page 43 of 78

Date: 2011-07-20



EUT		MII	D Model		Model		И7003		
Mode	ode 802.11g		1g Input Volt		11g Input Voltage		Input Voltage		20V~
Temperati	ure	re 24 deg. C, Humidity		Humidity		C, Humidity 5		5% RH	
Channel	Cha	annel Frequency (MHz)	•		Peak Power Limit (dBm)		Pass/ Fail		
1		2412 9.87		7 3)	Pass		
6		2437	10.88		30)	Pass		
11		2462	11.45		30)	Pass		

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

Page 44 of 78


Report No: 1104204-01

Date: 2011-07-20



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 10kHz VBW, set sweep time=100s, **PK detector.**

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

9.4Test Result

EUT		MII	D Model		Iodel		M7003		
Mode		802.1	1b Input		1b Input Voltage		Input Voltage		20V~
Temperati	erature 24 deg. C, Hur		Humidity		5% RH				
Channel	Ch	Channel Frequency (MHz) Final R Level in (dl		Maximu			Pass/ Fail		
1		2412	-17.48		8		Pass		
6		2437	-17.28		8		Pass		
11		2462	-17.03		8		Pass		

Note: For 802.11b mode at finial test to get the worst-case emission at 11Mbps for CH11, CH06 and CH01

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1104204-01 Page 45 of 78

Date: 2011-07-20



EUT		Mobile Inter	net Device Mo		odel	MID	
Mode		802.1	1g Input		Voltage	1	20V~
Temperati	ure	24 deg	24 deg. C, Hum		nidity	56	5% RH
Channel	Cha	Channel Frequency (MHz) Final RF Power Level in 3kHz BW (dBm)			Maximur (dB		Pass/ Fail
1		2412		-23.22			Pass
6		2437 -22.41			8		Pass
11		2462	-26.73		8		Pass

Note: For 802.11g mode at finial test to get the worst-case emission at 6Mbps for CH11, CH06 and CH01

Page 46 of 78


Report No: 1104204-01

Date: 2011-07-20



9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01



Date: 16.JUL.2011 14:37:36


Page 47 of 78

Date: 2011-07-20



2. 802.11b at 11Mbps at CH06

Report No: 1104204-01



Date: 16.JUL.2011 14:40:35


Page 48 of 78

Report No: 1104204-01

Date: 2011-07-20



3. 802.11b at 1Mbps of CH11



Date: 16.JUL.2011 14:45:08


Page 49 of 78

Report No: 1104204-01

Date: 2011-07-20



4. 802.11g at 6Mbps of CH01




Date: 16.JUL.2011 14:34:48

Report No: 1104204-01 Page 50 of 78

Date: 2011-07-20



5. 802.11g at 6Mbps of CH06



Date: 16.JUL.2011 14:32:48


Page 51 of 78

Report No: 1104204-01

Date: 2011-07-20



6. 802.11g at 6Mbps of CH11



Date: 16.JUL.2011 14:30:00


Report No: 1104204-01 Page 52 of 78

Date: 2011-07-20



10 Out of Band Measurement

10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test.(Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Page 53 of 78

Report No: 1104204-01

Date: 2011-07-20




For 802.11b mode

CH01 at 11Mbps

10.4 Band-edge Measurement

Product:	MID	Test Mode:	CH1
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 16.JUL.2011 14:21:07

Page 54 of 78

Report No: 1104204-01

Date: 2011-07-20




CH11 at 1Mbps

10.4 Band-edge Measurement

Product:	MID	Test Mode:	CH11
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 16.JUL.2011 14:19:53

Page 55 of 78

Report No: 1104204-01

Date: 2011-07-20




For 802.11g mode

CH01 at 6Mbps

10.4 Band-edge Measurement

Product:	MID	Test Mode:	CH1
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 16.JUL.2011 14:22:04

Page 56 of 78

Report No: 1104204-01

Date: 2011-07-20




CH11 at 6Mbps

10.4 Band-edge Measurement

Product:	MID		Test Mode:	CH11
Mode	Keeping 7	Keeping Transmitting		120V~
Temperature	24 d	24 deg. C,		56% RH
Test Result:		Pass	Detector	PK

Test Figure:



Date: 16.JUL.2011 14:23:31

Page 57 of 78

Report No: 1104204-01

Date: 2011-07-20




For 802.11b mode

CH01 at 11Mbps

10.4 Restricted band Measurement

Product:		MID		M7003
Mode	Keeping	g Transmitting	Input Voltage	AC 120V
Temperature	24	l deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2400	PK (dBµV/m)	36.17	T ::4	$74(dB\mu V/m)$
	AV ($dB\mu V/m$)		Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	27.87	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)			54(dBµV/m)
2398.357	PK (dBμV/m)	36.55	T imit	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBμV/m)

Test Figure: Horizontal



Page 58 of 78

Report No: 1104204-01

Date: 2011-07-20




For 802.11b mode

CH01 at 11Mbps

10.4 Restricted band Measurement

Product:		MID	Model:	M7003
Mode	Keeping	g Transmitting	Input Voltage	AC 120V
Temperature	24	4 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2400	PK (dBµV/m)	40.46	T imait	$74(dB\mu V/m)$
	AV ($dB\mu V/m$)		Limit	$54(dB\mu V/m)$
2390	PK (dBµV/m)	29.95	Limit	$74(dB\mu V/m)$
	AV ($dB\mu V/m$)		Lillit	$54(dB\mu V/m)$
2397	PK (dBµV/m)	42.77	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Liffill	54(dBµV/m)

Test Figure: Vertical



Report No: 1104204-01 Page 59 of 78

Date: 2011-07-20




For 802.11b mode

CH11 at 11Mbps

10.4 Restricted band Measurement

Product:	MID		Model:	M7003
Mode	Keeping	g Transmitting	Input Voltage	AC 120V
Temperature	24	l deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2483.500	PK (dBµV/m)	35.59	T :!4	$74(dB\mu V/m)$
	AV ($dB\mu V/m$)		Limit	$54(dB\mu V/m)$

Test Figure: Vertical



Report No: 1104204-01 Page 60 of 78

Date: 2011-07-20




For 802.11b mode

CH11 at 11Mbps

10.4 Restricted band Measurement

Product:	MID		Model:	M7003
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.500	PK (dBµV/m)	28.76	T ::14	$74(dB\mu V/m)$
	AV ($dB\mu V/m$)		Limit	$54(dB\mu V/m)$

Test Figure: Horizontal



Report No: 1104204-01 Page 61 of 78

Date: 2011-07-20




For 802.11g mode

CH01 at 6Mbps

10.4 Restricted band Measurement

Product:	MID		Model:	M7003
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2390.000	PK (dBµV/m)	37.01	T imit	74(dBµV/m)
	AV $(dB\mu V/m)$	1	Limit	$54(dB\mu V/m)$
2400.000	PK (dBµV/m)	59.67	Limit	$74(dB\mu V/m)$
	AV ($dB\mu V/m$)	40.67		$54(dB\mu V/m)$

Test Figure: Horizontal



Report No: 1104204-01 Page 62 of 78

Date: 2011-07-20




For 802.11g mode

CH01 at 6Mbps

10.4 Restricted band Measurement

Product:	MID		Model:	M7003
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2390.000	PK (dBµV/m)	47.11	T imais	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$
2400.000	PK (dBµV/m)	66.33	Limit	$74(dB\mu V/m)$
	AV ($dB\mu V/m$)	47.05		$54(dB\mu V/m)$

Test Figure: Vertical



Report No: 1104204-01 Page 63 of 78

Date: 2011-07-20



For 802.11g mode


CH11 at 6Mbps

10.4 Restricted band Measurement

Product:	MID		Model:	M7003
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.500	PK (dBµV/m)	49.59	T :14	$74(dB\mu V/m)$
	AV ($dB\mu V/m$)	-	Limit	$54(dB\mu V/m)$

Test Figure: Vertical





Report No: 1104204-01 Page 64 of 78

Date: 2011-07-20



For 802.11g mode

CH11 at 6Mbps

10.4 Restricted band Measurement

Product:	MID		Model:	M7003
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.500	PK (dBµV/m)	43.50	T :14	$74(dB\mu V/m)$
	$AV (dB\mu V/m)$		Limit	$54(dB\mu V/m)$

Test Figure: Horizontal



Report No: 1104204-01 Page 65 of 78

Date: 2011-07-20



11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

It is A PCB antenna. The maximum Gain of the antenna is 2.0dBi.

Date: 2011-07-20



Page 66 of 78

12.0 RF Exposure

Applicable Standard

According to §1.1307(b)(5), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Portable device. **KDB616217 was used as the guidance.**

According to §1.1310 and §2.1093 RF exposure is calculated.

Measurement Result

For 802.11g Mode:

This is a Mobile Internet Device and the conducted output power is 11.45dBm (17.58mW), so the EIRP is 13.96*1.585=22.1266mW which is lower than low threshold 60/fGHz mW (60/2.462GHz= 24.37 mW), and the antenna is 2dBi which is less than 6dBi.

For 802.11b Mode:

This is a Mobile Internet Device and the conducted output power is 11.29dBm (16.94mW), so the EIRP is 13.46*1.585=21.3341mW which is lower than low threshold 60/fGHz mW (60/2.462GHz= 24.37 mW), and the antenna is 2dBi which is less than 6dBi.

The SAR measurement is not necessary.

Report No: 1104204-01 Page 67 of 78

Date: 2011-07-20




13.0 FCC ID Label

FCC ID: UFKM7003

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:




Date: 2011-07-20



14.0 Photo of testing

Conducted Emissions





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2011-07-20



Radiated Emissions







The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2011-07-20



14.3 Photographs - EUT

Outside View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 71 of 78

Report No: 1104204-01

Date: 2011-07-20



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 72 of 78

Report No: 1104204-01

Date: 2011-07-20



Interior View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 73 of 78


Report No: 1104204-01

Date: 2011-07-20



Interior View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 74 of 78

Report No: 1104204-01

Date: 2011-07-20



Interior View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 75 of 78

Report No: 1104204-01

Date: 2011-07-20



Interior View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 76 of 78

Report No: 1104204-01

Date: 2011-07-20



Interior View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 77 of 78

Report No: 1104204-01

Date: 2011-07-20



Interior View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd vill not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104204-01 Page 78 of 78

Date: 2011-07-20





-- End of the Report--