Radio Test Report

FCC ID: UFOOPN4200I

This report concerns (check one) : ☒ Original Grant ☐ Class II Change

Project No.	:	1405026
Equipment	:	Handy Image Scanner
Model Name	:	OPN-4200i
Applicant	:	OPTOELECTRONICS CO., LTD.
Address	:	4-12-17, Tsukagoshi, Warabi-shi, Saitama Pref., 335-0002, Japan

Date of Receipt	:	May. 06, 2014
Date of Test	:	May. 06, 2014 ~ Sep. 19, 2014
Issued Date	:	Sep. 23, 2014
Tested by	:	BTL Inc.

Testing Engineer : _Rush Kao_
(Rush Kao)

Technical Manager : _Jeff Yang_
(Jeff Yang)

Authorized Signatory : _Amy Chiu_
(Andy Chiu)

BTL INC.

B1, No.37, Lane 365, Yang Guang St.,
Nei-Hu District, Taipei City 114, Taiwan.
TEL:+886-0-2657-3299 FAX: +886-2- 2657-3331

ilac-MRA

TAF
Testing Laboratory
0659

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C**., or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL**'s authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents

Table of Contents

Table of Contents

REPORT ISSUED HISTORY

Issue No.	Description	Issued Date
BTL-FCCP-1-1405026	Original report.	Sep. 23, 2014

1 CERTIFICATION

Equipment   : Handy Image Scanner
Brand Name   : OPTICON
Model Name   : OPN-4200i
Applicant   : OPTOELECTRONICS CO., LTD.
Manufacturer : OPTOELECTRONICS CO., LTD.
Address   : 4-12-17, Tsukagoshi, Warabi-shi, Saitama Pref., 335-0002, Japan
Factory   : Hokkaido Electronic Industry Co., Ltd.
Address   : 118-122 Kamiashibetsu-cho, Ashibetsu-shi, Hokkaido 079-1371 Japan.
Date of Test : May. 06, 2014 ~ Sep. 19, 2014
Standard(s)   : FCC Part 15, Subpart C: 2013
                 ANSI C63.4-2009

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1405026) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2.SUMMARY OF TEST RESULTS

Standard Clause	Test Item	Result
15.207	Conducted Emission	**PASS**
15.247 (c)	Antenna conducted Spurious Emission	**PASS**
15.247 (a)(1)	Hopping Channel Separation	**PASS**
15.247 (b)	Maximum Peak Conducted Output Power	**PASS**
15.247 (c)	Radiated Spurious Emission	**PASS**
15.247 (b)(1)	Number of Hopping Frequency	**PASS**
15.247 (a)(1)	Average time of occupancy	**PASS**
15.205	Restricted Bands	**PASS**
15.203	Antenna Requirement	**PASS**

NOTE:
    1. **N/A**: denotes test is not applicable in this Test Report

2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

Conducted emission Test:
    C02: (VCCI RN: C-3477; FCC RN: 614388; FCC DN: TW1054)
        1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Radiated emission Test (Below 1 GHz):
    CB08: (FCC RN: 614388; FCC DN: TW1054; IC Assigned Code: 4428C-1)
        1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Radiated emission Test (Above 1 GHz):
    CB08: (VCCI RN: G-91; FCC RN: 614388; FCC DN: TW1054; IC Assigned Code: 4428C-1)
        1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

2.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty is not specified by FCC rules and for reference only.
The reported uncertainty of measurement **y ± U**，where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95**%.
The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

A. Conducted emission test:

Test Site	Measurement Frequency Range	U，(dB)	NOTE
C02	150 kHz ~ 30 MHz	1.94	

B. Radiated emission test:

Test Site	Item	Measurement Frequency Range		Uncertainty	NOTE
CB08	Radiated emission at 3m	Horizontal Polarization	30 - 200MHz	3.35 dB	
			200 - 1000MHz	3.11 dB	
			1 - 18GHz	3.97 dB	
			18 - 40GHz	4.01 dB	
		Vertical Polarization	30 - 200MHz	3.22 dB	
			200 - 1000MHz	3.24 dB	
			1 - 18GHz	4.05 dB	
			18 - 40GHz	4.04 dB	

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our U_{lab} values in CISPR 16-4-2 terminology.
Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called U_{CISPR}, as follows:
    Conducted Disturbance (mains port) – 150 kHz – 30 MHz : 3.6 dB
    Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz : 5.2 dB
It can be seen that our U_{lab} values are smaller than U_{CISPR}.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Handy Image Scanner
Brand Name	OPTICON
Model Name	OPN-4200i
OEM Brand/Model Name	N/A
Model Difference	N/A
Product Description	<table><tr><td>Operation Frequency</td><td>2402 MHz~ 2480 MHz</td></tr><tr><td>Modulation Type</td><td>FHSS(GFSK、π/4-DQPSK、8DPSK)</td></tr><tr><td>Bit Rate of Transmitter</td><td>1/2/3 Mbps</td></tr><tr><td>Number Of Channel</td><td>Please refer to the Note 2.</td></tr><tr><td>Antenna Designation</td><td>Please refer to the Note 3.</td></tr><tr><td>Antenna Gain(Peak)</td><td>Please refer to the Note 3.</td></tr><tr><td>Maximum Peak Conducted Output Power:</td><td>1 Mbps: -0.48dBm (0.0009W) 3 Mbps: 1.64dBm (0.0015W)</td></tr></table>More details of EUT technical specification please refer to the User's Manual.

Power Source	1# DC Voltage supplied from AC/DC adapter via charger (CHG-3201)
	    Model Name: SFP0602000P-PSE/Ver.2
	2# Supplied from lithium-ion battery
	    Brand/Name: OPTICON, OPR33015505-0-00

Power Rating	1# I/P: AC 100-240V 50/60Hz 0.5A / O/P: DC 6V 2000mA 2# 3.7V 1100mAh 4.1Wh
Connecting I/O Port(s)	Please refer to the User's Manual

NOTE:
1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Panasonic	EBMGH5A245GJ	Chip antenna	N/A	0.5

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Items	Mode	Data Rate	Tested Channel/Mode
Conducted Emission	FHSS(GFSK)	1 Mbps	2441 MHz
Antenna conducted Spurious Emission	FHSS(GFSK)	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
		3 Mbps	
Hopping Channel Separation	FHSS(GFSK)	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
		3 Mbps	
Maximum Peak Conducted Output Power	FHSS(GFSK)	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
		3 Mbps	
Radiated Spurious Emission (30 MHz to 1 GHz)	FHSS(GFSK)	1 Mbps	2441 MHz
Radiated Spurious Emission (above 1 GHz)	FHSS(GFSK)	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
		3 Mbps	
Number of Hopping Frequency	FHSS(GFSK)	1 Mbps	2402 MHz ~ 2480 MHz
		3 Mbps	
Average time of occupancy	FHSS(GFSK)	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
		3 Mbps	
Restricted Bands	FHSS(GFSK)	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
		3 Mbps	
Antenna Requirement	FHSS(GFSK)	---	---

NOTE: (1)The measurements are performed at the highest, middle, lowest available channels.
(2)Both adapter and battery are evaluated, operated the adapter is the worst and recorded as below test data.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Data Rate	1 Mbps		
Test software Version	N/A		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameter	N/A	N/A	N/A

Data Rate	3 Mbps		
Test software Version	N/A		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameter	N/A	N/A	N/A

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

EUT

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
-	-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	-

NOTE: The support equipment was authorized by Declaration of Conformity (DOC).

4 CONDUCTED EMISSION

4.1 LIMIT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 - 5.0	73.00	60.00	56.00	46.00
5.0 - 30.0	73.00	60.00	60.00	50.00

NOTE:
    1. The tighter limit applies at the band edges.
    2. The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
    3. The test result calculated as following:
        Measurement Value = Reading Level + Correct Factor
        Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)
        Margin Level = Measurement Value – Limit Value

4.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	Schwarzbeck	NSLK 8127	8127685	Jan. 08, 2015
2	Test Cable	TIMES	CFD300-NL	C01	Jun. 16, 2015
3	Spectrum Analyzer	Agilent	N9020A	MY51160196	Jun. 20, 2015
4	Measurement Software	EZ	EZ_EMC (Version NB-02A)	N/A	N/A

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

4.3 TEST PROCEDURES

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.
NOTE:
a. Reading in which marked as Peak, QP or AVG means measurements by using are Quasi-Peak or Average Mode with Detector BW=9 kHz (6 dB Bandwidth).
b. All readings are Peak Mode value unless otherwise stated QP or AVG in column of Note. If the Peak or QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only Peak or QP Mode was measured, but AVG Mode didn't perform.

4.4 TEST SETUP LAYOUT


4.5 DEVIATION FROM TEST STANDARD

No deviation

4.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.7 TEST RESULTS

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Phase: Line

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.2004	46.63	9.31	55.94	63.59	-7.65	peak	
2		0.2004	29.31	9.31	38.62	53.59	-14.97	AVG	
3		0.2620	42.97	8.89	51.86	61.37	-9.51	peak	
4		0.2620	29.76	8.89	38.65	51.37	-12.72	AVG	
5		0.3370	38.98	8.75	47.73	59.28	-11.55	peak	
6		0.3370	27.36	8.75	36.11	49.28	-13.17	AVG	
7		0.3908	34.63	8.89	43.52	58.05	-14.53	peak	
8		2.8220	23.70	9.42	33.12	56.00	-22.88	peak	
9		11.8000	20.45	9.97	30.42	60.00	-29.58	peak	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Phase: Neutral

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.2040	47.23	9.28	56.51	63.45	-6.94	peak	
2		0.2040	32.06	9.28	41.34	53.45	-12.11	AVG	
3		0.2634	43.03	8.89	51.92	61.32	-9.40	peak	
4		0.2634	31.26	8.89	40.15	51.32	-11.17	AVG	
5		0.3410	38.76	8.76	47.52	59.18	-11.66	peak	
6		0.3410	28.42	8.76	37.18	49.18	-12.00	AVG	
7		0.3943	34.67	8.89	43.56	57.97	-14.41	peak	
8		1.9760	26.44	9.26	35.70	56.00	-20.30	peak	
9		12.1000	24.46	9.98	34.44	60.00	-25.56	peak	

5 ANTENNA CONDUCTED SPURIOUS EMISSION

5.1 LIMIT

Test Item	Frequency Range (MHz)	Limit
Antenna conducted Spurious Emission	30-25000	20 dB less than the peak value of fundamental frequency

5.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2015

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

5.3 TEST PROCEDURES

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.4 TEST SETUP LAYOUT

5.5 DEVIATION FROM TEST STANDARD

No deviation

5.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

5.7 TEST RESULTS

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps		

| Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2399.00	-49.70	2483.60	-46.83
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.			

Bluetooth/1 Mbps/The max. radio frequency power in any 100kHz bandwidth outside the frequency band


Date: 15.MAY.2014 16:22:12

Bluetooth/1 Mbps/The max. radio frequency power in any 100 kHz bandwidth within the frequency band


Date: 15.MAY.2014 17:50:20

Bluetooth/1 Mbps/2402 MHz/10 Harmonic of the frequency

Date: 15.MAY.2014 16:21:21

Bluetooth/1 Mbps/2441 MHz/10 Harmonic of the frequency

Date: 15.MAY.2014 17:44:13

## Bluetooth/1 Mbps/2480 MHz/10 Harmonic of the frequency


```
                                    *RBW  100 kHz    Marker 2 [T1 ]
                                    *VBW  100 kHz              -42.35 dBm
Ref  10 dBm         *Att  20 dB      SWT 2.5 s           4.924120000 GHz

10  Offset  0.5 dB                              Marker 1 [T1 ]
                                                          -2.87 dBm
0                                               2.477060000 GHz    A

-10
                                                                  LVL
-20
   D1 -22.87 dBm
-30

-40

-50

-70

-80

-90
Start 30 MHz              2.497 GHz/           Stop 25 GHz
```

Date: 15.MAY.2014 17:49:34

| EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps		

Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2399.80	-50.38	2483.60	-45.10
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.			

Bluetooth/3 Mbps/The max. radio frequency power in any 100kHz bandwidth outside the frequency band


Date: 15.MAY.2014 18:05:00

Bluetooth/3 Mbps/The max. radio frequency power in any 100 kHz bandwidth within the frequency band


Date: 15.MAY.2014 18:18:08

## Bluetooth/3 Mbps/2402 MHz/10 Harmonic of the frequency

Date: 15.MAY.2014 18:04:16

Bluetooth/3 Mbps/2441 MHz/10 Harmonic of the frequency

Date: 15.MAY.2014 18:11:32

Bluetooth/3 Mbps/2480 MHz/10 Harmonic of the frequency

Date: 15.MAY.2014 18:17:17

6 HOPPING CHANNEL SEPARATION

6.1 LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

6.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2015

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

6.3 MEASURING INSTRUMENTS SETTING

EMI Test Receiver	Parameter Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 300 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.4 TEST PROCEDURES

a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
b. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
c. The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised for channel separation measurement.

6.5 TEST SETUP LAYOUT

6.6 DEVIATION FROM TEST STANDARD

No deviation

6.7 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.

6.8 TEST RESULTS

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz, 2441 MHz, 2480 MHz		

| Frequency	Channel Separation (MHz)	20 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Two-thirds of the 20 dB Bandwidth	Result
2402 MHz	1.002	0.946	0.876	0.631	PASS
2441 MHz	1.002	0.942	0.872	0.628	PASS
2480 MHz	1.002	0.946	0.880	0.631	PASS

NOTE: Ch. Separation Limits: >25 KHz or >2/3 of 20dB bandwidth

Bluetooth/1 Mbps/2402 MHz/Channel Separation

Date: 15.MAY.2014 17:40:33

Bluetooth/1 Mbps/2402 MHz/20dB Bandwidth

Date: 15.MAY.2014 16:21:52

Bluetooth/1 Mbps/2441 MHz/Channel Separation

Date: 15.MAY.2014 17:46:11

Bluetooth/1 Mbps/2441 MHz/20dB Bandwidth

Date: 15.MAY.2014 17:44:40

Bluetooth/1 Mbps/2480 MHz/Channel Separation

Date: 15.MAY.2014 17:52:38

Bluetooth/1 Mbps/2480 MHz/20dB Bandwidth

Date: 15.MAY.2014 17:50:00

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz, 2441 MHz, 2480 MHz		

Frequency	Channel Separation (MHz)	20 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Two-thirds of the 20 dB Bandwidth	Result
2402 MHz	1.002	1.261	1.180	0.841	PASS
2441 MHz	1.002	1.265	1.180	0.844	PASS
2480 MHz	1.008	1.261	1.176	0.841	PASS

NOTE: Ch. Separation Limits: >25 KHz or >2/3 of 20dB bandwidth

Bluetooth/3 Mbps/2402 MHz/Channel Separation

Date: 15.MAY.2014 18:08:05

Bluetooth/3 Mbps/2402 MHz/20dB Bandwidth

Date: 15.MAY.2014 18:04:43

## Bluetooth/3 Mbps/2441 MHz/Channel Separation

Date: 15.MAY.2014 18:14:27

## Bluetooth/3 Mbps/2441 MHz/20dB Bandwidth

Date: 15.MAY.2014 18:11:58

Bluetooth/3 Mbps/2480 MHz/Channel Separation

Date: 15.MAY.2014 18:19:55

Bluetooth/3 Mbps/2480 MHz/20dB Bandwidth


Date: 15.MAY.2014 18:17:48

7 MAXIMUM PEAK CONDUCTED OUTPUT POWER

7.1 LIMIT

Test Item	Frequency Range (MHz)	Limit
Maximum Peak Conducted Output Power	2400-2483.5	1 watt or 30 dBm

7.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2015

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

7.3 TEST PROCEDURES

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting: RBW= 3 MHz, VBW= 3 MHz, Sweep time = Auto.

7.4 TEST SETUP LAYOUT

7.5 DEVIATION FROM TEST STANDARD

No deviation

7.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.

7.7 TEST RESULTS

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz, 2441 MHz, 2480 MHz		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2402 MHz	-0.63	0.0009	30	1	PASS
2441 MHz	-0.48	0.0009	30	1	PASS
2480 MHz	-0.84	0.0008	30	1	PASS

Bluetooth/1 Mbps/2402 MHz/Peak Output Power

Date: 15.MAY.2014 16:23:00

Bluetooth/1 Mbps/2441 MHz/Peak Output Power

```
                                    *RBW 3 MHz      Marker 1 [T1 ]
                                    *VBW 3 MHz              -0.48 dBm
Ref  10 dBm          *Att  20 dB    *SWT 2.5 ms      2.441000000 GHz
```



```
10 Offset 0.5 dB                                               A

 0

-10                                                           LVL

-20

-30

-40

-50

-60

-70

-80

-90
Center 2.441 GHz        2 MHz/              Span 20 MHz
```

Date: 15.MAY.2014 17:45:16

Bluetooth/1 Mbps/2480 MHz/Peak Output Power

```
                                    *RBW 3 MHz      Marker 1 [T1 ]
                                    *VBW 3 MHz              -0.84 dBm
Ref  10 dBm          *Att  20 dB    *SWT 2.5 ms      2.479920000 GHz
```



```
10 Offset 0.5 dB                                               A

 0

-10                                                           LVL

-20

-30

-40

-50

-60

-70

-80

-90
Center 2.48 GHz         2 MHz/              Span 20 MHz
```

Date: 15.MAY.2014 17:51:05

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz, 2441 MHz, 2480 MHz		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2402 MHz	1.64	0.0015	30	1	PASS
2441 MHz	1.37	0.0014	30	1	PASS
2480 MHz	0.58	0.0011	30	1	PASS

Bluetooth/3 Mbps/2402 MHz/Peak Output Power

Date: 15.MAY.2014 18:06:32

Bluetooth/3 Mbps/2441 MHz/Peak Output Power

Date: 15.MAY.2014 18:12:38

## Bluetooth/3 Mbps/2480 MHz/Peak Output Power

Date: 15.MAY.2014 18:18:45

8 RADIATED SPURIOUS EMISSION (9 KHZ TO 1 GHZ)

8.1 LIMIT

20 dB in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range: 9 kHz to 1 GHz		
FREQUENCY (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range: above 1 GHz				
FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
above 1 GHz	80	60	74	54

NOTE:
    (1) The limit for radiated test was performed according to FCC PART 15B.
    (2) The tighter limit applies at the band edges.
    (3) Emission level (dBuV/m)=20log Emission level (uV/m).
    (4) The test result calculated as following:
        Measurement Value = Reading Level + Correct Factor
        Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain(if use)
        Margin Level = Measurement Value – Limit Value

8.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2015
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 14, 2015
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 15, 2015
4	Microflex Cable	Harbour industries	27478LL142	1m	May. 12, 2015
5	Microflex Cable	EMC	S104-SMA	8m	May. 12, 2015
6	Microflex Cable	Harbour industries	27478LL142	3m	May. 12, 2015
7	Test Cable	LMR	LMR-400	12m	May. 13, 2015
8	Test Cable	LMR	LMR-400	3m	May. 13, 2015
9	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 18, 2015
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 11, 2015

Remark: "N/A" denotes No Model Name, No Serial No. or No Calibration specified.

8.3 MEASURING INSTRUMENTS SETTING

EMI Test Receiver	Parameter Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

8.4 TEST PROCEDURES

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1 GHz. For frequencies above 1 GHz, any suitable measuring distance may be used.

b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m Semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.

f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

g. The testing follows the guidelines in ANSI C63.4 and FCC Public Notice DA 00-705 Measurement Guidelines. In case the emission is fail due to the used RBW/VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

NOTE:

a. Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode with Detector BW=120 kHz; SPA setting in RBW=100 kHz, VBW =100 kHz, Swp. Time = 0.3 sec./ MHz.

b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.

8.5 DEVIATION FROM TEST STANDARD

No deviation

8.6 TEST SETUP LAYOUT

8.7 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.

8.8 TEST RESULTS

Test Mode：	TX Mode

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.012	0°	44.20	22.35	66.55	126.02	-59.47	PEAK
0.012	0°	31.52	22.35	53.87	126.02	-72.15	AV
0.024	0°	42.10	22.04	64.14	119.89	-55.75	PEAK
0.024	0°	28.24	22.04	50.28	119.89	-69.61	AV
0.036	0°	34.64	21.76	56.40	116.55	-60.15	PEAK
0.036	0°	24.51	21.76	46.27	116.55	-70.28	AV
0.063	0°	35.92	21.19	57.11	111.58	-54.47	PEAK
0.063	0°	24.10	21.19	45.29	111.58	-66.29	AV
0.243	0°	34.18	20.46	54.64	99.88	-45.25	PEAK
0.243	0°	22.64	20.46	43.10	99.88	-56.79	AV
1.267	0°	37.34	20.33	57.67	65.55	-7.88	QP

| Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0120	90°	47.34	22.35	69.69	126.02	-56.33	PEAK
0.0120	90°	32.45	22.35	54.80	126.02	-71.22	AV
0.0243	90°	43.15	22.04	65.19	119.89	-54.70	PEAK
0.0243	90°	29.60	22.04	51.64	119.89	-68.25	AV
0.0357	90°	35.47	21.76	57.23	116.55	-59.32	PEAK
0.0357	90°	24.15	21.76	45.91	116.55	-70.64	AV
0.0633	90°	36.74	21.19	57.93	111.58	-53.65	PEAK
0.0633	90°	23.84	21.19	45.03	111.58	-66.55	AV
0.2432	90°	33.37	20.46	53.83	99.88	-46.06	PEAK
0.2432	90°	22.51	20.46	42.97	99.88	-56.92	AV
1.2670	90°	39.45	20.33	59.78	65.55	-5.77	QP

Remark:
   (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
   (2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
   (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		114.8750	39.60	-17.05	22.55	43.50	-20.95	peak	
2		165.8000	34.20	-14.44	19.76	43.50	-23.74	peak	
3		359.8000	29.36	-12.38	16.98	46.00	-29.02	peak	
4		434.9750	28.60	-10.19	18.41	46.00	-27.59	peak	
5		624.1250	28.84	-6.83	22.01	46.00	-23.99	peak	
6	*	936.9500	31.33	-2.71	28.62	46.00	-17.38	peak	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		85.7750	36.14	-19.62	16.52	40.00	-23.48	peak	
2		114.8750	35.09	-17.05	18.04	43.50	-25.46	peak	
3		304.0250	32.92	-13.78	19.14	46.00	-26.86	peak	
4		437.4000	28.19	-10.12	18.07	46.00	-27.93	peak	
5		575.6250	29.31	-7.47	21.84	46.00	-24.16	peak	
6	*	939.3750	29.77	-2.66	27.11	46.00	-18.89	peak	

9 RADIATED SPURIOUS EMISSION (ABOVE 1 GHZ)

9.1 LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range: 9 kHz to 1 GHz		
FREQUENCY (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range: above 1 GHz				
FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
above 1 GHz	80	60	74	54

NOTE:
    (1) The limit for radiated test was performed according to FCC PART 15B.
    (2) The tighter limit applies at the band edges.
    (3) Emission level (dBuV/m)=20log Emission level (uV/m).
    (4) The test result calculated as following:
        Measurement Value = Reading Level + Correct Factor
        Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain(if use)
        Margin Level = Measurement Value – Limit Value

9.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2015
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 14, 2015
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 15, 2015
4	Microflex Cable	Harbour industries	27478LL142	1m	May. 12, 2015
5	Microflex Cable	EMC	S104-SMA	8m	May. 12, 2015
6	Microflex Cable	Harbour industries	27478LL142	3m	May. 12, 2015
7	Test Cable	LMR	LMR-400	12m	May. 13, 2015
8	Test Cable	LMR	LMR-400	3m	May. 13, 2015
9	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 18, 2015
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 11, 2015

Remark: "N/A" denotes No Model Name, No Serial No. or No Calibration specified.

9.3 MEASURING INSTRUMENTS SETTING

Spectrum Analyzer	Parameter Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

9.4 TEST PROCEDURES

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1 GHz. For frequencies above 1 GHz, any suitable measuring distance may be used.

b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m Semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.

f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

g. The testing follows the guidelines in ANSI C63.4 and FCC Public Notice DA 00-705 Measurement Guidelines. In case the emission is fail due to the used RBW/VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

NOTE:

a. Reading in which marked as Peak means measurements by using are Peak Mode with instrument setting in RBW= 1 MHz, VBW= 1 MHz, Swp. Time = Auto.
Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW= 1 MHz, VBW= 10 Hz, Swp. Time = Auto.

b. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform.

9.5 DEVIATION FROM TEST STANDARD

No deviation

9.6 TEST SETUP LAYOUT

9.7 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.

9.8 TEST RESULTS

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	25.19	31.37	56.56	74.00	-17.44	peak	
2		2390.000	13.21	31.37	44.58	54.00	-9.42	AVG	
3	X	2402.000	58.69	31.42	90.11	74.00	16.11	peak	Fundamental frequency, no limit
4	*	2402.000	49.25	31.42	80.67	54.00	26.67	AVG	Fundamental frequency, no limit

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.080	50.09	5.57	55.66	74.00	-18.34	peak	
2		4804.080	41.16	5.57	46.73	54.00	-7.27	AVG	
3		7206.045	46.69	12.25	58.94	74.00	-15.06	peak	
4	*	7206.045	34.61	12.25	46.86	54.00	-7.14	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	25.36	31.37	56.73	74.00	-17.27	peak	
2		2390.000	13.21	31.37	44.58	54.00	-9.42	AVG	
3	X	2402.000	65.68	31.42	97.10	74.00	23.10	peak	Fundamental frequency, no limit
4	*	2402.000	54.94	31.42	86.36	54.00	32.36	AVG	Fundamental frequency, no limit

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.050	47.95	5.57	53.52	74.00	-20.48	peak	
2		4804.050	37.84	5.57	43.41	54.00	-10.59	AVG	
3		7206.035	47.53	12.25	59.78	74.00	-14.22	peak	
4	*	7206.035	35.39	12.25	47.64	54.00	-6.36	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	60.38	31.60	91.98	74.00	17.98	peak	Fundamental frequency, no limit
2	*	2441.000	50.67	31.60	82.27	54.00	28.27	AVG	Fundamental frequency, no limit

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.040	49.16	5.72	54.88	74.00	-19.12	peak	
2		4882.040	40.27	5.72	45.99	54.00	-8.01	AVG	
3		7323.025	46.24	12.70	58.94	74.00	-15.06	peak	
4	*	7323.025	34.07	12.70	46.77	54.00	-7.23	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2441.000	65.36	31.60	96.96	74.00	22.96	peak	Fundamental frequency, no limit
2	*	2441.000	54.74	31.60	86.34	54.00	32.34	AVG	Fundamental frequency, no limit

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.070	47.34	5.72	53.06	74.00	-20.94	peak	
2		4882.070	36.42	5.72	42.14	54.00	-11.86	AVG	
3		7323.040	46.68	12.70	59.38	74.00	-14.62	peak	
4	*	7323.040	34.25	12.70	46.95	54.00	-7.05	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2480.000	59.59	31.77	91.36	74.00	17.36	peak	Fundamental frequency, no limit
2	*	2480.000	49.96	31.77	81.73	54.00	27.73	AVG	Fundamental frequency, no limit
3		2483.500	27.23	31.78	59.01	74.00	-14.99	peak	
4		2483.500	14.33	31.78	46.11	54.00	-7.89	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.055	49.37	5.88	55.25	74.00	-18.75	peak	
2	*	4960.055	40.88	5.88	46.76	54.00	-7.24	AVG	
3		7440.020	46.48	13.15	59.63	74.00	-14.37	peak	
4		7440.020	33.55	13.15	46.70	54.00	-7.30	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2480.000	63.60	31.77	95.37	74.00	21.37	peak	Fundamental frequency, no limit
2	*	2480.000	53.19	31.77	84.96	54.00	30.96	AVG	Fundamental frequency, no limit
3		2483.500	27.66	31.78	59.44	74.00	-14.56	peak	
4		2483.500	15.74	31.78	47.52	54.00	-6.48	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.110	46.89	5.88	52.77	74.00	-21.23	peak	
2		4960.110	36.27	5.88	42.15	54.00	-11.85	AVG	
3		7440.025	47.18	13.15	60.33	74.00	-13.67	peak	
4	*	7440.025	34.06	13.15	47.21	54.00	-6.79	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	25.15	31.37	56.52	74.00	-17.48	peak	
2		2390.000	13.06	31.37	44.43	54.00	-9.57	AVG	
3	X	2402.000	59.37	31.42	90.79	74.00	16.79	peak	Fundamental frequency, no limit
4	*	2402.000	47.45	31.42	78.87	54.00	24.87	AVG	Fundamental frequency, no limit

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.050	48.64	5.57	54.21	74.00	-19.79	peak	
2		4804.050	31.66	5.57	37.23	54.00	-16.77	AVG	
3		7206.580	44.98	12.25	57.23	74.00	-16.77	peak	
4	*	7206.580	30.98	12.25	43.23	54.00	-10.77	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	25.39	31.37	56.76	74.00	-17.24	peak	
2		2390.000	13.19	31.37	44.56	54.00	-9.44	AVG	
3	X	2402.000	66.10	31.42	97.52	74.00	23.52	peak	Fundamental frequency, no limit
4	*	2402.000	52.93	31.42	84.35	54.00	30.35	AVG	Fundamental frequency, no limit

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4803.875	44.29	5.57	49.86	74.00	-24.14	peak	
2		4803.875	30.63	5.57	36.20	54.00	-17.80	AVG	
3		7205.910	44.89	12.25	57.14	74.00	-16.86	peak	
4	*	7205.910	30.95	12.25	43.20	54.00	-10.80	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2441.000	59.94	31.60	91.54	74.00	17.54	peak	Fundamental frequency, no limit
2	*	2441.000	47.92	31.60	79.52	54.00	25.52	AVG	Fundamental frequency, no limit

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4882.115	45.01	5.72	50.73	74.00	-23.27	peak	
2		4882.115	31.10	5.72	36.82	54.00	-17.18	AVG	
3		7323.875	45.03	12.70	57.73	74.00	-16.27	peak	
4	*	7323.875	30.70	12.70	43.40	54.00	-10.60	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	65.11	31.60	96.71	74.00	22.71	peak	Fundamental frequency, no limit
2	*	2441.000	52.15	31.60	83.75	54.00	29.75	AVG	Fundamental frequency, no limit

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.200	44.70	5.72	50.42	74.00	-23.58	peak	
2		4882.200	30.56	5.72	36.28	54.00	-17.72	AVG	
3		7323.515	44.25	12.70	56.95	74.00	-17.05	peak	
4	*	7323.515	30.67	12.70	43.37	54.00	-10.63	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2480.000	61.79	31.77	93.56	74.00	19.56	peak	Fundamental frequency, no limit
2	*	2480.000	49.41	31.77	81.18	54.00	27.18	AVG	Fundamental frequency, no limit
3		2483.500	29.21	31.78	60.99	74.00	-13.01	peak	
4		2483.500	16.34	31.78	48.12	54.00	-5.88	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.095	45.21	5.88	51.09	74.00	-22.91	peak	
2		4960.095	31.29	5.88	37.17	54.00	-16.83	AVG	
3		7439.580	46.19	13.15	59.34	74.00	-14.66	peak	
4	*	7439.580	31.40	13.15	44.55	54.00	-9.45	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2480.000	64.79	31.77	96.56	74.00	22.56	peak	Fundamental frequency, no limit
2	*	2480.000	51.84	31.77	83.61	54.00	29.61	AVG	Fundamental frequency, no limit
3		2483.500	30.78	31.78	62.56	74.00	-11.44	peak	
4		2483.500	17.93	31.78	49.71	54.00	-4.29	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4959.730	44.76	5.88	50.64	74.00	-23.36	peak	
2		4959.730	30.57	5.88	36.45	54.00	-17.55	AVG	
3		7439.235	45.31	13.14	58.45	74.00	-15.55	peak	
4	*	7439.235	31.30	13.14	44.44	54.00	-9.56	AVG	

9.9 TEST RESULTS (RESTRICTED BANDS)

| EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	25.19	31.37	56.56	74.00	-17.44	peak	
2	*	2390.000	13.21	31.37	44.58	54.00	-9.42	AVG	

| EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2483.500	27.23	31.78	59.01	74.00	-14.99	peak	
2	*	2483.500	14.33	31.78	46.11	54.00	-7.89	AVG	

| EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	25.36	31.37	56.73	74.00	-17.27	peak	
2	*	2390.000	13.21	31.37	44.58	54.00	-9.42	AVG	

| EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2483.500	27.66	31.78	59.44	74.00	-14.56	peak	
2	*	2483.500	15.74	31.78	47.52	54.00	-6.48	AVG	

| EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	25.15	31.37	56.52	74.00	-17.48	peak	
2	*	2390.000	13.06	31.37	44.43	54.00	-9.57	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2483.500	29.21	31.78	60.99	74.00	-13.01	peak	
2	*	2483.500	16.34	31.78	48.12	54.00	-5.88	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	25.39	31.37	56.76	74.00	-17.24	peak	
2	*	2390.000	13.19	31.37	44.56	54.00	-9.44	AVG	

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2483.500	30.78	31.78	62.56	74.00	-11.44	peak	
2	*	2483.500	17.93	31.78	49.71	54.00	-4.29	AVG	

10 NUMBER OF HOPPING FREQUENCY

10.1 LIMIT

Test Item	Frequency Range (MHz)	Limit
Number of Hopping Channel	2400-2483.5	shall use at least 15 channels

10.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2015

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

10.3 MEASURING INSTRUMENTS SETTING

Spectrum Analyzer	Parameter Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

10.4 TEST PROCEDURES

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW= 100 kHz, VBW=100 kHz, Sweep time = Auto.

10.5 TEST SETUP LAYOUT

10.6 DEVIATION FROM TEST STANDARD

No deviation

10.7 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.

10.8 TEST RESULTS

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps		

Number of Hopping Channel	Limit	Result
79	15	Pass

Date: 15.MAY.2014 17:56:10

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps		

Number of Hopping Channel	Limit	Result
79	15	Pass

Date: 15.MAY.2014 18:03:31

11 AVERAGE TIME OF OCCUPANCY

11.1 LIMIT

Test Item	Frequency Range (MHz)	Limit
Average time of occupancy	2400-2483.5	shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

11.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2015

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

11.3 TEST PROCEDURES

a. The transmitter output (antenna port) was connected to the spectrum analyzer
b. Set RBW of spectrum analyzer to 100 kHz and VBW to 100 kHz.
c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
d. Sweep Time is more than once pulse time.
e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
f. Measure the maximum time duration of one single pulse.
g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
h. Measure the maximum time duration of one single pulse.
i. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds.
j. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
k. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.

11.4 TEST SETUP LAYOUT

11.5 DEVIATION FROM TEST STANDARD

No deviation

11.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.

11.7 TEST RESULTS

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2402 MHz	3.0818	0.3287	0.4	PASS
DH3	2402 MHz	1.8009	0.2881	0.4	PASS
DH1	2402 MHz	0.5205	0.1666	0.4	PASS

Bluetooth/1 Mbps/2402 MHz/DH1

Date: 15.MAY.2014 17:42:00

Bluetooth/1 Mbps/2402 MHz/DH3

RBW 100 kHz Delta 1 [T1]
VBW 100 kHz   -0.91 dB
SWT 20 ms   1.800878 ms
Ref 10 dBm   Att 20 dB

Marker 1 [T1]
           -62.69 dBm
         7.959122 ms

Center 2.402 GHz   2 ms/

Date: 15.MAY.2014 17:42:58

Bluetooth/1 Mbps/2402 MHz/DH5

RBW 100 kHz Delta 1 [T1]
VBW 100 kHz   2.15 dB
SWT 20 ms   3.081756 ms
Ref 10 dBm   Att 20 dB

Marker 1 [T1]
           -68.19 dBm
         9.398244 ms

Center 2.402 GHz   2 ms/

Date: 15.MAY.2014 16:23:46

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2441 MHz	3.0411	0.3244	0.4	PASS
DH3	2441 MHz	1.8015	0.2882	0.4	PASS
DH1	2441 MHz	0.5217	0.1669	0.4	PASS

Bluetooth/1 Mbps/2441 MHz/DH1

Date: 15.MAY.2014 17:47:22

Bluetooth/1 Mbps/2441 MHz/DH3


```
                          RBW 100 kHz   Delta 1 [T1 ]
                        * VBW 100 kHz              2.25 dB
Ref  10 dBm      * Att  20 dB   SWT 20 ms          1.801517 ms

10  Offset  0.5 dB                    Marker 1 [T1 ]
                                              -67.68 dBm
                                              9.238483 ms
```

Center 2.441 GHz   2 ms/

Date: 15.MAY.2014 17:48:22

Bluetooth/1 Mbps/2441 MHz/DH5


```
                          RBW 100 kHz   Delta 1 [T1 ]
                        * VBW 100 kHz             -0.92 dB
Ref  10 dBm      * Att  20 dB   SWT 20 ms          3.041118 ms

10  Offset  0.5 dB                    Marker 1 [T1 ]
                                              -66.48 dBm
                                              9.039892 ms
```

Center 2.441 GHz   2 ms/

Date: 15.MAY.2014 17:45:07

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

| Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2480 MHz	3.0445	0.3247	0.4	PASS
DH3	2480 MHz	1.8038	0.2886	0.4	PASS
DH1	2480 MHz	0.5213	0.1668	0.4	PASS

Bluetooth/1 Mbps/2480 MHz/DH1

Date: 15.MAY.2014 17:53:41

Bluetooth/1 Mbps/2480 MHz/DH3

Date: 15.MAY.2014 17:54:40

Bluetooth/1 Mbps/2480 MHz/DH5

Date: 15.MAY.2014 17:50:49

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2402 MHz	3.0425	0.3245	0.4	PASS
DH3	2402 MHz	1.8043	0.2887	0.4	PASS
DH1	2402 MHz	0.5224	0.1672	0.4	PASS

Bluetooth/3 Mbps/2402 MHz/DH1

Date: 15.MAY.2014 18:09:33

Bluetooth/3 Mbps/2402 MHz/DH3

Date: 15.MAY.2014 18:10:31

Bluetooth/3 Mbps/2402 MHz/DH5

Date: 15.MAY.2014 18:07:21

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2441 MHz	3.0407	0.3243	0.4	PASS
DH3	2441 MHz	1.8037	0.2886	0.4	PASS
DH1	2441 MHz	0.5219	0.1670	0.4	PASS

Bluetooth/3 Mbps/2441 MHz/DH1

Date: 15.MAY.2014 18:15:22

Bluetooth/3 Mbps/2441 MHz/DH3


Date: 15.MAY.2014 18:16:16

Bluetooth/3 Mbps/2441 MHz/DH5

Date: 15.MAY.2014 18:12:27

EUT	Handy Image Scanner	Model Name	OPN-4200i
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2480 MHz	3.0406	0.3243	0.4	PASS
DH3	2480 MHz	1.7602	0.2816	0.4	PASS
DH1	2480 MHz	0.5202	0.1665	0.4	PASS

Bluetooth/3 Mbps/2480 MHz/DH1

Date: 15.MAY.2014 18:21:09

Bluetooth/3 Mbps/2480 MHz/DH3

Date: 15.MAY.2014 18:21:54

Bluetooth/3 Mbps/2480 MHz/DH5


Date: 15.MAY.2014 18:18:35

12 EUT TEST PHOTO

Conducted emission test photos

Radiated spurious emission test photos

9K-30MHz

Radiated spurious emission test photos

Below 1G

Radiated spurious emission test photos

Above 1G