

XXXX-YYYYY-ZZZZ

MPE Evaluation Intel® Centrino® Advanced-N 6200 FCC ID: UGL622ANH IC: 7888B-622ANH

xxxx-yyyyy-zzzz	-	ENGINEERING
NUMBER	REVISION	DEPARTMENT

THIS DOCUMENT CONTAINS TECHNOLOGY CONTROLLED UNDER THE U.S. EXPORT ADMINISTRATION REGULATIONS (EAR) AND MAY NOT BE EXPORTED OR TRANSFERRED TO ANY FOREIGN PERSON, FOREIGN COUNTRY OR FOREIGN ENTITY, BY ANY MEANS, WITHOUT PRIOR WRITTEN APPROVAL FROM THE U.S. DEPARTMENT OF COMMERCE, BUREAU OF INDUSTRY AND SECURITY (BIS) AND DRS TECHNOLOGIES.

THE INFORMATION DISCLOSED IN THIS DOCUMENT IS PROPRIETARY DATA OF DRS TACTICAL SYSTEMS, INC., AND MAY NOT BE REPRODUCED, USED, OR DISCLOSED WITHOUT THE PRIOR WRITTEN AUTHORIZATION OF DRS TACTICAL SYSTEMS, INC.

DISTRIBUTION AUTHORIZED FOR USE PER DOCUMENT NUMBER 9120-02737-0100. VALIDATION REQUIRED FOR PLANNING, TESTING, INSPECTION, MANUFACTURING, PROCUREMENT AND QUOTES.

DRS						
	Engineering Test Report					
Program	ARMOR X7					
Report Title	MPE Evaluation – Intel® Centrino	3 Advance	d-N 6200			
Author	Dillard Gilmore	Time				
Report Number		Date				

RECORD CHANGES TO DOCUMENT AS FOLLOWS	

DOCUMENT: xxxx-yyyyy-zzzz	ECO #:	OLD REV:	NEW REV:
			

The following changes have been made:

1. Initial release

xxxx-yyyyy-zzzz Rev x Page 2 of 4

DRS					
TECHNOLOGIES	Engineering Test Re	port			
Program	ARMOR X7				
Report Title	Report Title MPE Evaluation – Intel® Centrino® Advanced-N 6200				
Author	Dillard Gilmore	Time			
Report Number		Date			

1 Introduction

Systems operating under the provision of 47 CFR 1.1307(b)(1) shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user or nearby persons when used with the vehicle docking station and external antenna. It can therefore be considered a mobile transmitter per 47 CFR 2.1091(b) in this configuration. When docked, only Chain A of the WLAN module is available at the external antenna port. The MPE calculation for this exposure is shown below.

2 Antenna

The antenna used for this evaluation is Mobile Mark SMW-301-3C3J2C. The peak gain (G_{dB}) of this antenna is +5dBi in both frequency bands 2.4 – 2.5 GHz and 4.9 – 6.0 GHz.

3 MPE Calculations

From 47 CFR 1.1310 Table 1, the maximum permissible exposure (MPE) for the general population/uncontrolled exposure is 1.0 mW/cm² for the frequency range 1500 – 100,000 MHz.

The peak radiated output power is calculated as follows

Frequency Band (MHz)	Power Input to Antenna (P _{dB}) (dBm)	Gain of the Antenna (G _{dB}) (dBi)	EIRP _{dB} (dBm)	EIRP (mW)
2.4	16.74	5	21.74	149.3
5	16.94	5	21.94	156.3

 $EIRP_{dB} = P_{dB} + G_{dB}$ $EIRP = 10^{(EIRP_{db}/10)}$

The power density at 20 cm is

Frequency Band Power Input to Antenna (P) (mW)		Numeric Gain of the Antenna (G)	Power Spectral Density (mW/cm²) Spectral Density Limit (mW/cm²)		
	2.4	47.21	3.16	0.030	1.0

DISCLOSURE OF THE DATA ON THIS PAGE IS SUBJECT TO THE DISTRIBUTION AUTHORIZATION, PROPRIETARY DATA AND EXPORT CONTROL RESTRICTIONS ON THE TITLE PAGE OF THIS DOCUMENT.

DRS						
710//W0100/20	Engineering Test Report					
Program	ARMOR X7					
Report Title MPE Evaluation – Intel® Centrino® Advanced-N 6200						
Author	Dillard Gilmore	Time				
Report Number		Date				

 $G = 10^{(G_{dB}/10)} = 3.16$

 $P = 10^{(P_{dB}/10)}$ $S = PG/(4\pi D^2)$

Where

S = Power spectral density (mW/cm²)

P = Power input to the antenna (mW)

G = Numeric gain of the antenna

D = Distance from the center of the radiation of the antenna

4 Conclusion

The power density at 20 cm does not exceed the 1 mW/cm² limit. Therefore the exposure condition is compliant with FCC rules.

Rev x Page 4 of 4 xxxx-yyyyy-zzzz