

## EMI Test Report

On Model Name: Microwave oven

Model Numbers: P12034X-Z

Brand Name: Galanz

FCC ID: UHW12034001

Prepared for Guangdong Galanz Enterprises Co., Ltd

According to

*FCC Part 18*

*Industrial, Scientific and Medical Equipment*

*FCC/OST MP-5(1986)*

*FCC methods of measurements of radio noise emission from industrial, scientific and medical equipment*


Test Report #: PSZ-0703-0346-FCC+ID

Prepared by: Ravin Su

Reviewed by: Ivan Wen

QC Manager: Paul Chen

Test Report Released by:



Paul Chen

2007, March 28

Date

### **List Attached Files**

<b>Exhibit Type</b>	<b>File Description</b>	<b>File Name</b>
<i>Test Report</i>	<i>Test Report</i>	<i>UHW12034001 _Test report.pdf</i>
<i>Operation Description</i>	<i>Technical Description</i>	<i>UHW12034001 _operation description.pdf</i>
<i>External Photos</i>	<i>External Photos</i>	<i>UHW12034001 _External Photos</i>
<i>Internal Photos</i>	<i>Internal Photos</i>	<i>UHW12034001 _Internal Photos</i>
<i>Block Diagram</i>	<i>Block Diagram</i>	<i>UHW12034001 _Block Diagram.pdf</i>
<i>Schematics</i>	<i>Circuit Diagram</i>	<i>UHW12034001 _Schematics.pdf</i>
<i>ID Label/Location</i>	<i>Label Artwork and Location</i>	<i>UHW12034001 _Label &amp; Location.pdf</i>
<i>User Manual</i>	<i>User Manual</i>	<i>UHW12034001 _User Manual.pdf</i>
<i>Test setup photos</i>	<i>Test setup photos</i>	<i>UHW12034001 _Test Setup Photos</i>

### **Test Location**

*Tests performed at Galanz in a Certified ANSI Semi-Anechoic Chamber and Shielded Room.*

**Test Site Location:** Guangdong Galanz Enterprises Co., Ltd  
25 South Ronggui Rd., Shunde, Foshan,  
Guangdong, China.  
**Tel:** 86-757-23612785  
**Fax:** 86-757-23612537

**FCC Registration Number:** 580210

### **Accreditation Bodies**

*EMC Compliance Management Group is a fully accredited Test Laboratory for ITE, ISM, MIL-STD and Telecommunications Products.*



*In compliance with the site registration requirements of Section 2.948 of the FCC Rules to perform EMI measurements for the general public. FCC Registration #: 894293.*



*Accredited by the National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code # 200068-0.*

# ***Table of Contents***

---

<b><i>GOVERNMENT DISCLAIMER NOTICE</i></b>	<b><i>1</i></b>
<b><i>REPRODUCTION CLAUSE</i></b>	<b><i>1</i></b>
<b><i>OPINIONS AND INTERPRETATIONS</i></b>	<b><i>1</i></b>
<b><i>STATEMENT OF MEASUREMENT UNCERTAINTY</i></b>	<b><i>1</i></b>
<b><i>ADMINISTRATIVE DATA</i></b>	<b><i>2</i></b>
<b><i>EUT DESCRIPTION</i></b>	<b><i>2</i></b>
<b><i>TYPE OF DERIVER</i></b>	<b><i>3</i></b>
<b><i>TEST SUMMARY</i></b>	<b><i>4</i></b>
<b><i>LOAD FOR MICROWAVE OVENS</i></b>	<b><i>5</i></b>
<b><i>EQUIPMENT MODIFICATION</i></b>	<b><i>5</i></b>
<b><i>EUT SAMPLE PHOTOS FOR MODEL P12034AP</i></b>	<b><i>6</i></b>
<b><i>TEST SYSTEM DETAILS</i></b>	<b><i>10</i></b>
<b><i>CONFIGURATION OF TESTED SYSTEM</i></b>	<b><i>11</i></b>
<b><i>ATTACHMENT 1 - RADIATION HAZARD TEST</i></b>	<b><i>12</i></b>
<b><i>ATTACHMENT 2 - INPUT POWER MEASUREMENT</i></b>	<b><i>15</i></b>
<b><i>ATTACHMENT 3 - RF OUTPUT POWER MEASUREMENT</i></b>	<b><i>18</i></b>
<b><i>ATTACHMENT 4 - OPERATING FREQUENCY MEASUREMENT</i></b>	<b><i>21</i></b>
<b><i>ATTACHMENT 5 - CONDUCTED EMISSION TEST RESULTS</i></b>	<b><i>24</i></b>
<b><i>ATTACHMENT 6 - RADIATED EMISSION TEST RESULTS</i></b>	<b><i>28-31</i></b>

### **Government Disclaimer Notice**

*When government drawing, specification, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawing, specifications, or other data, is not to be regarded by implication or otherwise in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell patented invention that may in any way be related thereto. This report must not be used to claim product endorsement by NVLAP or any agency of the U.S. Government.*

### **Reproduction Clause**

*Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from EMC Compliance Management Group, 670 National Ave., Mountain View, CA 94043.*

### **Opinions and Interpretations**

*This test report relates to the abovementioned equipment under test (EUT). Without the permission of EMC Compliance Management Group Test Lab this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products. The manufacturer has sole responsibility of continued compliance of the device.*

### **Statement of Measurement Uncertainty**

*The data and results referenced in the document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities that can account for a nominal measurement error. Furthermore, component and process variability of devices similar to that tested may result in additional deviation.*

### **Administrative Data**

*Test Sample* : Microwave Oven

*Model Numbers* : P12034X-Z

*Model Tested* : P12034AP

*Brand Name* : Galanz

*Date Tested* : 2007, March 16<sup>th</sup>

*Applicant* : Guangdong Galanz Enterprises Co., Ltd.  
25 Ronggui Nan Rd., Shunde, Foshan, Guangdong,  
China.

*Telephone* : 86-0757-23612785

*Fax* : 86-757-23612537

*Manufacturer* : Guangdong Galanz Enterprises Co., Ltd.  
25 Ronggui Nan Rd., Shunde, Foshan, Guangdong,  
China.

### **EUT Description**

Guangdong Galanz Enterprises Co., Ltd. model tested P12034AP (referred to the EUT in this report) is a Microwave Oven.

#### **Specifications:**

<i>Model Number:</i>	P12034AP
<i>Power Consumption</i>	120V~60Hz, 1650W
<i>Output</i>	1200W
<i>Operation Frequency</i>	2450MHz
<i>Magnetron Manufacturer</i>	Panasonic
<i>Magnetron Model Number</i>	2M289-M47
<i>Outside Dimensions(H×W×D)</i>	11 13/16×21 1/4×17 11/16 in.
<i>Oven Cavity Dimensions(H×W×D)</i>	9 7/16×14 13/16×15 7/8 in.
<i>Oven Capacity:</i>	1.2 cu.ft.
<i>Cooking Uniformity:</i>	Turntable System (Φ12 13/16")
<i>Net Weight:</i>	Approx. 37.5lbs.

### **Type of Deriver**

*P12034X-Z model designations:*

*P: denotes only the Microwave functions.*

*120: denotes the output power is 1200W.*

*34: denote different capacity in 34 liters.*

*X may be AL, EL, AP, EP, ASP. "A, E" denote the electrical control model; "L, P" just denote the different open mode for door ;"L" denotes the door handle is on the side of the door; "P" denotes the push-down type door; "S" denotes the stainless steel cavity.*

*Z may be blank, -T1, -T3, -T4, -C5, -D1, -D2, -F4, -MT1, denotes the different appearance.*

## Test Summary

The Electromagnetic Compatibility requirements on model tested P12034AP for this test is stated below. All results listed in this report relate exclusively to this above-mentioned model as the Equipment Under Test. This report confers no approval or endorsement upon any other component, host or subsystem used in the test set-up.

Emission Tests				
Specifications	Description	Test Results	Test Point	Remark
FCC Part 18:2004 FCC/OST MP-5:1986 ANSI C63.4: 2003	Radiation Hazard Measurement	Passed by 0.0046mW/cm <sup>2</sup>	EUT	Attachment 1
FCC Part 18:2004 FCC/OST MP-5:1986 ANSI C63.4: 2003	Input Power Measurement	Refer to Attachment2	EUT	Attachment 2
FCC Part 18:2004 FCC/OST MP-5:1986 ANSI C63.4: 2003	RF Output power Measurement	Refer to Attachment3	EUT	Attachment 3
FCC Part 18:2004 FCC/OST MP-5:1986 ANSI C63.4: 2003	Operating Frequency Measurement	Passed	EUT	Attachment 4
FCC Part 18:2004 FCC/OST MP-5:1986 ANSI C63.4: 2003	Conducted Emission	Passed by 15.2 dB of QP	AC Input Port	Attachment 5
FCC Part 18:2004 FCC/OST MP-5:1986 ANSI C63.4: 2003	Radiated Emission	Passed by 16.52 dB of AVE	Enclosure	Attachment 6



### ***Load for Microwave Ovens***

*For all measurements the energy developed by the oven was absorbed by a dummy load consisting of a quantity of tap water in a beaker. If the oven was provided with a shelf or other utensil support, this support was in its initial normal position. For ovens rated at 1000watts or less power output, the beaker contained quantities of water as listed in the following subparagraphs. For ovens rated at more than 1000watts output, each quantity was increased by 50% for each 500watts or fraction thereof in excess of 1000watts. Additional beakers were used if necessary.*

*--Load for power output measurement: 1000 milliliters of water in the beaker located in the center of the oven.*

*--Load for frequency measurement: 1000 milliliters of water in the beaker located in the center of the oven.*

*--Load for measurement of radiation on second and third harmonic: Two loads, one of 700 and the other of 300 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner.*

*--Load for all other measurements: 700 milliliters of water, with the beaker located in the center of the oven.*

### ***Equipment Modification***

*Any modifications installed previous to testing by Guangdong Galanz Enterprises Co., Ltd. will be incorporated in each production model sold or leased in United States.*

*There were no modifications installed by EMC Compliance Management Group (China) test personnel.*

***EUT Sample Photos for model P12034AP***



***Front & Top View***




***Rear View***




*Door opened View*



*Uncovered View*




*AC power filter board*




*AC power filter board - Reversed*





**PCB**




**PCB - Reversed**

### Test System Details

EUT					
Model Numbers:	P12034X-Z				
Model Tested:	P12034AP				
Description:	Microwave Oven				
Manufacturer:	Guangdong Galanz Enterprises Co., Ltd.				
Support Equipment					
N/A					
Cable Description					
Description	From	To	Length (Meters)	Shielded (Y/N)	Ferrite (Y/N)
Power Cable	EUT	Plug	1.20	N	N

### ***Configuration of Tested System***



**ATTACHMENT 1 – RADIATION HAZARD TEST**

<b>CLIENT:</b>	Guangdong Galanz Enterprises Co., Ltd.	<b>TEST STANDERD:</b>	FCC Part 18
<b>MODEL NUMBERS:</b>	P12034X-Z	<b>PRODUCT:</b>	Microwave Oven
<b>MODEL TESTED:</b>	P12034AP	<b>EUT DESIGNATION:</b>	Home or Office
<b>TEMPERATURE:</b>	22°C	<b>HUMIDITY:</b>	60%RH
<b>ATM PRESSURE:</b>	101.1kPa	<b>GROUNDING:</b>	Through AC Power Cord
<b>TESTED BY:</b>	King Su	<b>DATE OF TEST:</b>	2007, March 16 <sup>th</sup>
<b>TEST REFERENCE:</b>	ANSI C63.4: 2003, FCC/OST MP-5:1986		
<b>TEST PROCEDURE:</b>	The EUT was set up according to the FCC MP-5 and FCC Part 18 for Radiation Hazard Measurement. The measurement was using a microwave leakage meter to measure the Radiation leakage in the as-received condition with the oven door closed. A 1000ml water load in a beaker was located in the center of the oven and the Microwave oven was set to maximum power. While the oven operating, the microwave meter will check the leakage and then record the maximum leakage.		
<b>TESTED RANGE:</b>	N/A		
<b>TEST VOLTAGE:</b>	120VAC / 60Hz		
<b>RESULTS:</b>	<p>There was no microwave leakage exceeding a power level of 0.0046 mW/cm<sup>2</sup> observed at any point 5cm or more from the external surface of the oven.</p> <p>A maximum of 1.0mW/cm<sup>2</sup> is allowed in accordance with the applicable FCC standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed.</p> <p>The test results relate only to the equipment under test provided by client.</p>		
<b>Changes or Modifications:</b>	There were no modifications installed by EMC Compliance Management Group (China) test personnel.		
<b>M. UNCERTAINTY:</b>	0.0001 mW/cm <sup>2</sup>		



***Test equipments list:***

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
Field Monitor	R&S	AR FM5004	A0304252	25/05/06	24/05/07
Electric FieldProber	R&S	AR FP6001	A0304302	15/03/06	14/03/07
Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).					

SIGNED BY:  \_\_\_\_\_  
ENGINEER



***Radiation Hazard Test Set-up***

**ATTACHMENT 2 – INPUT POWER MEASUREMENT**

<b>CLIENT :</b>	Guangdong Galanz Enterprises Co., Ltd.	<b>TEST STANDERD:</b>	FCC Part 18
<b>MODEL NUMBERS:</b>	P12034X-Z	<b>PRODUCT:</b>	Microwave Oven
<b>MODEL TESTED:</b>	P12034AP	<b>EUT DESIGNATION:</b>	Home or Office
<b>TEMPERATURE:</b>	22°C	<b>HUMIDITY:</b>	60%RH
<b>ATM PRESSURE:</b>	101.1kPa	<b>GROUNDING:</b>	Through AC Power Cord
<b>TESTED BY:</b>	King Su	<b>DATE OF TEST:</b>	2007, March 16 <sup>th</sup>
<b>TEST REFERENCE:</b>	ANSI C63.4: 2003, FCC/OST MP-5:1986		
<b>TEST PROCEDURE:</b>	The EUT was set up according to the FCC MP-5 and FCC Part 18 for Input power Measurement. The input power and current was measured using a power analyzer. A 1000ml water load in a beaker was located in the center of the oven and the Microwave oven was set to maximum power. While the oven is operating, use a voltmeter and an ampmeter to test the AC input voltage and current		
<b>TESTED RANGE:</b>	N/A		
<b>TEST VOLTAGE:</b>	120VAC / 60Hz		
<b>RESULTS :</b>	Based on the measured input power, the EUT was found to be operating within the intended specifications.  The test results relate only to the equipment under test provided by client.		
<b>Changes or Modifications:</b>	There were no modifications installed by EMC Compliance Management Group (China) test personnel.		
<b>M. UNCERTAINTY :</b>	± 5W		

**Test Data:**

Input Voltage (Vac/Hz)	Input Current (amps)	Measured Input Power (watts)	Rated Input Power (watts)
120	14.46	1663	1650

**Test equipments list :**

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
Power frequency test system	Ainuo	AN8716PX	058704273	07/12/06	06/12/07

Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).

SIGNED BY:   
ENGINEER



### *Input Power Test Set-Up*

**ATTACHMENT 3 – RF OUTPUT POWER MEASUREMENT**

<b>CLIENT:</b>	Guangdong Galanz Enterprises Co., Ltd.	<b>TEST STANDERD:</b>	FCC Part 18
<b>MODEL NUMBERS:</b>	P12034X-Z	<b>PRODUCT:</b>	Microwave Oven
<b>MODEL TESTED:</b>	P12034AP	<b>EUT DESIGNATION:</b>	Home or Office
<b>TEMPERATURE:</b>	22°C	<b>HUMIDITY:</b>	60%RH
<b>ATM PRESSURE:</b>	101.1kPa	<b>GROUNDING:</b>	Through AC Power Cord
<b>TESTED BY:</b>	King Su	<b>DATE OF TEST:</b>	2007, March 16 <sup>th</sup>
<b>TEST REFERENCE:</b>	ANSI C63.4: 2003, FCC/OST MP-5:1986		
<b>TEST PROCEDURE:</b>	<p>The EUT was set up according to the FCC MP-5 and FCC Part 18C for RF output power Measurement. The Caloric Method was used to determine maximum RF output power. The initial temperature of the water load was measured. A 1000ml water load in a beaker was located in the center of the oven. The oven was operated at maximum output power for 120 seconds, the temperature of the water was re-measured.</p> <p>RF Output Power</p> $= (4.2\text{joules/calorie})(\text{volume in milliliters})(\text{temperature rise}) / (\text{time in seconds})$ $= 4.2 \text{ joules/calorie} \times 1000 \times (\text{Final Temp} - \text{Initial Temp}) / 120$		
<b>TESTED RANGE:</b>	N/A		
<b>TEST VOLTAGE:</b>	120VAC / 60Hz		
<b>RESULTS:</b>	<p>RF Output Power = 878.5watts</p> <p>The test results relate only to the equipment under test provided by client.</p>		
<b>Changes or Modifications:</b>	There were no modifications installed by EMC Compliance Management Group (China) test personnel.		
<b>M. UNCERTAINTY:</b>	± 0.3°C		

**Test Data:**

Quality of Water (ml)	Starting Temperature (°C)	Final Temperature (°C)	Elapsed Time (Seconds)	RF Output Power (watts)
120V/60Hz	16.70	41.80	120	878.5

**Test equipments list :**

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
Data Acquisition	TES	TES-1310	020907011	12/03/06	11/03/07

Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).

SIGNED BY:   
ENGINEER



***RF Output Power Test Set-Up***



**ATTACHMENT 4 - OPERATING FREQUENCY MEASUREMENT**

<b>CLIENT:</b>	Guangdong Galanz Enterprises Co., Ltd.	<b>TEST STANDERD:</b>	FCC Part 18
<b>MODEL NUMBERS:</b>	P12034X-Z	<b>PRODUCT:</b>	Microwave Oven
<b>MODEL TESTED:</b>	P12034AP	<b>EUT DESIGNATION:</b>	Home or Office
<b>TEMPERATURE:</b>	22°C	<b>HUMIDITY:</b>	60%RH
<b>ATM PRESSURE:</b>	101.1kPa	<b>GROUNDING:</b>	Through AC Power Cord
<b>TESTED BY:</b>	King Su	<b>DATE OF TEST:</b>	2007, March 16 <sup>th</sup>
<b>TEST REFERENCE:</b>	ANSI C63.4: 2003, FCC/OST MP-5:1986		
<b>TEST PROCEDURE:</b>	<p>The EUT was set up according to the FCC MP-5 and FCC Part 18 for Operating Frequency Measurement.</p> <p>1) The variation of frequency with time.</p> <p>The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1000ml water load in a beaker was located in the center of the oven. Set a spectrum analyzer with antenna at 3 meters distance form the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load.</p> <p>2) The variation of frequency with Line Voltage.</p> <p>The operating frequency was measured using a spectrum analyzer. The EUT was operated/warmed by at least 10 minutes of use with a 1000ml water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating.</p>		
<b>TESTED RANGE:</b>	2450 ± 50MHz		
<b>TEST VOLTAGE:</b>	120VAC / 60Hz		
<b>RESULTS:</b>	<p>Please refer to following pages for details of the variation in operating frequency with time &amp; line voltage measurement.</p> <p>The test results relate only to the equipment under test provided by client.</p>		
<b>Changes or Modifications:</b>	There were no modifications installed by EMC Compliance Management Group (China) test personnel.		
<b>M. UNCERTAINTY:</b>	Freq. ±10kHz		

***Variation in Operating Frequency with Time:***


Minimum Frequency (MHz)	Maximum Frequency (MHz)
2466.2	2466.4


***Variation in Operating Frequency with Line Voltage:***

Minimum Frequency (MHz)	Maximum Frequency (MHz)
2466.2	2469.2
Note: Line voltage varied from 96Vac to 150Vac.	

***Test equipments list:***

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
Ultra Broadband Antenna	ETS	3142C	00042672	04/12/06	03/12/07
Horn Antenna	ETS	3115	6587	04/07/06	03/07/07
EMI Receiver	R&S	FSP30	100755	04/12/06	03/12/07
5M Anechoic chamber	ETS	3m	N/A	19/03/05	18/03/07
Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).					


SIGNED BY:   
ENGINEER




***Operating Frequency Test Set-up***

**ATTACHMENT 5 - CONDUCTED EMISSION TEST RESULTS**

<b>CLIENT:</b>	Guangdong Galanz Enterprises Co., Ltd.	<b>TEST STANDERD:</b>	FCC Part 18
<b>MODEL NUMBERS:</b>	P12034X-Z	<b>PRODUCT:</b>	Microwave Oven
<b>MODEL TESTED:</b>	P12034AP	<b>EUT DESIGNATION:</b>	Home or Office
<b>TEMPERATURE:</b>	22°C	<b>HUMIDITY:</b>	60%RH
<b>ATM PRESSURE:</b>	101.1kPa	<b>GROUNDING:</b>	Through AC Power Cord
<b>TESTED BY:</b>	King Su	<b>DATE OF TEST:</b>	2007, March 16 <sup>th</sup>
<b>TEST REFERENCE:</b>	ANSI C63.4: 2003, FCC/OST MP-5:1986		
<b>TEST PROCEDURE:</b>	The EUT was set up according to the guideline of ANSI C63.4: 2003 & FCC MP-5 for conducted emissions. The measurement was using a AMN on each line and an EMI receiver peak scan was made at the frequency measurement range. The six highest significant peaks were then marked, and these signals were then quasi-peaked and averaged. The frequency range investigated was from 150kHz to 30MHz.		
<b>TESTED RANGE:</b>	150kHz to 30MHz		
<b>TEST VOLTAGE:</b>	120VAC / 60Hz		
<b>RESULTS:</b>	The EUT meets the requirements of test reference for Conducted Emissions on line N by 15.2 dB of Quasi-Peak detector.  The test results relate only to the equipment under test provided by client.		
<b>Changes or Modifications:</b>	There were no modifications installed by EMC Compliance Management Group (China) test personnel.		
<b>M. UNCERTAINTY:</b>	±2.5 dB		



**Line L Conducted Emission Graph**



**Line N Conducted Emission Graph**

**Test data:**


Line	Frequency [KHz]	Corrected QP Reading [dB $\mu$ V]	Delta QP [dB]	Limit [dB $\mu$ V/m]	Corrected AVE Reading [dB $\mu$ V]	Delta AVE [dB]	Limit [dB $\mu$ V/m]
L	0.1608	41.40	-24.0	65.40	/	/	55.40
L	0.8002	35.60	-20.4	56.00	/	/	46.00
L	0.8786	33.60	-22.4	56.00	/	/	46.00
N	0.1570	44.90	-20.7	65.60	/	/	55.60
N	0.6418	40.80	-15.2	56.00	/	/	46.00
N	0.8082	39.00	-17.0	56.00	/	/	46.00

Note: All readings are using a bandwidth of 9 kHz, with a 30 ms sweep time.

**Test equipments list:**

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
EMI Receiver	SCHAFFNE	SMR4503	44	04/07/06	03/07/07
LISN	AGILENT	482512	1161	04/07/06	03/07/07

Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).

SIGNED BY:   
ENGINEER



***Conducted Emission Test Set-up***

## ATTACHMENT 6 - RADIATED EMISSION TEST RESULTS


<b>CLIENT:</b>	Guangdong Galanz Enterprises Co., Ltd.	<b>TEST STANDERD:</b>	FCC Part 18
<b>MODEL NUMBERS:</b>	P12034X-Z	<b>PRODUCT:</b>	Microwave Oven
<b>MODEL TESTED:</b>	P12034AP	<b>EUT DESIGNATION:</b>	Home or Office
<b>TEMPERATURE:</b>	22°C	<b>HUMIDITY:</b>	60%RH
<b>ATM PRESSURE:</b>	101.1kPa	<b>GROUNDING:</b>	Through AC Power Cord
<b>TESTED BY:</b>	King Su	<b>DATE OF TEST:</b>	2007, March 16 <sup>th</sup>
<b>TEST REFERENCE:</b>	ANSI C63.4: 2003, FCC/OST MP-5:1986		
<b>TEST PROCEDURE:</b>	<p>The EUT was set up according to the guidelines of ANSI C63.4: 2003 &amp; FCC MP-5 for radiated emissions. Microwave oven was placed on a 1m *1.5m nonconductive table. The top of the table is 1.0 m above the ground. The table is placed on a flush mounted metal turntable.</p> <p>An EMI receiver peak scan was made at the frequency measurement range (pre-scan) in an Anechoic chamber. Signal discrimination was then performed and the significant peaks marked. All data was recorded in Quasi-peak detection mode from 30 MHz to 1GHz and average detector mode above 1GHz.</p> <p>The following data lists the significant emission frequencies, measured levels, correction factors (including cable and antenna correction factors), and the corrected readings against the limits. Explanation of the Correction Factor are given as follows:</p> <p>FS= RA + AF + CF - AG</p> <p>Where: FS = Field Strength</p> <p>RA = Receiver Amplitude</p> <p>AF = Antenna Factor</p> <p>CF = Cable Attenuation Factor</p> <p>AG = Amplifier Gain</p>		
<b>TESTED RANGE:</b>	30MHz to 24.5GHz		
<b>TEST VOLTAGE:</b>	120VAC / 60Hz		
<b>RESULTS:</b>	The EUT meets the requirements of test reference for Radiated Emissions on Vertical polarization by 16.52 dB of Average detector at 4.9151 GHz. The test results relate only to the equipment under test provided by client.		
<b>Changes or Modifications:</b>	There were no modifications installed by EMC Compliance Management Group (China) test personnel.		
<b>M. UNCERTAINTY:</b>	± 3.2 dB		



30MHz – 1GHz				
Frequency [MHz]	Antenna Polarization [V/H]	Corrected Reading [dB $\mu$ V/m]	Delta, QP [dB]	3 Meters Limits [dB $\mu$ V/m]
133.0000	H	29.20	-41.21	70.41
188.2000	H	32.50	-37.91	70.41
232.6000	H	29.40	-41.01	70.41
130.0000	V	21.90	-48.51	70.41
262.0000	V	24.40	-46.01	70.41
284.8000	V	35.20	-35.21	70.41
Note: All readings are quasi-peak unless stated otherwise, using a bandwidth of 120kHz, with a 30 ms sweep time. A video filter was not used.				
1GHz – 25GHz				
Frequency [GHz]	Antenna Polarization [V/H]	Corrected Reading [dB $\mu$ V/m]	Delta, AVE [dB]	3 Meters Limits [dB $\mu$ V/m]
4.9190	H	51.44	-18.79	70.41
7.3856	H	47.21	-23.20	70.41
9.8365	H	49.74	-20.67	70.41
4.9151	V	53.89	-16.52	70.41
7.3809	V	48.02	-22.39	70.41
14.8074	V	51.71	-18.70	70.41
Comments: None				
Note: All readings are average unless stated otherwise, using a bandwidth of 1MHz, with a 30 ms sweep time. A video filter was not used.				


***Test equipments list:***

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
Ultra Broadband Antenna	ETS	3142C	00042672	20/07/06	19/07/07
Horn Antenna	ETS	3115	6587	04/07/06	03/07/07
Band-pass Filter	Micro-Tronics	BRM50702	SIN-030	04/07/06	03/07/07
EMI Receiver 1	SCHAFFNE	SMR4503	44	04/07/06	03/07/07
Semi-anechoic chamber	ETS	3m	N/A	19/03/05	18/03/07
EMI Receiver 2	R&S	FSP30	100755	04/12/06	03/12/07
Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).					

SIGNED BY:   
ENGINEER



***Radiated Emission Test Set-up (30~1000MHz)***



***Radiated Emission Test Set-up (1~25GHz)***