

# **FCC Test Report**

FCC ID : UIDGPW2200

Equipment : G.hn Powerline to Wi-Fi extender

Model No. : GPW2200

Brand Name : ARRIS

Applicant : ARRIS Group, Inc.

Address : 3871 Lakefield Drive, Suite 300, Suwanee,

Georgia 30024, United States

Standard : 47 CFR FCC Part 15.407

Received Date : Aug. 28, 2017

Tested Date : Sep. 04 ~ Sep. 28, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen / Assistant Manager Gary Chang / Manager

Testing Laboratory

Report No.: FR782803AN Page: 1 of 73



## **Table of Contents**

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	
1.4	The Equipment List	9
1.5	Testing Applied Standards	11
1.6	Measurement Uncertainty	11
2	TEST CONFIGURATION	12
2.1	Testing Condition	12
2.2	The Worst Test Modes and Channel Details	
3	TRANSMITTER TEST RESULTS	14
3.1	Conducted Emissions	14
3.2	Emission Bandwidth	19
3.3	RF Output Power	
3.4	Peak Power Spectral Density	24
3.5	Transmitter Radiated and Band Edge Emissions	28
3.6	Frequency Stability	71
4	TEST LABORATORY INFORMATION	73



## **Release Record**

Report No.	Version	Description	Issued Date
FR782803AN	Rev. 01	Initial issue	Nov. 09, 2017

Report No.: FR782803AN Page: 3 of 73



# **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.198MHz 32.42 (Margin -21.29dB) - AV	Pass
15.407(b) 15.209	Radiated Emissions	[dBuV/m at 3m]: 5650.00MHz 67.77 (Margin -0.43dB) - PK	Pass
15.407(a)	Emission Bandwidth	Meet the requirement of limit	Pass
15.407(e)	6dB bandwidth	Meet the requirement of limit	Pass
15.407(a)	RF Output Power	Max Power [dBm]: 5150-5250MHz: 25.37 5725-5850MHz: 25.83	Pass
15.407(a)	Peak Power Spectral Density	Meet the requirement of limit	Pass
15.407(g)	Frequency Stability	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR782803AN Page: 4 of 73



## 1 General Description

## 1.1 Information

## 1.1.1 Specification of the Equipment under Test (EUT)

	RF General Information				
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS
5150-5250	а	5180-5240	36-48 [4]	2	6-54 Mbps
5150-5250	n (HT20)	5180-5240	36-48 [4]	2	MCS 0-15
5150-5250	n (HT40)	5190-5230	38-46 [2]	2	MCS 0-15
5150-5250	ac (VHT20)	5180-5240	36-48 [4]	2	MCS 0-9
5150-5250	ac (VHT40)	5190-5230	38-46 [2]	2	MCS 0-9
5150-5250	ac (VHT80)	5210	42 [1]	2	MCS 0-9

Note 1: RF output power specifies that Maximum Conducted Output Power.

Note 2: 802.11a/n/ac uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM modulation.

	RF General Information				
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS
5725-5850	а	5745-5825	149-165 [5]	2	6-54 Mbps
5725-5850	n (HT20)	5745-5825	149-165 [5]	2	MCS 0-15
5725-5850	n (HT40)	5755-5795	151-159 [2]	2	MCS 0-15
5725-5850	ac (VHT20)	5745-5825	149-165 [5]	2	MCS 0-9
5725-5850	ac (VHT40)	5755-5795	151-159 [2]	2	MCS 0-9
5725-5850	ac (VHT80)	5775	155 [1]	2	MCS 0-9

Note 1: RF output power specifies that Maximum Conducted Output Power.

Note 2: 802.11a/n/ac uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM modulation.

### 1.1.2 Antenna Details

Ant. No.	Model	Turno	Connector	Operating Freq	uencies (MHz) / Ant	enna Gain (dBi)
Ant. No.	Wiodei	Туре	Connector	2400~2483.5	5150~5250	5725~5850
1	Ant 1	Dipole	UFL	3.46	3.14	3.41
2	Ant 2	Dipole	UFL	2.43	3.25	2.6

## 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	100-240Vac

Report No.: FR782803AN Page: 5 of 73



## 1.1.4 Accessories

	Accessories				
No.	Equipment	Description			
1	RJ45 cable	2.0m non-shielded without core			

## 1.1.5 Channel List

For Frequency band 5150-5250 MHz			
802.11 a / HT20 / VHT20 HT40 / VHT40			
Channel	Frequency(MHz)	Channel	Frequency(MHz)
36	5180	38	5190
40	5200	46	5230
44	5220	VHT80	
48	5240	42	5210

For Frequency band 5725~5850 MHz			
802.11 a / HT20 / VHT20 HT40 / VHT40			
Channel	Frequency(MHz)	Channel	Frequency(MHz)
149	5745	151	5755
153	5765	159	5795
157	5785	VH	T80
161	5805	155	5775
165	5825		

## 1.1.6 Test Tool and Duty Cycle

Test Tool	Putty, version: 0.6			
	Mode	Duty cycle (%)	Duty factor (dB)	
	11a	87.84%	0.56	
Duty Cycle and Duty Factor	VHT20	88.94%	0.51	
	VHT40	80.55%	0.94	
	VHT80	64.52%	1.90	

Report No.: FR782803AN Page: 6 of 73



## 1.1.7 Power Setting

	For Frequency band 5150-5250 MHz			
Modulation Mode	Test Frequency (MHz)	Power Set		
11a	5180	23/27		
11a	5200	32/36		
11a	5240	32/36		
HT20	5180	22/26		
HT20	5200	32/36		
HT20	5240	32/36		
HT40	5190	17/21		
HT40	5230	30/34		
VHT20	5180	22/26		
VHT20	5200	32/36		
VHT20	5240	32/36		
VHT40	5190	17/21		
VHT40	5230	30/34		
VHT80	5210	13/17		

F	For Frequency band 5725~5850 MHz							
Modulation Mode	Test Frequency (MHz)	Power Set						
11a	5745	32/32						
11a	5785	32/32						
11a	5825	32/32						
HT20	5745	32/32						
HT20	5785	32/32						
HT20	5825	32/32						
HT40	5755	32/32						
HT40	5795	32/32						
VHT20	5745	32/32						
VHT20	5785	32/32						
VHT20	5825	32/32						
VHT40	5755	32/32						
VHT40	5795	32/32						
VHT80	5775	24/24						


Report No.: FR782803AN Page: 7 of 73



## 1.2 Local Support Equipment List

Support Equipment List							
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)		
1	Notebook	DELL	Latitude E6440	DoC	RJ45, 10m non-shielded.		

## 1.3 Test Setup Chart



Report No.: FR782803AN Page: 8 of 73



## 1.4 The Equipment List

Test Item	Conducted Emission	Conducted Emission							
Test Site	Conduction room 1 / (	Conduction room 1 / (CO01-WS)							
Tested Date	Sep. 28, 2017	Sep. 28, 2017							
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until				
Receiver	R&S	ESR3	101657	Dec. 21, 2016	Dec. 20, 2017				
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 08, 2016	Nov. 07, 2017				
RF Cable-CON	EMC	EMCCFD300-BM-B M-6000	50821	Dec. 20, 2016	Dec. 19, 2017				
Measurement Software	AUDIX	e3	6.120210k	NA	NA				

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03C	H03-WS)			
Tested Date	Sep. 04, 2017				
Instrument	Manufacturer	Model No.	Calibration Until		
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40	101486	Nov. 15, 2016	Nov. 14, 2017
Receiver	Agilent	N9038A	MY53290044	Oct. 06, 2016	Oct. 05, 2017
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 28, 2017	Apr. 27, 2018
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 09, 2017	Feb. 08, 2018
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 25, 2016	Oct. 24, 2017
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW 101354-BW Dec. 09,		Dec. 08, 2017
Preamplifier	EMC	EMC02325	980187	Sep. 08, 2016	Sep. 07, 2017
Preamplifier	Agilent	83017A	MY53270014 Aug. 21, 2017		Aug. 20, 2018
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 04, 2017	Feb. 03, 2018
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 04, 2017	Feb. 03, 2018
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 04, 2017	Feb. 03, 2018
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Feb. 04, 2017	Feb. 03, 2018
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Feb. 04, 2017	Feb. 03, 2018
LF cable-13M	EMC	EMC8D-NM-NM-130 00	0 131104 Feb. 04, 2017 F		Feb. 03, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Inte	rval of instruments liste	d above is one year.			

Report No.: FR782803AN Page: 9 of 73



Test Item	Radiated Emission								
Test Site	966 chamber 3 / (03C	H03-WS)							
Tested Date	Sep. 26, 2017	Sep. 26, 2017							
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until				
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40	101486	Nov. 15, 2016	Nov. 14, 2017				
Receiver	Agilent	N9038A	MY53290044	Oct. 06, 2016	Oct. 05, 2017				
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 28, 2017	Apr. 27, 2018				
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 09, 2017	Feb. 08, 2018				
Horn Antenna 18G-40G	SCHWARZBECK	SCHWARZBECK BBHA 9170 BBHA 9170517			Oct. 24, 2017				
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017				
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 09, 2016	Dec. 08, 2017				
Preamplifier	EMC	EMC02325	980187	Sep. 04, 2017	Sep. 03, 2018				
Preamplifier	Agilent	83017A	MY53270014	Aug. 21, 2017	Aug. 20, 2018				
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018				
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 04, 2017	Feb. 03, 2018				
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 04, 2017	Feb. 03, 2018				
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 04, 2017	Feb. 03, 2018				
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Feb. 04, 2017	Feb. 03, 2018				
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Feb. 04, 2017	Feb. 03, 2018				
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104 Feb. 04, 2017 Fe		Feb. 03, 2018				
Measurement Software	AUDIX	e3	6.120210g	NA	NA				
Note: Calibration Inter	val of instruments liste	d above is one year.							

Test Item	RF Conducted	RF Conducted							
Test Site	(TH01-WS)	(TH01-WS)							
Tested Date	Sep. 20 ~ Sep. 28, 20	)17							
Instrument	Manufacturer	Manufacturer Model No. Serial No. Calibration Date Calibration Until							
Spectrum Analyzer	R&S	FSV40	101063	Mar. 15, 2017	Mar. 14, 2018				
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 21, 2016	Nov. 20, 2017				
Power Meter	Anritsu	ML2495A	1241002	Oct. 06, 2016	Oct. 05, 2017				
Power Sensor	Anritsu	MA2411B	1207366	Oct. 06, 2016	Oct. 05, 2017				
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 28, 2016	Oct. 27, 2017				
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA				
Note: Calibration Inte	rval of instruments liste	d above is one year.		•					

Report No.: FR782803AN Page: 10 of 73



## 1.5 Testing Applied Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04

FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty						
Parameters	Uncertainty					
Bandwidth	±34.134 Hz					
Conducted power	±0.808 dB					
Frequency error	±34.134 Hz					
Power density	±0.463 dB					
Conducted emission	±2.670 dB					
AC conducted emission	±2.90 dB					
Radiated emission ≤ 1GHz	±3.66 dB					
Radiated emission > 1GHz	±5.37 dB					
Time	±0.1%					
Temperature	±0.6 °C					

Report No.: FR782803AN Page: 11 of 73



# 2 Test Configuration

## 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	22°C / 60%	Howard Huang
Radiated Emissions	03CH03-WS	24-25°C / 65-66%	Aska Huang Brad Wu
RF Conducted	TH01-WS	23°C / 62%	Felix Sung

FCC Designation No.: TW0009
 FCC site registration No.: 207696
 IC site registration No.: 10807C-1

Report No.: FR782803AN Page: 12 of 73



## 2.2 The Worst Test Modes and Channel Details

	For Frequency band 5150-5250 MHz								
Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration					
Conducted Emissions	11a	5200	6 Mbps						
Radiated Emissions ≤1GHz	11a	5200	6 Mbps						
	11a	5180 / 5200 / 5240	6 Mbps						
	HT20	5180 / 5200 / 5240	MCS 0						
RF Output Power	HT40	5190 / 5230	MCS 0						
Tri Odipat i Owei	VHT20	5180 / 5200 / 5240	MCS 0						
	VHT40	5190 / 5230	MCS 0						
	VHT80	5210	MCS 0						
	11a	5180 / 5200 / 5240	6 Mbps						
Radiated Emissions >1GHz	VHT20	5180 / 5200 / 5240	MCS 0						
Emission Bandwidth Peak Power Spectral Density	VHT40	5190 / 5230	MCS 0						
Todak i Swor Opoolidi Boriolly	VHT80	5210	MCS 0						
Frequency Stability	Un-modulation	5200							

### NOTE:

<sup>1.</sup> The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.

For Frequency band 5725-5850 MHz									
Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration					
Conducted Emissions	11a	5745	6 Mbps						
Radiated Emissions ≤1GHz	11a	5745	6 Mbps						
	11a	5745 / 5785 / 5825	6 Mbps						
	HT20	5745 / 5785 / 5825	MCS 0						
DE Output Dower	HT40	5755 / 5795	MCS 0						
RF Output Power	VHT20	5745 / 5785 / 5825	MCS 0						
	VHT40	5755 / 5795	MCS 0						
	VHT80	5775	MCS 0						
Radiated Emissions >1GHz	11a	5745 / 5785 / 5825	6 Mbps						
Emission Bandwidth	VHT20	5745 / 5785 / 5825	MCS 0						
6dB bandwidth	VHT40	5755 / 5795	MCS 0						
Peak Power Spectral Density	VHT80	5775	MCS 0						
Frequency Stability	Un-modulation	5785							

### NOTE:

Report No.: FR782803AN Page: 13 of 73

<sup>1.</sup> The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.



## 3 Transmitter Test Results

### 3.1 Conducted Emissions

### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit						
Frequency Emission (MHz) Quasi-Peak Average						
0.15-0.5	66 - 56 *	56 - 46 *				
0.5-5	56	46				
5-30	60	50				
Note 1: * Decreases with the logarithm of the frequency.						

#### 3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR782803AN Page: 14 of 73




### 3.1.4 Test Result of Conducted Emissions




Report No.: FR782803AN Page: 15 of 73






Report No.: FR782803AN Page: 16 of 73





Report No.: FR782803AN Page: 17 of 73





Report No.: FR782803AN Page: 18 of 73



### 3.2 Emission Bandwidth

#### 3.2.1 Limit of Emission bandwidth

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

#### 3.2.2 Test Procedures

#### 26dB Bandwidth

- 1. Set RBW = approximately 1% of the emission bandwidth.
- 2. Set the VBW > RBW, Detector = Peak.
- Trace mode = max hold.
- 4. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.


#### **Occupied Bandwidth**

- 1. Set RBW = 1 % to 5 % of the OBW
- 2. Set VBW ≥ 3 RBW
- 3. Sample detection and single sweep mode shall be used
- 4. Use the 99 % power bandwidth function of the instrument

#### 6dB Bandwidth

- 1. Set RBW = 100kHz, VBW = 300kHz
- 2. Detector = Peak, Trace mode = max hold.
- 3. Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 3.2.3 Test Setup




Report No.: FR782803AN Page: 19 of 73



### 3.2.4 Test Result of Emission Bandwidth


	For Frequency band 5150-5250 MHz									
	Emission Bandwidth									
Mode	l N	Freq.	2	26dB Band	width (MHz	)	l.	99% Bandv	vidth (MHz)	
Wode	N <sub>TX</sub>	(MHz)	Chain 0	Chain 1	Chain 2	Chain 3	Chain 0	Chain 1	Chain 2	Chain 3
11a	2	5180	21.39	23.48			16.83	16.84		
11a	2	5200	37.86	37.68			17.42	17.41		
11a	2	5240	36.23	36.41			17.21	17.31		
VHT20	2	5180	23.54	24.29			17.69	17.72		
VHT20	2	5200	44.35	43.84			18.77	18.66		
VHT20	2	5240	44.78	42.46			18.42	18.38		
VHT40	2	5190	41.62	41.51			36.12	36.12		
VHT40	2	5230	78.84	78.70			37.00	36.98		
VHT80	2	5210	81.62	81.39			75.12	75.12		



Report No.: FR782803AN Page: 20 of 73



				For Fre	quency b	and 5725-	5850 MHz				
Emission Bandwidth											
			o	BW Band	width (MH	z)		6dB B	andwidth	(MHz)	
Mode	N <sub>TX</sub>	Freq. (MHz)	Chain 0	Chain 1	Chain 2	Chain 3	Chain 0	Chain 1	Chain 2	Chain 3	6dB BW Limit (MHz)
11a	2	5745	18.45	18.26			15.13	15.07			0.5
11a	2	5785	17.59	17.91			15.36	15.13			0.5
11a	2	5825	17.30	17.67			15.48	15.36			0.5
VHT20	2	5745	19.33	19.43			15.19	15.77			0.5
VHT20	2	5785	18.47	19.02			15.48	15.65			0.5
VHT20	2	5825	18.19	18.50			15.71	15.48			0.5
VHT40	2	5755	39.62	39.02			35.13	35.13			0.5
VHT40	2	5795	37.84	38.92			35.13	35.13			0.5
VHT80	2	5775	75.60	75.68			75.13	75.13			0.5



Report No.: FR782803AN Page: 21 of 73



## 3.3 RF Output Power

## 3.3.1 Limit of RF Output Power

	Frequ	iency band 5150-5250 MHz
Оре	erating Mode	Limit
	Outdoor access point	Conducted Power: 1 W The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm)
	Indoor access point	Conducted Power: 1 W
	Fixed point-to-point access points	Conducted Power: 1 W
	Client devices	Conducted Power: 250 mW

Fred	quency Band (MHz)	Limit
	5250 ~ 5350	250mW or 11dBm+10 log B
	5470 ~ 5725	250mW or 11dBm+10 log B
	5725 ~ 5850	1 W
Note	e: "B" is the 26dB emission bandwidth i	n MHz.

### 3.3.2 Test Procedures

### Method PM-G (Measurement using a gated RF average power meter)

Measurements may is performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

## 3.3.3 Test Setup



Report No.: FR782803AN Page: 22 of 73



## 3.3.4 Test Result of Maximum Conducted Output Power

			For Frequ	uency band	d 5150-5250	MHz			
NA - d -		F (MIII-)	С	onducted I	Power (dBn	n)	Total		Limit
Mode	N <sub>TX</sub>	Freq. (MHz)	Chain 0	Chain 1	Chain 2	Chain 3	Power (mW)	Power (dBm)	(dBm)
11a	2	5180	17.89	18.22			127.892	21.07	30.00
11a	2	5200	22.33	22.38			343.983	25.37	30.00
11a	2	5240	22.16	22.02			323.658	25.10	30.00
HT20	2	5180	17.46	17.62			113.528	20.55	30.00
HT20	2	5200	22.03	21.86			313.050	24.96	30.00
HT20	2	5240	21.78	21.55			293.550	24.68	30.00
HT40	2	5190	14.82	15.03			62.181	17.94	30.00
HT40	2	5230	21.11	21.09			257.651	24.11	30.00
VHT20	2	5180	17.59	17.77			117.253	20.69	30.00
VHT20	2	5200	22.04	22.01			318.810	25.04	30.00
VHT20	2	5240	21.83	21.62			297.616	24.74	30.00
VHT40	2	5190	14.89	15.16			63.641	18.04	30.00
VHT40	2	5230	21.20	21.12			261.245	24.17	30.00
VHT80	2	5210	13.25	13.43			43.164	16.35	30.00

			For Freq	uency band	5725-5850	MHz			
			C	onducted I	Power (dBn	Total	Total	Limit	
Mode	N <sub>TX</sub>	Freq. (MHz)	Chain 0	Chain 1	Chain 2	Chain 3	Power (mW)	Power (dBm)	(dBm)
11a	2	5745	22.65	22.98			382.687	25.83	30.00
11a	2	5785	22.26	22.75			356.632	25.52	30.00
11a	2	5825	21.65	22.15			310.277	24.92	30.00
HT20	2	5745	22.46	22.65			360.275	25.57	30.00
HT20	2	5785	21.87	22.29			323.249	25.10	30.00
HT20	2	5825	21.07	21.43			266.933	24.26	30.00
HT40	2	5755	22.49	22.38			350.401	25.45	30.00
HT40	2	5795	21.65	22.17			311.034	24.93	30.00
VHT20	2	5745	22.58	22.72			368.202	25.66	30.00
VHT20	2	5785	21.95	22.36			328.862	25.17	30.00
VHT20	2	5825	21.13	21.56			272.937	24.36	30.00
VHT40	2	5755	22.55	22.48			356.898	25.53	30.00
VHT40	2	5795	21.76	22.21			316.310	25.00	30.00
VHT80	2	5775	19.15	19.32			167.731	22.25	30.00

Report No.: FR782803AN Page: 23 of 73



## 3.4 Peak Power Spectral Density

### 3.4.1 Limit of Peak Power Spectral Density

	Frequency band 5150-5250 MHz							
Ope	rating Mode	Limit						
	Outdoor access point	17 dBm / MHz						
$\boxtimes$	Indoor access point	17 dBm / MHz						
	Fixed point-to-point access points	17 dBm / MHz						
	Client devices	11 dBm / MHz						

Fred	quency Band (MHz)	Limit
	5250 ~ 5350	11 dBm / MHz
	5470 ~ 5725	11 dBm / MHz
	5725 ~ 5850	30 dBm / 500 kHz

#### 3.4.2 Test Procedures

#### For 5150 ~ 5250 MHz

- ☐ Method SA-1
  - 1. Set RBW = 1 MHz, VBW = 3 MHz, Sweep time = auto, Detector = RMS.
  - 2. Trace average 100 traces.
  - 3. Use the peak marker function to determine the maximum amplitude level.
- Method SA-2 Alternative
  - 1. Set RBW = 1 MHz, VBW = 3 MHz, Detector = RMS.
  - 2. Set sweep time ≥ 10 \* (number of points in sweep) \* (total on/off period of the transmitted signal).
  - 3. Perform a single sweep.
  - 4. Use the peak marker function to determine the maximum amplitude level.
  - 5. Add  $10 \log(1/x)$ , where x is the duty cycle.


#### For 5725 ~ 5850 MHz

- - 1. Set RBW = 500 kHz, VBW = 2 MHz, Sweep time = auto, Detector = RMS.
  - 2. Trace average 100 traces.
  - 3. Use the peak marker function to determine the maximum amplitude level.
- - 1. Set RBW = 500 kHz, VBW = 2 MHz, Detector = RMS.
  - 2. Set sweep time ≥ 10 \* (number of points in sweep) \* (total on/off period of the transmitted signal).
  - 3. Perform a single sweep.
  - 4. Use the peak marker function to determine the maximum amplitude level.
  - 5. Add 10 log(1/x), where x is the duty cycle.

Report No.: FR782803AN Page: 24 of 73



## 3.4.3 Test Setup



Report No.: FR782803AN Page: 25 of 73




#### **Test Result of Peak Power Spectral Density** 3.4.4

			For Frequency	band 5150-5250 MH	łz	
Co	ndition			Peak Power Spectra	al Density (dBm/MH	z)
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	PPSD w/o D.F (dBm/MHz)	Duty Factor (dB)	PPSD with D.F (dBm/MHz)	PPSD Limit (dBm/MHz)
11a	2	5180	7.51	0.56	8.07	16.79
11a	2	5200	11.52	0.56	12.08	16.79
11a	2	5240	11.43	0.56	11.99	16.79
VHT20	2	5180	7.06	0.51	7.57	16.79
VHT20	2	5200	11.40	0.51	11.91	16.79
VHT20	2	5240	11.33	0.51	11.84	16.79
VHT40	2	5190	1.61	0.94	2.55	16.79
VHT40	2	5230	7.50	0.94	8.44	16.79
VHT80	2	5210	-3.88	1.90	-1.98	16.79

#### Note:

- 1. D.F is duty factor.
- Test results are bin-by-bin summing measured value of each TX port.
   Directional gain = 10 \* log((10<sup>3.14/20</sup>+10<sup>3.25/20</sup>)<sup>2</sup>/2) = 6.21 dBi > 6 dBi Limit shall be reduced to 17 dBm - (6.21 dBi - 6 dBi) = 16.79 dBm



Note: Worst plot is w/o duty factor.


Report No.: FR782803AN Page: 26 of 73



			For Frequency	band 5725-5850 MF	łz	
Co	ondition	1	F	Peak Power Spectral	Density (dBm/500kl	Hz)
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	PPSD w/o D.F (dBm/500kHz)	Duty Factor (dB)	PPSD with D.F (dBm/500kHz)	PPSD Limit (dBm/500kHz)
11a	2	5745	10.85	0.56	11.41	29.98
11a	2	5785	10.33	0.56	10.89	29.98
11a	2	5825	9.44	0.56	10.00	29.98
VHT20	2	5745	10.46	0.51	10.97	29.98
VHT20	2	5785	9.93	0.51	10.44	29.98
VHT20	2	5825	9.06	0.51	9.57	29.98
VHT40	2	5755	6.87	0.94	7.81	29.98
VHT40	2	5795	6.28	0.94	7.22	29.98
VHT80	2	5775	0.31	1.90	2.21	29.98

### Note:

- D.F is duty factor.
   Test results are bin-by-bin summing measured value of each TX port.
   Directional gain = 10 \* log((10<sup>3.41/20</sup>+10<sup>2.6/20</sup>)<sup>2</sup>/2) = 6.02 dBi > 6 dBi Limit shall be reduced to 30 dBm (6.02 dBi 6 dBi) = 29.98 dBm



Note: Worst plot is w/o duty factor.

Report No.: FR782803AN Page: 27 of 73



## 3.5 Transmitter Radiated and Band Edge Emissions

## 3.5.1 Limit of Transmitter Radiated and Band Edge Emissions

	Restricted Band	Emissions Limit	
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:** 

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

	Un-restricted band emissions above 1GHz Limit
Operating Band	Limit
5.15 - 5.25 GHz	e.i.r.p27 dBm [68.2 dBuV/m@3m]
5.725 - 5.850 GHz	15.407(b)(4)(i) All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
	15.407(b)(4)(ii) ,compliance with the emission limits in § 15.247(d) Shall be at least 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power,. Attenuation below the general limits specified in §15.209(a) is not required. In addition,radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see § 15.205(c))

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Report No.: FR782803AN Page: 28 of 73



#### 3.5.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR782803AN Page: 29 of 73




## 3.5.3 Test Setup



Report No.: FR782803AN Page: 30 of 73



### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR782803AN Page: 31 of 73





\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR782803AN Page: 32 of 73



Modulation			11a				Test l	Freq	. (MHz	)	!	5745	
Polarization			Horiz	zontal		•					•		
	90Le	vel (dBu	ıV/m)										
	00												
	80												
	70												
	60												
												FCC CL	ASS-B
	50								3		5		
	40						2		Ť	4		-6	
	30					1							
	20												
	10							_					
	0												
	030	100.	20	0. 30	0. 40		00. ency (M	600. Hz)	70	0.	800.	900.	1000
		F	rea. E	missior	n Limit				Factor	Rei	mark	ANT	Turn
				level			read					Hig	h Table
			MHz	dBuV/m	dBuV/n	ı dB	dBu	V	dB			cm	deg
1		4	38.21	31.26	46.00	-14.74	35.	61	-4.35	Pe	ak		
2			62.44	39.52		-6.48	41.		-1.99				
3			87.23			-4.43	41.		0.13				
4			49.24	38.59		-7.41	37.		1.57				
5 6			12.72 74.77	42.83 37.62	46.00 46.00	-3.17 -8.38	40. 34.		2.33 3.24				


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR782803AN Page: 33 of 73





\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR782803AN Page: 34 of 73



## 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11a




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR782803AN Page: 35 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 36 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 37 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 38 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 39 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 40 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 41 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 42 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 43 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 44 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 45 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 46 of 73



## 3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for VHT20




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 47 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 48 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 49 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 50 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 51 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 52 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 53 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 54 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 55 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 56 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 57 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 58 of 73



### 3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for VHT40




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR782803AN Page: 59 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 60 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 61 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 62 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 63 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 64 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 65 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 66 of 73



## 3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for VHT80




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR782803AN Page: 67 of 73

<sup>\*</sup>Factor includes antenna factor, cable loss and amplifier gain






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 68 of 73






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 69 of 73





\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803AN Page: 70 of 73



## 3.6 Frequency Stability


## 3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

#### 3.6.2 Test Procedures

- 1. The EUT is installed in an environment test chamber with external power source.
- Set the chamber to operate at 50 centigrade and external power source to output at nominal voltage of EUT.
- 3. A sufficient stabilization period at each temperature is used prior to each frequency measurement.
- 4. When temperature is stabled, measure the frequency stability.
- 5. The test shall be performed under -30 to 50 centigrade and 85 to 115 percent of the nominal voltage. Change setting of chamber and external power source to complete all conditions.

### 3.6.3 Test Setup



Report No.: FR782803AN Page: 71 of 73



# 3.6.4 Test Result of Frequency Stability

Frequency: 5200 MHz	Frequency Drift (ppm)				
Temperature (°C)	0 minute	2 minutes	5 minutes	10 minutes	
T20°CVmax	0.34	0.12	0.93	0.71	
T20°CVmin	-0.26	0.22	0.12	0.03	
T50°CVnom	0.82	1.34	0.24	0.49	
T40°CVnom	-0.04	0.10	-0.76	-0.46	
T30°CVnom	0.74	1.45	1.01	0.55	
T20°CVnom	1.52	0.95	1.26	0.91	
T10°CVnom	0.86	0.07	0.17	0.89	
T0°CVnom	0.40	1.07	1.19	1.46	
T-10°CVnom	-0.08	0.38	-0.06	0.09	
T-20°CVnom	0.61	0.28	0.77	0.74	
T-30°CVnom	-0.78	0.28	-0.57	-0.28	
Vnom [Vac]: 120		max [Vac]: 138	Vmin [Vac]: 1	Vmin [Vac]: 102	
Tnom [°C]: 20		max [°C]: 50	Tmin [°C]: -30	Tmin [°C]: -30	

Frequency: 5785 MHz	Frequency Drift (ppm)				
Temperature (°C)	0 minute	2 minutes	5 minutes	10 minutes	
T20°CVmax	2.13	1.70	1.42	1.23	
T20°CVmin	0.45	0.40	-0.05	-0.38	
T50°CVnom	1.21	1.09	0.93	0.97	
T40°CVnom	0.97	0.95	1.24	1.22	
T30°CVnom	2.83	3.25	2.31	3.33	
T20°CVnom	1.77	1.52	1.74	1.42	
T10°CVnom	2.75	1.91	2.44	2.17	
T0°CVnom	2.24	1.33	1.77	1.80	
T-10°CVnom	0.69	1.58	1.64	0.83	
T-20°CVnom	1.99	2.14	2.47	2.74	
T-30°CVnom	-0.08	0.03	0.13	0.13	
Vnom [Vac]: 120		max [Vac]: 138	Vmin [Vac]: 1	Vmin [Vac]: 102	
Tnom [°C]: 20		max [°C]: 50	Tmin [°C]: -30	Tmin [°C]: -30	

Report No.: FR782803AN Page: 72 of 73



## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

#### Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

#### Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

#### Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FR782803AN Page: 73 of 73