

FCC Co-Location Test Report

FCC ID : **UIDGPW2200**

Equipment : G.hn Powerline to Wi-Fi extender

Model No. : GPW2200

Brand Name : ARRIS

Applicant : ARRIS Group, Inc.

Address : 3871 Lakefield Drive, Suite 300, Suwanee,

Georgia 30024, United States

: 47 CFR FCC Part 15.247 Standard

47 CFR FCC Part 15.407

: Aug. 28, 2017 **Received Date**

Tested Date : Sep. 05 ~ Sep. 26, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Cherly Assistant Manager Gary Chang / Manager Testing Laboratory

Page: 1 of 17

Report No.: FR782803CO



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	
1.2	The Equipment List	
1.3	Test Standards	
1.4	Measurement Uncertainty	8
2	TEST CONFIGURATION	9
2.1	Testing Condition	g
2.2	The Worst Test Modes and Channel Details	g
3	TRANSMITTER TEST RESULTS	10
3.1	Unwanted Emissions into Restricted Frequency Bands	10
4	TEST LABORATORY INFORMATION	17



Release Record

Report No.	Version	Description	Issued Date
FR782803CO	Rev. 01	Initial issue	Nov. 09, 2017

Report No.: FR782803CO Page: 3 of 17



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d)			
15.407(b)	Radiated Emissions	[dBuV/m at 3m]: 812.79MHz 42.80 (Margin -3.20dB) - QP	Pass
15.209			

Report No.: FR782803CO Page: 4 of 17



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Operating Frequency	802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5745 ~ 5825 MHz
Modulation Type	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

1.1.2 Antenna Details

Ant. No.	Model	Turno	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi) 2400~2483.5 5150~5250 5725~5850			
Ant. No.	Wiodei	Туре	Connector	2400~2483.5	5150~5250	5725~5850	
1	Ant 1	Dipole	UFL	3.46	3.14	3.41	
2	Ant 2	Dipole	UFL	2.43	3.25	2.6	

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	100-240Vac
-------------------	------------

Report No.: FR782803CO Page: 5 of 17



1.2 The Equipment List

Test Item	Radiated Emission						
Test Site	966 chamber 3 / (03CH03-WS)						
Tested Date	Sep. 05, 2017						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40	101486	Nov. 15, 2016	Nov. 14, 2017		
Receiver	Agilent	N9038A	MY53290044	Oct. 06, 2016	Oct. 05, 2017		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 28, 2017	Apr. 27, 2018		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 09, 2017	Feb. 08, 2018		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 25, 2016	Oct. 24, 2017		
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017		
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 09, 2016	Dec. 08, 2017		
Preamplifier	EMC	EMC02325	980187	Sep. 08, 2016	Sep. 07, 2017		
Preamplifier	Agilent	83017A	MY53270014	Aug. 21, 2017	Aug. 20, 2018		
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018		
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 04, 2017	Feb. 03, 2018		
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 04, 2017	Feb. 03, 2018		
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 04, 2017	Feb. 03, 2018		
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Feb. 04, 2017	Feb. 03, 2018		
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Feb. 04, 2017	Feb. 03, 2018		
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104	Feb. 04, 2017	Feb. 03, 2018		
Measurement Software	AUDIX	e3	6.120210g	NA	NA		

Report No.: FR782803CO Page: 6 of 17



Test Item	Radiated Emission						
Test Site	966 chamber 3 / (03CH03-WS)						
Tested Date	Sep. 26, 2017						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40	101486	Nov. 15, 2016	Nov. 14, 2017		
Receiver	Agilent	N9038A	MY53290044	Oct. 06, 2016	Oct. 05, 2017		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 28, 2017	Apr. 27, 2018		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 09, 2017	Feb. 08, 2018		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 25, 2016	Oct. 24, 2017		
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017		
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 09, 2016	Dec. 08, 2017		
Preamplifier	EMC	EMC02325	980187	Sep. 04, 2017	Sep. 03, 2018		
Preamplifier	Agilent	83017A	MY53270014	Aug. 21, 2017	Aug. 20, 2018		
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018		
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 04, 2017	Feb. 03, 2018		
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 04, 2017	Feb. 03, 2018		
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 04, 2017	Feb. 03, 2018		
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Feb. 04, 2017	Feb. 03, 2018		
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Feb. 04, 2017	Feb. 03, 2018		
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104	Feb. 04, 2017	Feb. 03, 2018		
Measurement Software	AUDIX	e3	6.120210g	NA	NA		

Test Item	RF Conducted	RF Conducted					
Test Site	(TH01-WS)	TH01-WS)					
Tested Date	Sep. 26, 2017	Sep. 26, 2017					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	R&S	FSV40	101063	Mar. 15, 2017	Mar. 14, 2018		
Power Meter	Anritsu	ML2495A	1241002	Oct. 06, 2016	Oct. 05, 2017		
Power Sensor	Anritsu	MA2411B	1207366	Oct. 06, 2016	Oct. 05, 2017		
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 28, 2016	Oct. 27, 2017		
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA		
Note: Calibration Inte	rval of instruments liste	d above is one year.		•			

Report No.: FR782803CO Page: 7 of 17



1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v04

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04

FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty					
Parameters	Uncertainty				
Radiated emission ≤ 1GHz	±3.66 dB				
Radiated emission > 1GHz	±5.37 dB				

Report No.: FR782803CO Page: 8 of 17



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH03-WS	24-25°C / 65-66%	Aska Huang Brad Wu
RF Conducted	TH01-WS	23°C / 62%	Felix Sung

➤ FCC Designation No.: TW0009
➤ FCC site registration No.: 207696
➤ IC site registration No.: 10807C-1

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Channel	Data Rate	Test Configuration		
Radiated Emissions	2.40.44a . 50.44a	CH6 + CH149	6Mbps + 6Mbps			
Conducted Emissions	2.4G 11g + 5G 11a					
NOTE: The selected channel is the maximum power channel of Wi-Fi mode.						

Report No.: FR782803CO Page: 9 of 17



3 Transmitter Test Results

3.1 Unwanted Emissions into Restricted Frequency Bands

3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit								
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)					
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300					
0.490~1.705	24000/F(kHz)	33.8 - 23	30					
1.705~30.0	30	29	30					
30~88	100	40	3					
88~216	150	43.5	3					
216~960	200	46	3					
Above 960	500	54	3					

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:**

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR782803CO Page: 10 of 17




3.1.3 Test Setup



Report No.: FR782803CO Page: 11 of 17



3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR782803CO Page: 12 of 17



Modulation		2.40	2.4G 11g + 5G 11a			T	est Chann	CH6 + CH149		
Polarization Vertical						•				
	Loyal (d	IDuV/m)								
!	00 Level (d	Du V/III)								
	80									
1	70									
	60									
									FCC CLAS	S-B
!	50							5		
	40		_				3	4 j	6	
									Ī	
;	30									
	20									
	10									
	030 10	0. 20	0. 30	0. 40	0. 50	0 60	00. 700.	800.	900.	1000
	30 10	0. 20	0. 30	U. 4U		บ.		800.	900.	1000
		Frea. E	mission	Limit	Margin	SA	Factor	Remark	ANT	Turn
			level		Ü	readin	g		High	Table
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	-	46 18	26.32	40 00	-13 68	34.64	-8.32	QP QP	100	9
2		562.53		46.00		44.08		Peak		
3			41.31			41.18		Peak		
4		749.74	37.83	46.00	-8.17	36.25		Peak		
5		812.79	42.80	46.00	-3.20	40.47	2.33	QP	100	145
6		874.87	37.00	46.00	-9.00	33.76	3.24	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR782803CO Page: 13 of 17



3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803CO Page: 14 of 17



Modulation	2.4G 11g + 5G 11a	Test Channel	CH6 + CH149	
Polarization	Vertical			



	Freq.	Emission level		Margin	SA reading		Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	3308.00	38.70	54.00	-15.30	37.97	0.73	Average	100	135
2	3308.00	51.70	74.00	-22.30	50.97	0.73	Peak	100	135
3	8182.00	39.02	54.00	-14.98	28.73	10.29	Average	100	165
4	8182.00	51.62	74.00	-22.38	41.33	10.29	Peak	100	165

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR782803CO Page: 15 of 17



3.1.6 Conducted Emissions (30MHz~40GHz)





Report No.: FR782803CO Page: 16 of 17



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan

City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

___END___

Report No.: FR782803CO Page: 17 of 17