

# **FCC Co-Location Test Report**

FCC ID : UIDSBR-AC1200P

Equipment : AC1200 Wi-Fi Router with RipCurrent<sup>™</sup>

Technology

Model No. : SBR-AC1200P

Brand Name : ARRIS

Applicant : ARRIS Group, Inc.

Address : 3871 Lakefield Drive, Suite 300, Suwanee,

Georgia 30024, United States

Standard : 47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

Received Date : Sep. 22, 2015

Tested Date : Oct. 12 ~ Oct. 20, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

ilac-mra



Page: 1 of 15

Report No.: FR592203CO



## **Table of Contents**

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	The Equipment List	6
1.3	Test Standards	6
1.4	Measurement Uncertainty	7
2	TEST CONFIGURATION	8
2.1	Testing Condition	8
2.2	The Worst Test Modes and Channel Details	8
3	TRANSMITTER TEST RESULTS	9
3.1	Unwanted Emissions into Restricted Frequency Bands	g
4	TEST LABORATORY INFORMATION	15



## **Release Record**

Report No.	Version	Description	Issued Date
FR592203CO	Rev. 01	Initial issue	Nov. 20, 2015

Report No.: FR592203CO Page: 3 of 15



## **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.247(d)			
15.407(b)	Radiated Emissions	[dBuV/m at 3m]: 45.52MHz 38.99 (Margin -1.01dB) - QP	Pass
15.209		(waigii: 1101a2) Qi	

Report No.: FR592203CO Page: 4 of 15



## 1 General Description

### 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

Operating Frequency  802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5745 ~ 5825 MHz	
	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM/256QAM)

#### 1.1.2 Antenna Details

Ant No	Ant. No. Model		Type Connector		Operating Frequency (MHz) / Gain (dBi)		
Ant. No.	Wiodei	Туре	Connector	2400~2483.5	5150~5250	5725~5850	
1	617210JN	Dipole	I-pex	1.83			
2	617210JM	Dipole	I-pex	2.02			
3	617210JP	PIFA	I-pex		2.87	3.60	
4	617210K2	PIFA	I-pex		3.23	3.82	

## 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Lype	100-240Vac, 50-60Hz, 1.0A Power line: 1.5m non-shielded without core
	1 Ower line. 1.5m non-shielded without core

### 1.1.4 Accessories

	Accessories				
No.	Equipment	Description			
1	RJ45 cable	1m non-shielded without core			

Report No.: FR592203CO Page: 5 of 15



## 1.2 The Equipment List

Test Item	Radiated Emission be	Radiated Emission below 1GHz test						
Test Site	966 chamber 2 / (03CH02-WS)							
Tested Date	Oct. 20, 2015							
Instrument	Manufacturer	Manufacturer Model No. Serial No. Calibration Date Calibration Until						
Receiver	R&S	ESR3	101657	Jan. 15, 2015	Jan. 14, 2016			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Oct. 05, 2015	Oct. 04, 2016			
Preamplifier	Burgeon	BPA-530	100218	Nov. 10, 2014	Nov. 09, 2015			
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 16, 2014	Dec. 15, 2015			
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-004	Dec. 16, 2014	Dec. 15, 2015			
Measurement Software AUDIX e3 6.120210g NA NA								
Note: Calibration Interval of instruments listed above is one year.								

Test Item	Radiated Emission ab	Radiated Emission above 1GHz test					
Test Site	966 chamber 2 / (03CH02-WS)						
Tested Date	Oct. 12, 2015						
Instrument	Manufacturer	Manufacturer Model No. Serial No. Calibration Date Calibration Until					
Spectrum Analyzer	R&S	FSV40	101499	Dec. 31, 2014	Dec. 30, 2015		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Oct. 14, 2014	Oct. 13, 2015		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 10, 2014	Nov. 09, 2015		
Preamplifier	Agilent	83017A	MY39501309	Sep. 22, 2015	Sep. 21, 2016		
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 16, 2014	Dec. 15, 2015		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 16, 2014	Dec. 15, 2015		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 16, 2014	Dec. 15, 2015		
Measurement Software	AUDIX	e3	6.120210g	NA	NA		
Note: Calibration Inter	Note: Calibration Interval of instruments listed above is one year.						

### 1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r03

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01

FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Report No.: FR592203CO Page: 6 of 15



## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty			
Parameters	Uncertainty		
Radiated emission ≤ 1GHz	±3.62 dB		
Radiated emission > 1GHz	±5.60 dB		

Report No.: FR592203CO Page: 7 of 15



## 2 Test Configuration

## 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH02-WS	22-23°C / 63-66%	Anderson Hung Aska Huang

FCC site registration No.: 657002IC site registration No.: 10807A-2

### 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Channel	Data Rate		
Radiated Emissions	2.4G 11n HT20 + 5G 11ac VHT40	CH6 + CH46	MCS 0 + MCS 0		
NOTE: The selected channel is the maximum power channel of each Wi-Fi portion					

Report No.: FR592203CO Page: 8 of 15



#### 3 Transmitter Test Results

### 3.1 Unwanted Emissions into Restricted Frequency Bands

#### 3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:** 

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.1.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR592203CO Page: 9 of 15




### 3.1.3 Test Setup



Report No.: FR592203CO Page: 10 of 15



### 3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR592203CO Page: 11 of 15





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR592203CO Page: 12 of 15



### 3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR592203CO Page: 13 of 15

<sup>\*</sup>Factor includes antenna factor, cable loss and amplifier gain





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR592203CO Page: 14 of 15



## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C. Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FR592203CO Page: 15 of 15