

FCC PART 15.239

EMI MEASUREMENT AND TEST REPORT

For

SHENZHEN NETSHARP TECHNOLOGY CO., LTD

Suite 5A2 Langqingxinzhou Building, Binhe Road, Futian District, Shenzhen, Guangdong, China.

FCC ID: UIENSFMSB0410

August 25, 2006

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: Wireless FM Transmitter
Test Engineer: Deny Xiong	<i>Deny Xiong</i>
Report No.: RSZ06080801	
Test Date: August 19-25, 2006	
Reviewed By: EMC Manager: Boni Baniqued	<i>Boni Baniqued</i>
Prepared By:	Bay Area Compliance Lab Corp. (ShenZhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China Tel: +86-755-33320018 Fax: +86-755-33320008

Note: The test report is specially limited to the above company and this particular sample only. It may not be duplicated without prior written consent of Bay Area Compliance Lab Corp. (ShenZhen). This report **must not** be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
EXTERNAL I/O CABLE.....	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
SPECIAL ACCESSORIES	5
EQUIPMENT MODIFICATIONS	5
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
§15.203 - ANTENNA REQUIREMENT.....	8
STANDARD APPLICABLE	8
§15.209 AND §15.239- RADIATED EMISSION	9
MEASUREMENT UNCERTAINTY	9
EUT SETUP	9
EMI TEST RECEIVER SETUP.....	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST PROCEDURE	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST RESULTS SUMMARY	10
TEST DATA	11
PLOT(S) OF TEST DATA	11
§15.239 – OUT OF BAND EMISSION.....	16
MEASUREMENT UNCERTAINTY	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA	16

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The SHENZHEN NETSHARP TECHNOLOGY CO., LTD's product, model: *Songbird* or the "EUT" as referred to in this report is a *Wireless FM Transmitter* which measures approximately 8.5 cm L x 4.3 cm W x 2.2 cm H, rated input voltage: DC 3V battery.

** The test data gathered are from production sample, serial number: 0608012 provided by the manufacturer, we received EUT on 2006-8-8.*

Objective

This Type approval report is prepared on behalf of SHENZHEN NETSHARP TECHNOLOGY CO., LTD in accordance with FCC Part 15, Subpart C, and section 15.209, 15.35, 15.205, and 15.239 rules.

Related Submittal(s)/Grant(s)

No Related Submittals

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 - 2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (ShenZhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Lab Corp. (ShenZhen) to collect radiated and conducted emission measurement data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China.

Test site at Bay Area Compliance Lab Corp. (ShenZhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Lab Corp. (ShenZhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0). The current scope of accreditations can be found at <http://ts.nist.gov/ts/htdocs/210/214/scopes/2007070.htm>

External I/O Cable

Cable Description	Length (M)	From/Port	To
Audio Input Cable	0.195	Audio Generator	FM Transmitter

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

N/A.


Special Accessories

N/A.

Equipment Modifications


Bay Area Compliance Lab Corp. (ShenZhen) has not done any modification on the EUT.

Configuration of Test Setup



EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

RULES	DESCRIPTION OF TEST	RESULT
§15.205	Restricted Band of operation	Compliant
§15.209/§15.239	Radiated Emission	Compliant
§15.239	Out of Band Emission	Compliant
§15.203	Antenna Requirement	Compliant

§15.203 - ANTENNA REQUIREMENT

Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The antenna is build on board; fulfill the requirement of this section.

Test Result: Pass


§15.209 and §15.239- RADIATED EMISSION

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Lab Corp. (ShenZhen) is ± 4.0 dB.

EUT Setup



The radiated emission tests were performed in the 3 meters chamber A test site, using the setup accordance with the ANSI C63.4 - 2003. The specification used was the FCC Part 15.209 and FCC Part 15.239.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 1000 MHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>VBW</i>
30 – 1000 MHz	100 kHz	300 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	DE25330 or 830245/006	2006-3-20	2007-3-19
HP	Amplifier	HP8447E	1937A01046	2006-8-17	2007-8-17
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2006-4-28	2007-4-28

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of –7.0 dB means the emission is 7.0 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 and 15.239, with the worst margin reading of:

-14.4 dB at 106.70 MHz in the Horizontal polarization, Low Channel.
-14.76 dB at 107.90 MHz in the Horizontal polarization, High Channel.

Test Data**Environmental Conditions**

Temperature:	25 ° C
Relative Humidity:	53%
ATM Pressure:	1002mbar


The testing was performed by Deny Xiong on 2006-8-19.

Test Mode: Transmitting

Frequency	Meter Reading	Detector	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier Gain	Corr. Ampl.	FCC PART 15.239 & FCC PART 15.209		
MHz	dBuV/m	PK/QP/AV	Degree	Meter	H / V	dB	dB	dB	dBuV/m	Limit dBuV/m	Margin dB	
Low Channel												
106.70	50.1	AV	289	1.0	H	11.0	1.0	28.5	33.60	48.00	-14.40	Fundamental
33.79	32.29	QP	60	1.2	V	16.9	0.6	28.7	21.09	40.00	-18.91	Spurious
869.13	29.34	QP	45	1.2	H	22.2	3.4	28.1	26.84	46.00	-19.16	Spurious
642.86	29.18	QP	60	1.0	H	19.9	2.9	28.6	23.38	46.00	-22.62	Spurious
106.70	41.8	AV	45	1.0	V	11.0	1.0	28.5	25.30	48.00	-22.70	Fundamental
428.02	31.88	QP	289	1.0	H	16.8	2.1	28.3	22.48	46.00	-23.52	Spurious
578.66	29.18	QP	35	3.8	V	19.2	2.6	28.6	22.38	46.00	-23.62	Spurious
197.89	33.26	QP	35	3.8	V	12.0	1.3	28.0	18.56	43.50	-24.94	Spurious
106.70	51.84	PK	289	1.0	H	11.0	1.0	28.5	35.34	68.00	-32.66	Fundamental
106.70	45.17	PK	45	1.0	V	11.0	1.0	28.5	28.67	68.00	-39.33	Fundamental
High Channel												
107.90	49.74	AV	289	1.0	H	11.00	1.00	28.5	33.24	48.00	-14.76	Fundamental
30.63	29.23	QP	289	1.0	H	20.40	0.37	28.7	21.30	40.00	-18.70	Spurious
30.63	28.43	QP	35	3.8	V	20.40	0.37	28.7	20.50	40.00	-19.50	Spurious
140.34	32.93	QP	60	1.2	V	13.80	1.87	28.4	20.20	43.50	-23.30	Spurious
107.90	37.88	AV	45	1.0	V	11.00	1.00	28.5	21.38	48.00	-26.62	Fundamental
372.00	27.54	QP	180	1.2	H	15.50	3.06	28.0	18.10	46.00	-27.90	Spurious
138.38	27.13	QP	45	1.2	H	14.20	1.87	28.4	14.80	43.50	-28.70	Spurious
51.12	30.84	QP	35	3.8	V	8.50	0.36	28.7	11.00	40.00	-29.00	Spurious
158.11	27.58	QP	90	1.2	V	12.80	1.92	27.8	14.50	43.50	-29.00	Spurious
197.89	27.98	QP	60	1.0	H	12.00	1.92	27.8	14.10	43.50	-29.40	Spurious
107.90	52.16	PK	289	1.0	H	11.00	1.00	28.5	35.66	68.00	-32.34	Fundamental
107.90	41.47	PK	45	1.0	V	11.00	1.00	28.5	24.97	68.00	-43.03	Fundamental


Plot(s) of Test Data

Plot(s) of Test Data is presented hereinafter as reference.




Transmit low frequency(Horizontal)

Date: 19.AUG.2006 11:57:38




Transmit low frequency(Vertical)

Date: 19.AUG.2006 13:20:52



Transmit High frequency(Horizontal)

Date: 19.AUG.2006 14:26:59



Transmit High frequency(Vertical)

Date: 19.AUG.2006 14:32:49

§15.239 – OUT OF BAND EMISSION

Measurement Uncertainty

Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88–108 MHz.

The field strength of any emissions radiated on any frequency outside of the specified 200 kHz band shall not exceed the general radiated emission limits in §15.209.

Test Procedure

With the EUT's antenna attached, the EUT's radiated emission power was received by the test antenna which was connected to the spectrum analyzer with the START and STOP frequencies set to the EUT's operation band.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	DE25330 or 830245/006	2006-3-20	2007-3-19
HP	Amplifier	HP8447E	1937A01046	2006-8-17	2007-8-17
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2006-4-28	2007-4-28

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Data


Environmental Conditions

Temperature:	27 ° C
Relative Humidity:	56%
ATM Pressure:	1002mbar

The testing was performed by Deny Xiong on 2006-8-25.


The result has been complied with the 15.239, see the following plot:

Frequency MHz	Emission dB μ V/m	Limit dB μ V/m
107.80	11.09	43.5
108.00	6.97	43.5
106.60	7.73	43.5
106.80	7.58	43.5

1 PK
VIEW

OUT OF BAND EMISSION

Date: 25.AUG.2006 14:43:06



OUT OF BAND EMISSION

Date: 25.AUG.2006 14:48:13