



NVLAP LAB CODE 200707-0



## FCC PART 15.249

### MEASUREMENT AND TEST REPORT

For

**Chuang feng Electronics Co., Ltd.**

HuaLi Industrial Zone, SongBoTang, ChangPing Town,  
DongGuan City, Guangdong, China

**FCC ID: UK5KM1036W**

|  |  |
|--|--|
| <b>Report Type:</b><br>Original Report   | <b>Product Type:</b><br>Wireless Optical Mouse |
| <b>Test Engineer:</b>  | Felix Li                                       |
| <b>Report Number:</b>  | RSZ10061081-A                                  |
| <b>Report Date:</b>  | 2010-07-02                                     |
| <b>Reviewed By:</b>  | Merry Zhao                                     |
| <b>Prepared By:</b>  | EMC Engineer                                   |
| Bay Area Compliance Laboratories Corp. (Shenzhen)<br>6/F, the 3rd Phase of WanLi Industrial Building,<br>ShiHua Road, FuTian Free Trade Zone<br>Shenzhen, Guangdong, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008 |  |

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, NIST, or any agency of the Federal Government.

\* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "\*" (Rev.2)

## **TABLE OF CONTENTS**

|  |           |
|--|-----------|
| <b>GENERAL INFORMATION.....</b>                                      | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....             | 3         |
| OBJECTIVE .....  | 3         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                   | 3         |
| TEST METHODOLOGY .....   | 3         |
| TEST FACILITY .....  | 3         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                | <b>5</b>  |
| JUSTIFICATION .....  | 5         |
| EQUIPMENT MODIFICATIONS .....  | 5         |
| BLOCK DIAGRAM OF TEST SETUP .....                                    | 5         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                 | <b>6</b>  |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                        | <b>7</b>  |
| APPLICABLE STANDARD .....  | 7         |
| ANTENNA CONNECTOR CONSTRUCTION .....                                 | 7         |
| <b>FCC §15.205, §15.209 &amp; §15.249 - RADIATED EMISSIONS .....</b> | <b>8</b>  |
| APPLICABLE STANDARD .....  | 8         |
| MEASUREMENT UNCERTAINTY.....   | 8         |
| TEST EQUIPMENT SETUP .....   | 8         |
| EUT SETUP .....  | 9         |
| TEST EQUIPMENT LIST AND DETAILS.....                                 | 9         |
| TEST PROCEDURE .....   | 10        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                       | 10        |
| TEST RESULTS SUMMARY .....   | 10        |
| TEST DATA .....  | 11        |
| <b>FCC §15.249(D) – OUT OF BAND EMISSIONS.....</b>                   | <b>13</b> |
| APPLICABLE STANDARD .....  | 13        |
| TEST PROCEDURE .....   | 13        |
| MEASUREMENT UNCERTAINTY.....   | 13        |
| TEST EQUIPMENT SETUP .....   | 13        |
| TEST EQUIPMENT LIST AND DETAILS.....                                 | 13        |
| TEST DATA .....  | 14        |
| <b>FCC §15.215(C) – 20 DB BANDWIDTH.....</b>                         | <b>16</b> |
| STANDARD APPLICABLE .....  | 16        |
| TEST EQUIPMENT LIST AND DETAILS.....                                 | 16        |
| TEST PROCEDURE .....   | 16        |
| TEST DATA .....  | 16        |

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Chuang feng Electronics Co., Ltd.* 's product, model *KM-1036W* (FCC ID: *UK5KM1036W*), or the "EUT" as referred to in this report is a *Wireless Optical Mouse* which measures approximately: 10.0 cm L x 6.0 cm W x 3.0 cm H, rated input voltage: DC 1.5V AAA battery.

*\* All measurement and test data in this report was gathered from production sample serial number: 1006005 (Assigned by BACL, Shenzhen). The EUT was received on 2010-06-10.*

### Objective

This Type approval report is prepared on behalf of *Chuang feng Electronics Co., Ltd.* in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

### Related Submittal(s)/Grant(s)

Part of the system Submitted with the FCC ID: UK5NANO.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION

---


### Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

### Equipment Modifications

No modifications were made to the unit tested.

### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| FCC Rules  | Description of Test   | Result    |
|--|-----------------------|-----------|
| §15.203  | Antenna Requirement   | Compliant |
| §15.207(a)   | Conduction Emissions  | N/A       |
| §15.205(a), §15.209(a),<br>15.249(a), §15.249(c), §15.35 | Radiated Emissions    | Compliant |
| §15.249(d)   | Out of Band Emissions | Compliant |
| §15.215(c)   | 20 dB Bandwidth       | Compliant |

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

For intentional device, according to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

### **Antenna Connector Construction**

The EUT has a printed antenna on PCB, which in accordance to FCC §15.203, is considered sufficient to comply with the provisions of this section.

**Result:** Compliant.

Please refer to the EUT photos.

## **FCC §15.205, §15.209 & §15.249 - RADIATED EMISSIONS**

### **Applicable Standard**

As per FCC §15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| <b>Fundamental frequency</b> | <b>Field strength of fundamental (millivolts/meter)</b> | <b>Field strength of harmonics (microvolts/meter)</b> |
|------------------------------|---|---|
| 902–928 MHz                  | 50  | 500   |
| 2400–2483.5 MHz              | 50  | 500   |
| 5725–5875 MHz                | 50  | 500   |
| 24.0–24.25 GHz               | 250   | 2500  |

As per FCC §15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### **Measurement Uncertainty**

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is  $\pm 4.0$  dB.

### **Test Equipment Setup**

The spectrum analyzer or receiver is set as:

Below 1000 MHz:


$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

$$\begin{aligned} \text{Peak: RBW} &= 1\text{MHz} / \text{VBW} = 1\text{MHz} / \text{Sweep} = \text{Auto} \\ \text{Average: RBW} &= 1\text{MHz} / \text{VBW} = 10\text{Hz} / \text{Sweep} = \text{Auto} \end{aligned}$$



## EUT Setup



The radiated emission and out of band emission tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209 and FCC 15.249 limits.

## Test Equipment List and Details

| Manufacturer    | Description       | Model    | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|----------|---------------|------------------|----------------------|
| HP              | Amplifier         | 8447E    | 1937A01046    | 2009-08-02       | 2010-08-01           |
| Rohde & Schwarz | EMI Test Receiver | ESCI     | 100224        | 2009-11-24       | 2010-11-23           |
| Sunol Sciences  | Broadband Antenna | JB1      | A040904-1     | 2010-03-11       | 2011-03-11           |
| HP              | Amplifier         | 2VA-213+ | T-E27H        | 2010-03-08       | 2011-03-07           |
| Sunol Sciences  | Horn Antenna      | DRH-118  | A052604       | 2010-05-05       | 2011-05-04           |
| Rohde & Schwarz | Spectrum Analyzer | FSEM30   | 849720/019    | 2009-07-08       | 2010-07-07           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

For the radiated emissions test, the EUT, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 mete, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.249, with the worst margin reading of:

### Below 1 GHz:

**19.8 dB at 30.400022 MHz in the Horizontal polarization**

### Above 1 GHz:

**6.80 dB at 4810 MHz in the Horizontal polarization (Low Channel)**  
**5.25 dB at 2439 MHz in the Horizontal polarization (Middle Channel)**  
**8.34 dB at 4952 MHz in the Horizontal polarization (High Channel)**


## Test Data

### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 56 %      |
| ATM Pressure:      | 100.2 kPa |

The testing was performed by Felix Li on 2010-06-29.

### Below 1GHz:



| Frequency (MHz) | Corrected Amplitude (dBμV/m) | Antenna Height (cm) | Antenna Polarity (H/V) | Turntable Position (deg) | Correction Factor (dB) | Limit (dBμV/m) | Margin (dB) |
|-----------------|------------------------------|---------------------|------------------------|--------------------------|------------------------|----------------|-------------|
| 30.400022       | 20.2                         | 346.0               | H                      | 20.0                     | -15.2                  | 40.0           | 19.8        |
| 934.275750      | 25.5                         | 198.0               | H                      | 0.0                      | -0.8                   | 46.0           | 20.5        |
| 811.084500      | 24.1                         | 342.0               | H                      | 36.0                     | -1.4                   | 46.0           | 21.9        |
| 35.976000       | 14.8                         | 200.0               | H                      | 26.0                     | -13.4                  | 40.0           | 25.2        |
| 698.577250      | 21.2                         | 400.0               | H                      | 135.0                    | -4.7                   | 46.0           | 24.8        |
| 121.737000      | 11.9                         | 302.0               | H                      | 14.0                     | -12.7                  | 40.0           | 28.1        |

**Above 1 GHz:**

| Freq.<br>(MHz)            | S.A.<br>Reading<br>(dBμV/m) | Detector<br>(PK/AV) | Turntable<br>Direction<br>Degree | Test Antenna  |                |                | Cable<br>Loss<br>(dB) | Amp.<br>Gain<br>(dB) | Cord.<br>Amp.<br>(dBμV/m) | FCC 15.249 & 15.209 |                |          |
|---------------------------|-----------------------------|---------------------|----------------------------------|---------------|----------------|----------------|-----------------------|----------------------|---------------------------|---------------------|----------------|----------|
|                           |                             |                     |                                  | Height<br>(m) | Polar<br>(H/V) | Factor<br>(dB) |                       |                      |                           | Limit<br>(dBμV/m)   | Margin<br>(dB) | Comment  |
| Low Channel (2405 MHz)    |                             |                     |                                  |               |                |                |                       |                      |                           |                     |                |          |
| 4810                      | 34.11                       | AV                  | 358                              | 1.47          | H              | 36.3           | 4.3                   | 27.51                | 47.2                      | 54                  | 6.80           | harmonic |
| 4810                      | 34.12                       | AV                  | 61                               | 1.32          | V              | 35             | 4.3                   | 27.51                | 45.91                     | 54                  | 8.09           | harmonic |
| 2405                      | 78.25                       | AV                  | 360                              | 1.50          | H              | 30.9           | 3.03                  | 27.54                | 84.64                     | 94                  | 9.36           | Fund.    |
| 2405                      | 75.78                       | AV                  | 79                               | 1.24          | V              | 30.3           | 3.03                  | 27.54                | 81.57                     | 94                  | 12.43          | Fund.    |
| 2312                      | 27.83                       | AV                  | 328                              | 1.12          | H              | 30.9           | 3.03                  | 27.54                | 34.22                     | 54                  | 19.78          | spurious |
| 2312                      | 27.98                       | AV                  | 215                              | 1.17          | V              | 30.3           | 3.03                  | 27.54                | 33.77                     | 54                  | 20.23          | spurious |
| 4810                      | 36.60                       | PK                  | 358                              | 1.47          | H              | 36.3           | 4.3                   | 27.51                | 49.69                     | 74                  | 24.31          | harmonic |
| 4810                      | 36.31                       | PK                  | 61                               | 1.32          | V              | 35             | 4.3                   | 27.51                | 48.1                      | 74                  | 25.90          | harmonic |
| 2405                      | 78.91                       | PK                  | 360                              | 1.50          | H              | 30.9           | 3.03                  | 27.54                | 85.3                      | 114                 | 28.70          | Fund.    |
| 2312                      | 36.28                       | PK                  | 328                              | 1.12          | H              | 30.9           | 3.03                  | 27.54                | 42.67                     | 74                  | 31.33          | spurious |
| 2312                      | 36.30                       | PK                  | 215                              | 1.17          | V              | 30.3           | 3.03                  | 27.54                | 42.09                     | 74                  | 31.91          | spurious |
| 2405                      | 76.12                       | PK                  | 79                               | 1.24          | V              | 30.3           | 3.03                  | 27.54                | 81.91                     | 114                 | 32.09          | Fund.    |
| Middle Channel (2439 MHz) |                             |                     |                                  |               |                |                |                       |                      |                           |                     |                |          |
| 2439                      | 82.36                       | AV                  | 355                              | 1.46          | H              | 30.9           | 3.03                  | 27.54                | 88.75                     | 94                  | 5.25           | Fund.    |
| 4878                      | 31.52                       | AV                  | 355                              | 1.37          | H              | 36.3           | 4.3                   | 27.51                | 44.61                     | 54                  | 9.39           | harmonic |
| 2439                      | 78.14                       | AV                  | 168                              | 1.34          | V              | 30.3           | 3.03                  | 27.54                | 83.93                     | 94                  | 10.07          | Fund.    |
| 4878                      | 30.98                       | AV                  | 346                              | 1.26          | V              | 35             | 4.3                   | 27.51                | 42.77                     | 54                  | 11.23          | harmonic |
| 4878                      | 37.81                       | PK                  | 355                              | 1.37          | H              | 36.3           | 4.3                   | 27.51                | 50.9                      | 74                  | 23.10          | harmonic |
| 2439                      | 83.18                       | PK                  | 355                              | 1.46          | H              | 30.9           | 3.03                  | 27.54                | 89.57                     | 114                 | 24.43          | Fund.    |
| 4878                      | 37.35                       | PK                  | 346                              | 1.26          | V              | 35             | 4.3                   | 27.51                | 49.14                     | 74                  | 24.86          | harmonic |
| 2439                      | 79.77                       | PK                  | 168                              | 1.34          | V              | 30.3           | 3.03                  | 27.54                | 85.56                     | 114                 | 28.44          | Fund.    |
| High Channel (2476 MHz)   |                             |                     |                                  |               |                |                |                       |                      |                           |                     |                |          |
| 4952                      | 32.57                       | AV                  | 159                              | 1.64          | H              | 36.3           | 4.3                   | 27.51                | 45.66                     | 54                  | 8.34           | harmonic |
| 4952                      | 32.11                       | AV                  | 132                              | 1.93          | V              | 35             | 4.3                   | 27.51                | 43.9                      | 54                  | 10.10          | harmonic |
| 2476                      | 73.39                       | AV                  | 10                               | 1.51          | H              | 30.9           | 3.03                  | 27.54                | 79.78                     | 94                  | 14.22          | Fund.    |
| 2476                      | 70.75                       | AV                  | 191                              | 1.98          | V              | 30.3           | 3.03                  | 27.54                | 76.54                     | 94                  | 17.46          | Fund.    |
| 2925.6                    | 24.50                       | AV                  | 74                               | 2.0           | H              | 31.2           | 3.8                   | 27.54                | 31.96                     | 54                  | 22.04          | spurious |
| 2925.6                    | 23.67                       | AV                  | 225                              | 1.9           | V              | 30.9           | 3.8                   | 27.54                | 30.83                     | 54                  | 23.17          | spurious |
| 4952                      | 36.60                       | PK                  | 159                              | 1.64          | H              | 36.3           | 4.3                   | 27.51                | 49.69                     | 74                  | 24.31          | harmonic |
| 4952                      | 36.42                       | PK                  | 132                              | 1.93          | V              | 35             | 4.3                   | 27.51                | 48.21                     | 74                  | 25.79          | harmonic |
| 2925.6                    | 35.27                       | PK                  | 74                               | 2.0           | H              | 31.2           | 3.8                   | 27.54                | 42.73                     | 74                  | 31.27          | spurious |
| 2925.6                    | 34.89                       | PK                  | 225                              | 1.9           | V              | 30.9           | 3.8                   | 27.54                | 42.05                     | 74                  | 31.95          | spurious |
| 2476                      | 74.27                       | PK                  | 10                               | 1.51          | H              | 30.9           | 3.03                  | 27.54                | 80.66                     | 114                 | 33.34          | Fund.    |
| 2476                      | 71.27                       | PK                  | 191                              | 1.98          | V              | 30.3           | 3.03                  | 27.54                | 77.06                     | 114                 | 36.94          | Fund.    |

## FCC §15.249(d) – OUT OF BAND EMISSIONS

### Applicable Standard

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### Test Procedure

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 mete, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission at the band edge. The receiving antenna should be changed the polarization both of horizontal and vertical.

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is  $\pm 4.0$  dB.

### Test Equipment Setup

The spectrum analyzer or receiver is set as:

Above 1000 MHz:

Peak: RBW = 1MHz / VBW = 3MHz / Sweep = Auto  
Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

### Test Equipment List and Details

| Manufacturer    | Description       | Model    | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|----------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI     | 100224        | 2009-11-24       | 2010-11-23           |
| HP              | Amplifier         | 2VA-213+ | T-E27H        | 2010-03-08       | 2011-03-07           |
| Sunol Sciences  | Horn Antenna      | DRH-118  | A052604       | 2010-05-05       | 2011-05-04           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) Corp. attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25 °C     |
| <b>Relative Humidity:</b> | 56 %      |
| <b>ATM Pressure:</b>      | 100.2 kPa |

*\*The testing was performed by Felix Li on 2010-06-28 and 2010-06-29.*


**Test Result:** Compliant

Please refer to the following table and plots.

*Test Mode: Transmitting (worse case)*


| Freq.<br>(MHz)    | S.A.<br>Reading<br>(dBμV/m) | Detector<br>(PK/AV) | Turntable<br>Direction<br>Degree | Test Antenna  |                |              | Cable<br>Loss<br>(dB) | Pre-<br>Amp.<br>Gain<br>(dB) | Cord.<br>Amp.<br>(dBμV/m) | FCC 15.209        |                |
|-------------------|-----------------------------|---------------------|----------------------------------|---------------|----------------|--------------|-----------------------|------------------------------|---------------------------|-------------------|----------------|
|                   |                             |                     |                                  | Height<br>(m) | Polar<br>(H/V) | Loss<br>(dB) |                       |                              |                           | Limit<br>(dBμV/m) | Margin<br>(dB) |
| 2390MHz-2400MHz   |                             |                     |                                  |               |                |              |                       |                              |                           |                   |                |
| 2398.8            | 17.84                       | AV                  | 125                              | 1.40          | H              | 33.9         | 3.18                  | 26.85                        | 28.07                     | 54                | 28.07          |
| 2398.8            | 26.43                       | PK                  | 125                              | 1.40          | H              | 33.9         | 3.18                  | 26.85                        | 36.66                     | 74                | 36.66          |
| 2483.5MHz-2500MHz |                             |                     |                                  |               |                |              |                       |                              |                           |                   |                |
| 2485.5            | 19.86                       | AV                  | 358                              | 1.10          | H              | 33.9         | 3.03                  | 26.83                        | 29.96                     | 54                | 29.96          |
| 2485.5            | 27.54                       | PK                  | 358                              | 1.10          | H              | 33.9         | 3.03                  | 26.83                        | 37.64                     | 74                | 37.64          |

## Left Side



Date: 28.JUN.2010 16:45:14

## Right Side



Date: 29.JUN.2010 08:35:55

## FCC §15.215(c) – 20 dB BANDWIDTH

### Standard Applicable

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### Test Equipment List and Details

| Manufacturer    | Description       | Model    | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|----------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI     | 100224        | 2009-11-24       | 2010-11-23           |
| HP              | Amplifier         | 2VA-213+ | T-E27H        | 2010-03-08       | 2011-03-07           |
| Sunol Sciences  | Horn Antenna      | DRH-118  | A052604       | 2010-05-05       | 2011-05-04           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that indicated 20dB bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Data

#### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25 °C     |
| <b>Relative Humidity:</b> | 56 %      |
| <b>ATM Pressure:</b>      | 100.2 kPa |

*The testing was performed by Felix Li on 2010-07-01.*


*Test Mode: Transmitting*

Pleas refer to the plot and tabular data sheet attached.




| Channel Frequency<br>(MHz) | 20 dB Bandwidth<br>(kHz) |
|----------------------------|--------------------------|
| 2405                       | 260                      |
| 2439                       | 316                      |
| 2476                       | 332                      |

### Low Channel




## Middle Channel



Date: 1.JUL.2010 11:53:20

## High Channel



Date: 1.JUL.2010 11:37:06

\*\*\*\*\* END OF REPORT \*\*\*\*\*