

Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6 \text{ MHz}$; $\sigma = 0.905 \text{ mho/m}$; $\epsilon_r = 40.3$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Cheek High CH4233/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.516 mW/g

Left Cheek High CH4233/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.2 V/m; Power Drift = -0.081 dB

Peak SAR (extrapolated) = 0.533 W/kg

SAR(1 g) = 0.456 mW/g; SAR(10 g) = 0.351 mW/g

Maximum value of SAR (measured) = 0.499 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.886$ mho/m; $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Tilted Low CH4132/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.374 mW/g

Left Tilted Low CH4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = -0.047 dB

Peak SAR (extrapolated) = 0.448 W/kg

SAR(1 g) = 0.374 mW/g; SAR(10 g) = 0.277 mW/g

Maximum value of SAR (measured) = 0.414 mW/g

Left Tilted Low CH4132/Zoom Scan (5x5x7)/Cube 1: Measurement grid:


dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = -0.047 dB

Peak SAR (extrapolated) = 0.425 W/kg

SAR(1 g) = 0.364 mW/g; SAR(10 g) = 0.266 mW/g

Maximum value of SAR (measured) = 0.408 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.895$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Tilted Middle CH4183/Area Scan (8x8x1): Measurement grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.451 mW/g

Left Tilted Middle CH4183/Zoom Scan (5x5x7)/Cube 0: Measurement

grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 22.8 V/m; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 0.497 W/kg

SAR(1 g) = 0.428 mW/g; SAR(10 g) = 0.318 mW/g

Maximum value of SAR (measured) = 0.481 mW/g

Left Tilted Middle CH4183/Zoom Scan (5x5x7)/Cube 1: Measurement


grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 22.8 V/m; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 0.538 W/kg

SAR(1 g) = 0.427 mW/g; SAR(10 g) = 0.291 mW/g

Maximum value of SAR (measured) = 0.496 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6 \text{ MHz}$; $\sigma = 0.905 \text{ mho/m}$; $\epsilon_r = 40.3$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Tilted High CH4233/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.484 mW/g


Left Tilted High CH4233/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 22.0 V/m; Power Drift = -0.054 dB

Peak SAR (extrapolated) = 0.570 W/kg

SAR(1 g) = 0.446 mW/g; SAR(10 g) = 0.329 mW/g

Maximum value of SAR (measured) = 0.551 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.907$ mho/m; $\epsilon_r = 42.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Cheek Low CH4132/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.423 mW/g

Right Cheek Low CH4132/Zoom Scan (5x5x7)/Cube 0: Measurement

grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.7 V/m; Power Drift = -0.063 dB

Peak SAR (extrapolated) = 0.457 W/kg

SAR(1 g) = 0.390 mW/g; SAR(10 g) = 0.300 mW/g

Maximum value of SAR (measured) = 0.438 mW/g

Right Cheek Low CH4132/Zoom Scan (5x5x7)/Cube 1: Measurement


grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.7 V/m; Power Drift = -0.063 dB

Peak SAR (extrapolated) = 0.410 W/kg

SAR(1 g) = 0.338 mW/g; SAR(10 g) = 0.232 mW/g

Maximum value of SAR (measured) = 0.382 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.917 \text{ mho/m}$; $\epsilon_r = 42.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Cheek Middle CH4183/Area Scan (8x8x1): Measurement grid:

$dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.501 mW/g

Right Cheek Middle CH4183/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.1 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 0.550 W/kg

SAR(1 g) = 0.455 mW/g; SAR(10 g) = 0.344 mW/g

Maximum value of SAR (measured) = 0.515 mW/g

Right Cheek Middle CH4183/Zoom Scan (5x5x7)/Cube 1:


Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.1 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 0.548 W/kg

SAR(1 g) = 0.418 mW/g; SAR(10 g) = 0.300 mW/g

Maximum value of SAR (measured) = 0.502 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6 \text{ MHz}$; $\sigma = 0.926 \text{ mho/m}$; $\epsilon_r = 41.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Cheek High CH4233/Area Scan (8x8x1): Measurement grid:

$dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.543 mW/g

Right Cheek High CH4233/Zoom Scan (5x5x7)/Cube 0: Measurement

grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.6 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 0.626 W/kg

SAR(1 g) = 0.500 mW/g; SAR(10 g) = 0.360 mW/g

Maximum value of SAR (measured) = 0.558 mW/g

Right Cheek High CH4233/Zoom Scan (5x5x7)/Cube 1: Measurement


grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.6 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 0.603 W/kg

SAR(1 g) = 0.499 mW/g; SAR(10 g) = 0.379 mW/g

Maximum value of SAR (measured) = 0.555 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.907$ mho/m; $\epsilon_r = 42.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Tilted Low CH4132/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.433 mW/g

Right Tilted Low CH4132/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.3 V/m; Power Drift = -0.073 dB

Peak SAR (extrapolated) = 0.508 W/kg

SAR(1 g) = 0.384 mW/g; SAR(10 g) = 0.267 mW/g

Maximum value of SAR (measured) = 0.466 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.917$ mho/m; $\epsilon_r = 42.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Tilted Middle CH4183/Area Scan (8x8x1): Measurement grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.528 mW/g

Right Tilted Middle CH4183/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 21.2 V/m; Power Drift = -0.060 dB

Peak SAR (extrapolated) = 0.634 W/kg

SAR(1 g) = 0.420 mW/g; SAR(10 g) = 0.281 mW/g

Maximum value of SAR (measured) = 0.536 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6 \text{ MHz}$; $\sigma = 0.926 \text{ mho/m}$; $\epsilon_r = 41.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.57, 10.57, 10.57);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Tilted High CH4233/Area Scan (8x8x1): Measurement grid:

$dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.567 mW/g

Right Tilted High CH4233/Zoom Scan (5x5x7)/Cube 0: Measurement

grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.4 V/m; Power Drift = -0.140 dB

Peak SAR (extrapolated) = 0.673 W/kg

SAR(1 g) = 0.485 mW/g; SAR(10 g) = 0.326 mW/g

Maximum value of SAR (measured) = 0.542 mW/g

Right Tilted High CH4233/Zoom Scan (5x5x7)/Cube 1: Measurement


grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.4 V/m; Power Drift = -0.140 dB

Peak SAR (extrapolated) = 0.564 W/kg

SAR(1 g) = 0.475 mW/g; SAR(10 g) = 0.353 mW/g

Maximum value of SAR (measured) = 0.534 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Cheek Low CH9262/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.05 mW/g

Left Cheek Low CH9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.6 V/m; Power Drift = -0.066 dB

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.940 mW/g; SAR(10 g) = 0.572 mW/g

Maximum value of SAR (measured) = 1.12 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Cheek Middle CH9400/Area Scan (8x8x1): Measurement grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.04 mW/g

Left Cheek Middle CH9400/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 23.7 V/m; Power Drift = -0.118 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.946 mW/g; SAR(10 g) = 0.596 mW/g

Maximum value of SAR (measured) = 1.16 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1907.6$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Cheek High CH9538/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.919 mW/g

Left Cheek High CH9538/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.6 V/m; Power Drift = -0.137 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.832 mW/g; SAR(10 g) = 0.511 mW/g

Maximum value of SAR (measured) = 1.03 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Tilted Low CH9262/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.827 mW/g

Left Tilted Low CH9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.4 V/m; Power Drift = -0.048 dB

Peak SAR (extrapolated) = 1.28 W/kg

SAR(1 g) = 0.864 mW/g; SAR(10 g) = 0.515 mW/g

Maximum value of SAR (measured) = 1.09 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Tilted Middle CH9400/Area Scan (8x8x1): Measurement grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.09 mW/g

Left Tilted Middle CH9400/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 26.5 V/m; Power Drift = -0.105 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 1.090 mW/g; SAR(10 g) = 0.643 mW/g

Maximum value of SAR (measured) = 1.32 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Left Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1907.6$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Left Tilted High CH9538/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.811 mW/g


Left Tilted High CH9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.5 V/m; Power Drift = -0.134 dB

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.801 mW/g; SAR(10 g) = 0.496 mW/g

Maximum value of SAR (measured) = 0.979 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Cheek Low CH9262/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.22 mW/g

Right Cheek Low CH9262/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 16.7 V/m; Power Drift = -0.072 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 1.210 mW/g; SAR(10 g) = 0.729 mW/g

Maximum value of SAR (measured) = 1.46 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Cheek Middle CH9400/Area Scan (8x8x1): Measurement grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.29 mW/g

Right Cheek Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 20.9 V/m; Power Drift = -0.024 dB

Peak SAR (extrapolated) = 1.81 W/kg

SAR(1 g) = 1.350 mW/g; SAR(10 g) = 0.763 mW/g

Maximum value of SAR (measured) = 1.70 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1907.6$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Cheek High CH9538/Area Scan (8x8x1): Measurement grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.06 mW/g

Right Cheek High CH9538/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 18.1 V/m; Power Drift = -0.115 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 1.090 mW/g; SAR(10 g) = 0.626 mW/g

Maximum value of SAR (measured) = 1.32 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Tilted Low CH9262/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.02 mW/g

Right Tilted Low CH9262/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.6 V/m; Power Drift = -0.118 dB

Peak SAR (extrapolated) = 1.84 W/kg

SAR(1 g) = 1.260 mW/g; SAR(10 g) = 0.697 mW/g

Maximum value of SAR (measured) = 1.66 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Tilted Middle CH9400/Area Scan (8x8x1): Measurement grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.16 mW/g

Right Tilted Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 22.3 V/m; Power Drift = -0.083 dB

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 1.280 mW/g; SAR(10 g) = 0.720 mW/g

Maximum value of SAR (measured) = 1.69 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1907.6$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Right Tilted High CH9538/Area Scan (8x8x1): Measurement grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.996 mW/g

Right Tilted High CH9538/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 21.4 V/m; Power Drift = -0.095 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.947 mW/g; SAR(10 g) = 0.559 mW/g

Maximum value of SAR (measured) = 1.09 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+Right Cheek Middle CH9400/Area

Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.28 mW/g

co-Location 802.11b+BT+Right Cheek Middle CH9400/Zoom


Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = -0.032 dB

Peak SAR (extrapolated) = 1.86 W/kg

SAR(1 g) = 1.290 mW/g; SAR(10 g) = 0.738 mW/g

Maximum value of SAR (measured) = 1.58 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Right Head ULTIMATE 9502 slide

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Air Temperature: 24.2 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.52, 8.52, 8.52);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+Right Cheek Middle CH9400/Area

Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.10 mW/g

co-Location 802.11g+BT+Right Cheek Middle CH9400/Zoom


Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.6 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 1.72 W/kg

SAR(1 g) = 1.200 mW/g; SAR(10 g) = 0.677 mW/g

Maximum value of SAR (measured) = 1.51 mW/g



Test Laboratory: Compliance Certification Services Inc.

GSM 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Up Middle CH190/Area Scan (6x9x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.178 mW/g

GSM Body Face Up Middle CH190/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.9 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.180 W/kg

SAR(1 g) = 0.159 mW/g; SAR(10 g) = 0.127 mW/g

Maximum value of SAR (measured) = 0.177 mW/g



Test Laboratory: Compliance Certification Services Inc.

GSM 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 824.2 \text{ MHz}$; $\sigma = 0.911 \text{ mho/m}$; $\epsilon_r = 55.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down Low CH128/Area Scan (6x9x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.518 mW/g

GSM Body Face Down Low CH128/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.9 V/m; Power Drift = -0.145 dB

Peak SAR (extrapolated) = 0.599 W/kg

SAR(1 g) = 0.503 mW/g; SAR(10 g) = 0.389 mW/g

Maximum value of SAR (measured) = 0.563 mW/g



Test Laboratory: Compliance Certification Services Inc.

GSM 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down Middle CH190/Area Scan (6x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.558 mW/g

GSM Body Face Down Middle CH190/Zoom Scan (5x5x7)/Cube

0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.3 V/m; Power Drift = -0.136 dB

Peak SAR (extrapolated) = 0.598 W/kg

SAR(1 g) = 0.521 mW/g; SAR(10 g) = 0.415 mW/g

Maximum value of SAR (measured) = 0.587 mW/g

GSM Body Face Down Middle CH190/Zoom Scan (5x5x7)/Cube


1: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.3 V/m; Power Drift = -0.136 dB

Peak SAR (extrapolated) = 0.637 W/kg

SAR(1 g) = 0.509 mW/g; SAR(10 g) = 0.391 mW/g

Maximum value of SAR (measured) = 0.584 mW/g



Test Laboratory: Compliance Certification Services Inc.

GSM 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 848.8 \text{ MHz}$; $\sigma = 0.933 \text{ mho/m}$; $\epsilon_r = 54.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down High CH251/Area Scan (6x9x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.460 mW/g

GSM Body Face Down High CH251/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.7 V/m; Power Drift = -0.065 dB

Peak SAR (extrapolated) = 0.535 W/kg

SAR(1 g) = 0.425 mW/g; SAR(10 g) = 0.329 mW/g

Maximum value of SAR (measured) = 0.494 mW/g

GSM Body Face Down High CH251/Zoom Scan (5x5x7)/Cube 1:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.7 V/m; Power Drift = -0.065 dB

Peak SAR (extrapolated) = 0.524 W/kg

SAR(1 g) = 0.450 mW/g; SAR(10 g) = 0.340 mW/g

Maximum value of SAR (measured) = 0.494 mW/g



Test Laboratory: Compliance Certification Services Inc.

GSM 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+GSM Body Face Down Middle

CH190/Area Scan (6x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.414 mW/g

co-Location 802.11b+BT+GSM Body Face Down Middle


CH190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.6 V/m; Power Drift = -0.157 dB

Peak SAR (extrapolated) = 0.438 W/kg

SAR(1 g) = 0.373 mW/g; SAR(10 g) = 0.285 mW/g

Maximum value of SAR (measured) = 0.425 mW/g



Test Laboratory: Compliance Certification Services Inc.

GSM 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+GSM Body Face Down Middle

CH190/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.320 mW/g

co-Location 802.11g+BT+GSM Body Face Down Middle


CH190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.1 V/m; Power Drift = -0.090 dB

Peak SAR (extrapolated) = 0.311 W/kg

SAR(1 g) = 0.271 mW/g; SAR(10 g) = 0.212 mW/g

Maximum value of SAR (measured) = 0.310 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GPRS Body Face Up Middle CH190/Area Scan (6x9x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.649 mW/g

GPRS Body Face Up Middle CH190/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.7 V/m; Power Drift = -0.130 dB

Peak SAR (extrapolated) = 0.666 W/kg

SAR(1 g) = 0.591 mW/g; SAR(10 g) = 0.460 mW/g

Maximum value of SAR (measured) = 0.647 mW/g

GPRS Body Face Up Middle CH190/Zoom Scan (5x5x7)/Cube 1:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.7 V/m; Power Drift = -0.130 dB

Peak SAR (extrapolated) = 0.614 W/kg

SAR(1 g) = 0.514 mW/g; SAR(10 g) = 0.402 mW/g

Maximum value of SAR (measured) = 0.602 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 850; Frequency: 824.2 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.911$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GPRS Body Face Down Low CH128/Area Scan (6x9x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.39 mW/g

GPRS Body Face Down Low CH128/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 29.2 V/m; Power Drift = -0.128 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 1.270 mW/g; SAR(10 g) = 0.988 mW/g

Maximum value of SAR (measured) = 1.45 mW/g

GPRS Body Face Down Low CH128/Zoom Scan (5x5x7)/Cube 1:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 29.2 V/m; Power Drift = 0.328 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 1.280 mW/g; SAR(10 g) = 0.982 mW/g

Maximum value of SAR (measured) = 1.44 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GPRS Body Face Down Middle CH190/Area Scan (6x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.82 mW/g

GPRS Body Face Down Middle CH190/Zoom Scan (5x5x7)/Cube

0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.0 V/m; Power Drift = -0.109 dB

Peak SAR (extrapolated) = 1.78 W/kg

SAR(1 g) = 1.530 mW/g; SAR(10 g) = 1.18 mW/g

Maximum value of SAR (measured) = 1.71 mW/g

GPRS Body Face Down Middle CH190/Zoom Scan (5x5x7)/Cube

1: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.0 V/m; Power Drift = -0.109 dB

Peak SAR (extrapolated) = 1.77 W/kg



SAR(1 g) = 1.390 mW/g; SAR(10 g) = 1.06 mW/g

Maximum value of SAR (measured) = 1.59 mW/g

GPRS Body Face Down Middle CH190 2/Z Scan (1x1x21):

Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$, $dz=5\text{mm}$

Maximum value of SAR (measured) = 1.08 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 850; Frequency: 848.8 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 848.8 \text{ MHz}$; $\sigma = 0.933 \text{ mho/m}$; $\epsilon_r = 54.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GPRS Body Face Down High CH251/Area Scan (6x9x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.39 mW/g

GPRS Body Face Down High CH251/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 28.6 V/m; Power Drift = -0.070 dB

Peak SAR (extrapolated) = 1.80 W/kg

SAR(1 g) = 1.490 mW/g; SAR(10 g) = 1.13 mW/g

Maximum value of SAR (measured) = 1.68 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+GPRS Body Face Down Middle

CH190/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.44 mW/g

co-Location 802.11b+BT+GPRS Body Face Down Middle

CH190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 32.4 V/m; Power Drift = -0.095 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 1.310 mW/g; SAR(10 g) = 0.992 mW/g

Maximum value of SAR (measured) = 1.47 mW/g

co-Location 802.11b+BT+GPRS Body Face Down Middle


CH190/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 32.4 V/m; Power Drift = -0.095 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 1.160 mW/g; SAR(10 g) = 0.871 mW/g

Maximum value of SAR (measured) = 1.32 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+GPRS Body Face Down Middle

CH190/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.36 mW/g

co-Location 802.11g+BT+GPRS Body Face Down Middle

CH190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 29.9 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 1.150 mW/g; SAR(10 g) = 0.883 mW/g

Maximum value of SAR (measured) = 1.31 mW/g

co-Location 802.11g+BT+GPRS Body Face Down Middle


CH190/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 29.9 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 1.110 mW/g; SAR(10 g) = 0.812 mW/g

Maximum value of SAR (measured) = 1.25 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

EGPRS Body Face Up Middle CH190/Area Scan (6x8x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.209 mW/g

EGPRS Body Face Up Middle CH190/Zoom Scan (5x5x7)/Cube

0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.3 V/m; Power Drift = -0.168 dB

Peak SAR (extrapolated) = 0.218 W/kg

SAR(1 g) = 0.186 mW/g; SAR(10 g) = 0.151 mW/g

Maximum value of SAR (measured) = 0.210 mW/g

EGPRS Body Face Up Middle CH190/Zoom Scan (5x5x7)/Cube


1: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.3 V/m; Power Drift = -0.168 dB

Peak SAR (extrapolated) = 0.211 W/kg

SAR(1 g) = 0.186 mW/g; SAR(10 g) = 0.143 mW/g

Maximum value of SAR (measured) = 0.208 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 850; Frequency: 824.2 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.911$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

EGPRS Body Face Down Low CH128/Area Scan (6x8x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.602 mW/g

EGPRS Body Face Down Low CH128/Zoom Scan (5x5x7)/Cube

0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 18.1 V/m; Power Drift = -0.092 dB

Peak SAR (extrapolated) = 0.653 W/kg

SAR(1 g) = 0.535 mW/g; SAR(10 g) = 0.418 mW/g

Maximum value of SAR (measured) = 0.584 mW/g

EGPRS Body Face Down Low CH128/Zoom Scan (5x5x7)/Cube


1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 18.1 V/m; Power Drift = -0.092 dB

Peak SAR (extrapolated) = 0.623 W/kg

SAR(1 g) = 0.533 mW/g; SAR(10 g) = 0.403 mW/g

Maximum value of SAR (measured) = 0.591 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

EGPRS Body Face Down Middle CH190/Area Scan (6x9x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.672 mW/g

EGPRS Body Face Down Middle CH190/Zoom Scan

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.6 V/m; Power Drift = -0.099 dB

Peak SAR (extrapolated) = 0.692 W/kg

SAR(1 g) = 0.611 mW/g; SAR(10 g) = 0.455 mW/g

Maximum value of SAR (measured) = 0.665 mW/g

EGPRS Body Face Down Middle CH190/Zoom Scan


(5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.6 V/m; Power Drift = -0.099 dB

Peak SAR (extrapolated) = 0.687 W/kg

SAR(1 g) = 0.591 mW/g; SAR(10 g) = 0.440 mW/g

Maximum value of SAR (measured) = 0.660 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 850; Frequency: 848.8 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 0.933$ mho/m; $\epsilon_r = 54.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

EGPRS Body Face Down High CH251/Area Scan (6x8x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.565 mW/g

EGPRS Body Face Down High CH251/Zoom Scan (5x5x7)/Cube


0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.7 V/m; Power Drift = -0.056 dB

Peak SAR (extrapolated) = 0.579 W/kg

SAR(1 g) = 0.495 mW/g; SAR(10 g) = 0.383 mW/g

Maximum value of SAR (measured) = 0.549 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+EGPRS Body Face Down Low

CH190/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.477 mW/g

co-Location 802.11b+BT+EGPRS Body Face Down Low

CH190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.9 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.498 W/kg

SAR(1 g) = 0.434 mW/g; SAR(10 g) = 0.331 mW/g

Maximum value of SAR (measured) = 0.479 mW/g

co-Location 802.11b+BT+EGPRS Body Face Down Low


CH190/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.9 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.490 W/kg

SAR(1 g) = 0.396 mW/g; SAR(10 g) = 0.271 mW/g

Maximum value of SAR (measured) = 0.462 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS 835-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+EGPRS Body Face Down Low

CH190/Area Scan (6x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.436 mW/g

co-Location 802.11g+BT+EGPRS Body Face Down Low

CH190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.2 V/m; Power Drift = -0.118 dB

Peak SAR (extrapolated) = 0.472 W/kg

SAR(1 g) = 0.398 mW/g; SAR(10 g) = 0.278 mW/g

Maximum value of SAR (measured) = 0.461 mW/g

co-Location 802.11g+BT+EGPRS Body Face Down Low


CH190/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.2 V/m; Power Drift = -0.118 dB

Peak SAR (extrapolated) = 0.500 W/kg

SAR(1 g) = 0.421 mW/g; SAR(10 g) = 0.321 mW/g

Maximum value of SAR (measured) = 0.466 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Up Middle CH661/Area Scan (6x9x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.160 mW/g

GSM Body Face Up Middle CH661/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.57 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 0.164 W/kg

SAR(1 g) = 0.137 mW/g; SAR(10 g) = 0.095 mW/g

Maximum value of SAR (measured) = 0.159 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 1850.2 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down Low CH512/Area Scan (6x8x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.326 mW/g

GSM Body Face Down Low CH512/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.4 V/m; Power Drift = 0.124 dB

Peak SAR (extrapolated) = 0.379 W/kg

SAR(1 g) = 0.292 mW/g; SAR(10 g) = 0.200 mW/g

Maximum value of SAR (measured) = 0.350 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down Middle CH661/Area Scan (6x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.307 mW/g

GSM Body Face Down Middle CH661/Zoom Scan (5x5x7)/Cube


0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.6 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 0.377 W/kg

SAR(1 g) = 0.294 mW/g; SAR(10 g) = 0.194 mW/g

Maximum value of SAR (measured) = 0.345 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 1909.8 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down High CH810/Area Scan (6x8x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.320 mW/g

GSM Body Face Down High CH810/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.1 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.373 W/kg

SAR(1 g) = 0.287 mW/g; SAR(10 g) = 0.191 mW/g

Maximum value of SAR (measured) = 0.342 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Up Middle CH661/Area Scan (6x9x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.160 mW/g

GSM Body Face Up Middle CH661/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.57 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 0.164 W/kg

SAR(1 g) = 0.137 mW/g; SAR(10 g) = 0.095 mW/g

Maximum value of SAR (measured) = 0.159 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 1850.2 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down Low CH512/Area Scan (6x8x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.326 mW/g

GSM Body Face Down Low CH512/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.4 V/m; Power Drift = 0.124 dB

Peak SAR (extrapolated) = 0.379 W/kg

SAR(1 g) = 0.292 mW/g; SAR(10 g) = 0.200 mW/g

Maximum value of SAR (measured) = 0.350 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down Middle CH661/Area Scan (6x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.307 mW/g

GSM Body Face Down Middle CH661/Zoom Scan (5x5x7)/Cube


0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.6 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 0.377 W/kg

SAR(1 g) = 0.294 mW/g; SAR(10 g) = 0.194 mW/g

Maximum value of SAR (measured) = 0.345 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium parameters used (interpolated): $f = 1909.8 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GSM Body Face Down High CH810/Area Scan (6x8x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.320 mW/g

GSM Body Face Down High CH810/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.1 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.373 W/kg

SAR(1 g) = 0.287 mW/g; SAR(10 g) = 0.191 mW/g

Maximum value of SAR (measured) = 0.342 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+GSM Body Face Down Middle

CH661/Area Scan (6x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.283 mW/g

co-Location 802.11b+BT+GSM Body Face Down Middle


CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.5 V/m; Power Drift = -0.120 dB

Peak SAR (extrapolated) = 0.305 W/kg

SAR(1 g) = 0.248 mW/g; SAR(10 g) = 0.177 mW/g

Maximum value of SAR (measured) = 0.293 mW/g



Test Laboratory: Compliance Certification Services Inc.

PCS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+GSM Body Face Down Middle

CH661/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.266 mW/g

co-Location 802.11g+BT+GSM Body Face Down Middle


CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 13.6 V/m; Power Drift = -0.151 dB

Peak SAR (extrapolated) = 0.291 W/kg

SAR(1 g) = 0.231 mW/g; SAR(10 g) = 0.160 mW/g

Maximum value of SAR (measured) = 0.276 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GPRS Body Face Up Middle CH661/Area Scan (6x8x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.480 mW/g

GPRS Body Face Up Middle CH661/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 16.3 V/m; Power Drift = -0.085 dB

Peak SAR (extrapolated) = 0.538 W/kg

SAR(1 g) = 0.427 mW/g; SAR(10 g) = 0.303 mW/g

Maximum value of SAR (measured) = 0.496 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GPRS Body Face Down Low CH512/Area Scan (6x8x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.35 mW/g

GPRS Body Face Down Low CH512/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 31.2 V/m; Power Drift = -0.165 dB

Peak SAR (extrapolated) = 1.44 W/kg

SAR(1 g) = 1.040 mW/g; SAR(10 g) = 0.722 mW/g

Maximum value of SAR (measured) = 1.26 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GPRS Body Face Down Middle CH661/Area Scan (6x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.21 mW/g

GPRS Body Face Down Middle CH661/Zoom Scan 2

(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 27.6 V/m; Power Drift = -0.001 dB

Peak SAR (extrapolated) = 1.39 W/kg



SAR(1 g) = 1.110 mW/g; SAR(10 g) = 0.784 mW/g

Maximum value of SAR (measured) = 1.29 mW/g

GPRS Body Face Down Middle CH661/Z Scan (1x1x21): Measurement

grid: $dx=20\text{mm}$, $dy=20\text{mm}$, $dz=5\text{mm}$

Maximum value of SAR (measured) = 0.728 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 1909.8 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

GPRS Body Face Down High CH810/Area Scan (6x8x1): Measurement

grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.12 mW/g

GPRS Body Face Down High CH810/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 26.8 V/m; Power Drift = -0.135 dB

Peak SAR (extrapolated) = 1.23 W/kg

SAR(1 g) = 0.914 mW/g; SAR(10 g) = 0.614 mW/g

Maximum value of SAR (measured) = 1.06 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+GPRS Body Face Down Middle

CH661/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.09 mW/g

co-Location 802.11b+BT+GPRS Body Face Down Middle


CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 28.2 V/m; Power Drift = -0.115 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.943 mW/g; SAR(10 g) = 0.664 mW/g

Maximum value of SAR (measured) = 1.11 mW/g



Test Laboratory: Compliance Certification Services Inc.

GPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+GPRS Body Face Down Middle

CH661/Area Scan (6x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.932 mW/g

co-Location 802.11g+BT+GPRS Body Face Down Middle


CH661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.4 V/m; Power Drift = -0.043 dB

Peak SAR (extrapolated) = 1.14 W/kg

SAR(1 g) = 0.906 mW/g; SAR(10 g) = 0.620 mW/g

Maximum value of SAR (measured) = 1.04 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

EGPRS Body Face Up Middle CH661/Area Scan (6x8x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.255 mW/g

EGPRS Body Face Up Middle CH661/Zoom Scan (5x5x7)/Cube


0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.4 V/m; Power Drift = -0.130 dB

Peak SAR (extrapolated) = 0.282 W/kg

SAR(1 g) = 0.240 mW/g; SAR(10 g) = 0.171 mW/g

Maximum value of SAR (measured) = 0.277 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 1850.2 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

EGPRS Body Face Down Low CH512/Area Scan (6x8x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.598 mW/g

EGPRS Body Face Down Low CH512/Zoom Scan (5x5x7)/Cube


0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.2 V/m; Power Drift = -0.144 dB

Peak SAR (extrapolated) = 0.706 W/kg

SAR(1 g) = 0.549 mW/g; SAR(10 g) = 0.377 mW/g

Maximum value of SAR (measured) = 0.639 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

EGPRS Body Face Down Middle CH661/Area Scan (6x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.547 mW/g

EGPRS Body Face Down Middle CH661/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.8 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 0.655 W/kg

SAR(1 g) = 0.509 mW/g; SAR(10 g) = 0.347 mW/g

Maximum value of SAR (measured) = 0.582 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 1909.8 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

EGPRS Body Face Down High CH810/Area Scan (6x8x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.503 mW/g

EGPRS Body Face Down High CH810/Zoom Scan (5x5x7)/Cube


0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.1 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 0.803 W/kg

SAR(1 g) = 0.633 mW/g; SAR(10 g) = 0.425 mW/g

Maximum value of SAR (measured) = 0.742 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 1909.8 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+EGPRS Body Face Down Low

CH810/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.414 mW/g

co-Location 802.11b+BT+EGPRS Body Face Down Low


CH810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 16.0 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.475 W/kg

SAR(1 g) = 0.379 mW/g; SAR(10 g) = 0.269 mW/g

Maximum value of SAR (measured) = 0.447 mW/g



Test Laboratory: Compliance Certification Services Inc.

EGPRS1900-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: EGPRS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium parameters used (interpolated): $f = 1909.8$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+EGPRS Body Face Down Low

CH810/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.453 mW/g

co-Location 802.11g+BT+EGPRS Body Face Down Low

CH810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 16.1 V/m; Power Drift = -0.119 dB

Peak SAR (extrapolated) = 0.513 W/kg

SAR(1 g) = 0.394 mW/g; SAR(10 g) = 0.279 mW/g

Maximum value of SAR (measured) = 0.471 mW/g

co-Location 802.11g+BT+EGPRS Body Face Down Low


CH810/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 16.1 V/m; Power Drift = -0.119 dB

Peak SAR (extrapolated) = 0.590 W/kg

SAR(1 g) = 0.427 mW/g; SAR(10 g) = 0.272 mW/g

Maximum value of SAR (measured) = 0.512 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Up Middle CH4183/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.261 mW/g

WCDMA Body Face Up Middle CH4183/Zoom Scan

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.1 V/m; Power Drift = -0.010 dB

Peak SAR (extrapolated) = 0.270 W/kg

SAR(1 g) = 0.242 mW/g; SAR(10 g) = 0.189 mW/g

Maximum value of SAR (measured) = 0.266 mW/g

WCDMA Body Face Up Middle CH4183/Zoom Scan


(5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.1 V/m; Power Drift = -0.010 dB

Peak SAR (extrapolated) = 0.267 W/kg

SAR(1 g) = 0.228 mW/g; SAR(10 g) = 0.175 mW/g

Maximum value of SAR (measured) = 0.264 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.913$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Down Low CH4132/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.701 mW/g

WCDMA Body Face Down Low CH4132/Zoom Scan

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.2 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.751 W/kg

SAR(1 g) = 0.673 mW/g; SAR(10 g) = 0.524 mW/g

Maximum value of SAR (measured) = 0.730 mW/g

WCDMA Body Face Down Low CH4132/Zoom Scan


(5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.2 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.754 W/kg

SAR(1 g) = 0.676 mW/g; SAR(10 g) = 0.498 mW/g

Maximum value of SAR (measured) = 0.748 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Down Middle CH4183/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.776 mW/g

WCDMA Body Face Down Middle CH4183/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.3 V/m; Power Drift = -0.127 dB

Peak SAR (extrapolated) = 0.810 W/kg

SAR(1 g) = 0.677 mW/g; SAR(10 g) = 0.534 mW/g

Maximum value of SAR (measured) = 0.760 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6 \text{ MHz}$; $\sigma = 0.931 \text{ mho/m}$; $\epsilon_r = 54.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Down High CH4233/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.708 mW/g

WCDMA Body Face Down High CH4233/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.2 V/m; Power Drift = -0.106 dB

Peak SAR (extrapolated) = 0.721 W/kg

SAR(1 g) = 0.629 mW/g; SAR(10 g) = 0.494 mW/g

Maximum value of SAR (measured) = 0.697 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+GPRS Body Face Down Middle

CH4183/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.524 mW/g

co-Location 802.11b+BT+GPRS Body Face Down Middle


CH4183/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.3 V/m; Power Drift = -0.102 dB

Peak SAR (extrapolated) = 0.557 W/kg

SAR(1 g) = 0.458 mW/g; SAR(10 g) = 0.360 mW/g

Maximum value of SAR (measured) = 0.517 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+GPRS Body Face Down Middle

CH4183/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.719 mW/g

co-Location 802.11g+BT+GPRS Body Face Down Middle


CH4183/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.2 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 0.783 W/kg

SAR(1 g) = 0.678 mW/g; SAR(10 g) = 0.520 mW/g

Maximum value of SAR (measured) = 0.777 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSDPA Body Face Up Middle CH4183/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.240 mW/g

HSDPA Body Face Up Middle CH4183/Zoom Scan (5x5x7)/Cube

0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 13.2 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.237 W/kg

SAR(1 g) = 0.211 mW/g; SAR(10 g) = 0.171 mW/g

Maximum value of SAR (measured) = 0.237 mW/g

HSDPA Body Face Up Middle CH4183/Zoom Scan (5x5x7)/Cube


1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 13.2 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.240 W/kg

SAR(1 g) = 0.212 mW/g; SAR(10 g) = 0.162 mW/g

Maximum value of SAR (measured) = 0.238 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.913$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Down Low CH4132/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.724 mW/g

WCDMA Body Face Down Low CH4132/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.6 V/m; Power Drift = -0.048 dB

Peak SAR (extrapolated) = 0.695 W/kg

SAR(1 g) = 0.610 mW/g; SAR(10 g) = 0.490 mW/g

Maximum value of SAR (measured) = 0.695 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSDPA Body Face Down Middle CH4183/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.717 mW/g

HSDPA Body Face Down Middle CH4183/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 22.3 V/m; Power Drift = -0.124 dB

Peak SAR (extrapolated) = 0.726 W/kg

SAR(1 g) = 0.645 mW/g; SAR(10 g) = 0.504 mW/g

Maximum value of SAR (measured) = 0.720 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6 \text{ MHz}$; $\sigma = 0.931 \text{ mho/m}$; $\epsilon_r = 54.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSDPA Body Face Down High CH4233/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.665 mW/g

HSDPA Body Face Down High CH4233/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.6 V/m; Power Drift = -0.057 dB

Peak SAR (extrapolated) = 0.713 W/kg

SAR(1 g) = 0.634 mW/g; SAR(10 g) = 0.487 mW/g

Maximum value of SAR (measured) = 0.700 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+HSDPA Body Face Down Middle

CH4183/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.646 mW/g

co-Location 802.11b+BT+HSDPA Body Face Down Middle


CH4183/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.7 V/m; Power Drift = -0.099 dB

Peak SAR (extrapolated) = 0.672 W/kg

SAR(1 g) = 0.590 mW/g; SAR(10 g) = 0.459 mW/g

Maximum value of SAR (measured) = 0.670 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band v-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+HSDPA Body Face Down Middle

CH4183/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.484 mW/g

co-Location 802.11g+BT+HSDPA Body Face Down Middle

CH4183/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.1 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 0.512 W/kg

SAR(1 g) = 0.436 mW/g; SAR(10 g) = 0.353 mW/g

Maximum value of SAR (measured) = 0.502 mW/g

co-Location 802.11g+BT+HSDPA Body Face Down Middle


CH4183/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.1 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 0.553 W/kg

SAR(1 g) = 0.452 mW/g; SAR(10 g) = 0.339 mW/g

Maximum value of SAR (measured) = 0.513 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band v-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSUPA Body Face Up Middle CH4183/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.103 mW/g

HSUPA Body Face Up Middle CH4183/Zoom Scan (5x5x7)/Cube


0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.52 V/m; Power Drift = -0.120 dB

Peak SAR (extrapolated) = 0.108 W/kg

SAR(1 g) = 0.098 mW/g; SAR(10 g) = 0.088 mW/g

Maximum value of SAR (measured) = 0.107 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band v-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band V; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.913$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSUPA Body Face Down Low CH4132/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.324 mW/g

HSUPA Body Face Down Low CH4132/Zoom Scan (5x5x7)/Cube


0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 13.9 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 0.340 W/kg

SAR(1 g) = 0.322 mW/g; SAR(10 g) = 0.276 mW/g

Maximum value of SAR (measured) = 0.339 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band v-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSUPA Body Face Down Middle CH4183/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.309 mW/g

HSUPA Body Face Down Middle CH4183/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.7 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 0.318 W/kg

SAR(1 g) = 0.298 mW/g; SAR(10 g) = 0.260 mW/g

Maximum value of SAR (measured) = 0.318 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band v-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6 \text{ MHz}$; $\sigma = 0.931 \text{ mho/m}$; $\epsilon_r = 54.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSUPA Body Face Down High CH4233/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.318 mW/g

HSUPA Body Face Down High CH4233/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.3 V/m; Power Drift = -0.057 dB

Peak SAR (extrapolated) = 0.355 W/kg

SAR(1 g) = 0.326 mW/g; SAR(10 g) = 0.280 mW/g

Maximum value of SAR (measured) = 0.347 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band v-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6$ MHz; $\sigma = 0.931$ mho/m; $\epsilon_r = 54.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+HSUPA Body Face Down High

CH4233/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.300 mW/g

co-Location 802.11b+BT+HSUPA Body Face Down High


CH4233/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.8 V/m; Power Drift = -0.113 dB

Peak SAR (extrapolated) = 0.308 W/kg

SAR(1 g) = 0.286 mW/g; SAR(10 g) = 0.247 mW/g

Maximum value of SAR (measured) = 0.305 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band v-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 846.6 \text{ MHz}$; $\sigma = 0.931 \text{ mho/m}$; $\epsilon_r = 54.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.3 deg C; Liquid Temperature: 23.3 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(10.96, 10.96, 10.96);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+HSUPA Body Face Down Middle

CH4233/Area Scan (6x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.282 mW/g

co-Location 802.11g+BT+HSUPA Body Face Down Middle


CH4233/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.2 V/m; Power Drift = -0.005 dB

Peak SAR (extrapolated) = 0.304 W/kg

SAR(1 g) = 0.275 mW/g; SAR(10 g) = 0.237 mW/g

Maximum value of SAR (measured) = 0.293 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.49$ mho/m; $\epsilon_r = 51.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Up Middle CH9400/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.386 mW/g

WCDMA Body Face Up Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.5 V/m; Power Drift = -0.062 dB

Peak SAR (extrapolated) = 0.466 W/kg

SAR(1 g) = 0.388 mW/g; SAR(10 g) = 0.282 mW/g

Maximum value of SAR (measured) = 0.465 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Down Low CH9262/Area Scan (6x9x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.854 mW/g

WCDMA Body Face Down Low CH9262/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.0 V/m; Power Drift = -0.120 dB

Peak SAR (extrapolated) = 0.884 W/kg

SAR(1 g) = 0.686 mW/g; SAR(10 g) = 0.467 mW/g

Maximum value of SAR (measured) = 0.839 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Down Middle CH9400/Area Scan (6x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.860 mW/g

WCDMA Body Face Down Middle CH9400/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.3 V/m; Power Drift = -0.093 dB

Peak SAR (extrapolated) = 0.995 W/kg

SAR(1 g) = 0.746 mW/g; SAR(10 g) = 0.493 mW/g

Maximum value of SAR (measured) = 0.881 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

WCDMA Body Face Down High CH9538/Area Scan (6x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.684 mW/g

WCDMA Body Face Down High CH9538/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.7 V/m; Power Drift = -0.067 dB

Peak SAR (extrapolated) = 0.706 W/kg

SAR(1 g) = 0.564 mW/g; SAR(10 g) = 0.374 mW/g

Maximum value of SAR (measured) = 0.667 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+GPRS Body Face Down Middle

CH9400/Area Scan (6x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.737 mW/g

co-Location 802.11b+BT+GPRS Body Face Down Middle


CH9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.5 V/m; Power Drift = -0.079 dB

Peak SAR (extrapolated) = 0.837 W/kg

SAR(1 g) = 0.669 mW/g; SAR(10 g) = 0.453 mW/g

Maximum value of SAR (measured) = 0.794 mW/g



Test Laboratory: Compliance Certification Services Inc.

WCDMA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: WCDMA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+GPRS Body Face Down Middle

CH9400/Area Scan (6x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.773 mW/g

co-Location 802.11g+BT+GPRS Body Face Down Middle


CH9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.2 V/m; Power Drift = -0.060 dB

Peak SAR (extrapolated) = 0.921 W/kg

SAR(1 g) = 0.707 mW/g; SAR(10 g) = 0.487 mW/g

Maximum value of SAR (measured) = 0.825 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSDPA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSDPA Body Face Up Middle CH9400/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.442 mW/g

HSDPA Body Face Up Middle CH9400/Zoom Scan (5x5x7)/Cube


0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.4 V/m; Power Drift = -0.021 dB

Peak SAR (extrapolated) = 0.480 W/kg

SAR(1 g) = 0.388 mW/g; SAR(10 g) = 0.273 mW/g

Maximum value of SAR (measured) = 0.452 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSDPA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSDPA Body Face Down Low CH9262/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.717 mW/g

HSDPA Body Face Down Low CH9262/Zoom Scan (5x5x7)/Cube


0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.9 V/m; Power Drift = -0.105 dB

Peak SAR (extrapolated) = 0.780 W/kg

SAR(1 g) = 0.618 mW/g; SAR(10 g) = 0.416 mW/g

Maximum value of SAR (measured) = 0.733 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSDPA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSDPA Body Face Down Middle CH9400/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.739 mW/g

HSDPA Body Face Down Middle CH9400/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.3 V/m; Power Drift = -0.124 dB

Peak SAR (extrapolated) = 0.816 W/kg

SAR(1 g) = 0.658 mW/g; SAR(10 g) = 0.439 mW/g

Maximum value of SAR (measured) = 0.776 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSDPA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSDPA Body Face Down High CH9538/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.595 mW/g

HSDPA Body Face Down High CH9538/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.2 V/m; Power Drift = -0.065 dB

Peak SAR (extrapolated) = 0.655 W/kg

SAR(1 g) = 0.486 mW/g; SAR(10 g) = 0.333 mW/g

Maximum value of SAR (measured) = 0.569 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSDPA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+HSDPA Body Face Down Middle CH9400/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.833 mW/g

co-Location 802.11b+BT+HSDPA Body Face Down Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$,
 $dz=5\text{mm}$

Reference Value = 22.4 V/m; Power Drift = -0.057 dB

Peak SAR (extrapolated) = 0.974 W/kg

SAR(1 g) = 0.696 mW/g; SAR(10 g) = 0.477 mW/g

Maximum value of SAR (measured) = 0.854 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSDPA Band II-Body ULTIMATE 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSDPA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+HSDPA Body Face Down Middle CH9400/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.851 mW/g

co-Location 802.11g+BT+HSDPA Body Face Down Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.0 V/m; Power Drift = -0.123 dB

Peak SAR (extrapolated) = 0.948 W/kg

SAR(1 g) = 0.715 mW/g; SAR(10 g) = 0.478 mW/g

Maximum value of SAR (measured) = 0.862 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band II-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSUPA Body Face Up Middle CH9400/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.126 mW/g

HSUPA Body Face Up Middle CH9400/Zoom Scan (5x5x7)/Cube


0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.65 V/m; Power Drift = -0.100 dB

Peak SAR (extrapolated) = 0.146 W/kg

SAR(1 g) = 0.121 mW/g; SAR(10 g) = 0.093 mW/g

Maximum value of SAR (measured) = 0.141 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band II-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSUPA Body Face Down Low CH9262/Area Scan (6x10x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.332 mW/g

HSUPA Body Face Down Low CH9262/Zoom Scan (5x5x7)/Cube


0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 14.7 V/m; Power Drift = -0.102 dB

Peak SAR (extrapolated) = 0.381 W/kg

SAR(1 g) = 0.300 mW/g; SAR(10 g) = 0.204 mW/g

Maximum value of SAR (measured) = 0.351 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band II-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSUPA Body Face Down Middle CH9400/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.313 mW/g

HSUPA Body Face Down Middle CH9400/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.6 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 0.375 W/kg

SAR(1 g) = 0.271 mW/g; SAR(10 g) = 0.188 mW/g

Maximum value of SAR (measured) = 0.323 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band II-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1908 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

HSUPA Body Face Down High CH9538/Area Scan (6x10x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.246 mW/g

HSUPA Body Face Down High CH9538/Zoom Scan


(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.7 V/m; Power Drift = -0.082 dB

Peak SAR (extrapolated) = 0.287 W/kg

SAR(1 g) = 0.222 mW/g; SAR(10 g) = 0.153 mW/g

Maximum value of SAR (measured) = 0.264 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band II-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11b+BT+HSUPA Body Face Down Low

CH9262/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.302 mW/g

co-Location 802.11b+BT+HSUPA Body Face Down Low


CH9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 13.8 V/m; Power Drift = -0.126 dB

Peak SAR (extrapolated) = 0.371 W/kg

SAR(1 g) = 0.273 mW/g; SAR(10 g) = 0.192 mW/g

Maximum value of SAR (measured) = 0.325 mW/g



Test Laboratory: Compliance Certification Services Inc.

HSUPA Band II-Body ATLAS 9502

DUT: ULTIMATE 9502; Type: ATLAS; Serial: N/A

Communication System: HSUPA Band II; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(8.43, 8.43, 8.43);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 8/29/2007
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

co-Location 802.11g+BT+HSUPA Body Face Down Low

CH9262/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.283 mW/g

co-Location 802.11g+BT+HSUPA Body Face Down Low

CH9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 14.2 V/m; Power Drift = -0.124 dB

Peak SAR (extrapolated) = 0.341 W/kg

SAR(1 g) = 0.258 mW/g; SAR(10 g) = 0.181 mW/g

Maximum value of SAR (measured) = 0.301 mW/g

