

MPE REPORT

Report No.: SRMC2006-H024-E002

Equipment Type Name: CDMA Fixed Wireless Phone

Equipment type: Indigo FWT-200E

Manufacture: MAYBROOKE ENTERPRISES INC.

Specification: FCC Part2.1093,

OET Bulletin 65 Supplement [June 2001]

FCC ID: UN3FWT-200E

STATE RADIO MONITORING CENTER (SRMC)

No.80 Beilishi Road Xicheng District Beijing, China

Tel: 86-10-68009181 Fax: 86-10-68009195



CONTENTS

1. General information	3
1.1 Notes of the test report	3
1.2 Information about the testing laboratory	3
1.3 Applicant's details	3
1.4 Manufacturer's details	3
1.5 Application details	4
1.6 Reference specification	4
1.7 Information of EUT	4
1.7.1 General information	4
1.7.2 EUT details	5
1.7.3 Auxiliary equipment details	5
2. Test information:	6
2.1 Summary of the test results:	6
2.2 Calculation result	7
2.2.1 Maximum Permissible Exposure (MPE)	7



1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio Monitoring Center.

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: State Radio Monitoring Center
Address: No.80 Beilishi Road, Xicheng District, Beijing China
100037
City: Beijing
Country or Region: China
Contacted person: Wang Junfeng
Tel: +86 10 68009181
Fax: +86 10 68009195
Email: Wangjf@srcc.org.cn

1.3 Applicant's details

Company: MAYBROOKE ENTERPRISES INC.
Address: Edificio Torre MMG, Piso 14, Calle 53E Urb. Marbella
Panama City, PANAMA 0831-01587
City: Panama City
Country or Region: PANAMA
Grantee Code: UN3
Contacted person: Robert J Scodellaro
Tel: + (507) 265 7691
Fax: + (507) 223-1467
Email: maybrooke@ptycmd.com

1.4 Manufacturer's details

Company: MAYBROOKE ENTERPRISES INC.
Address: Edificio Torre MMG, Piso 14, Calle 53E Urb. Marbella
Panama City, PANAMA 0831-01587
City: Panama City
Country or Region: PANAMA
Grantee Code: UN3
Contacted person: Robert J Scodellaro
Tel: + (507) 265 7691
Fax: + (507) 223-1467
Email: maybrooke@ptycmd.com



1.5 Application details

Date of receipt of application: 18th Sep. 2006

Date of receipt of test sample: 22th Sep. 2006

Date of test: 26th Sep. 2006 to 28th Sep. 2006

1.6 Reference specification

FCC Part2.1093, OET Bulletin Supplement [June 2001]

1.7 Information of EUT

1.7.1 General information

Name and type of EUT	CDMA Fixed Wireless Phone
FCC ID	UN3FWT-200E
Frequency range	PCS1900: Tx:1850~1910MHz Rx:1930~1990MHz
Rated output power	23.0dBm
Modulation type	CDMA
Duplex mode	FDD
Duplex spacing:	80MHz
Antenna type	External
Power Supply	Battery or charger
Rated Power Supply Voltage	3.7V
Extreme Temperature	-30°C~+50°C



1.7.2 EUT details

Name	Model	Serial number
CDMA Fixed Wireless Phone	Indigo FWT-200E	Sample 1

1.7.3 Auxiliary equipment details

Equipment	Charger
Manufacturer	Pacific Tel
Model Number	P-010B-B818

Equipment	Battery
Manufacturer	Pacific Tel
Model Number	-----
Capacity	1200mAh
Rated Voltage	3.7V



The State Radio Monitoring Center

Tel: 86-10-68009181

Fax: 86-10-68009195





Report S/N: SRMC2006-H024-E002

Version: 1.0 Page 6 of 8

2. Test information:

2.1 Summary of the calculation results:

No.	Test case	FCC reference	Verdict
1	MPE Calculation	FCC Part2.1093, OET Bulletin 65 Supplement [June 2001]	Pass

This Test Report Is Issued by: 	Checked By: 
Tested By: 	Issued date: 



2.2 Calculation result

2.2.1 Maximum Permissible Exposure (MPE)

Limit:

FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

(A) Limits for Occupational/Controlled Exposure ☐

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	100*	6
3.0-30	1842/f	4.89/f	(900/f ²) *	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure ☒

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	100*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz *Plane-wave equivalent power density

Calculation procedure:

In accordance with 47CFR FCC Part 2.1091, the product has been defined as a mobile device where a distance of 0.4m normally can be maintained between the user and product.

Calculation formula:

Power Density: $P_d (W/m^2) = E^2/377$

$E (V/m) = (30 \cdot P \cdot G)^{0.5}/d$

E: Electric Field Strength (V/m)



The State Radio Monitoring Center

Tel: 86-10-68009181

Fax: 86-10-68009195

Report S/.N: SRMC2006-H024-E002

Version: 1.0 Page 8 of 8

P: Peak RF Output Power (W)

G: Antenna Numeric Gain (Numeric)

d: Separation Distance Between the Radiator and Human Body (m)

So the calculation formula can be changed as:

$$P_d = (30 * P * G) / (377 * d^2)$$

Calculation result:

Channel No.	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (W)	Power Density (S) (mW/cm2)	Limit of Power Density (S) (mW/cm2)	Verdict
25	1.17	23.2	0.209	0.0122	1.0	Pass
600	1.17	23.0	0.199	0.0116	1.0	Pass
1175	1.17	23.1	0.204	0.0119	1.0	Pass