FCC PART 15 SUBPART C TEST REPORT

for

Communicator

Model No.: XC-7107

FCC ID: UNG-XC7107

of

Applicant: Honeywld Technology Corp.

Address: 4F-1, No.5, Hsin-Ann Rd., Hsinchu Science Park,

Hsinchu 30076, Taiwan, R.O.C.

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1477, TW0020, TW1072

Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1

A2LA Accredited No.: 2732.01





Report No.: W6M21812-18685-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C. TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com

FCC ID: UNG-XC7107

TABLE OF CONTENTS

1 (GENERAL INFORMATION	2
1.1	Notes	2
1.2	2 Testing laboratory	3
1.3	B Details of approval holder	3
1.4	4 Application details	4
1.5	General information of Test item	4
1.6	5 Test standards	5
2 7	TECHNICAL TEST	6
2.1	Summary of test results	6
2.2	2 Test environment	6
2.3	3 Test Equipment List	7
2.4	4 General Test Procedure	10
3 7	TEST RESULTS (ENCLOSURE)	12
3.1	Peak Output Power (transmitter)	13
3.2	2 Equivalent isotropic radiated power	23
3.3	RF Exposure Compliance Requirements	23
3.4	Transmitter Radiated Emissions in Restricted Bands	24
3.5	5 Spurious Emissions (tx)	25
3.6	Radiated Emission on the band edge	27
3.7	7 Minimum 6 dB Bandwidth	34
3.8	Peak Power Spectral Density	44
3.9	Padiated Emission from Digital Part	54
Anne	endix	58

FCC ID: UNG-XC7107

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that is performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.

Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.

The test sample is able to work according IEEE 802.11 b/g/n.

This report is related to FCC Part 15 C (DSSS and OFDM device).

Tester:

March 14, 2019

Kent Lin

WTS-Lab. Name

Signature

Technical responsibility for area of testing:

March 14, 2019 Kevin Wang

Date WTS Name Signature

FCC ID: UNG-XC7107

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist., New Taipei City 207,

Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228 FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd. 6F, NO. 58, LANE 188, RUEY-KUANG RD. NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877 Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. TW1477, TW0020, TW1072

Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd.:

Name:	./.
Accredited number:	./.
Street:	./.
Town:	./.
Country:	./.
Telephone:	./.
Fax:	/

1.3 Details of approval holder

Name: Honeywld Technology Corp.

Street: 4F-1, No.5, Hsin-Ann Rd., Hsinchu Science Park,

Town: Hsinchu 30076, Country: Taiwan, R.O.C. Telephone: +886-3-5770725 Fax: +886-3-5770185

FCC ID: UNG-XC7107

1.4 Application details

Date of receipt of test item: February 26, 2019

Date of test: from February 27, 2019 to March 14, 2019

1.5 General information of Test item

Type of test item: Communicator
Model Number: XC-7107
Brand Name: Honeywld

Multi-listing model number: /.
Photos: /.

Technical data

Frequency band: 2.4 GHz – 2.4835 GHz

11b, 11g, 11n 20MHz

Frequency (ch 1 or A): 2.412 GHz Frequency (ch 6 or B): 2.437 GHz Frequency (ch 11 or C): 2.462 GHz

11n 40MHz

Frequency (ch 1 or A): 2.422 GHz Frequency (ch 4 or B): 2.437 GHz Frequency (ch 7 or C): 2.452 GHz

Bluetooth Low Energy

Frequency (ch 0): 2.402 GHz Frequency (ch 19): 2.440 GHz Frequency (ch 39): 2.480 GHz

Number of Channels: 11b, 11g, 11n 20MHz: 11

11n 40MHz: 7 Bluetooth: 40

Operation modes: duplex

Modulation Type: DSSS / OFDM / GFSK

Fixed point-to-point operation: \square Yes $/ \boxtimes$ No

Type of Antenna: WLAN: PCB antenna / BT: Portable antenna

Antenna gain: WLAN: 0dBi / BT: 2dBi

Power supply: Adaptor (I/P: 100-240V~50/60Hz, 0.3A MAX,

O/P: 5V / 1000mA)

Emission designator: 11b: 15M2G1D

11g: 17M8D1D

11n 20MHz: 19M0D1D 11n 40MHz: 38M4D1D

Bluetooth low energy: 1M40G1D Bluetooth low energy: 2M75G1D

Host device: none



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107 Classification :

Fixed Device	
Mobile Device (Human Body distance > 20cm)	
Portable Device (Human Body distance < 20cm)	

Transmitter Unom

Mode A (802.11b)

Power (ch 1 or A): Conducted: 16.53 dBm Power (ch 6 or B): Conducted: 15.66 dBm Power (ch 11 or C): Conducted: 15.00 dBm

Mode B (802.11g)

Power (ch 1 or A): Conducted: 15.90 dBm Power (ch 6 or B): Conducted: 14.90 dBm Power (ch 11 or C): Conducted: 14.20 dBm

Mode C (802.11n 20 MHz)

Power (ch 1 or A): Conducted: 15.92 dBm Power (ch 6 or B): Conducted: 14.86 dBm Power (ch 11 or C): Conducted: 14.11 dBm

Mode D (802.11n 40 MHz)

Power (ch 1 or A): Conducted: 13.81 dBm Power (ch 4 or B): Conducted: 13.37 dBm Power (ch 7 or C): Conducted: 12.68 dBm

Mode E (Bluetooth Low energy)

Power (ch 0 or A): Conducted: 4.56 dBm Power (ch 19 or B): Conducted: 4.42 dBm Power (ch 39 or C): Conducted: 4.26 dBm

Mode F (Bluetooth Low energy)

Power (ch 0 or A): Conducted: 4.64 dBm Power (ch 19 or B): Conducted: 4.46 dBm Power (ch 39 or C): Conducted: 4.38 dBm

Manufacturer: (if applicable)

Name: ./.
Street: ./.
Town: ./.
Country: ./.

1.6 Test standards

Technical standard: FCC RULES PART 15 SUBPART C § 15.247 (2017-10)

FCC ID: UNG-XC7107 **Technical test**

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.

2.2 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Power supply: Adaptor (I/P: 100-240V~50/60Hz, 0.3A MAX,

O/P: 5V / 1000mA)

Extreme conditions parameters: ./.

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission	Expanded Uncertainty: AMN: 1.30 dB Voltage probe: 1.36 dB
Estimation Result of Uncertainty of Radiated Emission(3M)	Expanded Uncertainty: 0.009-30 MHz: 2.02 dB 30-1000 MHz: 3.49 dB 1-18 GHz: 3.01 dB 18-40 GHz: 2.43 dB
Estimation Result of Uncertainty of Bandwidth Measurement 20 dB Bandwidth, Occupied bandwidth, Channel bandwidth, Necessary Bandwidth	Expanded Uncertainty: 0.45 kHz
Estimation Result of Uncertainty of Conducted Output Power Measurement Output power	Expanded Uncertainty: 1.72 dB
Estimation Result of Uncertainty of Power Density Measurement Power density	Expanded Uncertainty: 1.73 dB
Estimation Result of Uncertainty of Band Edge Measurement	Expanded Uncertainty: 0.98 dBc

The decision rule is: Measurement uncertainty is not taken into account.



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

2.3 Test Equipment List

No.	Test equipment	Туре	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2018/5/30	2019/5/29
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function	on Test
ETSTW-CE 004	ZWEILEITER-V- NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2018/11/1	2019/10/31
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2018/8/21	2019/8/20
ETSTW-CE 008	HF-EICHLEITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function	on Test
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2018/7/13	2019/7/12
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2018/9/25	2019/9/24
ETSTW-CE 028	MXE EMI Receiver	N9038A	MY53220110	Agilent	2018/7/16	2019/7/15
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2018/5/30	2019/5/29
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2018/5/21	2019/5/20
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function	on Test
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function	on Test
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2018/7/13	2019/7/12
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2018/7/12	2019/7/11
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2018/3/26	2019/3/25
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2019/1/29	2020/1/28
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2018/4/13	2019/4/12
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2018/4/26	2019/4/25
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-te	st Use
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2019/2/26	2020/2/28
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2019/2/26	2020/2/28
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2019/2/26	2020/2/28
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2019/2/26	2020/2/28
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2019/2/26	2020/2/28
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2018/3/30	2019/3/29
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function	on Test
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function	on Test
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2018/9/17	2019/9/16
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2018/9/18	2019/9/17
ETSTW-RE 091	Match Pad	MDCS1500	None	WOKEN	2018/4/16	2019/4/15
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2019/2/13	2020/2/12
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Functi	on test
ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2019/1/15	2020/1/14



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

FCC ID: UNG) (D0200	V CD0210 111022	A DATA W.C.		
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC		on test
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2018/5/29	2019/5/28
ETSTW-RE 125	5GHz Notch filter	5NSL11- 5200/E221.3-O/O	1	K&L Microwave	2018/8/8	2019/8/7
ETSTW-RE 126	5GHz Notch filter	5NSL12- 5800/E221.3-O/O	1	K&L Microwave	2018/8/8	2019/8/7
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2019/2/26	2020/2/28
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2018/8/8	2019/8/7
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2018/8/8	2019/8/7
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-te	st Use
ETSTW-RE 142	Amplifier	8447D	2805A03378	Agilent	2018/3/30	2019/3/29
ETSTW-RE 147	Bi- log Hybrid Antenna	MCTD 2786B	BLB16M04005	ETC	2018/3/23	2019/3/22
ETSTW-RE 151	Thermohygrometer	608-h1	45104376	TESTO	2018/8/17	2019/8/16
ETSTW-EMI 011	USB Compact Modulator	SFC-U	101689	R&S	2018/5/10	2019/5/9
ETSTW-EMS 008	Exposure Level Tester	ELT-400	G-0009	Narda	2018/7/17	2019/7/16
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2019/2/26	2020/2/28
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2019/2/26	2020/2/28
ETSTW-GSM 004	Wideband Radio Communication Tester	CMW500	128092	R&S	2018/10/19	2019/10/18
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849- 822/851-40 /12+9SS	3	WI	2019/1/14	2020/1/13
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748- 1743/1752-32/5SS	1	WI	2019/1/14	2020/1/13
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5 -1875.5/1884.5- 32/5SS	3	WI	2019/1/14	2020/1/13
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1- 904.25-50/8SS	1	WI	2019/1/14	2020/1/13
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2018/9/12	2019/9/11
ETSTW-GSM 024	Radio Communication Analyzer	MT8821C	None	Anritsu	2019/2/26	2020/2/28
ETSTW-GSM 025	Band Reject Filter	BRM19835	001	Micro-Tronics	2018/8/9	2019/8/8
ETSTW-Cable 011	SMA to N type Cable	RGU-400	None	THERMAX	Pre-test U	Jse NCR
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2019/2/21	2020/2/20
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2019/2/21	2020/2/20
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2019/2/21	2020/2/20
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2019/2/21	2020/2/20
ETSTW-Cable 020	N TYPE Cable	OATS Cable 1	N30N30-L335-15M	JYE BAO CO.,LTD.	2018/7/2	2019/7/1
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2019/2/26	2020/2/28
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2018/5/14	2019/5/13
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2018/9/18	2019/9/17
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2018/9/18	2019/9/17
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2019/2/26	2020/2/28
ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S Cable 10)	238092	HUBER+SUHNER	2018/3/30	2019/3/29
ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2018/3/30	2019/3/29
ETSTW-Cable 048	Microwave Cable	SUCOFLEX 104	325519	HUBER+SUHNER	2018/3/30	2019/3/29



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2018/6/9	2019/6/8
ETSTW-Cable 064	Microwave Cable	SUCOFLEX 104	MY28891	HUBER+SUHNER	2018/3/30	2019/3/29
ETSTW-Cable 066	SMA type cable	32022	None	ASTROLAB	2018/8/30	2019/8/29
ETSTW-Cable 071	N TYPE CABLE	EMCCFD400-NM- NM-25000	170239	EMCI	2018/6/9	2019/6/8
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version F	ETS-03A1
WTSTW-SW 006	EMI TEST SOFTWARE	e3	None	AUDIX	Version	9.161014
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version	2.0.0.1

FCC ID: UNG-XC7107

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.10-2013 6.2 using a 50µH LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.10-2013 6.3 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of $dB\mu V$) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS(to the receiver) = FS

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.10-2013 6.2.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



FCC ID: UNG-XC7107

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = 20 log (dwell time/T)

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI STANDARD C63.10-2013 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	×	×	
Equivalent isotropically radiated Power	15.247(b)	×	×	
Spurious Emissions radiated – Transmitter	15.247(c):	×	×	
operating	15.209			
Band Edge Measurement	15.247(d)	×	×	
Minimum 6 dB Bandwidth	15.247(a)(2)	×	×	
Peak Power Spectral Density	15.247(e)	×	×	
Radiated Emission from Digital Part	15.109	×	×	
Power Line Conducted Emission	15.207	×	×	

FCC ID: UNG-XC7107


3.1 Peak Output Power (transmitter)

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Mode A




MAX OUTPUT POWER 802.11B CH01 Date: 13.MAR.2019 16:43:54




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



MAX OUTPUT POWER 802.11B CH06 Date: 13.MAR.2019 16:44:37




MAX OUTPUT POWER 802.11B CH11 Date: 13.MAR.2019 16:45:16




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode B



MAX OUTPUT POWER 802.11G CH01 Date: 13.MAR.2019 16:46:03




MAX OUTPUT POWER 802.11G CH06 Date: 13.MAR.2019 16:46:46



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



MAX OUTPUT POWER 802.11G CH11 Date: 13.MAR.2019 16:47:28

Mode C




MAX OUTPUT POWER 802.11N 20MHZ CH1 Date: 13.MAR.2019 16:48:15




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



MAX OUTPUT POWER 802.11N 20MHZ CH6
Date: 13.MAR.2019 16:48:59




MAX OUTPUT POWER 802.11N 20MHZ CH11 Date: 13.MAR.2019 16:49:37




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode D



MAX OUTPUT POWER 802.11N 40MHZ CH1 Date: 13.MAR.2019 16:50:28




MAX OUTPUT POWER 802.11N 40MHZ CH4
Date: 13.MAR.2019 16:51:56




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



MAX OUTPUT POWER 802.11N 40MHZ CH7
Date: 13.MAR.2019 16:52:40

Mode E




MAX OUTPUT POWER BT4.0 CH00 Date: 12.MAR.2019 20:43:07




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



MAX OUTPUT POWER BT4.0 CH19 Date: 12.MAR.2019 20:43:45




MAX OUTPUT POWER BT4.0 CH39 Date: 12.MAR.2019 20:44:23




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode F



MAX OUTPUT POWER BT5.0 CH00 Date: 12.MAR.2019 20:45:13



MAX OUTPUT POWER BT5.0 CH19 Date: 12.MAR.2019 20:45:42



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



MAX OUTPUT POWER BT5.0 CH39 Date: 12.MAR.2019 20:46:08

Limits:

Frequency	Power
MHz	dBm
902 - 928	30
2400 – 2483.5	30
5725 - 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider \$15.247 (b)(4)

Test equipment used: ETSTW-RE 055, ETSTW-RE 050, ETSTW-RE 064

FCC ID: UNG-XC7107

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power

EIRP = 16.53 dBm

Limit: EIRP = +36 dBm for Antenna gain < 6 dBi

Test equipment used: ETSTW-RE 055

3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a "worst case" or conservative prediction.

$$S = \frac{PG}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

110 1 micelina Gam			
Item	Unit	Value	Remarks
P	mW	44.9780	Peak value
D	dB		
AG	dBi	0	
G		1	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.0089	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure		
Frequency (MHz)	Power Density (mW/cm ²)	
1500 – 100.000	1.0	

FCC ID: UNG-XC7107

3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency ≤ 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements) Frequency > 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements) Frequency > 1 GHz, RBW:1 MHz, VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission	Field strength	Field Strength
(MHz)	(microvolts/meter)	(dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of Digit Transmission Systems:

"If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation."

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = 20 log (dwell time/ 100ms)

Note: No duty cycle correction was added to the reading of this EUT.

Explanation: see attached diagrams in Appendix.

FCC ID: UNG-XC7107

3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies above 1GHz (Peak measurements).

Modified Limit for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

For frequencies above 1GHz (Average measurements). Max. reading – 20dB

Max. reading – 20 dB

Guidance on Measurement of Digit Transmission Systems:

"If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation."

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = 20 log (dwell time/100ms)

Note: No duty cycle correction was added to the reading of EUT.

FCC ID: UNG-XC7107

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits. In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Correction Factor".

Summary table with radiated data of the test plots

Model: XC-7107 Date: -
Mode: -- Temperature: -- °C Engineer: -
Polarization: -- Humidity: --

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	 Margin (dB)	Table Degree (Deg.)	Ant. High (cm)

Frequency		ding BuV)	Factor (dB)	Res (dBu			mit V/m)	Margin	Table Degree	Ant. High
(MHz)	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.	(dB)	(Deg.)	(m)
									-	

Note

- 1. Correction Factor = Antenna factor + Cable loss Preamplifier
- 2. The formula of measured value as: Test Result = Reading + Correction Factor
- 3. Detector function in the form: PK = Peak, QP = Quasi Peak, AV = Average
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.
- 5. After evaluated, the test result in this report adopt the worst case to measure, please see attached diagrams in appendix.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 030, ETSTW-RE 111, ETSTW-RE 088, ETSTW-RE 018, ETSTW-RE 064


FCC ID: UNG-XC7107

3.6 Radiated Emission on the band edge

According to FCC rules part 15 subpart C §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

Mode A




BANDEDGE 802.11B CH01
Date: 13.MAR.2019 16:44:12




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



BANDEDGE 802.11B CH11
Date: 13.MAR.2019 16:45:34

Mode B




BANDEDGE 802.11G CH01
Date: 13.MAR.2019 16:46:21




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



BANDEDGE 802.11G CH11
Date: 13.MAR.2019 16:47:46

Mode C




BANDEDGE 802.11N 20MHZ CH01 Date: 13.MAR.2019 16:48:33




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



BANDEDGE 802.11N 20MHZ CH11 Date: 13.MAR.2019 16:49:55

Mode D




BANDEDGE 802.11N 40MHZ CH01 Date: 13.MAR.2019 16:51:31




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



BANDEDGE 802.11N 40MHZ CH07 Date: 13.MAR.2019 16:53:33

Mode E




BANDEDGE BT4.0 CH00
Date: 12.MAR.2019 20:55:16




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



BANDEDGE BT4.0 CH39
Date: 12.MAR.2019 20:57:09

Mode F




BANDEDGE BT5.0 CH00
Date: 12.MAR.2019 20:55:51



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



BANDEDGE BT5.0 CH39

Date: 12.MAR.2019 20:56:34

Limit:

Frequency Range / MHz	Limit			
902 –928				
2400 – 2483.5	- 20 dB			
5725 - 5850				


Test equipment used: ETSTW-RE 055, ETSTW-RE 050

FCC ID: UNG-XC7107

3.7 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission. The 6 dB bandwidth is the frequency difference between the two markers.

Mode A




6DB BANDWIDTH 802.11B CH01 Date: 13.MAR.2019 16:44:01




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



6DB BANDWIDTH 802.11B CH06
Date: 13.MAR.2019 16:44:43




6DB BANDWIDTH 802.11B CH11 Date: 13.MAR.2019 16:45:22




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode B



6DB BANDWIDTH 802.11G CH01 Date: 13.MAR.2019 16:46:09




6DB BANDWIDTH 802.11G CH06 Date: 13.MAR.2019 16:46:52




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



6DB BANDWIDTH 802.11G CH11 Date: 13.MAR.2019 16:47:34

Mode C




6DB BANDWIDTH 802.11N 20MHZ CH1 Date: 13.MAR.2019 16:48:21




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



6DB BANDWIDTH 802.11N 20MHZ CH6
Date: 13.MAR.2019 16:49:05




6DB BANDWIDTH 802.11N 20MHZ CH11 Date: 13.MAR.2019 16:49:43




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode D



6DB BANDWIDTH 802.11N 40MHZ CH1 Date: 13.MAR.2019 16:50:34




6DB BANDWIDTH 802.11N 40MHZ CH4 Date: 13.MAR.2019 16:52:02




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



6DB BANDWIDTH 802.11N 40MHZ CH7
Date: 13.MAR.2019 16:52:46

Mode E



6DB BANDWIDTH BT4.0 CH00
Date: 12.MAR.2019 20:47:32




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



6DB BANDWIDTH BT4.0 CH19
Date: 12.MAR.2019 20:48:06




6DB BANDWIDTH BT4.0 CH39
Date: 12.MAR.2019 20:48:37




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode F



6DB BANDWIDTH BT5.0 CH00 Date: 12.MAR.2019 20:50:29




6DB BANDWIDTH BT5.0 CH19
Date: 12.MAR.2019 20:49:59



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



6DB BANDWIDTH BT5.0 CH39
Date: 12.MAR.2019 20:49:27

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 055, ETSTW-RE 050

Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

3.8 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.

The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

Mode A




POWER DENSITY 802.11B CH01 Date: 13.MAR.2019 16:44:08




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



POWER DENSITY 802.11B CH06
Date: 13.MAR.2019 16:44:51




POWER DENSITY 802.11B CH11
Date: 13.MAR.2019 16:45:30




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode B



POWER DENSITY 802.11G CH01 Date: 13.MAR.2019 16:46:17




POWER DENSITY 802.11G CH06
Date: 13.MAR.2019 16:47:00




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



POWER DENSITY 802.11G CH11
Date: 13.MAR.2019 16:47:42


Mode C




POWER DENSITY 802.11N 20MHZ CH1
Date: 13.MAR.2019 16:48:29

Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



POWER DENSITY 802.11N 20MHZ CH6
Date: 13.MAR.2019 16:49:13




POWER DENSITY 802.11N 20MHZ CH11 Date: 13.MAR.2019 16:49:51




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode D



POWER DENSITY 802.11N 40MHZ CH1
Date: 13.MAR.2019 16:50:49




POWER DENSITY 802.11N 40MHZ CH4
Date: 13.MAR.2019 16:52:17




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



POWER DENSITY 802.11N 40MHZ CH7
Date: 13.MAR.2019 16:53:01


Mode E




POWER DENSITY BT4.0 CH00
Date: 12.MAR.2019 20:54:16

Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



POWER DENSITY BT4.0 CH19
Date: 12.MAR.2019 20:53:51




POWER DENSITY BT4.0 CH39
Date: 12.MAR.2019 20:53:21




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Mode F



POWER DENSITY BT5.0 CH00
Date: 12.MAR.2019 20:51:26




POWER DENSITY BT5.0 CH19
Date: 12.MAR.2019 20:52:12



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



POWER DENSITY BT5.0 CH39
Date: 12.MAR.2019 20:52:47

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483.5	8
5725-5850	8

Test equipment used: ETSTW-RE 055, ETSTW-RE 050

Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

3.9 Radiated Emission from Digital Part

FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission	Field Strength	Field Strength
(MHz)	(microvolts/meter)	(dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 030, ETSTW-RE 055, ETSTW-RE 064, ETSTW-RE 111

Explanation: The test results are listed in the separated test report no.: W6M21812-18685-P-15B.




Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

3.10 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.



Site: Chamber_03

Condition: FCC Part 15 Class B Conduction (QP)

Phase: A Power: 120 Va.c.

EUT: W6M21812-18685

M/N:


Test Mode:

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1540	37.91	QP	9.95	47.86	65.78	-17.92	
	0.1540	25.92	AVG	9.95	35.87	55.78	-19.91	
	0.1655	36.71	QP	9.94	46.65	65.18	-18.53	
	0.1655	16.81	AVG	9.94	26.75	55.18	-28.43	
	0.1850	35.53	QP	9.93	45.46	64.26	-18.80	
	0.1850	24.34	AVG	9.93	34.27	54.26	-19.99	
7. 78	0.2830	27.80	QP	9.91	37.71	60.73	-23.02	
	0.2830	14.76	AVG	9.91	24.67	50.73	-26.06	
	0.4924	32.84	QP	9.90	42.74	56.13	-13.39	
*	0.4924	24.09	AVG	9.90	33.99	46.13	-12.14	
2 20	0.8487	23.31	QP	9.91	33.22	56.00	-22.78	
	0.8487	15.44	AVG	9.91	25.35	46.00	-20.65	



Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107



Phase:

Power: 120 Va.c.

L1

Site: Chamber_03

Condition: FCC Part 15 Class B Conduction (QP)

EUT: W6M21812-18685

M/N: Test Mode: Note:

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1767	36.99	QP	9.93	46.92	64.64	-17.72	
	0.1767	17.24	AVG	9.93	27.17	54.64	-27.47	
	0.2177	33.29	QP	9.92	43.21	62.91	-19.70	
33	0.2177	17.89	AVG	9.92	27.81	52.91	-25.10	
	0.2527	30.80	QP	9.91	40.71	61.67	-20.96	
	0.2527	13.83	AVG	9.91	23.74	51.67	-27.93	
	0.2816	28.43	QP	9.91	38.34	60.77	-22.43	
	0.2816	14.34	AVG	9.91	24.25	50.77	-26.52	
	0.4742	25.89	QP	9.90	35.79	56.44	-20.65	
- 4	0.4742	19.18	AVG	9.90	29.08	46.44	-17.36	
	0.4942	31.26	QP	9.90	41.16	56.10	-14.94	
*	0.4942	22.84	AVG	9.90	32.74	46.10	-13.36	
- 8	2.1470	20.57	QP	9.93	30.50	56.00	-25.50	
3.0	2.1470	11.18	AVG	9.93	21.11	46.00	-24.89	

Note: 1. The formula of measured value as: Test Result = Reading + Correction Factor

- 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
- 3. Detector function in the form: PK = Peak, QP = Quasi Peak, AV = Average
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.

Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)				
	Quasi Peak	Average			
0.15-0.5	66 to 56	56 to 46			
0.5-5	56	46			
5-30	60	50			

Test equipment used: ETSTW-CE 001, ETSTW-CE 016, ETSTW-RE 045.

Registration number: W6M21812-18685-C-1

FCC ID: UNG-XC7107


Appendix

Measurement diagrams

Spurious Emissions radiated



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	251.6032	46.04	peak	-7.30	38.74	46.00	100	280	-7.26	
	599.5591	34.88	peak	-1.05	33.83	46.00	100	100	-12.17	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	47.4950	43.67	peak	-9.87	33.80	40.00	100	20	-6.20	
	263.2664	34.40	peak	-6.78	27.62	46.00	100	55	-18.38	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4823.915	56.39	peak	0.73	57.12	74.00	160	0	-16.88	
*	4823.915	50.45	AVG	0.73	51.18	54.00	160	0	-2.82	
	7235.900	55.11	peak	5.42	60.53	74.00	170	357	-13.47	
	7235.900	45.73	AVG	5.42	51.15	54.00	170	357	-2.85	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4825.651	54.18	peak	0.73	54.91	74.00	165	10	-19.09	
*	4825.651	48.93	AVG	0.73	49.66	54.00	165	10	-4.34	
	7238.477	53.17	peak	5.42	58.59	74.00	180	350	-15.41	
	7238.477	44.18	AVG	5.42	49.60	54.00	180	350	-4.40	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.49	peak	8.28	43.77	74.00	150	225	-30.23	
*	12060.000	35.12	peak	14.17	49.29	74.00	150	170	-24.71	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.33	peak	8.28	43.61	74.00	150	210	-30.39	
*	12060.000	34.98	peak	14.17	49.15	74.00	150	75	-24.85	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH1

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2521.042	58.16	peak	-3.66	54.50	74.00	150	225	-19.50	
*	2521.042	49.97	AVG	-3.66	46.31	54.00	150	225	-7.69	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2518.036	59.88	peak	-3.67	56.21	74.00	195	130	-17.79	
*	2518.036	51.18	AVG	-3.67	47.51	54.00	195	130	-6.49	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4873.953	56.68	peak	0.69	57.37	74.00	155	360	-16.63	
	4873.953	50.50	AVG	0.69	51.19	54.00	155	360	-2.81	
	7312.162	54.40	peak	5.58	59.98	74.00	180	360	-14.02	
*	7312.162	46.20	AVG	5.58	51.78	54.00	180	360	-2.22	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4873.748	46.26	peak	0.69	46.95	74.00	150	90	-27.05	
*	7311.000	42.88	peak	5.57	48.45	74.00	150	160	-25.55	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.51	peak	8.57	44.08	74.00	150	240	-29.92	
*	12185.000	34.36	peak	15.16	49.52	74.00	150	70	-24.48	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.86	peak	8.57	44.43	74.00	150	40	-29.57	
*	12185.000	33.36	peak	15.16	48.52	74.00	150	70	-25.48	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11b CH6

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH6

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2545.090	51.60	peak	-3.54	48.06	74.00	150	135	-25.94	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4921.844	48.10	peak	0.71	48.81	74.00	150	170	-25.19	
	7390.782	52.11	peak	6.02	58.13	74.00	160	360	-15.87	
*	7390.782	45.13	AVG	6.02	51.15	54.00	160	360	-2.85	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.31	peak	0.71	42.02	74.00	150	30	-31.98	
*	7386.000	42.48	peak	5.99	48.47	74.00	150	100	-25.53	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.24	peak	9.27	44.51	74.00	150	30	-29.49	
*	12310.000	33.93	peak	14.62	48.55	74.00	150	215	-25.45	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.51	peak	9.27	44.78	74.00	150	40	-29.22	
*	12310.000	35.08	peak	14.62	49.70	74.00	150	105	-24.30	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11b CH11

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.

Test Mode: TX 802.11g CH1

Note:


M/N:

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	

Distance: 3m



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	42.47	peak	0.73	43.20	74.00	150	115	-30.80	
*	7236.000	43.49	peak	5.42	48.91	74.00	150	270	-25.09	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	41.43	peak	0.73	42.16	74.00	150	225	-31.84	
*	7236.000	43.09	peak	5.42	48.51	74.00	150	10	-25.49	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.60	peak	8.28	43.88	74.00	150	35	-30.12	
*	12060.000	34.98	peak	14.17	49.15	74.00	150	105	-24.85	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.80	peak	8.28	44.08	74.00	150	95	-29.92	
*	12060.000	36.36	peak	14.17	50.53	74.00	150	180	-23.47	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH1

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.30	peak	0.69	42.99	74.00	150	65	-31.01	
*	7311.000	43.45	peak	5.57	49.02	74.00	150	110	-24.98	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	43.08	peak	0.69	43.77	74.00	150	110	-30.23	
*	7311.000	41.66	peak	5.57	47.23	74.00	150	5	-26.77	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.32	peak	8.57	43.89	74.00	150	90	-30.11	
*	12185.000	33.04	peak	15.16	48.20	74.00	150	180	-25.80	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.59	peak	8.57	44.16	74.00	150	60	-29.84	
*	12185.000	33.37	peak	15.16	48.53	74.00	150	130	-25.47	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH6

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.48	peak	0.71	42.19	74.00	150	225	-31.81	
*	7386.000	41.51	peak	5.99	47.50	74.00	150	190	-26.50	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.41	peak	0.71	42.12	74.00	150	75	-31.88	
*	7386.000	41.85	peak	5.99	47.84	74.00	150	190	-26.16	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.95	peak	9.27	45.22	74.00	150	30	-28.78	
*	12310.000	35.27	peak	14.62	49.89	74.00	150	170	-24.11	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	36.37	peak	9.27	45.64	74.00	150	20	-28.36	
*	12310.000	34.79	peak	14.62	49.41	74.00	150	110	-24.59	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11g CH11

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11g CH11

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 802.11n20 CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	42.41	peak	0.73	43.14	74.00	150	160	-30.86	
*	7236.000	43.28	peak	5.42	48.70	74.00	150	30	-25.30	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4824.000	41.75	peak	0.73	42.48	74.00	150	70	-31.52	
*	7236.000	43.58	peak	5.42	49.00	74.00	150	105	-25.00	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	36.21	peak	8.28	44.49	74.00	150	70	-29.51	
*	12060.000	35.44	peak	14.17	49.61	74.00	150	110	-24.39	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9648.000	35.93	peak	8.28	44.21	74.00	150	30	-29.79	
*	12060.000	34.80	peak	14.17	48.97	74.00	150	195	-25.03	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.35	peak	0.69	43.04	74.00	150	160	-30.96	
*	7311.000	42.31	peak	5.57	47.88	74.00	150	100	-26.12	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 802.11n20 CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.15	peak	0.69	42.84	74.00	150	35	-31.16	
*	7311.000	41.51	peak	5.57	47.08	74.00	150	160	-26.92	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.34	peak	8.57	43.91	74.00	150	360	-30.09	
*	12185.000	33.65	peak	15.16	48.81	74.00	150	105	-25.19	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	34.89	peak	8.57	43.46	74.00	150	225	-30.54	
*	12185.000	34.59	peak	15.16	49.75	74.00	150	270	-24.25	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	l
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH6

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	l
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH11

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH11

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 802.11n20 CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.84	peak	0.71	42.55	74.00	150	130	-31.45	
*	7386.000	41.32	peak	5.99	47.31	74.00	150	255	-26.69	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4924.000	41.61	peak	0.71	42.32	74.00	150	10	-31.68	
*	7386.000	40.95	peak	5.99	46.94	74.00	150	180	-27.06	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.84	peak	9.27	45.11	74.00	150	20	-28.89	
*	12310.000	33.90	peak	14.62	48.52	74.00	150	5	-25.48	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH11

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9848.000	35.84	peak	9.27	45.11	74.00	150	200	-28.89	
*	12310.000	33.97	peak	14.62	48.59	74.00	150	85	-25.41	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 802.11n20 CH11

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH11

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	l
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH11

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n20 CH11

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 802.11n40 CH1

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4844.000	41.54	peak	0.71	42.25	74.00	150	70	-31.75	
*	7266.000	41.78	peak	5.46	47.24	74.00	150	105	-26.76	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4844.000	41.55	peak	0.71	42.26	74.00	150	30	-31.74	
*	7266.000	41.58	peak	5.46	47.04	74.00	150	190	-26.96	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9688.000	35.91	peak	8.31	44.22	74.00	150	35	-29.78	
*	12110.000	35.00	peak	14.75	49.75	74.00	150	160	-24.25	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9688.000	35.79	peak	8.31	44.10	74.00	150	40	-29.90	
*	12110.000	34.23	peak	14.75	48.98	74.00	150	225	-25.02	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH1

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	42.19	peak	0.69	42.88	74.00	150	70	-31.12	
*	7311.000	41.29	peak	5.57	46.86	74.00	150	225	-27.14	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4874.000	41.88	peak	0.69	42.57	74.00	150	105	-31.43	
*	7311.000	41.58	peak	5.57	47.15	74.00	150	45	-26.85	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	35.73	peak	8.57	44.30	74.00	150	30	-29.70	
*	12185.000	33.42	peak	15.16	48.58	74.00	150	10	-25.42	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9748.000	34.83	peak	8.57	43.40	74.00	150	100	-30.60	
*	12185.000	33.84	peak	15.16	49.00	74.00	150	360	-25.00	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH4

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber


Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

Test Mode: TX 802.11n40 CH4

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH7

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	l
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH7

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4904.000	41.83	peak	0.68	42.51	74.00	150	200	-31.49	
*	7356.000	41.86	peak	5.82	47.68	74.00	150	140	-26.32	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4904.000	41.09	peak	0.68	41.77	74.00	150	40	-32.23	
*	7356.000	41.50	peak	5.82	47.32	74.00	150	160	-26.68	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9808.000	35.48	peak	8.92	44.40	74.00	150	95	-29.60	
*	12260.000	34.78	peak	14.79	49.57	74.00	150	310	-24.43	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 802.11n40 CH7

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9808.000	35.22	peak	8.92	44.14	74.00	150	75	-29.86	
*	12260.000	35.06	peak	14.79	49.85	74.00	150	240	-24.15	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH7

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH7

Г	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 802.11n40 CH7

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	l
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 802.11n40 CH7

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	66.9338	42.94	peak	-13.11	29.83	40.00	100	295	-10.17	
	204.9500	43.28	peak	-10.16	33.12	43.50	100	40	-10.38	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	66.9340	48.43	peak	-13.11	35.32	40.00	100	145	-4.68	
	156.3527	36.33	peak	-8.12	28.21	43.50	100	90	-15.29	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4803.603	56.27	peak	0.75	57.02	74.00	150	115	-16.98	
*	4803.603	49.20	AVG	0.75	49.95	54.00	150	115	-4.05	
	7206.000	43.46	peak	5.38	48.84	74.00	150	185	-25.16	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4803.973	58.30	peak	0.75	59.05	74.00	150	185	-14.95	
*	4803.973	51.76	AVG	0.75	52.51	54.00	150	185	-1.49	
	7236.934	56.98	peak	5.42	62.40	74.00	175	215	-11.60	
	7236.934	38.24	AVG	5.42	43.66	54.00	175	215	-10.34	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	35.37	peak	8.25	43.62	74.00	150	35	-30.38	
*	12010.000	34.67	peak	13.50	48.17	74.00	150	170	-25.83	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	35.60	peak	8.25	43.85	74.00	150	310	-30.15	
*	12010.000	34.55	peak	13.50	48.05	74.00	150	85	-25.95	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4879.764	56.67	peak	0.69	57.36	74.00	150	60	-16.64	
*	4879.764	48.34	AVG	0.69	49.03	54.00	150	60	-4.97	
	7320.000	42.80	peak	5.62	48.42	74.00	150	115	-25.58	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4879.504	57.50	peak	0.69	58.19	74.00	150	130	-15.81	
*	4879.504	49.16	AVG	0.69	49.85	54.00	150	130	-4.15	
	7320.000	42.47	peak	5.62	48.09	74.00	150	80	-25.91	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	35.79	peak	8.64	44.43	74.00	150	315	-29.57	
*	12200.000	33.71	peak	15.24	48.95	74.00	150	60	-25.05	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	36.33	peak	8.64	44.97	74.00	150	230	-29.03	
*	12200.000	34.67	peak	15.24	49.91	74.00	150	45	-24.09	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment	l
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)		l



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m


!:over margin

Test Mode: TX 2480MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4960.000	44.05	peak	0.77	44.82	74.00	150	100	-29.18	
*	7440.000	42.34	peak	5.99	48.33	74.00	150	35	-25.67	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4961.924	57.41	peak	0.78	58.19	74.00	150	295	-15.81	
*	4961.924	50.27	AVG	0.78	51.05	54.00	150	295	-2.95	
	7440.000	42.03	peak	5.99	48.02	74.00	150	65	-25.98	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	35.59	peak	9.70	45.29	74.00	150	275	-28.71	
*	12400.000	34.32	peak	15.76	50.08	74.00	150	40	-23.92	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	35.42	peak	9.70	45.12	74.00	150	310	-28.88	
*	12400.000	33.69	peak	15.76	49.45	74.00	150	25	-24.55	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Г	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	66.9338	44.23	peak	-13.11	31.12	40.00	100	275	-8.88	
	204.9500	43.94	peak	-10.16	33.78	43.50	100	105	-9.72	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_30-1000MHz Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	31.9438	42.51	peak	-8.27	34.24	40.00	100	20	-5.76	
	156.3526	37.16	peak	-8.12	29.04	43.50	100	185	-14.46	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4804.605	56.26	peak	0.75	57.01	74.00	150	10	-16.99	
*	4804.605	46.34	AVG	0.75	47.09	54.00	150	10	-6.91	
	7206.000	44.71	peak	5.38	50.09	74.00	150	225	-23.91	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4804.819	57.93	peak	0.75	58.68	74.00	150	218	-15.32	
	4804.819	47.71	AVG	0.75	48.46	54.00	150	218	-5.54	
	7207.195	54.32	peak	5.38	59.70	74.00	150	200	-14.30	
*	7207.195	44.47	AVG	5.38	49.85	54.00	150	200	-4.15	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	36.30	peak	8.25	44.55	74.00	150	205	-29.45	
*	12010.000	34.90	peak	13.50	48.40	74.00	150	10	-25.60	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	35.70	peak	8.25	43.95	74.00	150	270	-30.05	
*	12010.000	34.79	peak	13.50	48.29	74.00	150	30	-25.71	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: **Vertical**

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2402MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4880.000	47.06	peak	0.69	47.75	74.00	150	0	-26.25	
*	7320.000	42.66	peak	5.62	48.28	74.00	150	115	-25.72	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4880.020	57.22	peak	0.69	57.91	74.00	150	142	-16.09	
*	4880.020	46.78	AVG	0.69	47.47	54.00	150	142	-6.53	
	7320.000	42.85	peak	5.62	48.47	74.00	150	190	-25.53	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	34.71	peak	8.64	43.35	74.00	150	90	-30.65	
*	12200.000	32.70	peak	15.24	47.94	74.00	150	220	-26.06	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	34.10	peak	8.64	42.74	74.00	150	145	-31.26	
*	12200.000	31.69	peak	15.24	46.93	74.00	150	20	-27.07	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2440MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4960.000	44.53	peak	0.77	45.30	74.00	150	65	-28.70	
*	7440.000	42.78	peak	5.99	48.77	74.00	150	185	-25.23	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4960.000	45.97	peak	0.77	46.74	74.00	150	300	-27.26	
*	7440.000	41.59	peak	5.99	47.58	74.00	150	5	-26.42	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	34.63	peak	9.70	44.33	74.00	150	170	-29.67	
*	12400.000	32.40	peak	15.76	48.16	74.00	150	25	-25.84	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	34.89	peak	9.70	44.59	74.00	150	70	-29.41	
*	12400.000	33.39	peak	15.76	49.15	74.00	150	215	-24.85	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

T	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel: +886-2-6606-8877 Fax: +886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Horizontal

EUT: W6M21812-18685 Power: 120 Va.c.


M/N: Distance: 3m

Test Mode: TX 2480MHz

Γ	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
M	· (MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	



Tel:+886-2-6606-8877 Fax:+886-2-6606-8875



Site: Chamber

Condition: FCC_part 15 RE-Class C_Above 1GHz_PK Polarization: Vertical

EUT: W6M21812-18685 Power: 120 Va.c.

M/N: Distance: 3m

Test Mode: TX 2480MHz

Ī	Frequency	Reading	Detector	Corr. factor	Result	Limit	Ant.Pos	Tab.Pos	Margin	Comment
Mk	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(cm)	(deg.)	(dB)	