301-14 Daessangnyeong-ri, Chowol-eup, Gwangju-si, Gyeonggi-do 464-862 Korea [TEL]+82-31-799-9500 [FAX]+82-31-799-9598

Date: December 07, 2011

Ref. No:

Subject: RADIO FREQUENCY EXPOSURE

Reference: FCC ID: UP4-GBT-T200

1 RF Exposure Limit

According to the FCC rule 1.1310, the limit for General Population/Uncontrolled exposure is 1 mW/cm² for the device operating 1 $500 \sim 100~000~MHz$.

2 EUT Description

Kind of EUT	FM Transmitter with Bluetooth module
Operating Frequency Band	□ WLAN: 2 400 MHz ~ 2 483.5 MHz
	□ WLAN: 5 180 MHz ~ 5 320 MHz / 5 500 MHz ~ 5
	700 MHz
	□ WLAN: 5 745 MHz ~ 5 825 MHz
	■ Bluetooth: 2 400 MHz ~ 2 483.5 MHz
Max. Output Power	2.30 dBm (1.698 mW)
Used Antenna	Internal PCB Antenna
Used Antenna Gain	-4.44 dBi

3 Test Result

SAR evaluation is not required for the device while its maximum output power is lower than threshold:

60/f(GHz) = 60/2.480 = 24.19 mW.

So, the device meets the RF exposure requirement.

전사-006 (Rev. 4) www.onetech.co.kr