ESTECH Co., Ltd.
Rm.1015, World Venture Center II,
426-5, Gasan-dong, Geumcheon-gu,
Seoul, 153-803, Korea
TEL: 82-2-867-3201
FAX: 82-2-867-3204

SAR Measurement Conditions for CDMA2000 1x

Handsets with EV-DO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev.O is less than 1/4dB higher than that measured in RC3(1xRTT), body SAR for Ev-Do is not required .Otherwise,SAR for Rev.O is measured on the maximum output channel at 153.6 kbps using the
body exposure configuration that reasults in the highest SAR for that channel in RC3.SAR for Rev.A is not required when the maximum average output of each channel is less than that measured in Rev.O or less than 1/4 dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corressponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in slots should be configured in the downlink for both ReV. O and Rev. A.

Band	Channel	SO2	SO2	SO55	SO55	TDSOSO32
		RC1/1	RC3/3	RC1/1	RC3/3	RC3/3
CDMA	363	24.4	24.37	24.4	24.37	24.4
	777	23.92	23.92	23.93	23.93	23.92
	1013	23.93	23.91	23.93	23.92	23.92

(OUTPUT POWER TABLE)