



TEST REPORT

Report No. : AJ010525-001 Date : 2007 May 22

Application No. : LJ210759(2)

Applicant : UNICORN MANUFACTURING LTD.
RM 2105, H.K. WORSTED MILLS IND. BUILDING,
31-39 WO TONG TSUI STREET,
KWAI CHUNG, H.K., HONG KONG

Sample Description : One(1) submitted sample(s) stated to be
Model Name : Digital Photo Frame
Model No. : DPF1102 and DPF-105
Rating : 2 x 1.5V AAA size batteries
No. of submitted sample : One (1) set(s) ***

Date Received : 2007 May 07

Test Period : 2007 May 07 – 2007 May 15

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)
ANSI C63.4 – 2003


Test Result : See attached sheet(s) from page 2 to 12.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15 Subpart B.

Remark : All two models are the same in circuitry and components. Therefore, model DPF1102 was chosen to be the representative of the test samples.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____


Danny Chui
Deputy Manager - EL. Division

FCC ID: UTF-DPF-105-01

Page 1 of 12



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

Table of Contents

| | | |
|-----|---|----|
| 1 | General Information | 3 |
| 1.1 | General Description | 3 |
| 1.2 | Related Submittal Grants | 3 |
| 1.3 | Location of the Test Site | 4 |
| 1.4 | List of Measuring Equipment..... | 5 |
| 1.5 | List of Support Equipment..... | 6 |
| 2 | Description of the radiated emission test | 7 |
| 2.1 | Test Procedure..... | 7 |
| 2.2 | Test Result..... | 7 |
| 2.3 | Radiated Emission Measurement Data | 8 |
| 3 | Description of the Line-conducted Test..... | 10 |
| 3.1 | Test Procedure..... | 10 |
| 3.2 | Test Result..... | 10 |
| 3.3 | Graph and Table of Conducted Emission Measurement Data | 10 |
| 4 | Photograph | 11 |
| 4.1 | Photographs of the Test Setup for Radiated Emission and Conduction Emission | 11 |
| 4.2 | Photographs of the External and Internal Configurations of the EUT | 11 |
| 5 | Supplementary Document..... | 11 |
| 6 | Appendices..... | 12 |



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

1 General Information

1.1 General Description

The equipment under test (EUT) is a digital photo frame for displaying photos downloaded from personal computer and powered by two 1.5V AAA size batteries. It contains 2 MB internal memory. Operating with 4 MHz, this digital photo frame has two features:

1. Photo frame (which supports .JPG and .BMP files)
2. Mass photo storage through USB2.0 interface for uploading and downloading files

The brief circuit description is listed as follows:

- IC U1 and U2 and their associated circuits act as USB connecting and data processing.
- IC U3 and its associated circuit act as data storage.
- IC U4 and its associated circuit act as Low Drop Out voltage regulator.
- IC U5 and its associated circuit act as DC to DC voltage step up.

A brief circuit description is saved with filename: OpDes.pdf

1.2 Related Submittal Grants

This is a single application for certification of a computer peripheral product.



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

1.3 Location of the Test Site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

1.4 List of Measuring Equipment

| Equipment | Manufacturer | Model No. | Serial No. |
|-------------------|--------------|-----------|------------|
| EMI Test Receiver | R&S | ESCI | 100152 |
| EMI Test Receiver | R&S | ESCS30 | 100001 |
| Bilog Antenna | Schaffner | CBL6112B | 2718 |
| LISN | R&S | ESH3-Z5 | 100010 |
| LISN | R&S | ESH3-Z5 | 100038 |



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

1.5 List of Support Equipment

1. Intel CPU P4 2.8GHz / 512k cache / 533MHz bus
Model: 9426A657
2. Intel Mother Board
Model: Intel Type: D845EPI/D845GVSR
3. Seagate Hard-disk
Model: ST340014A, 40GB
4. Proview LCD Monitor
Model: 568
5. Logitech Mouse
Model: M-S34
6. Hewlett Packard Keyboard
Model: SK-2502C
7. Hewlett Packard LaserJet 2100TN
Model: C4172A
8. PenPower Handwriting System
Model: PP403N
9. USB cable
(Provided by Applicant)



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

The device was rotated through three orthogonal to determine which attitude and configuration produce highest emission during measurement for Radiated Emission measurement.

2.2 Test Result

All modes had been tested. The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Mode: Photo Frame

| Frequency (MHz) | Polarity (H/V) | Reading at 3m (dBμV/m) | Antenna and Cable factor (dB) | Field Strength (dBμV/m) | Limit at 3m (dBμV/m) | Margin (dB) |
|--------------------|-------------------|------------------------------|-------------------------------------|-------------------------------|-------------------------|----------------|
| 32.039 | H | 5.5 | 18.5 | 24.0 | 40.0 | -16.0 |
| 48.245 | H | 11.9 | 10.6 | 22.5 | 40.0 | -17.5 |
| 50.110 | H | 14.3 | 8.4 | 22.7 | 40.0 | -17.3 |
| 56.028 | H | 13.0 | 8.4 | 21.4 | 40.0 | -18.6 |
| 64.376 | H | 17.4 | 5.8 | 23.2 | 40.0 | -16.8 |
| 72.491 | H | 16.9 | 6.0 | 22.9 | 40.0 | -17.1 |
| 80.532 | H | 14.6 | 7.3 | 21.9 | 40.0 | -18.1 |
| 82.426 | H | 15.7 | 7.3 | 23.0 | 40.0 | -17.0 |
| 86.373 | H | 15.9 | 7.3 | 23.2 | 40.0 | -16.8 |
| 87.657 | H | 16.6 | 7.3 | 23.9 | 40.0 | -16.1 |



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Mode: PC connected (USB)

| Frequency (MHz) | Polarity (H/V) | Reading at 3m (dB μ V/m) | Antenna and Cable factor (dB) | Field Strength (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------------|-------------------|------------------------------------|-------------------------------------|-------------------------------------|-------------------------------|----------------|
| 96.010 | H | 30.0 | 9.5 | 39.5 | 43.5 | -4.0 |
| 240.028 | H | 30.3 | 9.8 | 40.1 | 46.0 | -5.9 |
| 250.169 | H | 21.5 | 13.9 | 35.4 | 46.0 | -10.6 |
| 252.015 | H | 21.9 | 13.9 | 35.8 | 46.0 | -10.2 |
| 276.024 | H | 25.5 | 13.9 | 39.4 | 46.0 | -6.6 |
| 284.026 | H | 25.5 | 13.9 | 39.4 | 46.0 | -6.6 |
| 288.040 | H | 24.0 | 13.9 | 37.9 | 46.0 | -8.1 |
| 290.043 | H | 23.5 | 13.9 | 37.4 | 46.0 | -8.6 |
| 336.044 | H | 25.1 | 14.9 | 40.0 | 46.0 | -6.0 |
| 432.070 | H | 18.4 | 17.9 | 36.3 | 46.0 | -9.7 |



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The EUT is connected to PC with a USB cable in order to produce maximum emission.

The measurement data was indicated in Appendix.

It was found that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the documents are saved with filename TestRpt2.pdf.



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to Tsup5.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.

5 Supplementary Document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

| Document | Filename |
|-------------------------|-----------------|
| ID Label/Location | LabelSmp.jpg |
| Block Diagram | BlkDia.pdf |
| Schematic Diagram | Schem.pdf |
| Users Manual | UserMan.pdf |
| Operational Description | OpDes.pdf |



TEST REPORT

Report No. : AJ010525-001

Date : 2007 May 22

6 Appendices

| | | | |
|------|---|----|-------|
| A1. | Photos of the set-up of Radiated Emissions | 1 | page |
| A2. | Photos of the set-up of Conducted Emissions | 2 | pages |
| A3. | Photos of External Configurations | 1 | page |
| A4. | Photos of Internal Configurations | 1 | page |
| A5. | ID Label/Location | 1 | page |
| A6. | Conducted Emission Measurement Data | 2 | pages |
| A7. | Block Diagram | 1 | page |
| A8. | Schematics Diagram | 1 | page |
| A9. | User Manual | 10 | pages |
| A10. | Operation Description | 1 | page |

***** End of Report *****