Product code: TW06

Date: 7-2-12 Frequency: 27.145 MHz Battery: 9V 6F22 Product name: Walkie talkie

	ame: Walkie talkie		0. /	T	D 1
	P/N Material name	Description	Qty/s	Location	Remark
	components:	DCD 04V0 VD F0*9E*1 6 DOUG	0	DCD1	
1	PCB	PCB 94V0 KB, 50*25*1. 6mm ROHS	2	PCB1	
2		PCB 94V0 KB, 19*12*1. 6mm ROHS	2	PCB2	
3		PCB 94V0 KB, 16. 5*12*1.6mm ROHS	2	PCB3	
4	SMD resistors	0603 2.2K $Ω \pm 5\%$ ROHS	10	R1 R2 R5 R13 R14	
5		0603 330 Ω ± 5% RoHS	2	R3	
6		0603 100 Ω ±1% ROHS	2	R4	
7		0603 1M $Ω \pm 5\%$ 0603 ROHS	2	R6	
8		0603 8.2K $Ω ± 5% 0603$ ROHS	2	R7	
9		0603 6. 8K Ω \pm 5% 0603 ROHS	2	R8	
10		0603 18 K $Ω ± 5% 0603$ ROHS	4	R9 R11	
11		$0603 10 Ω \pm 5\% 0603 ROHS$	2	R10	
12		0603 5.6 K $Ω ± 5% 0603$ ROHS	2	R12	
13		$0603 75 Ω \pm 5\% 0603$ ROHS	2	R16	
14		$0805 2.2 Ω \pm 5\% 0805 ROHS$	2	R17	
15	SMD capacitors	0603 10NF 50V \pm 20% RoHS	2	C2	
16		$0603 \text{ 1NF50V} \pm 20\% \text{ RoHS}$	2	С9	
17		0603 39NF 50V \pm 20% RoHS	2	C1	
18		0603 500P 50V ± 5% RoHS	2	C3	
19		0805 470NF 50V±5% RoHS	2	C4	
20		0603 20NF 25V ± 20% RoHS	2	C5	
21		0603 100NF 50V±5% RoHS	4	C6 C7	
22		0603 15P 25V±20% RoHS	6	C16 C17 C8	
23		0603 82P 25V±20% RoHS	2	C10	
24		0603 3P 25V±20% RoHS	2	C11	
25		0603 68P 50V±5% RoHS	2	C12	
26		0603 502P 50V±5% RoHS	2	C15	
27		0603 33P 50V±5% RoHS	2	C13	
28		0000 301 30V <u>1</u> 0/0 KOND	2	010	
29	E-cap	220uF 16V ±20% Φ6×7 ROHS	6	C18 C20 C21	
30	E cap	100uF 16V \pm 20% Φ 5×7 ROHS	2	C19 C20 C21	
31	Crystal	27. 145MHZ ±20ppm 49-S	2	Y1	
32	Inductor	4. 7uH ±5% Q>90 0307 RoHS	2	L1	
33	Illudetor	1. 5uH ±5% Q>90 0410 RoHS	2	L2	
34	LED	Red, dia 3mm LED	2	LED1	
	LED		2	LED1 LED2	
35	CMD +	Red, dia 5mm LED			
36	SMD transistor	C380Y SOT-23 ROHS	2	Q1	
37		28D SOT-23 ROHS	2	Q2	
38	01:1	C9014 SOT-23 ROHS	2	Q3	
39	Slide siwtch	SS-23D07G4 (2P3T)	2	SW3	
40	Push siwtch	PS-42D03	2	SW1	
41	Adj inductor	K175-10T-015 (2-4-4)	2	T1	
42	Transformer	EI145	2	TK1	
43	Mylar speaker	HB-FB27075SF08F1-G1	2	SPK1	
44		r Red & black wire 130mm	2	BT±	
45	Wire	3+50+3mm Black	2	Φ3LED1-	
46		3+50+3mm Red	2	Φ3LED+	
47		3+70+3mm Red	2	Φ5LED+	
48		3+120+3mm Black	2	Ф5LED-& push sw+	
49		3+50+3mm Black	2	B-& push swl	
50		3+80+3mm Red	2	В+	
51		3+65+3mm White	2	SPK+	
52		3+60+3mm Yellow	2	SPK+	
53		3+40+3mm Black	2	SPK-	
54	Jumper wire	L=3+10+3mm	2	J1	
55	single Rubber kev	SW-2812A	2	SW1	
υυ	2 Pringre Vrinder KeA	1011 4014A	4	N/I	