

FCC TEST REPORT

according to

47 CFR Part 15 Subpart B

Equipment : Mobile Text Device
Model No. : D00111
FCC ID : UUU-L7E20070323
Filing Type : Declaration of Conformity
Applicant : **Payne LLC**
The Neumours Bldg, Suite 1414 Wilmington, Delaware 19801

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.
- Report Version: Rev. 02.

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

History of this test report.....	ii
CERTIFICATE OF COMPLIANCE.....	1
1. General Description of Equipment under Test.....	2
1.1 Applicant.....	2
1.2 Manufacturer	2
1.3 Basic Description of Equipment under Test	2
1.4 Feature of Equipment under Test	3
2. Test Configuration of Equipment under Test.....	4
2.1 Test Manner	4
2.2 Description of Test System	4
2.3 Connection Diagram of Test System	4
3. Test Software	5
4. General Information of Test.....	6
4.1 Test Facility	6
4.2 Test Voltage	6
4.3 Standard for Methods of Measurement.....	6
4.4 Test in Compliance with	6
4.5 Frequency Range Investigated	6
4.6 Test Distance	6
5. Test of Conducted Powerline	7
5.1 Major Measuring Instruments.....	7
5.2 Test Procedures	7
5.3 Typical Test Setup Layout of Conducted Powerline	8
5.4 Test Result of AC Powerline Conducted Emission	9
5.5 Photographs of Conducted Powerline Test Configuration	13
6. Test of Radiated Emission.....	14
6.1 Major Measuring Instruments.....	14
6.2 Test Procedures	15
6.3 Typical Test Setup Layout of Radiated Emission.....	16
6.4 Test Result of Radiated Emission.....	17
6.5 Photographs of Radiated Emission Test Configuration	23
7. List of Measuring Equipment Used	24
8. Uncertainty of Evaluation	25
9. Certificate of NVLAP Accreditation	27
Appendix A. Photographs of EUT	
Appendix B. Setup Photographs	

History of this test report

Report Issue Date: Jul. 09, 2007

Report No.	Description



CERTIFICATE OF COMPLIANCE


according to

47 CFR Part 15 Subpart B

Equipment : Mobile Text Device
Model No. : D00111
FCC ID : UUU-L7E20070323
Filing Type : Declaration of Conformity
Applicant : Payne LLC
The Neumours Bldg, Suite 1414 Wilmington, Delaware 19801

I **HEREBY** CERTIFY THAT:

The measurements shown in this test report were made in accordance with the procedures given in ANSI C63.4 - 2003 and the energy emitted by this equipment was *passed* FCC Part 15 B in both radiated and conducted emission class B limits. Testing was carried out on Jul. 07, 2007 at SPORTON International Inc. LAB.



Roy Wu
Manager

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. General Description of Equipment under Test

1.1 Applicant

Payne LLC

The Neumours Bldg, Suite 1414 Wilmington, Delaware 19801

1.2 Manufacturer

Hon Hai Precision Ind. Co., Ltd.

4F, No. 2, ZihYou St., Tu-Cheng City, Taipei County 236, Taiwan

1.3 Basic Description of Equipment under Test

Equipment	: Mobile Text Device
Model No.	: D00111
Power Supply Type	: Switching, From battery 3.7V
AC Power Cord	: AC 120V, Wall-mound, 1.8 meter 2 pin
Adapter	: Foxlink, FA-052000SA
Battery	: BA1001
USB Cable	: N/A

1.4 Feature of Equipment under Test

Product Feature & Specification	
1. DUT Type :	Mobile Text Device
2. Model No. :	D00111
3. Type of Modulation :	QPSK
4. Tx Frequency :	CDMA2000 Cellular 850 : 824 ~ 849 MHz CDMA2000 PCS 1900 : 1850 ~ 1910 MHz
5. Rx Frequency :	CDMA2000 Cellular 850 : 869 ~ 894 MHz CDMA2000 PCS1900 : 1930 ~ 1990 MHz
6. Maximum Output Power to Antenna :	CDMA2000 Cellular 850 (1xRTT) FCH_RC1 : 25.80 dBm FCH_RC3 : 25.89 dBm FCH+SCH_RC3 : 25.91 dBm CDMA2000 Cellular 850 (1xEV-DO) 9.6Kbps : 25.06 dBm 38.4Kbps : 25.07 dBm 153.6Kbps : 25.34 dBm CDMA2000 PCS1900 (1xRTT) FCH_RC1 : 25.81 dBm FCH_RC3 : 25.85 dBm FCH+SCH_RC3 : 25.81 dBm CDMA2000 PCS1900 (1xEV-DO) 9.6Kbps : 25.20 dBm 38.4Kbps : 25.24 dBm 153.6Kbps : 25.33 dBm
7. Type of Antenna Connector :	N/A
8. Antenna Type :	Fixed Internal
9. Power Rating (DC/AC Voltage) :	DC 5V / 2A

2. Test Configuration of Equipment under Test

2.1 Test Manner


- a. The EUT has been setup pursuant to ANSI C63.4-2003 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The complete test system refers to 2.2 for EMI test.
- c. The following test modes were tested for conduction test:
 Mode 1: CDMA2000 Cellular 850 Idle Mode + USB Link + Adapter
 Mode 2: CDMA2000 PCS1900 Idle Mode + USB Link + Adapter
- d. The following test modes were tested for radiation test:
 Mode 1: CDMA2000 Cellular 850 Idle Mode + USB Link + Adapter
 Mode 2: CDMA2000 PCS1900 Idle Mode + USB Link + Adapter
- e. Frequency range investigated: conduction 150 kHz to 30 MHz, radiation 30 MHz to 13 GHz.

2.2 Description of Test System

Item	Asset	Trade Name	Model Name	FCC ID	Power Cord
1.	Base Station	R&S	CMU 200	N/A	N/A
2.	RS-232 Mouse	State	MS-303	DoC	Weave-shielded, 1.2 m
3.	Earphone	Sony	MDR-E828	DoC	N/A
4.	USB Cable (*)	N/A	N/A	N/A	Weave-shielded, 0.8 m
5.	Notebook	DELL	D400	E2K24GBRL	N/A
6.	USB Mouse	Microsoft	B75-00093	DoC	Non-shielded, 1.8 m

* Notice: Please refer to 1.3 Basic Description of Equipment under Test.

2.3 Connection Diagram of Test System



3. Test Software

The executive program, EMCTEST.EXE under WIN XP installed in notebook, which generates a complete line of continuously repeating "H" pattern were used as the test software.

The EUT is in CDMA2000 Idle mode controlled by Base Station Simulator.

4. General Information of Test

4.1 Test Facility

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park,
Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
TEL : 886-3-327-3456
FAX : 886-3-318-0055

Test Site No. : 03CH06-HY, CO01-HY

4.2 Test Voltage

120V / 60Hz

4.3 Standard for Methods of Measurement

ANSI C63.4-2003

4.4 Test in Compliance with

FCC Part 15 Subpart B

4.5 Frequency Range Investigated

- a. Conduction: from 150 kHz to 30 MHz
- b. Radiation: from 30 MHz to 13000MHz

4.6 Test Distance

The test distance of radiated emission from antenna to EUT is 3m.

5. Test of Conducted Powerline

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 kHz and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 5.3. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


5.1 Major Measuring Instruments

As described in Chapter 7.

5.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connect to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

5.3 Typical Test Setup Layout of Conducted Powerline




5.4 Test Result of AC Powerline Conducted Emission

5.4.1 Test Mode: Mode 1


- Frequency Range of Test: from 0.15 MHz to 30 MHz
- Temperature: 25°C
- Relative Humidity: 46%
- Test Engineer: Andy
- All emissions not reported here are more than 10 dB below the prescribed limit.

The test that passed at the minimum margin was marked by a frame in the following data



Site : CO01-HY
Condition : CNS/VCCI/CISPR-B 2001/004 2006/04 LINE
EUT :
Power : 120V/60Hz
Model :
Memo : CDMA2000 850 Idle+Adapter+USB Link
Memo :
Memo :

	Freq	Level	Over	Limit	Read	Probe	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
		dBuV	dB	dBuV	dBuV	dB	dB	
1	0.209	43.37	-19.87	63.24	43.17	0.10	0.10	QP
2	0.209	36.05	-17.19	53.24	35.85	0.10	0.10	Average
3	0.275	41.39	-19.57	60.96	41.22	0.10	0.07	QP
4	0.275	36.25	-14.71	50.96	36.08	0.10	0.07	Average
5	0.344	35.02	-24.09	59.11	34.87	0.10	0.05	QP
6	0.344	31.15	-17.96	49.11	31.00	0.10	0.05	Average
7	0.830	36.86	-19.14	56.00	36.62	0.10	0.14	QP
8	0.830	28.83	-17.17	46.00	28.59	0.10	0.14	Average
9	3.824	32.99	-23.01	56.00	32.63	0.19	0.17	QP
10	3.824	26.37	-19.63	46.00	26.01	0.19	0.17	Average
11	13.620	30.18	-29.82	60.00	29.68	0.30	0.20	QP
12	13.620	22.21	-27.79	50.00	21.71	0.30	0.20	Average




Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B 2001/004 200604 NEUTRAL
 EUT :
 Power : 120V/60Hz
 Model :
 Memo : CDMA2000 850 Idle+Adapter+USB Link
 Memo :
 Memo :

	Freq	Level	Over	Limit	Read	Probe	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.203	41.39	-22.08	63.47	41.19	0.10	0.10	QP
2	0.203	32.39	-21.08	53.47	32.19	0.10	0.10	Average
3	0.275	40.75	-20.22	60.97	40.58	0.10	0.07	QP
4	0.275	36.12	-14.85	50.97	35.95	0.10	0.07	Average
5	0.752	38.09	-17.91	56.00	37.86	0.10	0.13	QP
6	0.752	32.75	-13.25	46.00	32.52	0.10	0.13	Average
7	1.110	27.02	-18.98	46.00	26.74	0.10	0.18	Average
8	1.110	35.89	-20.11	56.00	35.61	0.10	0.18	QP
9	3.880	27.41	-18.59	46.00	27.05	0.20	0.16	Average
10	3.880	33.59	-22.41	56.00	33.23	0.20	0.16	QP
11	12.320	30.87	-29.13	60.00	30.32	0.30	0.25	QP
12	12.320	24.79	-25.21	50.00	24.24	0.30	0.25	Average

5.4.2 Test Mode: Mode 2


- Frequency Range of Test: from 0.15 MHz to 30 MHz
- Temperature: 25°C
- Relative Humidity: 46%
- Test Engineer: Andy
- All emissions not reported here are more than 10 dB below the prescribed limit.

■ The test that passed at the minimum margin was marked by a frame in the following data



Site : CO01-HY
Condition : CNS/VCCI/CISPR-B 2001/004 200604 LINE
EUT :
Power : 120V/60Hz
Model :
Memo : CDMA2000 1900 Idle+Adapter+USB Link
Memo :
Memo :

	Freq	Level	Over	Limit	Read	Probe	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.207	43.35	-19.97	63.32	43.15	0.10	0.10	QP
2	0.207	36.60	-16.72	53.32	36.40	0.10	0.10	Average
3	0.276	41.03	-19.91	60.94	40.86	0.10	0.07	QP
4	0.276	35.87	-15.07	50.94	35.70	0.10	0.07	Average
5	0.345	35.28	-23.80	59.08	35.13	0.10	0.05	QP
6	0.345	31.45	-17.63	49.08	31.30	0.10	0.05	Average
7	0.739	26.96	-19.04	46.00	26.73	0.10	0.13	Average
8	0.739	36.00	-20.00	56.00	35.77	0.10	0.13	QP
9	0.826	28.83	-17.17	46.00	28.59	0.10	0.14	Average
10	0.826	37.10	-18.90	56.00	36.86	0.10	0.14	QP
11	13.480	29.97	-30.03	60.00	29.47	0.30	0.20	QP
12	13.480	21.97	-28.03	50.00	21.47	0.30	0.20	Average



Site : CO01-HY
Condition : CNS/VCCI/CISPR-B 2001/004 200604 NEUTRAL
EUT :
Power : 120V/60Hz
Model :
Memo : CDMA2000 1900 Idle+Adapter+USB Link
Memo :
Memo :

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.186	41.15	-23.06	64.21	40.96	0.10	0.09	QP
2	0.186	34.52	-19.69	54.21	34.33	0.10	0.09	Average
3	0.224	38.29	-24.37	62.66	38.10	0.10	0.09	QP
4	0.224	33.03	-19.63	52.66	32.84	0.10	0.09	Average
5	0.274	35.94	-25.07	61.01	35.77	0.10	0.07	QP
6	0.274	32.56	-18.45	51.01	32.39	0.10	0.07	Average
7	0.763	35.12	-20.88	56.00	34.89	0.10	0.13	QP
8	0.763	28.93	-17.07	46.00	28.70	0.10	0.13	Average
9	1.260	27.49	-18.51	46.00	27.20	0.10	0.19	Average
10	1.260	32.45	-23.55	56.00	32.16	0.10	0.19	QP
11	12.920	23.70	-26.30	50.00	23.21	0.26	0.23	Average
12	12.920	30.23	-29.77	60.00	29.74	0.26	0.23	QP

5.5 Photographs of Conducted Powerline Test Configuration

Please refer to Appendix B

6. Test of Radiated Emission

Radiated emissions from 30 MHz to 13 GHz were measured with a bandwidth of 120 kHz and 1MHz according to the methods defines in ANSI C63.4-2003. The EUT was placed on a nonmetallic stand, 0.8 meter above the ground plane, as shown in section 6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.


6.1 Major Measuring Instruments

As described in Chapter 7.

6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a Bi-Log antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both for horizontal polarization and vertical polarization of the antenna.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the quasi-peak method and reported.

6.3 Typical Test Setup Layout of Radiated Emission





6.4 Test Result of Radiated Emission

6.4.1 Test Mode: Mode 1

- Test Distance: 3m
- Temperature: 26°C
- Relative Humidity: 57%
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Test Engineer: Andy
- Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level

The test that passed at the minimum margin was marked by a frame in the following data






Trace: (Discrete)

Site : 03CH06-HY
 Condition : HF-ANT-060410 HORIZONTAL
 EUT :
 Power : 120Vac/60Hz
 Model :
 Memo : CDMA 850 Idle and USB Link With
 Notebook + Adaptor
 Plane : E2


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	2588.00	45.17	-28.83	74.00	46.55	30.18	3.96	35.52	---	---
2 @	4948.00	46.04	-27.96	74.00	42.94	33.40	5.93	36.23	---	---



Trace: (Discrete)

Site : 03CH06-HY
 Condition : LF-ANT(951121) VERTICAL
 EUT :
 Power : 120Vac/60Hz
 Model :
 Memo : CDMA 850 Idle and USB Link With
 Memo : Notebook + Adaptor
 Plane : E2

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	31.08	27.13	-12.87	40.00	38.97	18.95	0.64	31.43	---	---	Peak
2 @	259.23	32.01	-13.99	46.00	48.76	12.44	1.77	30.95	---	---	Peak
3 @	299.73	28.38	-17.62	46.00	44.16	13.21	1.94	30.93	---	---	Peak
4 @	514.90	32.79	-13.21	46.00	43.32	17.58	2.66	30.77	---	---	Peak
5 @	598.90	34.73	-11.27	46.00	43.99	18.45	2.95	30.66	---	---	Peak
6 @	881.70	39.70	-6.30	46.00	45.95	20.40	3.74	30.39	100	139	Peak



Trace: (Discrete)


Site : 03CH06-HY
 Condition : HF-ANT-060410 VERTICAL
 EUT :
 Power : 120Vac/60Hz
 Model :
 Memo : CDMA 850 Idle and USB Link With
 Memo : Notebook + Adaptor
 Plane : E2


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2928.00	44.56	-29.44	74.00	46.11	29.72	4.24	35.51	---	---	Peak
2 @	4978.00	45.76	-28.24	74.00	42.53	33.53	5.94	36.25	---	---	Peak

6.4.2 Test Mode: Mode 2

- Test Distance: 3m
- Temperature: 26°C
- Relative Humidity: 57%
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Test Engineer: Andy
- Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level

The test that passed at the minimum margin was marked by a frame in the following data





Remark: The spurious emission above 1 GHz is too low to be taken.

6.5 Photographs of Radiated Emission Test Configuration

Please refer to Appendix B

7. List of Measuring Equipment Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
EMC Receiver	R&S	ESCS 30	100132	9kHz – 2.75GHz	Jul. 04, 2007	Jul. 04, 2008	Conduction (CO01-HY)
LISN	MessTec	NNB-2/16Z	2001/004	9kHz – 30MHz	Mar. 30, 2007	Mar. 30, 2008	Conduction (CO01-HY)
LISN (Support Unit)	MessTec	NNB-2/16Z	2001/009	9kHz – 30MHz	Mar. 30, 2007	Mar. 30, 2008	Conduction (CO01-HY)
EMI Filter	LINDGREN	LRE-2060	1004	< 450Hz	N/A	N/A	Conduction (CO01-HY)
EMI Filter	LINDGREN	N6006	201052	0 – 60Hz	N/A	N/A	Conduction (CO01-HY)
RF Cable-CON	Suhner Switzerland	RG223/U	CB029	9kHz – 30MHz	Dec. 04, 2006	Dec. 04, 2007	Conduction (CO01-HY)
Isolation Transformer	Erika Fiedler OHG	D-65396 Walluf	58	45MHz-2.15GHz	N/A	N/A	Conduction (CO01-HY)
Spectrum analyzer	Agilent	E4408B	MY44211030	9KHz-26.5GHz	Oct. 05, 2006	Oct. 04, 2007	Radiation (03CH06-HY)
EMI Test Receiver	R&S	ESCS30	100356	9KHz-2.75GHz	Jul. 13, 2006	Jul. 12, 2007	Radiation (03CH06-HY)
Bilog Antenna	SCHAFFNER	CBL6112B	2885	30MHz -2GHz	Nov. 20, 2006	Nov. 19, 2007	Radiation (03CH06-HY)
Double Ridge Horn Antenna	Com-Power	AH118	071025	1G~18G	Jun. 04, 2007	Jun. 04, 2008	Radiation (03CH06-HY)
SHF-EHF Horn	SCHWARZBEC K	BBHA 9170	9170-249	14G - 40G	Nov. 20, 2006	Nov. 19, 2008	Radiation (03CH06-HY)
Pre Amplifier	Agilent	8449B	3008A01917	1G - 26.5G	Nov. 15, 2006	Nov. 14, 2007	Radiation (03CH06-HY)
Pre Amplifier	Mini Circuits	ZKL-2	D092004-1	10~2500MHz	Nov. 15, 2006	Nov. 14, 2007	Radiation (03CH06-HY)
Base Station Simulator	R & S	CMU200	106656	WCDMA	Nov. 20, 2006	Nov. 19, 2007	Radiation (03CH06-HY)
Controller	INN-CO	CO2000	N/A	N/A	N/A	N/A	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0 ~ 360 degree	N/A	N/A	Radiation (03CH06-HY)
Antenna Mast	INN-CO	MM3000	114/8000604/L	1 m - 4 m	N/A	N/A	Radiation (03CH06-HY)

8. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.10	Normal(k=2)	0.05
Cable loss	0.10	Normal(k=2)	0.05
AMN insertion loss	2.50	Rectangular	0.63
Receiver Spec	1.50	Rectangular	0.43
Site imperfection	1.39	Rectangular	0.80
Mismatch	+0.34/-0.35	U-shape	0.24
combined standard uncertainty Uc(y)	1.13		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.26		

Uncertainty of Radiated Emission Measurement (30MHz ~ 1000MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.41	Normal(k=2)	0.21
Antenna factor calibration	0.83	Normal(k=2)	0.42
Cable loss calibration	0.25	Normal(k=2)	0.13
Pre Amplifier Gain calibration	0.27	Normal(k=2)	0.14
RCV/SPA specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site imperfection	1.43	Rectangular	0.83
Mismatch	+0.39/-0.41	U-shaped	0.28
combined standard uncertainty Uc(y)	1.27		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.54		

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Contribution	Uncertainty of x_i		$u(x_i)$	C_i	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	±0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	±1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	±0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2 * \Gamma_3)$	+0.34/-0.35	U-shaped	0.244	1	0.244
Combined standard uncertainty Uc(y)	2.36				
Measuring uncertainty for a level of confidence of 95% U=2Ue(y)	4.72				

9. Certificate of NVLAP Accreditation

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 200079-0

Sporton International, Inc. Hwa Ya EMC Laboratory

Tao Yuan Hsien 333

TAIWAN

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communique dated 18 June 2005).*

2007-01-01 through 2007-12-31

Effective dates




For the National Institute of Standards and Technology