

Test Report No.: FM191012N030

# RF EXPOSURE REPORT

Applicant	Amazon.com Services Inc.
Address	410 Terry Avenue North Seattle, United States, WA 98109

Manufacturer or Supplier	TCL Technoly Electronics(Huizhou) Co., Ltd.
Address	Section 37, Zhongkai High-tech Development Zone, Huizhou City, Guang Dong Province, China, 516006.
Product	Echo Wall Clock ME
Brand Name	Amazon
Model	C8G55Z
Additional Model & Model Difference	KL6G3L, see section 1
Date of tests	Oct. 12, 2019 ~ Oct. 26, 2019

- FCC Part 2 (Section 2.1091)
- **KDB 447498 D01**
- **⊠** IEEE C95.1

#### CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Tom Chen	Approved by Glyn He
Project Engineer / EMC Department	Assistant Manager/ EMC Department

Date: Nov. 13, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/">http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## **Table of Contents**

RELE	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6	CALCULATION RESULT OF MAXIMUM CONDUCTED DOWER	6

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



## **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM191012N030	Original release	Nov. 13, 2019

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



Test Report No.: FM191012N030

## 1. CERTIFICATION

FCC ID:	UUU-8459		
PRODUCT:	Echo Wall Clock ME		
BRAND NAME: Amazon			
MODEL NO.: C8G55Z			
ADDITIONAL NO.:	D.: KL6G3L		
APPLICANT: Amazon.com Services Inc.			
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01		
	IEEE C95.1		

#### NOTES:

1. Additional model KL6G3L is identical with the test model C8G55Z except the appearance and model number for marketing purpose.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



## 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY ELECTRIC FIELD MAGNETIC FIELD POWER DENSITY AVERAGE TO STRENGTH (V/m) STRENGTH (A/m) (mW/cm²) (minutes)						
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

### 3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

### 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: FM191012N030

### 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	2.89	PCB Antenna

## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

The tailed conducted twendage i ewer (decided by elient)						
Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)	
GFSK	2402-2480	4	+-1	3	5	
8DPSK	2402-2480	2	+-1	1	3	
BLE-GFSK	2402-2480	3	+-1	2	4	

The measured conducted Average Power

- monomore contention monega is a mar				
Mode	Frequency (MHz)	Averaged Power (dBm)		
GFSK	2402	3.58		
8DPSK	2402	2.02		
BLE-GFSK	2480	3.64		

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2402-2480	5	2.89	20	0.001224	1.0

--- END ---

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080