

FCC PART 15, SUBPART B and C TEST REPORT

for

TRANSMITTER, REMOTE CONTROL MODEL: MiE

Prepared for

JLCOOPER ELECTRONICS, INC. 142 ARENA STREET EL SEGUNDO, CALIFORNIA 90245-3901

Prepared by:

KYLE FUJIMOTO

Approved by: James Rom

JAMES ROSS

COMPATIBLE ELECTRONICS INC. 114 OLINDA DRIVE BREA, CALIFORNIA 92823 (714) 579-0500

DATE: DECEMBER 19, 2006

	REPORT	APPENDICES			TOTAL		
	BODY	A	В	C	D	E	
PAGES	16	2	2	2	12	11	45

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



TABLE OF CONTENTS

Sectio	n / Title	PAGE
GENEI	RAL REPORT SUMMARY	4
SUMM	ARY OF TEST RESULTS	4
1.	PURPOSE	5
2.	ADMINISTRATIVE DATA	6
2.1	Location of Testing	6
2.2	Traceability Statement	6
2.3	Cognizant Personnel	6
2.4	Date Test Sample was Received	6
2.5	Disposition of the Test Sample	6
2.6	Abbreviations and Acronyms	6
3.	APPLICABLE DOCUMENTS	7
4.	DESCRIPTION OF TEST CONFIGURATION	8
4.1	Description Of Test Configuration - EMI	8
4.1.		9
5.	LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1	EUT and Accessory List	10
5.2	EMI Test Equipment	11
6.	TEST SITE DESCRIPTION	12
6.1	Test Facility Description	12
6.2	EUT Mounting, Bonding and Grounding	12
7.	TEST PROCEDURES	13
7 . 7.1		13
7.1	Radiated Emissions (Spurious and Harmonics) Test Radiated Emissions (Spurious and Harmonics) Test (continued)	13
7.2	Bandwidth of the Fundamental	15
1.3	Dandwidth of the Fulldamental	13
8.	CONCLUSIONS	16

LIST OF APPENDICES

APPENDIX	TITLE		
A	Laboratory Recognitions		
В	Modifications to the EUT		
С	Additional Models Covered Under This Report		
D	Diagrams, Charts, and Photos		
	Test Setup Diagrams		
	Radiated Emissions Photos		
	Antenna and Effective Gain Factors		
Е	Data Sheets		

LIST OF FIGURES

FIGURE	TITLE
1	Plot Map And Layout of 3 Meter Radiated Site

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used to claim product endorsement by NVLAP, NIST or any other agency of the U.S. Government.

Device Tested: Transmitter, Remote Control

Model: MiE S/N: N/A

Product Description: See Expository Statement.

Modifications: The EUT was not modified in order to meet the specifications.

Manufacturer: JLCooper Electronics, Inc.

142 Arena Street

El Segundo, California 90245-3901

Test Date: December 13, 2006

Test Specifications: EMI requirements

CFR Title 47, Part 15 Subpart B; and Subpart C, Sections 15.205, 15.209 and 15.231

Test Procedure: ANSI C63.4

Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 150 kHz – 30 MHz	This test was not performed because the EUT is battery powered only and does not connect to the AC public mains.
2	Radiated RF Emissions, 10 kHz – 4400 MHz	Complies with the Class B limits of CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.231.

Model: MiE

PURPOSE 1.

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the Transmitter, Remote Control, Model: MiE. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the Class B specification limits defined by CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.231.

Report Number: B61213B1



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The EMI tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

JLCooper Electronics, Inc.

Chuck Thompson Vice President Joe Uribe Engineer

Compatible Electronics, Inc.

Kyle Fujimoto Test Engineer James Ross Test Engineer

2.4 Date Test Sample was Received

The test sample was received on December 13, 2006

2.5 Disposition of the Test Sample

The sample was returned to JLCooper Electronics, Inc. on December 20, 2006.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF Radio Frequency

EMI Electromagnetic Interference

EUT Equipment Under Test

P/N Part Number S/N Serial Number HP Hewlett Packard

ITE Information Technology Equipment

CML Corrected Meter Limit

LISN Line Impedance Stabilization Network

PCB Printed Circuit Board



3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this EMI Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

Report Number: B61213B1

I. DESCRIPTION OF TEST CONFIGURATION

4.1 Description Of Test Configuration - EMI

Setup and operation of the equipment under test.

Specifics of the EUT and Peripherals Tested

The Transmitter, Remote Control Model: MiE (EUT) was tested as a stand-alone unit and continuously transmitting. The EUT's antenna is hard wired into the PCB. The EUT was tested in three orthogonal axis.

After the EUT is activated by pressing the button, the transmission will cease operation immediately once the button is released.

The final radiated data was taken in the mode above. Please see Appendix E for the data sheets.

4.1.1 Cable Construction and Termination

There were no external cables connected to the EUT.



5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT

5.1 EUT and Accessory List

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL	FCC ID
			NUMBER	
TRANSMITTER,	JLCOOPER	MiE	N/A	UUVMIE
REMOTE CONTROL	ELECTRONICS, INC.			
(EUT)				



5.2 EMI Test Equipment

EQUIPMENT TYPE	MANU- FACTURER	MODEL NUMBER	SERIAL NUMBER	CALIBRATION DATE	CALIBRATION DUE DATE	
GENERAL TEST EQUIPMENT USED FOR ALL RF EMISSIONS TESTS						
EMI Receiver	Rohde & Schwarz	ESIB40	100194	November 18, 2005	Nov. 18, 2007	
Computer	Hewlett Packard	4530	US91912319	N/A	N/A	
Monitor	Hewlett Packard	D5258A	TW74500641	N/A	N/A	
	RF RA	DIATED EMIS	SIONS TEST EQ	QUIPMENT		
Radiated Emissions Data Capture Program	Compatible Electronics	2.0	N/A	N/A	N/A	
Loop Antenna	Com-Power	AL-130	17089	September 21, 2005	Sept. 21, 2007	
Biconical Antenna	Com-Power	AB-900	15227	March 9, 2006	March 9, 2007	
Log Periodic Antenna	Com-Power	AL-100	16060	July 17, 2006	July 17, 2007	
Preamplifier	Com-Power	PA-102	1017	January 19, 2006	Jan. 19, 2007	
Horn Antenna	Antenna Research	DRG-118/A	1053	March 6, 2006	March 6, 2008	
Microwave Preamplifier	Com Power	PA-122	181917	January 20, 2006	Jan. 20, 2007	
Antenna Mast	Com Power	AM-100	N/A	N/A	N/A	

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 and 7.1 of this report for EMI test location.

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

The EUT was not grounded.

7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 Radiated Emissions (Spurious and Harmonics) Test

The EMI Receiver was used as a measuring meter along with the quasi-peak adapter. Amplifiers were used to increase the sensitivity of the instrument. The Com-Power Preamplifier Model: PA-102 was used for frequencies from 30 MHz to 1 GHz, and the Com-Power Microwave Preamplifier Model: PA-122 was used for frequencies from 1 GHz to 4.4 GHz. The EMI Receiver was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the EMI Receiver records the highest measured reading over all the sweeps.

The readings were averaged by a "duty cycle correction factor", derived from 20 log (dwell time / one pulse train with blanking interval).

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
9 kHz to 150 kHz	200 Hz	Active Loop Antenna
150 kHz to 30 MHz	9 kHz	Active Loop Antenna
30 MHz to 300 MHz	120 kHz	Biconical Antenna
300 MHz to 1 GHz	120 kHz	Log Periodic Antenna
1 GHz to 4.4 GHz	1 MHz	Horn Antenna

The open field test site of Compatible Electronics, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.4. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna in order to ensure accurate results. The loop antenna was also rotated in the horizontal and vertical axis in order to ensure accurate results.

7.2 Radiated Emissions (Spurious and Harmonics) Test (continued)

The presence of ambient signals was verified by turning the EUT off. In case an ambient signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the ambient signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance to obtain final test data. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with the **Class B** limits of CFR Title 47, Part 15, Subpart B; and CFR Title 47, Part 15, Subpart C, sections 15.205, 15.209, and 15.231.

7.3 Bandwidth of the Fundamental

The -20 dB bandwidth was checked to see that it was within 0.25% of the fundamental frequency for the EUT. Plots of the -20 dB bandwidth are located in Appendix E.

Test Results:

The EUT complies with the requirements of CFR Title 47, Part 15, Subpart C, section 15.231 (c) for the -20 dB bandwidth of the fundamental. The EUT has a -20dB bandwidth that is less than 0.25% of frequency of the fundamental.

8. CONCLUSIONS

The Transmitter, Remote Control, Model: MiE meets all of the **Class B** specification limits defined in CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.231.



APPENDIX A

LABORATORY RECOGNITIONS

LABORATORY RECOGNITIONS

Compatible Electronics has the following agency accreditations:

National Voluntary Laboratory Accreditation Program - Lab Code: 200528-0

Voluntary Control Council for Interference - Registration Numbers: R-983, C-1026, R-984 and C-1027

Bureau of Standards and Metrology Inspection - Reference Number: SL2-IN-E-1031

Conformity Assessment Body for the EMC Directive Under the US/EU MRA Appointed by NIST

Compatible Electronics is recognized or on file with the following agencies:

Federal Communications Commission

Industry Canada

Radio-Frequency Technologies (Competent Body)

APPENDIX B

MODIFICATIONS TO THE EUT

MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC 15.231 or FCC Class B specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT.

APPENDIX C

ADDITIONAL MODELS COVERED UNDER THIS REPORT



ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Transmitter, Remote Control Model: MiE S/N: N/A

There were no additional models covered under this report.



APPENDIX D


DIAGRAMS, CHARTS, AND PHOTOS

OPEN LAND > 15 METERS



FIGURE 1: PLOT MAP AND LAYOUT OF 3 METER RADIATED SITE

OPEN LAND > 15 METERS



OPEN LAND > 15 METERS

X = GROUND RODS = GROUND SCREEN

D = TEST DISTANCE (meters) = WOOD COVER

COM-POWER AB-900

BICONICAL ANTENNA

S/N: 15227

CALIBRATION DATE: MARCH 9, 2006

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	11.12	120	13.50
35	10.17	125	12.63
40	9.75	140	12.20
45	12.22	150	11.85
50	13.28	160	13.25
60	11.36	175	15.74
70	7.95	180	16.23
80	5.95	200	16.79
90	7.62	250	16.47
100	10.89	300	17.49



COM-POWER AL-100

LOG PERIODIC ANTENNA

S/N: 16060

CALIBRATION DATE: JULY 17, 2006

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
300	13.58	700	20.49
400	14.53	800	20.13
500	15.36	900	22.15
600	18.29	1000	22.76

COM-POWER PA-102

PREAMPLIFIER

S/N: 1017

CALIBRATION DATE: JANUARY 19, 2006

ī			
FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	38.3	300	38.4
40	38.4	350	38.4
50	38.3	400	38.0
60	38.4	450	38.1
70	38.5	500	37.5
80	38.4	550	38.0
90	38.4	600	38.0
100	38.4	650	37.7
125	38.1	700	37.7
150	38.5	750	37.7
175	38.4	800	37.0
200	38.3	850	37.2
225	38.3	900	36.6
250	38.1	950	36.3
275	38.3	1000	36.3



COM-POWER PA-122

PREAMPLIFIER

S/N: 181917

CALIBRATION DATE: JANUARY 20, 2006

	r		
FREQUENCY	FACTOR	FREQUENCY	FACTOR
(GHz)	(dB)	(GHz)	(dB)
1.0	34.697	10.0	36.558
1.5	33.817	10.5	35.048
2.0	33.587	11.0	33.258
2.5	33.804	11.5	32.960
3.0	33.850	12.0	33.312
3.5	33.943	12.5	33.836
4.0	34.399	13.0	34.178
4.5	34.847	13.5	34.197
5.0	35.172	14.0	33.769
5.5	35.383	14.5	33.392
6.0	35.539	15.0	33.387
6.5	34.802	15.5	34.038
7.0	33.793	16.0	34.884
7.5	33.511	16.5	35.740
8.0	33.910	17.0	35.341
8.5	34.907	17.5	34.729
9.0	36.036	18.0	33.760
9.5	36.661		

ANTENNA RESEARCH DRG-118/A

HORN ANTENNA

S/N: 1053

CALIBRATION DATE: MARCH 6, 2006

FREQUENCY	FACTOR	FREQUENCY	FACTOR
(GHz)	(dB)	(GHz)	(dB)
1.0	24.46	10.0	39.55
1.5	25.05	10.5	39.86
2.0	28.42	11.0	38.49
2.5	29.91	11.5	40.71
3.0	31.46	12.0	40.59
3.5	31.91	12.5	40.17
4.0	31.55	13.0	39.70
4.5	31.94	13.5	40.84
5.0	32.90	14.0	41.58
5.5	34.07	14.5	45.14
6.0	35.69	15.0	42.20
6.5	33.11	15.5	39.42
7.0	36.51	16.0	38.80
7.5	37.27	16.5	41.08
8.0	37.21	17.0	44.11
8.5	37.16	17.5	46.29
9.0	38.27	18.0	41.61
9.5	39.73		



COM-POWER AL-130

LOOP ANTENNA

S/N: 17089

CALIBRATION DATE: SEPTEMBER 21, 2005

FREQUENCY	MAGNETIC	ELECTRIC
(MHz)	(dB/m)	(dB/m)
0.009	-42.84	8.66
0.01	-41.93	9.57
0.02	-41.29	10.21
0.05	-42.37	9.13
0.07	-41.8	9.7
0.1	-41.83	9.67
0.2	-44.13	7.37
0.3	-41.73	9.77
0.5	-41.8	9.7
0.7	-41.53	9.97
1	-41.46	10.04
2	-41.14	10.36
3	-41.26	10.24
4	-41.46	10.04
5	-41.10	10.40
10	-40.83	10.67
15	-41.47	10.03
20	-35.44	16.06
25	-42.37	9.13
30	-42.94	8.56




FRONT VIEW

JLCOOPER ELECTRONICS, INC.
TRANSMITTER, REMOTE CONTROL
MODEL: MiE
FCC SUBPART B AND FCC SUBPART C – RADIATED EMISSIONS – LAB B




REAR VIEW

JLCOOPER ELECTRONICS, INC.
TRANSMITTER, REMOTE CONTROL
MODEL: MiE
FCC SUBPART B AND FCC SUBPART C – RADIATED EMISSIONS – LAB B



FRONT VIEW

JLCOOPER ELECTRONICS, INC.
TRANSMITTER, REMOTE CONTROL
MODEL: MiE
FCC SUBPART B AND FCC SUBPART C – RADIATED EMISSIONS – LAB D



REAR VIEW

JLCOOPER ELECTRONICS, INC.
TRANSMITTER, REMOTE CONTROL
MODEL: MiE
FCC SUBPART B AND FCC SUBPART C – RADIATED EMISSIONS – LAB D

APPENDIX E

DATA SHEETS

RADIATED EMISSIONS

DATA SHEETS

JL Cooper Electronics Date: 12/13/06 Transmitter, Remote Control Labs: B and D

Model: MiE Tested By: Kyle Fujimoto

Duty Cycle: 100%

X-Axis

					Peak /	Ant.	Table	
Freq.	Level				QP/	Height	Angle	
(MHz)	(dBuV)	Pol (v/h)	Limit	Margin	Avg	(m)	(deg)	Comments
433.92	69.36	V	100.82	-31.46	Peak	1	135	
433.92	69.36	V	80.82	-11.46	Avg	1	135	
867.84	47.28	V	80.82	-33.54	Peak	1	135	
867.84	47.28	V	60.82	-13.54	Avg	1	135	
1301.76	28.78	V	74	-45.22	Peak	1.99	315	
1301.76	28.78	V	54	-25.22	Avg	1.99	315	
1735.68	35.73	V	80.82	-45.09	Peak	1.42	45	
1735.68	35.73	V	60.82	-25.09	Avg	1.42	45	
0.1.00.0	00.00		00.00	44.40		4.04		
2169.6	36.63	V	80.82	-44.19	Peak	1.64	90	
2169.6	36.63	V	60.82	-24.19	Avg	1.64	90	
2002 50	25.42	W	00.00	45.4	Daale	0.00	00	
2603.52	35.42	V	80.82	-45.4	Peak	2.02	90	
2603.52	35.42	V	60.82	-25.4	Avg	2.02	90	
3037.44	43.01	V	80.82	-37.81	Peak	1.89	180	
3037.44	43.01	V	60.82	-37.81		1.89	180	
3037.44	43.01	V	00.02	-17.01	Avg	1.09	100	
3471.36	39.11	V	80.82	-41.71	Peak	1.11	135	
3471.36	31.68	V	60.82	-29.14	Avg	1.11	135	
347 1.30	31.00	V	00.02	-23.14	Avg	1.11	155	
3905.28	40.85	V	74	-33.15	Peak	1.12	225	
3905.28	40.85	V	54	-13.15	Avg	1.12	225	
5000.20	10.00	•	5.	10.10	,,,,	1.12	220	
4339.2	41.53	V	74	-32.47	Peak	1.13	180	
4339.2	41.53	V	54	-12.47	Avg	1.13	180	
					,			

JLCooper Electronics Transmitter, Remote Control

Model: MiE

Date: 12/13/06 Labs: B and D

Tested By: Kyle Fujimoto

Duty Cycle: 100%

X-Axis

5	11				Peak /	Ant.	Table	
Freq.	Level	5 1 (//)	,		QP/	Height	Angle	
(MHz)	(dBuV)	Pol (v/h)		Margin	Avg	(m)	(deg)	Comments
433.92	80.66	Н	100.82	-20.16	Peak	1	270	
433.92	80.66	Н	80.82	-0.16	Avg	1	270	
207.24	00.00		22.22					
867.84	29.29	Н	80.82	-51.53	Peak	1.5	225	
867.84	29.29	Н	60.82	-31.53	Avg	1.5	225	
1001 70	00.50		7.4	40.44	D I	4.40	400	
1301.76	30.56	H	74	-43.44	Peak	1.42	180	
1301.76	30.56	Н	54	-23.44	Avg	1.42	180	
4705.00	25.70		00.00	45.4	Daala	4.40	00	
1735.68	35.72	H	80.82	-45.1	Peak	1.43	90	
1735.68	35.72	Н	60.82	-25.1	Avg	1.43	90	
0460.6	42.27	- 11	00.00	27.45	Peak	1 10	00	
2169.6	43.37	H	80.82	-37.45		1.43	90	
2169.6	43.37	П	60.82	-17.45	Avg	1.43	90	
2603.52	36.99	Н	80.82	-43.83	Peak	1.43	225	
2603.52	36.99	Н	60.82	-43.83		1.43	225	
2003.32	30.99	П	00.02	-23.63	Avg	1.43	223	
3037.44	42.36	Н	80.82	-38.46	Peak	1.48	125	
3037.44	42.36	Н	60.82	-18.46	Avg	1.48	125	
0007.11	12.00	• •	00.02	10.10	7.179	1.10	120	
3471.36	39.98	Н	80.82	-40.84	Peak	1.41	125	
3471.36	39.98	Н	60.82	-20.84	Avg	1.41	125	
3905.28	42.69	Н	74	-31.31	Peak	1.35	225	
3905.28	42.69	Н	54	-11.31	Avg	1.35	225	
4339.2	41.97	Н	74	-32.03	Peak	1.42	135	
4339.2	34.03	Н	54	-19.97	Avg	1.42	135	

JLCooper Electronics Date: 12/13/06 Transmitter, Remote Control Labs: B and D

Model: MiE Tested By: Kyle Fujimoto

Duty Cycle: 100%

Y-Axis

					Peak /	Ant.	Table	
Freq.	Level				QP/	Height	Angle	
(MHz)	(dBuV)	Pol (v/h)	Limit	Margin	Avg	(m)	(deg)	Comments
433.92	79.46	V	100.82	-21.36	Peak	1.1	135	
433.92	79.46	V	80.82	-1.36	Avg	1.1	135	
867.84	47.98	V	80.82	-32.84	Peak	1.25	90	
867.84	47.98	V	60.82	-12.84	Avg	1.25	90	
1301.76	30.69	V	74	-43.31	Peak	1.12	135	
1301.76	30.69	V	54	-23.31	Avg	1.12	135	
1735.68	34.71	V	80.82	-46.11	Peak	1.12	135	
1735.68	34.71	V	60.82	-26.11	Avg	1.12	135	
2169.6	44.96	V	80.82	-35.86	Peak	1.55	135	
2169.6	44.96	V	60.82	-15.86	Avg	1.55	135	
2603.52	38.66	V	80.82	-42.16	Peak	1.38	180	
2603.52	38.66	V	60.82	-22.16	Avg	1.38	180	
3037.44	44.11	V	80.82	-36.71	Peak	1.55	225	
3037.44	36.17	V	60.82	-24.65	Avg	1.55	225	
0.474.60	44.46		00.00	00.00	D 1	4.05	405	
3471.36	41.49	V	80.82	-39.33	Peak	1.25	135	
3471.36	41.49	V	60.82	-19.33	Avg	1.25	135	
2005.00	40.00	\/	7.4	20.07	Dest	4 4 4	005	
3905.28	43.33	V	74	-30.67	Peak	1.14	225	
3905.28	43.33	V	54	-10.67	Avg	1.14	225	
4220.2	42 FO	W	71	20.44	Dools	1.12	125	
4339.2 4339.2	43.59	V	74 54	-30.41	Peak		135	
4339.2	43.59	V	54	-10.41	Avg	1.12	135	

JLCooper Electronics Transmitter, Remote Control

Model: MiE

Date: 12/13/06 Labs: B and D

Tested By: Kyle Fujimoto

Duty Cycle: 100% **Y-Axis**

					Peak /	Ant.	Table	
Freq.	Level				QP/	Height	Angle	
(MHz)	(dBuV)	Pol (v/h)	Limit	Margin	Avg	(m)	(deg)	Comments
433.92	67.96	Н	100.82	-32.86	Peak	1	135	
433.92	67.96	Н	80.82	-12.86	Avg	1	135	
867.84	36.79	Н	80.82	-44.03	Peak	1	0	
867.84	36.79	Н	60.82	-24.03	Avg	1	0	
1301.76	30.91	Н	74	-43.09	Peak	1.25	135	
1301.76	30.91	Н	54	-23.09	Avg	1.25	135	
1735.68	37.53	Н	80.82	-43.29	Peak	1.29	45	
1735.68	37.53	Н	60.82	-23.29	Avg	1.29	45	
2169.6	44.61	Н	80.82	-36.21	Peak	1.31	225	
2169.6	44.61	Н	60.82	-16.21	Avg	1.31	225	
2603.52	39.44	Н	80.82	-41.38	Peak	1.31	225	
2603.52	39.44	Н	60.82	-21.38	Avg	1.31	225	
3037.44	41.04	Н	80.82	-39.78	Peak	1.09	125	
3037.44	41.04	Н	60.82	-19.78	Avg	1.09	125	
3471.36	40.12	Н	80.82	-40.7	Peak	1.25	135	
3471.36	40.12	Н	60.82	-20.7	Avg	1.25	135	
3905.28	42.93	Н	74	-31.07	Peak	1.41	180	
3905.28	42.93	Н	54	-11.07	Avg	1.41	180	
4339.2	43.78	Н	74	-30.22	Peak	1.36	135	
4339.2	43.78	Н	54	-10.22	Avg	1.36	135	

JLCooper Electronics Date: 12/13/06 Transmitter, Remote Control Labs: B and D

Model: MiE Tested By: Kyle Fujimoto

Duty Cycle: 100%

Z-Axis

					Peak /	Ant.	Table	
Freq.	Level				QP/	Height	Angle	
(MHz)	(dBuV)	Pol (v/h)	Limit	Margin	Avg	(m)	(deg)	Comments
433.92	72.66	V	100.82	-28.16	Peak	1	90	
433.92	72.66	V	80.82	-8.16	Avg	1	90	
867.84	49.46	V	80.82	-31.36	Peak	1	90	
867.84	49.46	V	60.82	-11.36	Avg	1	90	
1301.76	29.47	V	74	-44.53	Peak	1.35	225	
1301.76	29.47	V	54	-24.53	Avg	1.35	225	
1735.68	35.26	V	80.82	-45.56	Peak	1.46	180	
1735.68	35.26	V	60.82	-25.56	Avg	1.46	180	
2169.6	42.61	V	80.82	-38.21	Peak	1.42	180	
2169.6	42.61	V	60.82	-18.21	Avg	1.42	180	
2000 50	00.04		22.22	40.00	<u> </u>	4.40	405	
2603.52	36.94	V	80.82	-43.88	Peak	1.42	135	
2603.52	36.94	V	60.82	-23.88	Avg	1.42	135	
0007.44	40.00	\ /	00.00	07.00	D I -	4.05	00	
3037.44	42.83	V	80.82	-37.99	Peak	1.25	90	
3037.4	42.823	V	60.82	-17.997	Avg	1.25	90	
3471.36	41.64	V	80.82	-39.18	Peak	1.67	135	
3471.36	41.64	V	60.82	-39.18	Avg	1.67	135	
347 1.30	41.04	V	00.02	-13.10	Avy	1.07	133	
3905.28	42.22	V	74	-31.78	Peak	1.46	90	
3905.28	42.22	V	54	-11.78	Avg	1.46	90	
0000.20	76.66	v	<u> </u>	11.70	, .vg	1.70	30	
4339.2	42.85	V	74	-31.15	Peak	1.43	90	
4339.2	42.85	V	54	-11.15	Avg	1.43	90	
.550.2		·			9		- 55	
<u> </u>								

JLCooper Electronics Transmitter, Remote Control

Model: MiE

Date: 12/13/06 Labs: B and D

Tested By: Kyle Fujimoto

Duty Cycle: 100%

Z-Axis

_					Peak /	Ant.	Table	
Freq.	Level				QP/	Height	Angle	_
(MHz)	(dBuV)	Pol (v/h)		Margin	Avg	(m)	(deg)	Comments
433.92	76.76	Н	100.82	-24.06	Peak	1	270	
433.92	76.76	Н	80.82	-4.06	Avg	1	270	
867.84	37.89	Н	80.82	-42.93	Peak	1.5	90	
867.84	37.89	Н	60.82	-22.93	Avg	1.5	90	
1301.76	30.63	Н	74	-43.37	Peak	2.26	135	
1301.76	30.63	Н	54	-23.37	Avg	2.26	135	
1735.68	35.62	Н	80.82	-45.2	Peak	1.36	180	
1735.68	35.62	Н	60.82	-25.2	Avg	1.36	180	
2169.6	42.96	H	80.82	-37.86	Peak	1.56	180	
2169.6	42.96	Н	60.82	-17.86	Avg	1.56	180	
0000 50	40.00		00.00	40.74	D I	4.50	405	
2603.52	40.08	H	80.82	-40.74	Peak	1.56	135	
2603.52	40.08	Н	60.82	-20.74	Avg	1.56	135	
3037.44	46.13	Н	80.82	-34.69	Peak	1.25	45	
3037.44	46.13	H	60.82	-14.69	Avg	1.25	45	
3037.44	40.13	П	00.02	-14.09	Avg	1.25	40	
3471.36	41.61	Н	80.82	-39.21	Peak	1.42	90	
3471.36	41.61	Н	60.82	-19.21	Avg	1.42	90	
347 1.00	71.01		50.02	10.21	, wg	1.74	- 50	
3905.28	42.73	Н	74	-31.27	Peak	1.42	135	
3905.28	42.73	Н	54	-11.27	Avg	1.42	135	
					Ŭ			
4339.2	45.62	Н	74	-28.38	Peak	1.42	135	
4339.2	45.62	Н	54	-8.38	Avg	1.42	135	

JLCooper Electronics Date: 12/13/06
Transmitter, Remote Control Labs: B and D

Model: MiE Tested By: Kyle Fujimoto


Digital Portion and Non-Harmonic Emissions from the Tx -- 10 kHz to 4400 MHz Vertical and Horizontal Polarization Tested in the X-Axis, Y-Axis, and Z-Axis

					Peak /	Ant.	Table	
Eroa	Level				QP/			
Freq.		D - 1 (- //-)	1 2 24			Height	Angle	0
(MHz)	(aBuv)	Pol (v/h)	Limit	Margin	Avg	(m)	(deg)	Comments
								No Emissions
								Detected from the Digital
								Portion from
								10 kHz to 4400 MHz
								for Both the Vertical
								and Horizontal Polarizations
								No Emissions
								Detected from the Non-
								Harmonic Emissions from
								10 kHz to 4400 MHz
								for Both the Vertical
								and Horizontal Polarizations



-20 dB BANDWIDTH

DATA SHEET



-20 dB Bandwidth Plot of the Fundamental