Prima Contact ID Label and Location Info:





MATERIAL: Brady B-423 or B-484 or other with the same characteristics.

Glossy White Permanent Polyester for thermal transfer printing

Finish: White/Gloss

Adhesive: Permanent Acrylic (B-423) or Permanent Rubber Based (B-484)

ABRASION RESISTANCE: excellent

PROPERTIES: resisting to humidity, water, solvents, UV

Ideal for bar-codes, logotypes and graphics.

Max Temperature: 140°C.

RoHS compliant

SUPPLIER: BRADY

UL and CSA approvals.

	Itemref	mref Quantity Title/Name, designation, material, dimension etc			Tolerance (if not specified)	Article No./Reference		
			Material: Brady B-423 or B-484				-	
Designed by			Checked by	Approved by - date	Filename	Date	Sheet Size	Scale
Guariso)			FCC_PrimaContact_CTC.dwg	03/05/07	A4	1:1

Questo disegno e' di proprieta' della PRIMA ELECTRONICS S.p.A.
E' vietata ogni infondatione, anche parziale, senza l' autorizzazione
sortita della PRIMA ELECTRONICS S.p.A.
This drawing belongs to PRIMA ELECTRONICS S.p.A.
Il is not to be copied, after wholly or in part, without consent in
writing of PRIMA ELECTRONICS S.p.A.

PRIMA ELECTRONICS S.p.A. Moncalieri - Torino - Italy

Label FCC for MkIV PrimaContact Module 1/1 00

Checked