



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / [www.sporton.com.tw](http://www.sporton.com.tw)

## FCC RADIO TEST REPORT

Applicant's company	Cradlepoint Technology
Applicant Address	805W. Franklin Street, Boise, ID 83702
FCC ID	UXX-IBR600E
Manufacturer's company	U-MEDIA Communications, Inc.
Manufacturer Address	9F, No. 1, Jin-Shan 8th St., Hsinchu 300, Taiwan, R.O.C.

Product Name	Industrial Broadband Router
Brand Name	CradlePoint
Model Name	IBR600E
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Jul. 19, 2011
Final Test Date	May 08, 2012
Submission Type	Class II Change

### Statement

**Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies .....	7
3.5. Table for Test Modes.....	7
3.6. Table for Testing Locations.....	8
3.7. Table for Supporting Units .....	8
3.8. Table for Parameters of Test Software Setting .....	9
3.9. Test Configurations .....	10
<b>4. TEST RESULT .....</b>	<b>12</b>
4.1. AC Power Line Conducted Emissions Measurement.....	12
4.2. Peak Output Power Measurement .....	16
4.3. Average Output Power Measurement .....	19
4.4. Power Spectral Density Measurement .....	22
4.5. 6dB Spectrum Bandwidth Measurement .....	28
4.6. Radiated Emissions Measurement .....	33
4.7. Band Edge Emissions Measurement .....	51
4.8. Antenna Requirements .....	60
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>61</b>
<b>6. TEST LOCATION.....</b>	<b>64</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>65</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A6</b>
<b>APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>B1 ~ B3</b>
<b>APPENDIX C. CO-LOCATION REPORT.....</b>	<b>C1 ~ C3</b>

## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR171915-02	Rev. 01	Initial issue of report	May 18, 2012

## 1. CERTIFICATE OF COMPLIANCE

Product Name : Industrial Broadband Router  
Brand Name : CradlePoint  
Model Name : IBR600E  
Applicant : Cradlepoint Technology  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jul. 19, 2011 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Jordan Hsiao  
SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	10.22 dB
4.2	15.247(b)(3)	Peak Output Power	Complies	6.15 dB
4.3	-	Average Output Power	-	-
4.4	15.247(e)	Power Spectral Density	Complies	0.92 dB
4.5	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.6	15.247(d)	Radiated Emissions	Complies	0.41 dB
4.7	15.247(d)	Band Edge Emissions	Complies	0.08 dB
4.8	15.203	Antenna Requirements	Complies	-

Note: The EUT contains 3G transmitter module FCC ID: N7N-MC5728.

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 17.56 MHz ; MCS0 (40MHz): 36.00 MHz
Peak Output Power	MCS0 (20MHz): 23.85 dBm ; MCS0 (40MHz): 23.12 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

##### IEEE 802.11b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 15.04 MHz ; 11g: 16.40 MHz
Peak Output Power	11b: 17.94 dBm ; 11g: 22.15 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

### Antenna & Band width

Antenna	Single (TX)		Two (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz
IEEE 802.11b	V	X	X	X
IEEE 802.11g	V	X	X	X
IEEE 802.11n	X	X	V	V

### IEEE 802.11n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

### 3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	Powertron Electronics Corp.	PA1015-2HU	Input: 100-240VAC, 50-60Hz, 0.4A Output: 12VDC, 1.5A
Adapter 2	Powertron Electronics Corp.	PA1024-2HU	Input: 100-240VAC, 50-60Hz, 0.6A Output: 12VDC, 1.5A
Others			
Bracket			



### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
1	Joymax	IWX-1511RSXX-711	Dipole Antenna	Reversed-SMA	5.0	TX/RX
2	Joymax	IWX-241XRSXX-999	Dipole Antenna	Reversed-SMA	2.0	TX/RX
3	Invax	AN2400-5510RS	Dipole Antenna	Reversed-SMA	2.0	TX/RX

Note: The EUT has three antennas for WLAN function.

Due to Ant.1 ~ Ant.3 is the same type antenna, only the higher gain antenna "Ant. 1" was tested and recorded in this report.


**For IEEE 802.11b/g mode:**

Connector A can be used as transmitting/receiving antenna.

**For IEEE 802.11n mode:**

Both Connector A and Connector B can be used as transmitting/receiving antennas.

Connector A and Connector B will transmit/receive the same signal simultaneously.



Connector B: TX/RX

Connector A: TX/RX

### 3.4. Table for Carrier Frequencies

For IEEE 802.11b/g, use Channel 1~Channel 11.

There are two bandwidth systems for IEEE 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Connector
AC Power Line Conducted Emissions	Normal Link	-	-	-
Peak Output Power	MCS0/20MHz	6.5 Mbps	1/6/11	A/B/A+B
Average Output Power	MCS0/40MHz	13.5 Mbps	3/6/9	A/B/A+B
Power Spectral Density	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
6dB Spectrum Bandwidth	MCS0/20MHz	6.5 Mbps	1/6/11	A+B
	MCS0/40MHz	13.5 Mbps	3/6/9	A+B
	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 <sup>th</sup>	MCS0/20MHz	6.5 Mbps	1/6/11	A+B
Harmonic	MCS0/40MHz	13.5 Mbps	3/6/9	A+B
	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Band Edge Emissions	MCS0/20MHz	6.5 Mbps	1/11	A+B
	MCS0/40MHz	13.5 Mbps	3/9	A+B
	11b/BPSK	1 Mbps	1/11	A
	11g/BPSK	6 Mbps	1/11	A

The following test modes were performed for all tests:

EUT was performed at Horizontal and Vertical and the worst case was found at Horizontal, thus the measurement will follow this same test mode.

Mode 1. EUT + Adapter 1

Mode 2. EUT + Adapter 2

Due to Mode 2 generated the worst test result, so it was recorded in this report.

<For MPE and Co-location Test>:

The EUT could be applied with WLAN and 3G function; therefore Maximum Permissible Exposure (Please refer to Appendix B) and Co-location (please refer to Appendix C) tests are added for simultaneously transmit between WLAN and 3G function.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	187376	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	187376	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Existing Change

This product is an extension of original one reported under Sporton project number: 171915.

Adding new capacitance (C558), resistance (R460, R462, R456, R457, R458, R444, R188) and reset IC (U47).

### 3.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	E2K24GBRL
Notebook	DELL	1200	E2K4965AGNM

### 3.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11n

Test Software Version	Ralink QA 1.0.1.8		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	1F/1F	1F/1F	1F/1F
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	18/18	1F/1F	1F/1F

#### Power Parameters of IEEE 802.11b/g

Test Software Version	Ralink QA 1.0.1.8		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	19	17	18
IEEE 802.11g	1F	1F	1F


During the test, "Ralink QA 1.0.1.8" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.

### 3.10. Test Configurations


#### 3.10.1. Radiation Emissions Test Configuration

Test Mode: Mode 2

Test Configuration: 30MHz~1GHz




Test Configuration: above 1GHz



### 3.10.2.AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 2



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation

There is no deviation with the original standard.


#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.




#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	65%
Test Engineer	Sin Chang	Phase	Line
Configuration	Normal Link	Test Mode	Mode 2



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.19969	27.63	-25.99	53.62	27.38	0.05	0.20	AVERAGE
2	0.19969	46.33	-17.29	63.62	46.08	0.05	0.20	QP
3	0.48890	33.45	-12.73	46.19	33.31	0.03	0.11	AVERAGE
4	0.48890	39.19	-16.99	56.19	39.05	0.03	0.11	QP
5	1.762	27.08	-28.92	56.00	26.88	0.05	0.16	QP
6	1.762	16.11	-29.89	46.00	15.91	0.05	0.16	AVERAGE
7	3.224	30.76	-15.24	46.00	30.43	0.08	0.25	AVERAGE
8	3.224	36.84	-19.16	56.00	36.51	0.08	0.25	QP
9	6.523	39.75	-20.25	60.00	39.13	0.23	0.39	QP
10	6.523	33.29	-16.71	50.00	32.67	0.23	0.39	AVERAGE
11	10.233	43.62	-16.38	60.00	42.91	0.36	0.34	QP
12 ☺	10.233	38.83	-11.17	50.00	38.12	0.36	0.34	AVERAGE

Temperature	25°C	Humidity	65%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 2



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16677	34.01	-21.11	55.12	33.71	0.10	0.20	AVERAGE
2	0.16677	51.39	-13.73	65.12	51.09	0.10	0.20	QP
3	0.49673	35.84	-10.22	46.05	35.59	0.07	0.18	AVERAGE
4	0.49673	43.20	-12.86	56.05	42.95	0.07	0.18	QP
5	2.273	35.42	-20.58	56.00	35.12	0.10	0.20	QP
6	2.273	29.15	-16.85	46.00	28.85	0.10	0.20	AVERAGE
7	4.180	25.87	-20.13	46.00	25.42	0.15	0.30	AVERAGE
8	4.180	35.05	-20.95	56.00	34.60	0.15	0.30	QP
9	10.125	35.93	-24.07	60.00	35.21	0.39	0.32	QP
10	10.125	31.18	-18.82	50.00	30.46	0.39	0.32	AVERAGE
11	21.715	31.85	-28.15	60.00	30.40	0.95	0.50	QP
12	21.715	26.79	-23.21	50.00	25.34	0.95	0.50	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Peak Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the peak power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Peak

### 4.2.3. Test Procedures

Spectrum Parameter	Setting
RF Output Power Method	<input checked="" type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (a) power meter method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (b) channel integration method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.1 Method 1 - spectral trace averaging
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.2 Method 2 - zero-span mode with trace averaging

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Peak Output Power

Temperature	25.6°C	Humidity	56%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n
Test Date	Jul. 28, 2011		

##### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Connector A	Connector B			
1	2412 MHz	19.20	20.90	23.14	30.00	Complies
6	2437 MHz	20.99	20.68	23.85	30.00	Complies
11	2462 MHz	17.05	18.43	20.80	30.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Connector A	Connector B			
3	2422 MHz	17.26	19.74	21.68	30.00	Complies
6	2437 MHz	19.67	20.51	23.12	30.00	Complies
9	2452 MHz	19.05	19.80	22.45	30.00	Complies

<b>Temperature</b>	25.6°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Magic Lai	<b>Configurations</b>	IEEE 802.11b/g
<b>Test Date</b>	Jul. 28, 2011		

**Configuration IEEE 802.11b / Ant. 1 / Connector A**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.23	30.00	Complies
6	2437 MHz	17.94	30.00	Complies
11	2462 MHz	14.05	30.00	Complies

**Configuration IEEE 802.11g / Ant. 1 / Connector A**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.41	30.00	Complies
6	2437 MHz	22.15	30.00	Complies
11	2462 MHz	19.23	30.00	Complies

### 4.3. Average Output Power Measurement

#### 4.3.1. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

#### 4.3.2. Test Procedures

Spectrum Parameter	Setting
RF Output Power Method	<input checked="" type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (a) power meter method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (b) channel integration method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.1 Method 1 - spectral trace averaging
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.2 Method 2 - zero-span mode with trace averaging

#### 4.3.3. Test Setup Layout



#### 4.3.4. Test Deviation

There is no deviation with the original standard.

#### 4.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

Note: Average output power is only for Maximum Permissible Exposure use.

#### 4.3.6. Test Result of Average Output Power

Temperature	25.6°C	Humidity	56%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n
Test Date	Jul. 28, 2011		

##### Configuration IEEE 802.11n MCS8 20MHz / Ant. 1

Channel	Frequency	Average Conducted Power (dBm)		
		Connector A	Connector B	Total
1	2412 MHz	11.34	13.11	15.32
6	2437 MHz	12.71	13.79	16.29
11	2462 MHz	8.06	10.02	12.16

##### Configuration IEEE 802.11n MCS8 40MHz / Ant. 1

Channel	Frequency	Average Conducted Power (dBm)		
		Connector A	Connector B	Total
3	2422 MHz	9.34	10.88	13.19
6	2437 MHz	12.32	13.62	16.03
9	2452 MHz	11.13	12.69	14.99

Temperature	25.6°C	Humidity	56%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b/g
Test Date	Jul. 28, 2011		

**Configuration IEEE 802.11b / Ant. 1 / Connector A**

Channel	Frequency	Average Conducted Power (dBm)
1	2412 MHz	15.11
6	2437 MHz	16.01
11	2462 MHz	11.68

**Configuration IEEE 802.11g / Ant. 1 / Connector A**

Channel	Frequency	Average Conducted Power (dBm)
1	2412 MHz	14.13
6	2437 MHz	15.60
11	2462 MHz	11.19



#### 4.4. Power Spectral Density Measurement

##### 4.4.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30 kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

##### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.
5. When measuring power spectral density with multiple antenna systems, add every result of the values by mathematic formula.

##### 4.4.4. Test Setup Layout



##### 4.4.5. Test Deviation

There is no deviation with the original standard.

##### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of Power Spectral Density

Temperature	25.6°C	Humidity	56%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Connector A	Connector B			
1	2412 MHz	-14.39	-11.95	-9.99	8.00	Complies
6	2437 MHz	-12.81	-11.09	-8.86	8.00	Complies
11	2462 MHz	-18.30	-15.63	-13.75	8.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Connector A	Connector B			
3	2422 MHz	-18.93	-14.63	-13.26	8.00	Complies
6	2437 MHz	-14.75	-10.85	-9.37	8.00	Complies
9	2452 MHz	-16.51	-14.04	-12.09	8.00	Complies

Temperature	25.6°C	Humidity	56%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b/g

#### Configuration IEEE 802.11b / Ant. 1 / Connector 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density (mW/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-11.08	0.08	8.00	Complies
6	2437 MHz	-8.68	0.14	8.00	Complies
11	2462 MHz	-13.27	0.05	8.00	Complies


#### Configuration IEEE 802.11g / Ant. 1 / Connector 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density (mW/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-11.09	0.08	8.00	Complies
6	2437 MHz	-11.42	0.07	8.00	Complies
11	2462 MHz	-14.14	0.04	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

### Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Connector A / 2437 MHz




Date: 27.JUL.2011 22:15:40

### Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Connector B / 2437 MHz




Date: 27.JUL.2011 21:36:22

### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Connector A / 2437 MHz




Date: 27.JUL.2011 22:42:47

### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Connector B / 2437 MHz




Date: 27.JUL.2011 22:45:28

### Power Density Plot on Configuration IEEE 802.11b / Ant. 1 / Connector A / 2437 MHz



Date: 27.JUL.2011 20:33:01

### Power Density Plot on Configuration IEEE 802.11g / Ant. 1 / Connector A / 2412 MHz



Date: 27.JUL.2011 20:48:04

## 4.5. 6dB Spectrum Bandwidth Measurement

### 4.5.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### 4.5.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 4.5.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

### 4.5.4. Test Setup Layout



### 4.5.5. Test Deviation

There is no deviation with the original standard.

### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Test Result of 6dB Spectrum Bandwidth

Temperature	25.6°C	Humidity	56%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Connector A + Connector B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.12	17.56	500	Complies
6	2437 MHz	16.84	17.40	500	Complies
11	2462 MHz	17.16	17.56	500	Complies

##### Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Connector A + Connector B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.76	36.00	500	Complies
6	2437 MHz	31.28	35.68	500	Complies
9	2452 MHz	35.36	35.92	500	Complies



<b>Temperature</b>	25.6°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Magic Lai	<b>Configurations</b>	IEEE 802.11b/g

**Configuration IEEE 802.11b / Ant. 1 / Connector A**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.12	15.04	500	Complies
6	2437 MHz	10.16	14.76	500	Complies
11	2462 MHz	12.32	15.04	500	Complies


**Configuration IEEE 802.11g / Ant. 1 / Connector A**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.08	16.40	500	Complies
6	2437 MHz	15.32	16.32	500	Complies
11	2462 MHz	16.32	16.40	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

# 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Connector A + Connector B / 2437 MHz




Date: 27.JUL.2011 20:01:07

# 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Connector A + Connector B / 2437 MHz




Date: 27.JUL.2011 20:08:55

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / Ant. 1 / Connector A / 2437 MHz



Date: 27.JUL.2011 11:44:17

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / Ant. 1 / Connector A / 2437 MHz



Date: 27.JUL.2011 11:50:51

## 4.6. Radiated Emissions Measurement

### 4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.6.4. Test Setup Layout

For Radiated Emissions below 1GHz



For Radiated Emissions above 1GHz



#### 4.6.5. Test Deviation

There is no deviation with the original standard.

#### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	55%
Test Engineer	Magic Lai	Configurations	Normal Link
Test Date	May 08, 2012		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.6.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	24°C	Humidity	55%
Test Engineer	Magic Lai	Configurations	Normal Link
Test Mode	Mode 2		


##### Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	54.84	22.08	-17.92	40.00	46.00	6.90	0.67	31.49	---	---	Peak
2	145.29	28.74	-14.76	43.50	47.86	10.70	1.45	31.27	---	---	Peak
3	299.19	29.25	-16.75	46.00	45.31	13.20	2.41	31.67	---	---	Peak
4	308.40	33.17	-12.83	46.00	48.74	13.45	2.37	31.39	100	52	Peak
5	430.90	27.47	-18.53	46.00	39.62	16.51	2.49	31.14	---	---	Peak
6	540.80	25.95	-20.05	46.00	35.46	18.74	2.97	31.22	---	---	Peak



# Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
	54.03	34.58	-5.42	40.00	58.26	7.20	0.67	31.55	100	66 Peak
	76.98	32.53	-7.47	40.00	56.29	6.70	0.89	31.34	---	---
	98.58	29.75	-13.75	43.50	49.33	10.96	1.03	31.58	---	---
4	306.30	32.12	-13.88	46.00	47.82	13.39	2.38	31.47	---	---
5	507.90	30.58	-15.42	46.00	41.81	17.68	2.94	31.85	---	---
6	749.40	27.55	-18.45	46.00	35.02	19.80	3.57	30.84	---	---

## Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.6.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 1 / Connector A + Connector B
Test Date	Jul. 27, 2011		

##### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4821.16	47.56	74.00	-26.44	46.22	3.31	33.06	35.03	82	100	Peak	HORIZONTAL
2	4823.24	31.98	54.00	-22.02	30.64	3.31	33.06	35.03	82	100	Average	HORIZONTAL

##### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4822.00	36.84	54.00	-17.16	35.50	3.31	33.06	35.03	343	100	Average	VERTICAL
2	4824.84	55.27	74.00	-18.73	53.93	3.31	33.06	35.03	343	100	Peak	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 1 / Connector A + Connector B
Test Date	Jul. 27, 2011		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4871.40	44.53	74.00	-29.47	43.07	3.33	33.16	35.03	97	99	Peak	HORIZONTAL
2	4872.10	32.01	54.00	-21.99	30.55	3.33	33.16	35.03	97	99	Average	HORIZONTAL
3	7308.80	35.48	54.00	-18.52	30.86	4.06	35.96	35.40	321	100	Average	HORIZONTAL
4	7309.90	50.95	74.00	-23.05	46.33	4.06	35.96	35.40	321	100	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4872.50	52.66	74.00	-21.34	51.20	3.33	33.16	35.03	351	100	Peak	VERTICAL
2	4873.40	36.11	54.00	-17.89	34.65	3.33	33.16	35.03	351	100	Average	VERTICAL
3	7308.80	44.39	54.00	-9.61	39.77	4.06	35.96	35.40	181	129	Average	VERTICAL
4	7316.00	63.73	74.00	-10.27	59.11	4.06	35.96	35.40	181	129	Peak	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz Ch11 / Ant. 1 / Connector A + Connector B
Test Date	Jul. 27, 2011		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4914.80	44.88	74.00	-29.12	43.32	3.35	33.23	35.02	87	100	Peak	HORIZONTAL
2	4923.60	32.41	54.00	-21.59	30.81	3.35	33.26	35.01	87	100	Average	HORIZONTAL
3	7388.40	37.25	54.00	-16.75	32.50	4.06	36.09	35.40	285	146	Average	HORIZONTAL
4	7389.80	53.74	74.00	-20.26	48.99	4.06	36.09	35.40	285	146	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4915.10	51.58	74.00	-22.42	50.02	3.35	33.23	35.02	347	100	Peak	VERTICAL
2	4924.40	35.42	54.00	-18.58	33.82	3.35	33.26	35.01	347	100	Average	VERTICAL
3	7382.80	62.52	74.00	-11.48	57.77	4.06	36.09	35.40	237	138	Peak	VERTICAL
4	7386.00	44.22	54.00	-9.78	39.47	4.06	36.09	35.40	237	138	Average	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz Ch 3 / Ant. 1 / Connector A + Connector B
Test Date	Jul. 27, 2011		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4842.48	42.34	74.00	-31.66	40.96	3.32	33.09	35.03	135	101	Peak	HORIZONTAL
2	4843.33	29.98	54.00	-24.02	28.60	3.32	33.09	35.03	135	101	Average	HORIZONTAL
3	7266.72	33.22	54.00	-20.78	28.71	4.06	35.85	35.40	182	101	Average	HORIZONTAL
4	7267.75	44.86	74.00	-29.14	40.35	4.06	35.85	35.40	182	101	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4845.00	50.07	74.00	-23.93	48.69	3.32	33.09	35.03	354	100	Peak	VERTICAL
2	4847.90	32.08	54.00	-21.92	30.70	3.32	33.09	35.03	354	100	Average	VERTICAL
3	7272.90	37.36	54.00	-16.64	32.85	4.06	35.85	35.40	220	136	Average	VERTICAL
4	7275.00	55.94	74.00	-18.06	51.39	4.06	35.89	35.40	220	136	Peak	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz Ch 6 / Ant. 1 / Connector A + Connector B
Test Date	Jul. 27, 2011		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4850.60	42.53	74.00	-31.47	41.15	3.32	33.09	35.03	167	100	Peak	HORIZONTAL
2	4873.70	30.91	54.00	-23.09	29.45	3.33	33.16	35.03	167	100	Average	HORIZONTAL
3	7306.20	37.62	54.00	-16.38	33.04	4.06	35.92	35.40	212	100	Average	HORIZONTAL
4	7307.20	49.54	74.00	-24.46	44.96	4.06	35.92	35.40	212	100	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4874.80	50.90	74.00	-23.10	49.44	3.33	33.16	35.03	357	100	Peak	VERTICAL
2	4880.20	33.50	54.00	-20.50	32.04	3.33	33.16	35.03	357	100	Average	VERTICAL
3	7318.80	41.29	54.00	-12.71	36.67	4.06	35.96	35.40	205	150	Average	VERTICAL
4	7319.00	60.09	74.00	-13.91	55.47	4.06	35.96	35.40	205	150	Peak	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz Ch 9 / Ant. 1 / Connector A + Connector B
Test Date	Jul. 27, 2011		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4899.60	42.18	74.00	-31.82	40.67	3.34	33.19	35.02	143	100	Peak	HORIZONTAL
2	4904.20	30.82	54.00	-23.18	29.31	3.34	33.19	35.02	143	100	Average	HORIZONTAL
3	7360.40	37.12	54.00	-16.88	32.40	4.06	36.06	35.40	341	100	Average	HORIZONTAL
4	7361.00	47.83	74.00	-26.17	43.11	4.06	36.06	35.40	341	100	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4901.90	33.22	54.00	-20.78	31.71	3.34	33.19	35.02	5	100	Average	VERTICAL
2	4904.90	50.95	74.00	-23.05	49.40	3.34	33.23	35.02	5	100	Peak	VERTICAL
3	7350.00	41.76	54.00	-12.24	37.08	4.06	36.02	35.40	248	139	Average	VERTICAL
4	7360.40	59.58	74.00	-14.42	54.86	4.06	36.06	35.40	248	139	Peak	VERTICAL

#### Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 1 / Ant. 1 / Connector A
Test Date	Jul. 26, 2011		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4824.00	42.71	54.00	-11.29	41.37	3.31	33.06	35.03	87	100	Average	HORIZONTAL
2	4824.00	47.82	74.00	-26.18	46.48	3.31	33.06	35.03	87	100	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.94	55.33	74.00	-18.67	53.99	3.31	33.06	35.03	333	101	Peak	VERTICAL
2	4823.99	53.22	54.00	-0.78	51.88	3.31	33.06	35.03	333	101	Average	VERTICAL



Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 6 / Ant. 1 / Connector A
Test Date	Jul. 26, 2011		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.97	35.85	54.00	-18.15	34.39	3.33	33.16	35.03	85	100	Average	HORIZONTAL
2	4874.00	46.11	74.00	-27.89	44.65	3.33	33.16	35.03	85	100	Peak	HORIZONTAL
3	7311.72	43.44	54.00	-10.56	38.82	4.06	35.96	35.40	207	149	Average	HORIZONTAL
4	7312.06	50.90	74.00	-23.10	46.28	4.06	35.96	35.40	207	149	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Limit	Level	Loss	Factor	Factor		A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.97	49.45	74.00	-24.55	47.99	3.33	33.16	35.03	342	100	Peak	VERTICAL
2	4873.99	44.19	54.00	-9.81	42.73	3.33	33.16	35.03	342	100	Average	VERTICAL
3	7309.96	58.68	74.00	-15.32	54.06	4.06	35.96	35.40	173	152	Peak	VERTICAL
4	7310.24	53.57	54.00	-0.43	48.95	4.06	35.96	35.40	173	152	Average	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 11 / Ant. 1 / Connector A
Test Date	Jul. 26, 2011		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4923.94	47.38	74.00	-26.62	45.78	3.35	33.26	35.01	136	100	Peak	HORIZONTAL
2	4924.00	39.33	54.00	-14.67	37.73	3.35	33.26	35.01	136	100	Average	HORIZONTAL
3	7387.48	50.24	74.00	-23.76	45.49	4.06	36.09	35.40	189	101	Peak	HORIZONTAL
4	7388.70	42.56	54.00	-11.44	37.81	4.06	36.09	35.40	189	101	Average	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4924.00	46.38	54.00	-7.62	44.78	3.35	33.26	35.01	340	100	Average	VERTICAL
2	4924.05	50.61	74.00	-23.39	49.01	3.35	33.26	35.01	340	100	Peak	VERTICAL
3	7383.44	58.81	74.00	-15.19	54.06	4.06	36.09	35.40	125	146	Peak	VERTICAL
4	7385.26	53.59	54.00	-0.41	48.84	4.06	36.09	35.40	125	146	Average	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1 / Ant. 1 / Connector A
Test Date	Jul. 26, 2011		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4820.20	46.53	74.00	-27.47	45.19	3.31	33.06	35.03	81	100	Peak	HORIZONTAL
2	4822.06	31.91	54.00	-22.09	30.57	3.31	33.06	35.03	81	100	Average	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4824.90	52.61	74.00	-21.39	51.27	3.31	33.06	35.03	351	100	Peak	VERTICAL
2	4826.10	38.05	54.00	-15.95	36.71	3.31	33.06	35.03	351	100	Average	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 6 / Ant. 1 / Connector A
Test Date	Jul. 26, 2011		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4875.20	31.35	54.00	-22.65	29.89	3.33	33.16	35.03	95	100	Average	HORIZONTAL
2	4876.00	44.53	74.00	-29.47	43.07	3.33	33.16	35.03	95	100	Peak	HORIZONTAL
3	7309.40	40.43	54.00	-13.57	35.81	4.06	35.96	35.40	325	124	Average	HORIZONTAL
4	7315.00	55.77	74.00	-18.23	51.15	4.06	35.96	35.40	325	124	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4871.80	36.29	54.00	-17.71	34.83	3.33	33.16	35.03	341	100	Average	VERTICAL
2	4874.80	49.88	74.00	-24.12	48.42	3.33	33.16	35.03	341	100	Peak	VERTICAL
3	7313.20	50.42	54.00	-3.58	45.80	4.06	35.96	35.40	121	138	Average	VERTICAL
4	7314.70	68.11	74.00	-5.89	63.49	4.06	35.96	35.40	121	138	Peak	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 11 / Ant. 1 / Connector A
Test Date	Jul. 26, 2011		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4922.44	45.79	74.00	-28.21	44.19	3.35	33.26	35.01	136	101	Peak	HORIZONTAL
2	4923.92	31.54	54.00	-22.46	29.94	3.35	33.26	35.01	136	101	Average	HORIZONTAL
3	7388.20	40.66	54.00	-13.34	35.91	4.06	36.09	35.40	189	100	Average	HORIZONTAL
4	7389.80	56.51	74.00	-17.49	51.76	4.06	36.09	35.40	189	100	Peak	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4920.30	51.68	74.00	-22.32	50.11	3.35	33.23	35.01	16	100	Peak	VERTICAL
2	4923.90	36.85	54.00	-17.15	35.25	3.35	33.26	35.01	16	100	Average	VERTICAL
3	7388.20	50.03	54.00	-3.97	45.28	4.06	36.09	35.40	123	145	Average	VERTICAL
4	7389.70	66.41	74.00	-7.59	61.66	4.06	36.09	35.40	123	145	Peak	VERTICAL

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.7. Band Edge Emissions Measurement

### 4.7.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

### 4.7.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
- In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

### 4.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.7.5. Test Deviation

There is no deviation with the original standard.

### 4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.7.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 1 / Connector A + Connector B
Test Date	Jul. 26, 2011		

##### Channel 1

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	2389.00	71.97	74.00	-2.03	41.59	2.21	28.17	0.00	269	137	Peak	VERTICAL
2	2390.00	53.92	54.00	-0.08	23.53	2.22	28.17	0.00	269	137	Average	VERTICAL
3	2404.60	109.67				2.22	28.21	0.00	269	137	Peak	VERTICAL
4	2406.20	90.31				2.22	28.21	0.00	269	137	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	2388.80	56.27	74.00	-17.73	25.89	2.21	28.17	0.00	264	132	Peak	VERTICAL
2	2390.00	44.72	54.00	-9.28	14.33	2.22	28.17	0.00	264	132	Average	VERTICAL
3	2438.60	93.15				2.23	28.29	0.00	264	132	Average	VERTICAL
4	2439.40	111.98				2.23	28.29	0.00	264	132	Peak	VERTICAL
5	2483.50	42.26	54.00	-11.74	11.63	2.26	28.37	0.00	264	132	Average	VERTICAL
6	2486.70	54.42	74.00	-19.58	23.75	2.26	28.41	0.00	264	132	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

##### Channel 11

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	2456.20	88.28				2.24	28.33	0.00	268	130	Average	VERTICAL
2	2457.60	106.00				2.24	28.33	0.00	268	130	Peak	VERTICAL
3	2483.50	42.48	54.00	-11.52	11.85	2.26	28.37	0.00	268	130	Average	VERTICAL
4	2484.30	53.14	74.00	-20.86	22.51	2.26	28.37	0.00	268	130	Peak	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Ant. 1 / Connector A + Connector B
Test Date	Jul. 27, 2011		

### Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2390.00	53.68	54.00	-0.32	23.29	2.22	28.17	0.00	270	130	Average	VERTICAL
2	2390.00	73.35	74.00	-0.65	42.96	2.22	28.17	0.00	270	130	Peak	VERTICAL
3	2437.60	105.66				2.23	28.29	0.00	270	130	Peak	VERTICAL
4	2438.40	83.09				2.23	28.29	0.00	270	130	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2389.20	67.46	74.00	-6.54	37.08	2.21	28.17	0.00	271	135	Peak	VERTICAL
2	2390.00	50.38	54.00	-3.62	19.99	2.22	28.17	0.00	271	135	Average	VERTICAL
3	2440.20	109.75				2.23	28.29	0.00	271	135	Peak	VERTICAL
4	2440.60	85.13				2.23	28.29	0.00	271	135	Average	VERTICAL
5	2483.50	42.32	54.00	-11.68	11.69	2.26	28.37	0.00	271	135	Average	VERTICAL
6	2483.90	53.15	74.00	-20.85	22.52	2.26	28.37	0.00	271	135	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

### Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2438.80	84.90				2.23	28.29	0.00	270	129	Average	VERTICAL
2	2441.60	108.99				2.24	28.29	0.00	270	129	Peak	VERTICAL
3	2483.50	43.30	54.00	-10.70	12.67	2.26	28.37	0.00	270	129	Average	VERTICAL
4	2483.50	55.78	74.00	-18.22	25.15	2.26	28.37	0.00	270	129	Peak	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1 / Connector A
Test Date	Jul. 26, 2011		

#### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2386.00	57.35	74.00	-16.65	26.97	2.21	28.17	0.00	109	100	Peak	VERTICAL
2	2386.20	49.36	54.00	-4.64	18.98	2.21	28.17	0.00	109	100	Average	VERTICAL
3	2413.80	99.70				2.22	28.21	0.00	109	100	Average	VERTICAL
4	2414.60	104.35				2.22	28.21	0.00	109	100	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

#### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2389.40	54.05	74.00	-19.95	23.67	2.21	28.17	0.00	263	131	Peak	VERTICAL
2	2390.00	43.17	54.00	-10.83	12.78	2.22	28.17	0.00	263	131	Average	VERTICAL
3	2438.00	106.43				2.23	28.29	0.00	263	131	Peak	VERTICAL
4	2438.60	101.70				2.23	28.29	0.00	263	131	Average	VERTICAL
5	2483.50	42.34	54.00	-11.66	11.71	2.26	28.37	0.00	263	131	Average	VERTICAL
6	2485.30	52.70	74.00	-21.30	22.03	2.26	28.41	0.00	263	131	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

#### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2461.20	96.38				2.24	28.33	0.00	292	100	Average	VERTICAL
2	2463.00	101.07				2.24	28.33	0.00	292	100	Peak	VERTICAL
3	2483.50	42.31	54.00	-11.69	11.68	2.26	28.37	0.00	292	100	Average	VERTICAL
4	2485.10	53.00	74.00	-21.00	22.33	2.26	28.41	0.00	292	100	Peak	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	62%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1 / Connector A
Test Date	Jul. 26, 2011		

#### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2388.40	64.16	74.00	-9.84	33.78	2.21	28.17	0.00	111	102	Peak	VERTICAL
2	2390.00	49.04	54.00	-4.96	18.65	2.22	28.17	0.00	111	102	Average	VERTICAL
3	2413.60	104.76				2.22	28.21	0.00	111	102	Peak	VERTICAL
4	2415.60	89.17				2.23	28.21	0.00	111	102	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

#### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2390.00	43.63	54.00	-10.37	13.24	2.22	28.17	0.00	91	133	Average	VERTICAL
2	2390.00	53.95	74.00	-20.05	23.56	2.22	28.17	0.00	91	133	Peak	VERTICAL
3	2439.60	108.74				2.23	28.29	0.00	91	133	Peak	VERTICAL
4	2440.40	92.12				2.23	28.29	0.00	91	133	Average	VERTICAL
5	2483.50	42.33	54.00	-11.67	11.70	2.26	28.37	0.00	91	133	Average	VERTICAL
6	2484.90	53.38	74.00	-20.62	22.75	2.26	28.37	0.00	91	133	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

#### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2457.40	105.59				2.24	28.33	0.00	89	138	Peak	VERTICAL
2	2461.00	88.58				2.24	28.33	0.00	89	138	Average	VERTICAL
3	2483.50	42.48	54.00	-11.52	11.85	2.26	28.37	0.00	89	138	Average	VERTICAL
4	2484.70	53.32	74.00	-20.68	22.69	2.26	28.37	0.00	89	138	Peak	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


### For Emission not in Restricted Band

### Low Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Connector A + Connector B / 2412 MHz



Date: 27.JUL.2011 01:13:55


### High Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Connector A + Connector B / 2462 MHz



Date: 27.JUL.2011 01:27:51


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Connector A + Connector B  
/ 2422 MHz




Date: 27.JUL.2011 02:04:35

High Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Connector A + Connector B  
/ 2452 MHz




Date: 27.JUL.2011 02:16:29

### Low Band Edge Plot on Configuration IEEE 802.11b / Ant. 1 / Connector A / 2412 MHz




Date: 27.JUL.2011 02:48:52

### High Band Edge Plot on Configuration IEEE 802.11b / Ant. 1 / Connector A / 2462 MHz




Date: 27.JUL.2011 02:56:08

### Low Band Edge Plot on Configuration IEEE 802.11g / Ant. 1 / Connector A / 2412 MHz



Date: 27.JUL.2011 03:02:39

### High Band Edge Plot on Configuration IEEE 802.11g / Ant. 1 / Connector A / 2462 MHz



Date: 27.JUL.2011 03:08:52

## **4.8. Antenna Requirements**

### **4.8.1. Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### **4.8.2. Antenna Connector Construction**

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Sep. 01, 2011	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Oct. 28, 2010	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Nov. 16, 2010	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K~30MHz	Jan. 04, 2011	Conduction (CO01-CB)
COND Cable	-	Cable	-	0.15MHz~30MHz	Dec. 04, 2010	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 22, 2010	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Oct. 08, 2010	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2010	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP	100304	9kHz ~ 40GHz	Nov. 22, 2010	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 03, 2011	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 22, 2011	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Sep. 09, 2010*	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2011	Radiation (03CH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSV30	101026	9KHz~30GHz	Jul. 23, 2011	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	May 20, 2011	Conducted (TH01-CB)
Thermo-Hygro Meter	N/A	HC 520	#1	15~70 degree	Nov. 02, 2010	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-12	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-13	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 13, 2010	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 08, 2010	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

Note: \*Calibration Interval of instruments listed above is two year.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-110702

財團法人全國認證基金會  
Taiwan Accreditation Foundation


### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Road, Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : July 02, 2011

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix