

Report No.: FR8N2626D



FCC RADIO TEST REPORT

FCC ID : UZ7MC930P

Equipment : Mobile computer

Brand Name : Zebra
Model Name : MC930P

Applicant : Zebra Technologies Corporation

1 Zebra Plaza, Holtsville, NY 11742

Manufacturer : Zebra Technologies Corporation

1 Zebra Plaza, Holtsville, NY 11742

Standard : FCC Part 15 Subpart C §15.225

The product was received on Nov. 26, 2018 and testing was started from Dec. 26, 2018 and completed on Jan. 07, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

Table of Contents

Report No.: FR8N2626D

History	y of this test report	3
	ary of Test Result	
1. Gen	eral Description	5
1.1	Product Feature of Equipment Under Test	5
1.2	Product Specification of Equipment Under Test	6
1.3	Modification of EUT	6
1.4	Testing Location	7
1.5	Applicable Standards	7
2. Test	Configuration of Equipment Under Test	8
2.1	Descriptions of Test Mode	8
2.2	Connection Diagram of Test System	9
2.3	Table for Supporting Units	
2.4	EUT Operation Test Setup	
3. Test	Results	11
3.1	AC Power Line Conducted Emissions Measurement	
3.2	20dB and 99% OBW Spectrum Bandwidth Measurement	13
3.3	Frequency Stability Measurement	14
3.4	Field Strength of Fundamental Emissions and Mask Measurement	
3.5	Radiated Emissions Measurement	17
3.6	Antenna Requirements	20
4. List	of Measuring Equipment	21
5. Unce	ertainty of Evaluation	22
Append	dix A. Test Results of Conducted Emission Test	
Appen	dix B. Test Results of Conducted Test Items	
B1. ⁻	Test Result of 20dB Spectrum Bandwidth	
B2. ⁻	Test Result of Frequency Stability	
Appen	dix C. Test Results of Radiated Test Items	
C1.	Test Result of Field Strength of Fundamental Emissions	
C2. I	Results of Radiated Emissions (9 kHz~30MHz)	
C3. I	Results of Radiated Emissions (30MHz~1GHz)	
Append	dix D. Setup Photographs	

TEL: 886-3-327-3456 Page Number : 2 of 22
FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

History of this test report

Report No.: FR8N2626D

Report No.	Version	Description	Issued Date
FR8N2626D	01	Initial issue of report	Feb. 25, 2019

TEL: 886-3-327-3456 Page Number : 3 of 22
FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

Summary of Test Result

Report No.: FR8N2626D

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	Under limit 14.31 dB at 0.161MHz
2.2	15.215(c)	20dB Spectrum Bandwidth	Pass	-
3.2	2.1049	99% OBW Spectrum Bandwidth	Reporting only	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	Max level 67.49 dBµV/m at 13.560 MHz
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	Under limit 3.30 dB at 40.800MHz for Quasi-Peak
3.6	15.203	Antenna Requirements	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang Report Producer: Polly Tsai

TEL: 886-3-327-3456 Page Number : 4 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

1. General Description

1.1 Product Feature of Equipment Under Test

Product Feature			
Equipment	Mobile computer		
Brand Name	Zebra		
Model Name	MC930P		
FCC ID	UZ7MC930P		
Sample 1	EUT with SKU 3		
Sample 2	EUT with SKU 4		
Sample 3	EUT with SKU 5		
Sample 4	EUT with SKU 6		
Sample 5	EUT with SKU 7		
	NFC		
EUT supports Radios application	WLAN 11a/b/g/n HT20/HT40		
EOT Supports Radios application	WLAN 11ac VHT20/VHT40/VHT80		
	Bluetooth BR/EDR/LE		
HW Version	EV1		
SW Version	01-14-11.00-OG		
MFD	13NOV18		
EUT Stage	Engineering Sample		

Report No.: FR8N2626D

Remark: The above EUT's information was declared by manufacturer.

Specification of Accessories					
Adapter (5V/2.5A)	Brand Name	Zebra	Part Number	PWR-WUA5V12W0US	
USB-C Adapter	Brand Name	Zebra	Part Number	CBL-MC93-USBCHG-01	
USB-C cable	Brand Name	Zebra	Part Number	CBL-TC2X-USBC-01	
Std Battery	Brand Name	Zebra	Part Number	BT-000370-00	
Fzr Battery	Brand Name	Zebra	Part Number	BT-000371-00	
Holster	Brand Name	Zebra	Part Number	051607-79N1-18	

TEL: 886-3-327-3456 Page Number : 5 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

<Sample Information>

Model Name			MC930P		
	SKU3	SKU4	SKU5	SKU6	SKU7
Organization / Function / Group	EV1a-G21	EV1a-G22	EV1a-G23	EV1a-F11	EV1a-F13
nm	G-2S-1D-53k	G-2S-2D-53k	G-2S-LRI-53k	G-1F-1D-53k	G-1F-LRI-53k
Product Number	MC930P-GSBDG 4NA	MC930P-GSDDG 4NA	MC930P-GSFDG 4NA	MC930P-GFADG 4NA	MC930P-GFEDG 4NA
Form factor	Gun	Gun	Gun	Gun	Gun
Package/ Component Category	Pkg2	Pkg2	Pkg2	Pkg1 CS	Pkg 1 CS
NFC	YES	YES	YES	YES	YES
Vib	YES	YES	YES	YES	YES
Camera	YES	YES	YES	NO	NO
NI	NO	NO	NO	NO	NO
Side Trigger	NO	NO	NO	NO	NO
Display + TP Stackup	Option2	Option2	Option2	Option5	Option5
Scanner	SE965	SE4750SR	SE4850	SE965	SE4850
Battery	Std	Std	Std	Fzr	Fzr
Keyboard	53 Key				
Build Date	Oct 2018	Oct 2018	Oct 2018	Nov 2018	Nov 2018

Report No.: FR8N2626D

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification		
Tx/Rx Frequency Range	13.553 ~ 13.567MHz	
Channel Number	1	
20dBW	2.64 KHz	
99%OBW	2.24 KHz	
Antenna Type	Loop Antenna	
Type of Modulation	ASK	

Remark: The above EUT's information was declared by manufacturer.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

TEL: 886-3-327-3456 Page Number : 6 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978			
Test Site No.	TH03-HY	Sporton Site No.	03CH07-HY	
Test Engineer				
Temperature	22~24℃ 24~26℃ 21~23℃			
Relative Humidity	53~55% 51~53% 51~53%			

Report No.: FR8N2626D

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.225
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

TEL: 886-3-327-3456 Page Number : 7 of 22
FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items				
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions			
20dB Spectrum Bandwidth	Frequency Stability			
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz			

Report No.: FR8N2626D


The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report. Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

	Test Cases						
AC	Mode 1: Bluetooth Link + WLAN (5GHz) Link + NFC Link + MP3 Play + Keypad						
Conducted	(53) + Std Battery + USB-C Adapter + USB-C Cable + Data Link with						
Emission	Notebook (Notebook to SD Card) for Sample 2						
Remark: For	Radiated Test Cases, the tests were performed with Std Battery and Sample 1.						

TEL: 886-3-327-3456 Page Number : 8 of 22
FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019


2.2 Connection Diagram of Test System

<Radiated Emission Mode>



Report No.: FR8N2626D

<AC Conducted Emission Mode>



TEL: 886-3-327-3456 Page Number : 9 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
6.	NFC Card	N/A	N/A	N/A	N/A	N/A

Report No.: FR8N2626D

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 0.5 cm gap to the EUT.

TEL: 886-3-327-3456 Page Number : 10 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR8N2626D

Frequency of Emission	Conducted Limit (dBμV)		
(MHz)	Quasi-Peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30	60	50	

^{*}Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments


See list of measuring equipment of this test report.

3.1.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

TEL: 886-3-327-3456 Page Number : 11 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3.1.4 Test setup



Report No.: FR8N2626D

AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 12 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

Report No.: FR8N2626D


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

- The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
- 3. Measured the spectrum width with power higher than 20dB below carrier.
- 4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

TEL: 886-3-327-3456 Page Number : 13 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Report No.: FR8N2626D


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ± 100 ppm.
- 6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

TEL: 886-3-327-3456 Page Number : 14 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3.4 Field Strength of Fundamental Emissions and Mask Measurement

Report No.: FR8N2626D

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225						
Description	Compliance with th	Compliance with the spectrum mask is tested with RBW set to 9kHz.					
From of Emission (MIII)	Field Strength	Field Strength Field Strength		Field Strength			
Freq. of Emission (MHz)	(µV/m) at 30m	(dBµV/m) at 30m	(dBµV/m) at 10m	(dBµV/m) at 3m			
1.705~13.110	30	29.5	48.58	69.5			
13.110~13.410	106	40.5	59.58	80.5			
13.410~13.553	334	50.5	69.58	90.5			
13.553~13.567	15848	84.0	103.08	124.0			
13.567~13.710	334	50.5	69.58	90.5			
13.710~14.010	106	40.5	59.58	80.5			
14.010~30.000	30	29.5	48.58	69.5			

3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

TEL: 886-3-327-3456 Page Number : 15 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3.4.3 Test Procedures


 Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.

Report No.: FR8N2626D

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
- 4. For Fundamental emissions, use the receiver to measure QP reading.
- 5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- Compliance with the spectrum mask is tested with RBW set to 9kHz.
 Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

TEL: 886-3-327-3456 Page Number : 16 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Report No.: FR8N2626D

Frequencies	Field Strength	Measurement Distance
(MHz)	(μV/m)	(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

TEL: 886-3-327-3456 Page Number : 17 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3.5.4 Test Procedures

 Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.


Report No.: FR8N2626D

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.

TEL: 886-3-327-3456 Page Number : 18 of 22
FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019


3.5.5 Test Setup

For radiated emissions below 30MHz



Report No.: FR8N2626D

For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

TEL: 886-3-327-3456 Page Number : 19 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: FR8N2626D

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

TEL: 886-3-327-3456 Page Number : 20 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F104070011	50Hz~60Hz	Mar. 21, 2018	Dec. 26, 2018	Mar. 20, 2019	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 29, 2018	Dec. 26, 2018	Jun. 28, 2019	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Dec. 06, 2017	Dec. 26, 2018	Dec. 05, 2019	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 07, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	Jan. 07, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jan. 07, 2019	Nov. 13, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jan. 07, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2019	Jan. 07, 2019	Jan. 01, 2020	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Nov. 08, 2018	Jan. 07, 2019	Nov. 07, 2019	Conduction (CO05-HY)
Bilog Antenna	Schaffner	CBL6111C& N-6-06	2725&AT-N0 601	30MHz~1GHz	Oct. 13, 2018	Dec. 27, 2018	Oct. 12, 2019	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MX E)	MY5329005 3	20Hz to 26.5GHz	Jan. 16, 2018	Dec. 27, 2018	Jan. 15, 2019	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	May 21, 2018	Dec. 27, 2018	May 20, 2019	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4, MY28655/4	9KHz~30MHz	Jan. 02, 2018	Dec. 27, 2018	Jan. 01, 2019	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4, MY24971/4, MY15682/4	30MHz~1GHz	Feb. 27, 2018	Dec. 27, 2018	Feb. 26, 2019	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Dec. 27, 2018	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Dec. 27, 2018	N/A	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8 -24	8050400465 6H	N/A	N/A	Dec. 27, 2018	N/A	Radiation (03CH07-HY)
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz~30 MHz	May 29, 2018	Dec. 27, 2018	May 28, 2019	Radiation (03CH07-HY)
Filter	Wainwright	WHK20/100 0C7/40SS	SN3	20M High Pass	Nov. 02, 2018	Dec. 27, 2018	Nov. 01, 2019	Radiation (03CH07-HY)

Report No.: FR8N2626D

TEL: 886-3-327-3456 Page Number : 21 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.2
of 95% (U = 2Uc(y))	2.2

Report No.: FR8N2626D

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.4
of 95% (U = 2Uc(y))	3.4

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	F 7
of 95% (U = 2Uc(y))	5.7


TEL: 886-3-327-3456 Page Number : 22 of 22 FAX: 886-3-328-4978 Issued Date : Feb. 25, 2019



Appendix A. Test Results of Conducted Emission Test

Test Mode :	Mode 1	Temperature :	24~26℃			
Test Engineer :	Jimmy Chang	Relative Humidity :	51~53%			
Test Voltage :	120Vac / 60Hz	Phase :	Line			
Function Type:	Bluetooth Link + WLAN (5GHz) Link + NFC Link + MP3 Play + Keypad (53) + Std Battery + USB-C Adapter + USB-C Cable + Data Link with Notebook (Notebook to SD Card) for Sample 2					

Report No.: FR8N2626D



Final Result:


Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBuV)	(dBuV)	(dBuV)	(dB)			(dB)
0.161250		36.11	55.40	19.29	L1	OFF	19.5
0.161250	48.00		65.40	17.40	L1	OFF	19.5
0.181500		30.64	54.42	23.78	L1	OFF	19.5
0.181500	43.76		64.42	20.66	L1	OFF	19.5
0.521250		29.50	46.00	16.50	L1	OFF	19.5
0.521250	38.60		56.00	17.40	L1	OFF	19.5
1.495500		21.82	46.00	24.18	L1	OFF	19.6
1.495500	27.13		56.00	28.87	L1	OFF	19.6
3.428250		24.46	46.00	21.54	L1	OFF	19.6
3.428250	32.68		56.00	23.32	L1	OFF	19.6
3.855750		25.75	46.00	20.25	L1	OFF	19.6
3.855750	35.41		56.00	20.59	L1	OFF	19.6
9.444750		30.52	50.00	19.48	L1	OFF	19.7
9.444750	35.84		60.00	24.16	L1	OFF	19.7
13.560000		34.90	50.00	15.10	L1	OFF	19.7
13.560000	36.20		60.00	23.80	L1	OFF	19.7

TEL: 886-3-327-3456 Page Number : A1 of A2



Test Mode: Mode 1 Temperature: 24~26°C Jimmy Chang Test Engineer: Relative Humidity: 51~53% Test Voltage: 120Vac / 60Hz Phase: Neutral Bluetooth Link + WLAN (5GHz) Link + NFC Link + MP3 Play + Keypad (53) + Function Type: Std Battery + USB-C Adapter + USB-C Cable + Data Link with Notebook (Notebook to SD Card) for Sample 2

Report No.: FR8N2626D




Final Result:

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBuV)	(dBuV)	(dBuV)	(dB)			(dB)
0.161250		36.23	55.40	19.17	N	OFF	19.5
0.161250	51.09		65.40	14.31	N	OFF	19.5
0.172500		26.65	54.84	28.19	N	OFF	19.5
0.172500	46.15		64.84	18.69	N	OFF	19.5
0.501000		29.32	46.00	16.68	N	OFF	19.5
0.501000	36.12		56.00	19.88	N	OFF	19.5
1.477500		23.04	46.00	22.96	N	OFF	19.5
1.477500	29.00		56.00	27.00	N	OFF	19.5
3.963750		25.61	46.00	20.39	N	OFF	19.6
3.963750	34.25		56.00	21.75	N	OFF	19.6
9.528000		24.25	50.00	25.75	N	OFF	19.7
9.528000	29.56		60.00	30.44	N	OFF	19.7
13.560000		32.96	50.00	17.04	N	OFF	19.8
13.560000	34.22		60.00	25.78	N	OFF	19.8

TEL: 886-3-327-3456 Page Number : A2 of A2

Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth



Report No.: FR8N2626D

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

TEL: 886-3-327-3456 Page Number: B1 of B3



B2. Test Result of Frequency Stability

B3. Voltage vs. F	B3. Voltage vs. Frequency Stability		Temperature vs. Frequency Stability			
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)		
120	13.560180	-20	0	13.560160		
102	13.560170		2	13.560160		
138	13.560160		5	13.560150		
			10	13.560150		
		-10	0	13.560140		
			2	13.560150		
			5	13.560140		
			10	13.560150		
		0	0	13.560140		
			2	13.560140		
			5	13.560140		
			10	13.560140		
		10	0	13.560140		
			2	13.560140		
			5	13.560140		
			10	13.560140		
		20	0	13.560140		
			2	13.560140		
			5	13.560140		
			10	13.560140		
		30	0	13.560140		
			2	13.560140		
			5	13.560140		
			10	13.560140		
		40	0	13.560140		
			2	13.560140		
			5	13.560140		
			10	13.560140		

Report No.: FR8N2626D

TEL: 886-3-327-3456 Page Number : B2 of B3

Voltage vs. Frequ	ency Stability	Temperature vs. Frequency Stability			
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)	
		50	0	13.560140	
			2	13.560140	
			5	13.560140	
			10	13.560140	
Max.Deviation (MHz)	0.000180	Max.Deviati	on (MHz)	0.000160	
Max.Deviation (ppm)	13.2743	Max.Deviation (ppm)		11.7994	
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm	
Test Result	PASS	Test Result		PASS	


Report No.: FR8N2626D

TEL: 886-3-327-3456 Page Number : B3 of B3



Appendix C. Test Results of Radiated Test Items


C1. Test Result of Field Strength of Fundamental Emissions



Report No.: FR8N2626D


TEL: 886-3-327-3456 Page Number : C1 of C5

C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)



Report No.: FR8N2626D

TEL: 886-3-327-3456 Page Number : C2 of C5



Report No.: FR8N2626D

Note:

21.076

28.115

39.73

40.25

1. 13.56 MHz is fundamental signal which can be ignored.

-29.77

-29.25

2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

15.82

16.27

22.71

22.78

1.2

1.2

QΡ

QΡ

3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);


69.5

69.5

Limit line = specific limits (dBμV) + distance extrapolation factor.

TEL: 886-3-327-3456 Page Number: C3 of C5


C3. Results of Radiated Spurious Emissions (30MHz~1GHz)



Report No.: FR8N2626D

TEL: 886-3-327-3456 Page Number : C4 of C5





Report No.: FR8N2626D

Note:

- 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
- 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor= Level.

TEL: 886-3-327-3456 Page Number : C5 of C5