



EM7355/EM7655 Modem

Test Report

FOR
WCDMA / HSPA

Rev.2

FCC and IC Certifications

IC: 2417C-EM7355
FCC ID: N7NEM7355

© 2010 Sierra Wireless, Inc.

This document contains information which is proprietary and confidential to Sierra Wireless, Inc. Disclosure to persons other than the officers, employees, agents, or subcontractors of the Company or licensee of this document without the prior written permission of Sierra Wireless, Inc. is strictly prohibited.

Table of Contents

| | | |
|-----------|---|-----------|
| 1 | Introduction and Purpose | 4 |
| 1.1 | <i>Revision history.....</i> | 4 |
| 2 | Test Summary | 4 |
| 3 | Description of Equipment under Test | 4 |
| 3.1 | <i>Differences between EM7355 and EM7655</i> | 5 |
| 4 | Compliance Test Equipment List | 5 |
| 5 | Test Setup Block Diagrams | 6 |
| 5.1 | <i>Test Setup 1</i> | 6 |
| 5.2 | <i>Test Setup 2</i> | 6 |
| 6 | RF Power Output | 6 |
| 6.1 | <i>Test Procedure</i> | 7 |
| 6.1.1 | <i>WCDMA/HSDPA/HSUPA Max Power setup</i> | 7 |
| 6.2 | <i>Maximum Transmit Power Test Results</i> | 10 |
| 6.2.1 | <i>Test Results for WCDMA/HSDPA/HSUPA Output Power.....</i> | 10 |
| 7 | Occupied Bandwidth..... | 10 |
| 7.1 | <i>Test Procedure</i> | 10 |
| 7.2 | <i>Test Results</i> | 10 |
| 7.2.1 | <i>WCDMA Summary Results</i> | 10 |
| 7.2.2 | <i>WCDMA Rel99 Test Plots</i> | 11 |
| 7.2.3 | <i>HSUPA Rel6 (Subtest 5) Test Plots.....</i> | 12 |
| 8 | Out of Band Emissions at Antenna Terminals | 13 |
| 8.1 | <i>Test Procedure</i> | 14 |
| 8.2 | <i>Test Results</i> | 14 |
| 8.2.1 | <i>WCDMA Rel99 Test Plots</i> | 14 |
| 9 | Block Edge Compliance | 18 |
| 9.1 | <i>Test Procedure</i> | 18 |
| 9.2 | <i>Test Results</i> | 18 |
| 9.2.1 | <i>WCDMA Test Plots</i> | 19 |
| 10 | Frequency Stability versus Temperature..... | 21 |
| 10.1 | <i>Summary of Results.....</i> | 21 |
| 10.2 | <i>Test Procedure</i> | 22 |
| 10.3 | <i>Test Results</i> | 22 |
| 10.3.1 | <i>UMTS Frequency Error over Temperature</i> | 22 |
| 11 | Frequency Stability versus Voltage..... | 22 |
| 11.1 | <i>Summary of Results.....</i> | 22 |
| 11.2 | <i>Test Procedure</i> | 22 |
| 11.3 | <i>Test Results</i> | 23 |
| 11.3.1 | <i>UMTS Frequency Error over Voltage</i> | 23 |
| 12 | Peak to Average Ratio | 23 |
| 12.1 | <i>Summary of Results.....</i> | 23 |
| 12.2 | <i>Test Procedure</i> | 23 |
| 12.3 | <i>Test Results</i> | 23 |

SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|--------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 3 of 25 |
|------------------------------------|--------|---------------|--------------|

12.3.1 Test Plots..... 24

SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|--------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 4 of 25 |
|------------------------------------|--------|---------------|--------------|

1 Introduction and Purpose

This document provides test data for the EM7355 modem output power intended for FCC and Industry Canada certifications.

1.1 Revision history

| Rev | Date | Author | Summary of changes | ECO # |
|-----|---------------|--------------|--|-------|
| 1.0 | Aug. 15, 2012 | Markus Myers | First Release | |
| 2.0 | Feb. 05, 2013 | Markus Myers | Updated tables with channel frequencies. | |
| | | | | |

2 Test Summary

| FCC Rule | IC Standards | DESCRIPTION OF TEST | RESULT | PAGE |
|----------------------------------|------------------------------|--|----------|------|
| 2.1046 | RSS-132, 4.4 RSS-133, 6.4 | RF Power Output | Complies | 5 |
| 2.1049 | RSS-Gen, 4.6 | Occupied Bandwidth | Complies | 10 |
| 2.1051, 22.917, 24.238, 27.53 | RSS-132, 4.5 RSS-133, 6.5 | Out of Band Emissions at Antenna Terminals | Complies | 13 |
| 22.917, 24.238, 27.53 | RSS-Gen, 4.6 | Block Edge Compliance | Complies | 18 |
| 2.1055, 22.355, 24.235, 27.54 | RSS-132, 4.3 RSS-133, 6.3 | Frequency Stability versus Temperature | Complies | 21 |
| 2.1055, 22.355, 24.235, 27.54 | RSS-132, 4.3 RSS-133, 6.3 | Frequency Stability versus Voltage | Complies | 22 |
| 24.232, 27.50 | | Peak to Average Ratio | Complies | 23 |

3 Description of Equipment under Test

The EM7355/EM7655 modem, referred to as “EUT” hereafter, is a multi-band wireless modem operating on the GSM/GPRS/EDGE/UMTS/LTE/CDMA networks. The table below shows the supported North American bands for the device.

| Technology | Band | UL Freq. (MHz) | DL Freq. (MHz) | Max Power |
|------------|------|----------------|----------------|-------------------|
| LTE | B2 | 1850 – 1910 | 1930 – 1990 | 23 dBm (+/- 1 dB) |
| | B4 | 1710 – 1755 | 2110 – 2155 | 23 dBm (+/- 1 dB) |
| | B5 | 824 – 849 | 869 – 894 | 23 dBm (+/- 1 dB) |
| | B13 | 777 – 787 | 746 – 756 | 23 dBm (+/- 1 dB) |

© 2010 Sierra Wireless, Inc.

The contents of this page are subject to the confidentiality information on page one.

SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|--------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 5 of 25 |
|------------------------------------|--------|---------------|--------------|

| | | | | |
|---------------------------------|-------|-------------|-------------|-------------------|
| WCDMA / HSDPA/ HSUPA / HSPA+ | B17 | 704 – 716 | 734 – 746 | 23 dBm (+/- 1 dB) |
| | B25 | 1850 – 1915 | 1930 – 1995 | 23 dBm (+/- 1 dB) |
| | B2 | 1850 – 1910 | 1930 – 1990 | 23 dBm (+/- 1 dB) |
| | B4 | 1710 – 1755 | 2110 – 2155 | 23 dBm (+/- 1 dB) |
| | B5 | 824 – 849 | 869 – 894 | 23 dBm (+/- 1 dB) |
| CDMA / EVDO | BC0 | 824 – 849 | 869 – 894 | 24 dBm (+/- 1 dB) |
| | BC1 | 1850 – 1910 | 1930 – 1990 | 24 dBm (+/- 1 dB) |
| | BC10* | 817 – 824 | 862 – 869 | 24 dBm (+/- 1 dB) |
| GSM | G850 | 824 – 849 | 869 – 894 | 32.5 dBm (+/-1dB) |
| | G1900 | 1850 – 1910 | 1930 – 1990 | 29.5 dBm (+/-1dB) |
| EDGE | G850 | 824 – 849 | 869 – 894 | 27dBm (+/-1dB) |
| | G1900 | 1850 – 1910 | 1930 – 1990 | 26dBm (+/-1dB) |

* Only BC10 subclass 2 and 3 frequencies are supported by hardware and firmware.

3.1 Differences between EM7355 and EM7655


The EM7355 and EM7655 differ only in pcb length and host interface connector. Both products utilize the same pcb RF layout, components and firmware. Please refer to document “7x55 Comparison.pdf”.

4 Compliance Test Equipment List


| EQUIPMENT | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL. DUE DATE |
|---------------------|-----------------|------------|------------|------------------|
| Control Computer | TC | Generic PC | 100488 | N/A |
| Wireless Test Set | Rohde & Schwarz | CMU200 | 110521 | October 27, 2013 |
| Wireless Test Set | Rohde & Schwarz | CMW500 | 101060 | June 06, 2014 |
| Spectrum Analyzer | Rohde & Schwarz | FSP | 100060 | October 27, 2013 |
| DC Power Supply | HP | 6632A | 3530A | N/A |
| Interface Board | Shop built | ATEMux | N/A | N/A |
| Directional Coupler | Pasternack | PE2209-10 | N/A | N/A |

5 Test Setup Block Diagrams

5.1 Test Setup 1



5.2 Test Setup 2



6 RF Power Output

FCC 2.1046

6.1 Test Procedure

The transmitter output was connected to a Rohde & Schwarz CMU200 Test Set and configured to operate at maximum power in a call. The power was measured using the Average Power measurement of the CMU200. Refer to Test Setup 1.

6.1.1 WCDMA/HSDPA/HSUPA Max Power setup

Configure the call box to support all WCDMA tests in respect to the 3GPP 34.121 (listed in Table 4.2). Measure the power at Ch4132, 4182 and 4233 for US cell; Ch9262, 9400 and 9538 for US PCS band.

For Rel99 per 3GPP 35.121 5.2

- Set a Test Mode 1 loop back with a 12.2kbps Reference Measurement Channel (RMC)
- Set and send continuously Up power control commands to the EM7355 module.
- Measure the power at the EM7355 module antenna connector using the power meter with average detector

For HSDPA Rel 7 3 per GPP 35.121 5.2AA

- Establish a Test Mode 1 loop back with both 1 12.2kbps RMC channel and an H-Set1 Fixed Reference Channel (FRC). With the CMU200 this is accomplished by setting the signal Channel Coding to “Fixed Reference Channel” and configuring for HSET-1 QKSP.
- Set beta values and HSDPA settings for HSDPA Subtest1 according to Table 4.2
- Send continuously Up power control commands to the EM7355 module
- Measure the power at the EM7355 module antenna connector using the power meter with modulated average detector
- Repeat the measurement for the HSDPA Subtest2, 3 and 4 as given in Table 4.2

For HSUPA Rel 6 per 3GPP 35.121 5.2B

- Use UL RMC 12.2kbps and FRC H-Set1 QPSK, Test Mode 1 loop back. With the CMU200 this is accomplished by setting the signal Channel Coding to “E-DCH Test Channel” and configuring the equipment category to Cat5_10ms.
- Set the Absolute Grant for HSUPA Subtest1 according to Table 4.2
- Set the EM7355 module power to be at least 5dB lower than the Maximum output power
- Send power control bits to give one TPC_cmd = +1 command to the UNDP. If UNDP doesn’t send any E-DPCH data with decreased E-TFCI within 500ms, then repeat this process until the decreased E-TFCI is reported.
- Confirm that the E-TFCI transmitted by the EM7355 module is equal to the target E-TFCI in Table 4.2. If the E-TFCI transmitted by the EM7355 module is not equal to the target E-TFCI, then send power control bits to give one TPC_cmd = -1 command

SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|--------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 8 of 25 |
|------------------------------------|--------|---------------|--------------|

to the UE. If UE sends any E-DPCH data with decreased E-TFCI within 500 ms, send new power control bits to give one TPC_cmd = -1 command to the UE. Then confirm that the E-TFCI transmitted by the UE is equal to the target E-TFCI in Table 4.2. If the E-TFCI transmitted by the UE is not equal to the target E-TFCI, then fail the UE

- Measure the power using the power meter with an average detector
- Repeat the measurement for the HSUPA Subtest2, 3 and 4 as given in Table 4.2
- Test case 5 is tested using all up bits for maximum output power per 3GPP 34.521.

Table 4.2 3GPP Rel99/HSPA Subtest Settings

| | | | | | | Common Settings | | | | | HSDPA Specific Settings | | | | | | | HSUPA Sepcific Settings | | | HSUPA Additional Info | |
|---------|------------|---------------|-----------|----------|----------------|-----------------|-----------|-----|-----|---------------------------|-------------------------|-----------------|-----------------|---------------------------|-----------------------------|--------------------------------------|---------------------------------|-------------------------|------------------|----------|------------------------------------|----------------------------------|
| Subtest | Mode | Loopback Mode | Rel99 RMC | HSPA FRC | HSUPA Test | β_c | β_d | CM | MPR | Power Class 3 limit (dBm) | ΔA_{CK} | ΔN_{AK} | ΔC_{QI} | ACK-NAK repetition factor | CQI Feedback (Table 5.2B.4) | CQI Repetition Factor (Table 5.2B.4) | $A_{hs} = \beta_{hs} / \beta_c$ | $\Delta E-DPCCH$ | ΔH_{ARQ} | AG Index | ERFCI (from 34.121 Table C.11.1.3) | Associated Max UL Data Rate kbps |
| 1 | Rel99 | Testmode 1 | 12.2k bps | - | - | | | - | | 24 (+1.7/-3.7 dB) | | | | | | | | | | | | |
| 1 | Rel6 HSDPA | Testmode 1 | 12.2k bps | H-Set 1 | - | 2/15 | 15/15 | 0 | 0 | 24 (+1.7/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | | | | | |
| 2 | Rel6 HSDPA | Testmode 1 | 12.2k bps | H-Set 1 | - | 12/15 | 15/15 | 1 | 0 | 24 (+1.7/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | | | | | |
| 3 | Rel6 HSDPA | Testmode 1 | 12.2k bps | H-Set 1 | - | 15/15 | 8/15 | 1.5 | 0.5 | 23.5 (+2.2/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | | | | | |
| 4 | Rel6 HSDPA | Testmode 1 | 12.2k bps | H-Set 1 | - | 15/15 | 4/15 | 1.5 | 0.5 | 23.5 (+2.2/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | | | | | |
| 1 | Rel6 HSUPA | Testmode 1 | 12.2k bps | H-Set 1 | HSUPA Loopback | 11/15 | 15/15 | 1 | 0 | 24 (+1.7/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | 6 | 0 | 20 | 75 | 242.1 |
| 2 | Rel6 HSUPA | Testmode 1 | 12.2k bps | H-Set 1 | HSUPA Loopback | 6/15 | 15/15 | 3 | 2 | 22 (+3.7/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | 8 | 0 | 12 | 67 | 174.9 |
| 3 | Rel6 HSUPA | Testmode 1 | 12.2k bps | H-Set 1 | HSUPA Loopback | 15/15 | 9/15 | 2 | 1 | 23 (+2.7/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | 8 | 0 | 15 | 92 | 482.8 |
| 4 | Rel6 HSUPA | Testmode 1 | 12.2k bps | H-Set 1 | HSUPA Loopback | 2/15 | 15/15 | 3 | 2 | 22 (+3.7/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | 5 | 0 | 17 | 71 | 205.8 |
| 5 | Rel6 HSUPA | Testmode 1 | 12.2k bps | H-Set 1 | HSUPA Loopback | 15/15 | 15/15 | 1 | 0 | 24 (+1.7/-3.7 dB) | 8 | 8 | 8 | 3 | 4 ms | 2 | 30/15 | 7 | 0 | 81 | 81 | 308.9 |

© 2010 Sierra Wireless, Inc.

This document contains information which is proprietary and confidential to Sierra Wireless, Inc. Disclosure to persons other than the officers, employees, agents, or subcontractors of the Company or licensee of this document without the prior written permission of Sierra Wireless, Inc. is strictly prohibited.

6.2 Maximum Transmit Power Test Results

6.2.1 Test Results for WCDMA/HSDPA/HSUPA Output Power

| Mode | 3GPP Subtest | B5 (800 MHz) Channel Power (dBm) | | | B2 (1900 MHz) Channel Power (dBm) | | | B4 (1700 MHz) Channel Power (dBm) | | | MPR |
|------------|--------------|----------------------------------|------------------|------------------|-----------------------------------|-------------------|-------------------|-----------------------------------|-------------------|-------------------|-----|
| | | 4132 (826.4 MHz) | 4182 (836.4 MHz) | 4233 (846.6 MHz) | 9262 (1852.4 MHz) | 9400 (1880.0 MHz) | 9538 (1907.6 MHz) | 1312 (1712.4 MHz) | 1412 (1732.4 MHz) | 1513 (1752.6 MHz) | |
| Rel99 | 1 | 22.95 | 22.88 | 22.86 | 23.2 | 23.02 | 23.08 | 22.93 | 22.87 | 23.01 | N/A |
| Rel6 HSDPA | 1 | 22.44 | 22.28 | 22.35 | 22.52 | 22.54 | 22.66 | 22.85 | 22.37 | 22.82 | 0 |
| | 2 | 22.42 | 22.34 | 22.27 | 22.69 | 22.7 | 22.74 | 22.94 | 22.82 | 22.82 | 0 |
| | 3 | 21.89 | 21.81 | 21.9 | 22.25 | 22.16 | 22.36 | 22.3 | 22.22 | 22.27 | 0.5 |
| | 4 | 21.96 | 21.77 | 21.82 | 22.22 | 22.33 | 22.38 | 22 | 22.16 | 22.34 | 0.5 |
| Rel6 HSUPA | 1 | 22.25 | 22.31 | 22.27 | 22.23 | 22.49 | 22.53 | 22.23 | 22.52 | 22.43 | 0 |
| | 2 | 20.6 | 20.19 | 20.2 | 20.72 | 20.5 | 20.85 | 20.6 | 20.71 | 20.41 | 2 |
| | 3 | 21.45 | 21.16 | 21.2 | 21.59 | 21.89 | 21.5 | 21.85 | 21.46 | 21.78 | 1 |
| | 4 | 21.62 | 21.26 | 21.3 | 21.41 | 21.63 | 21.57 | 21.74 | 21.41 | 21.6 | 2 |
| | 5 | 22.65 | 22.35 | 22.38 | 22.67 | 22.62 | 22.67 | 22.43 | 22.55 | 22.76 | 0 |

7 Occupied Bandwidth

FCC 2.1049

7.1 Test Procedure

The transmitter output was connected to a spectrum analyzer through a calibrated coaxial cable and a directional coupler. The occupied bandwidth (defined as the 99% Power Bandwidth) was measured with the spectrum analyzer at low, middle, and high frequencies in each band. The -26dB bandwidth was also measured and recorded. Refer to Test Setup 1.

7.2 Test Results

For WCDMA testing, Rel 99 setup used RMC 12.2kps and R6 HSUPA used setup for 3GPP subtest 5.

7.2.1 WCDMA Summary Results

| Mode | Band | Frequency (MHz) | Channel | 99% Occupied Bandwidth (MHz) | -26dBc Occupied Bandwidth (MHz) | Corresponding Plot number |
|------|-------|-----------------|---------|------------------------------|---------------------------------|---------------------------|
| B2 | Rel99 | 1880 | 9400 | 4.20 | 4.72 | 7.2.2.1 |

© 2010 Sierra Wireless, Inc.

This document contains information which is proprietary and confidential to Sierra Wireless, Inc. Disclosure to persons other than the officers, employees, agents, or subcontractors of the Company or licensee of this document without the prior written permission of Sierra Wireless, Inc. is strictly prohibited.


SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 11 of 25 |
|------------------------------------|--------|---------------|---------------|


| | | | | | | |
|----|---------------|--------|------|------|------|---------|
| | Rel 6 (HSUPA) | 1880 | 9400 | 4.20 | 4.76 | 7.2.3.1 |
| B4 | Rel99 | 1732.4 | 1412 | 4.20 | 4.70 | 7.2.2.2 |
| | Rel 6 (HSUPA) | 1732.4 | 1412 | 4.18 | 4.72 | 7.2.3.2 |
| B5 | Rel99 | 836.4 | 4182 | 4.18 | 4.68 | 7.2.2.3 |
| | Rel 6 (HSUPA) | 836.4 | 4182 | 4.16 | 4.70 | 7.2.3.3 |

7.2.2 WCDMA Rel99 Test Plots


7.2.2.1 WCDMA Occupied Bandwidth, B2 Middle channel, 1880 MHz, 99% BW



7.2.2.2 WCDMA Occupied Bandwidth, B4 Middle channel, 1732.4 MHz, 99% BW




7.2.2.3 WCDMA Occupied Bandwidth, B5 Middle channel, 836.4 MHz, 99% BW



7.2.3 HSUPA Rel6 (Subtest 5) Test Plots


7.2.3.1 WCDMA Rel. 6 Occupied Bandwidth, B2 Middle channel, 1880 MHz, 99% BW




SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 13 of 25 |
|------------------------------------|--------|---------------|---------------|

7.2.3.2 WCDMA Rel. 6 Occupied Bandwidth, B4 Middle channel, 1732.4 MHz, 99% BW



7.2.3.3 WCDMA Rel. 6 Occupied Bandwidth, B5 Middle channel, 836.4 MHz, 99% BW



8 Out of Band Emissions at Antenna Terminals

FCC 2.1051, 22.917, 24.238(a), 27.53(h)

Out of Band Emissions:

The mean power of emissions must be attenuated below the mean power of the unmodulated carrier (P) on any frequency outside the frequency band by at least $(43 + 10 \log P)$ dB. The out of band emission limit translates to a worst case absolute limit of -13dBm in this case.

© 2010 Sierra Wireless, Inc.

The contents of this page are subject to the confidentiality information on page one.

SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 14 of 25 |
|------------------------------------|--------|---------------|---------------|

8.1 Test Procedure

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band emissions, if any, up to 10th harmonic. The EUT was scanned for spurious emissions from 1MHz to 20GHz with sufficient bandwidth and video resolution. Data plots are included. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were captured. Refer to Test Setup 1.

8.2 Test Results


Refer to the following plots.

| Mode | Band | Frequency (MHz) | Channel | Corresponding Plot number |
|-------|------|-----------------|---------|------------------------------|
| Rel99 | B2 | 1880 | 9400 | Plot 6.3.2.3, Plot 6.3.2.4 |
| | B4 | 1732.4 | 1412 | Plot 6.3.2.9, Plot 6.3.2.10 |
| | B5 | 836.4 | 4182 | Plot 6.3.2.11, Plot 6.3.2.11 |

The plots below show that the conducted emission limits requirements are met.

8.2.1 WCDMA Rel99 Test Plots


8.2.1.1 Out of Band Emissions at Antenna Terminals WCDMA B2, Middle channel, 1880 MHz, 2 Hz to 1 GHz



SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 15 of 25 |
|------------------------------------|--------|---------------|---------------|


8.2.1.2 Out of Band Emissions at Antenna Terminals WCDMA B2, Middle channel, 1880 MHz, 1 GHz to 10 GHz



Date: 4.OCT.2012 15:32:06

Note: The strong emission shown is the carrier signal.

8.2.1.3 Out of Band Emissions at Antenna Terminals WCDMA B2, Middle channel, 1880 MHz, 10 GHz to 20 GHz




Date: 4.OCT.2012 15:34:12


SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 16 of 25 |
|------------------------------------|--------|---------------|---------------|

8.2.1.4 Out of Band Emissions at Antenna Terminals WCDMA B4, Middle channel, 1880 MHz, 2 Hz to 1 GHz



8.2.1.5 Out of Band Emissions at Antenna Terminals WCDMA B4, Middle channel, 1880 MHz, 1 GHz to 10 GHz




Note: The strong emission shown is the carrier signal.


SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 17 of 25 |
|------------------------------------|--------|---------------|---------------|

8.2.1.6 Out of Band Emissions at Antenna Terminals WCDMA B4, Middle channel, 1880 MHz, 10 GHz to 20 GHz




8.2.1.7 Out of Band Emissions at Antenna Terminals WCDMA B5, Middle channel, 836.4 MHz, 2 Hz to 1 GHz



Note: The strong emission shown in each case is the carrier signal.

8.2.1.8 Out of Band Emissions at Antenna Terminals WCDMA B5, Middle channel, 836.4 MHz, 1 GHz to 10 GHz



9 Block Edge Compliance

FCC Part 2.1051, 22.917, 24.238(a), 27.53(h)

9.1 Test Procedure

The transmitter output was connected to a Rohde & Schwarz CMU200 Test Set, through a coaxial RF cable and a directional coupler, and configured to operate at maximum power. The block edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer. Refer to Test Setup 1.

The resolution bandwidth was set to at least 1% of the emission bandwidth (where applicable). The power was scaled accordingly:

$$\text{Power offset} = 10 \cdot \log(\text{FCC_RBW} / \text{Measurement_RBW})$$

9.2 Test Results

| Block Test | Band | Frequency Boundaries (MHz) | Channels Tested | Channel Frequencies (MHz) | Corresponding Plots | Result |
|------------|------|--------------------------------|-----------------|---------------------------|---------------------|----------|
| WCDMA | B2 | Below 1850 MHz, above 1910 MHz | 9262, 9538 | 1852.4, 1907.6 | 9.2.1.1, 9.2.1.2 | Complies |


SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 19 of 25 |
|------------------------------------|--------|---------------|---------------|


| | | | | | | |
|--|----|--------------------------------|------------|----------------|------------------|----------|
| | B4 | Below 1710 MHz, above 1755 MHz | 1312, 1513 | 1712.4, 1752.6 | 9.2.1.3, 9.2.1.4 | Complies |
| | B5 | Below 824 MHz, above 849 MHz | 4132, 4233 | 826.4, 846.6 | 9.2.1.5, 9.2.1.6 | Complies |

9.2.1 WCDMA Test Plots

9.2.1.1 WCDMA B2 low channel, below 1850 MHz



9.2.1.2 WCDMA B2 high channel, above 1910 MHz




© 2010 Sierra Wireless, Inc.

The contents of this page are subject to the confidentiality information on page one.


SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 20 of 25 |
|------------------------------------|--------|---------------|---------------|


9.2.1.3 WCDMA B4 low channel, below 1710 MHz




9.2.1.4 WCDMA B4 high channel, above 1755 MHz



9.2.1.5 WCDMA B5 low channel, below 824 MHz



9.2.1.6 WCDMA B5 high channel, above 849 MHz



10 Frequency Stability versus Temperature

FCC 2.1055, FCC 22.355, FCC 24.235, FCC 27.54

10.1 Summary of Results

The EUT's Frequency Stability versus temperature meets the requirements of less than 2.5ppm when temperature varies from -30°C to +50°C.

10.2 Test Procedure

The EUT was placed inside a temperature chamber. The temperature was set to -30°C and maintained to stabilize. After sufficient soak time, the transmitting frequency error was measured. The temperature was then increased by 10 degrees, maintained to stabilize, and the measurement was repeated. This procedure was repeated until +50°C is reached. Frequency metering included internal averaging of the CMU200 to stabilize the reading. Reference power supply voltage for these tests is 3.7 volts. Refer to Test Setup 2.

10.3 Test Results

10.3.1 UMTS Frequency Error over Temperature

| Temp (°C) | WCDMA R99 Mode | | | | | |
|-----------|----------------|--------------|---------------|--------------|--------------|--------------|
| | B2 (1900 MHz) | | B4 (1700 MHz) | | B5 (800 MHz) | |
| | Offset (Hz) | Offset (ppm) | Offset (Hz) | Offset (ppm) | Offset (Hz) | Offset (ppm) |
| -30 | -5.7 | -0.0029 | -11.0 | -0.0063 | -0.3 | -0.0003 |
| -20 | -6.3 | -0.0032 | -11.1 | -0.0063 | -4.2 | -0.0050 |
| -10 | 0.6 | 0.0003 | -10.9 | -0.0062 | -6.1 | -0.0073 |
| 0 | -6.1 | -0.0031 | -12.3 | -0.0070 | -0.8 | -0.0010 |
| 10 | -5.8 | -0.0030 | -10.9 | -0.0062 | -5.3 | -0.0064 |
| 20 | 1.4 | 0.0007 | -10.7 | -0.0061 | -5.4 | -0.0064 |
| 30 | -6.5 | -0.0033 | -11.7 | -0.0067 | -6.3 | -0.0075 |
| 40 | -7.0 | -0.0036 | -12.4 | -0.0071 | -4.3 | -0.0052 |
| 50 | 0.3 | 0.0002 | -9.7 | -0.0056 | -5.9 | -0.0071 |

11 Frequency Stability versus Voltage

FCC 2.1055, FCC 22.355, FCC 24.235, FCC 27.54

11.1 Summary of Results

The EUT is specified to operate with a supply voltage varying between 3.0 VDC and 4.2 VDC, having a nominal voltage of 3.7 VDC. It meets the frequency stability limit of less than 2.5ppm when supply voltage varies within the specified limits. Operation above or below these voltage limits is prohibited by firmware in order to prevent improper operation.

11.2 Test Procedure

The EUT was connected to a DC Power Supply and a UMTS test set (CMU 200) with frequency error measurement capability. The power supply output was adjusted to the test voltage as measured at the input terminals to the device while transmitting. A voltmeter was used to confirm the terminal voltage. The peak frequency error is recorded (worst case). The test voltages are 3.0 volts to 4.2 volts. Refer to Test Setup 2.

11.3 Test Results

11.3.1 UMTS Frequency Error over Voltage

| Voltage (V) | WCDMA R99 Mode | | | | | |
|-------------|----------------|--------------|---------------|--------------|--------------|--------------|
| | B2 (1900 MHz) | | B4 (1700 MHz) | | B5 (800 MHz) | |
| | Offset (Hz) | Offset (ppm) | Offset (Hz) | Offset (ppm) | Offset (Hz) | Offset (ppm) |
| 3 | -12.4 | -0.0064 | -3.1 | -0.0018 | -6.0 | -0.0072 |
| 3.7 | -9.7 | -0.0050 | -2.7 | -0.0016 | -4.1 | -0.0049 |
| 4.2 | -11.6 | -0.0059 | -8.3 | -0.0048 | -6.4 | -0.0076 |

12 Peak to Average Ratio

FCC 27.50(d)

12.1 Summary of Results

The EUT meets the requirement of having a peak to average ratio of less than 13dB.

12.2 Test Procedure

The transmitter output was connected to a Rohde & Schwarz CMU200 through a coaxial RF cable and directional coupler, and configured to operate at maximum power. The peak to average ratio was measured at the required operating frequencies in each band on the Spectrum Analyzer. Refer to Test Setup 1.


12.3 Test Results

| Band | Frequency (MHz) | Channel | Modulation | Plots | Peak to Average Ratio (dB) |
|------|-----------------|---------|------------|----------|----------------------------|
| B2 | 1880 | 9400 | QPSK | 12.3.1.1 | 3.36 |
| B4 | 1732.4 | 1412 | | 12.3.1.2 | 3.06 |
| B5 | 836.4 | 4182 | | 12.3.1.3 | 3.22 |

SIERRA WIRELESS, INC.


12.3.1 Test Plots

12.3.1.1 WCDMA peak to average ratio, QPSK Band 2, Mid channel, 1880 MHz



Date: 4.OCT.2012 14:50:20

12.3.1.2 WCDMA peak to average ratio, QPSK Band 4, Mid channel, 1732.4 MHz




Date: 4.OCT.2012 15:52:57

SIERRA WIRELESS, INC.

| | | | |
|------------------------------------|--------|---------------|---------------|
| FCC Part 22/24/27, RSS-132/133/139 | EM7355 | Feb. 05, 2013 | Page 25 of 25 |
|------------------------------------|--------|---------------|---------------|

12.3.1.3 WCDMA peak to average ratio, QPSK Band 5, Mid channel, 836.4 MHz



Date: 4.OCT.2012 16:43:47