#01_HAC_E_GSM850_GSM Voice_Ch128

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 824.2 MHz;Duty Cycle: 1:8.6896

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 29.61 V/m; Power Drift = 0.13 dB

Applied MIF = 3.63 dB

RF audio interference level = 32.90 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **29.7 dBV/m**	Grid 2 **M4** **31.66 dBV/m**	Grid 3 **M4** **31.66 dBV/m**
Grid 4 **M4** **30.62 dBV/m**	Grid 5 **M4** **32.37 dBV/m**	Grid 6 **M4** **32.37 dBV/m**
Grid 7 **M4** **31.89 dBV/m**	Grid 8 **M4** **32.9 dBV/m**	Grid 9 **M4** **32.75 dBV/m**

Cursor:
Total = 32.90 dBV/m
E Category: M4
Location: -4, 25, 8.7 mm

0 dB = 44.15 V/m = 32.90 dBV/m

#02_HAC_E_GSM850_GSM Voice_Ch189

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 836.4 MHz;Duty Cycle: 1:8.6896

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm
Device Reference Point: 0, 0, -6.3 mm
Reference Value = 41.96 V/m; Power Drift = -0.06 dB
Applied MIF = 3.63 dB
RF audio interference level = 36.19 dBV/m
**Emission category: M4**

MIF scaled E-field

Grid 1 **M4** **32.36 dBV/m**	Grid 2 **M4** **34.45 dBV/m**	Grid 3 **M4** **34.46 dBV/m**
Grid 4 **M4** **33.62 dBV/m**	Grid 5 **M4** **35.42 dBV/m**	Grid 6 **M4** **35.42 dBV/m**
Grid 7 **M4** **35.19 dBV/m**	Grid 8 **M4** **36.19 dBV/m**	Grid 9 **M4** **36.07 dBV/m**

Cursor:
Total = 36.19 dBV/m
E Category: M4
Location: -4.5, 25, 8.7 mm

0 dB = 64.52 V/m = 36.19 dBV/m

#03_HAC_E_GSM850_GSM Voice_Ch251

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 848.8 MHz;Duty Cycle: 1:8.6896

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 39.25 V/m; Power Drift = -0.05 dB

Applied MIF = 3.63 dB

RF audio interference level = 35.96 dBV/m

**Emission category: M4**

MIF scaled E-field

Grid 1 **M4** **31.43 dBV/m**	Grid 2 **M4** **34.01 dBV/m**	Grid 3 **M4** **34.06 dBV/m**
Grid 4 **M4** **32.96 dBV/m**	Grid 5 **M4** **35.14 dBV/m**	Grid 6 **M4** **35.15 dBV/m**
Grid 7 **M4** **34.65 dBV/m**	Grid 8 **M4** **35.96 dBV/m**	Grid 9 **M4** **35.9 dBV/m**

Cursor:
Total = 35.96 dBV/m
E Category: M4
Location: -5.5, 25, 8.7 mm

0 dB = 62.79 V/m = 35.96 dBV/m

#04_HAC_E_GSM1900_GSM Voice_Ch512

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1850.2 MHz;Duty Cycle: 1:8.6896

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 15.39 V/m; Power Drift = 0.01 dB

Applied MIF = 3.63 dB

RF audio interference level = 30.11 dBV/m

**Emission category: M3**

MIF scaled E-field

Grid 1 **M4** **25.76 dBV/m**	Grid 2 **M4** **29.64 dBV/m**	Grid 3 **M3** **30.11 dBV/m**
Grid 4 **M4** **24.47 dBV/m**	Grid 5 **M4** **29.14 dBV/m**	Grid 6 **M4** **29.71 dBV/m**
Grid 7 **M4** **25.16 dBV/m**	Grid 8 **M4** **27.15 dBV/m**	Grid 9 **M4** **28.08 dBV/m**

Cursor:
Total = 30.11 dBV/m
E Category: M4
Location: -14, -19.5, 8.7 mm

0 dB = 32.05 V/m = 30.11 dBV/m

#05_HAC_E_GSM1900_GSM Voice_Ch512;Battery 2

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1850.2 MHz;Duty Cycle: 1:8.6896

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 14.98 V/m; Power Drift = -0.01 dB

Applied MIF = 3.63 dB

RF audio interference level = 29.94 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **25.49 dBV/m**	Grid 2 **M4** **29.66 dBV/m**	Grid 3 **M4** **29.94 dBV/m**
Grid 4 **M4** **24.76 dBV/m**	Grid 5 **M4** **29.1 dBV/m**	Grid 6 **M4** **29.66 dBV/m**
Grid 7 **M4** **26.48 dBV/m**	Grid 8 **M4** **26.88 dBV/m**	Grid 9 **M4** **27.83 dBV/m**

Cursor:
Total = 29.94 dBV/m
E Category: M4
Location: -13.5, -18.5, 8.7 mm

0 dB = 31.40 V/m = 29.94 dBV/m

#06_HAC_E_GSM1900_GSM Voice_Ch512;Battery 3

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1850.2 MHz;Duty Cycle: 1:8.6896

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 14.97 V/m; Power Drift = -0.04 dB

Applied MIF = 3.63 dB

RF audio interference level = 29.86 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **25.53 dBV/m**	Grid 2 **M4** **29.63 dBV/m**	Grid 3 **M4** **29.86 dBV/m**
Grid 4 **M4** **24.66 dBV/m**	Grid 5 **M4** **29.06 dBV/m**	Grid 6 **M4** **29.59 dBV/m**
Grid 7 **M4** **26.45 dBV/m**	Grid 8 **M4** **26.87 dBV/m**	Grid 9 **M4** **27.77 dBV/m**

Cursor:
Total = 29.86 dBV/m
E Category: M4
Location: -13.5, -19, 8.7 mm

0 dB = 31.13 V/m = 29.86 dBV/m

#07_HAC_E_GSM1900_GSM Voice_Ch661

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz;Duty Cycle: 1:8.6896

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 14.96 V/m; Power Drift = -0.04 dB

Applied MIF = 3.63 dB

RF audio interference level = 29.78 dBV/m

**Emission category: M4**

MIF scaled E-field

Grid 1 **M4** **26.48 dBV/m**	Grid 2 **M4** **29.31 dBV/m**	Grid 3 **M4** **29.78 dBV/m**
Grid 4 **M4** **24.13 dBV/m**	Grid 5 **M4** **28.94 dBV/m**	Grid 6 **M4** **29.52 dBV/m**
Grid 7 **M4** **24.3 dBV/m**	Grid 8 **M4** **27.13 dBV/m**	Grid 9 **M4** **27.85 dBV/m**

Cursor:
Total = 29.78 dBV/m
E Category: M4
Location: -14.5, -19, 8.7 mm

0 dB = 30.83 V/m = 29.78 dBV/m

#08_HAC_E_GSM1900_GSM Voice_Ch810

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1909.8 MHz;Duty Cycle: 1:8.6896

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 15.27 V/m; Power Drift = -0.08 dB

Applied MIF = 3.63 dB

RF audio interference level = 29.21 dBV/m

**Emission category: M4**

MIF scaled E-field

Grid 1 **M4** **25.79 dBV/m**	Grid 2 **M4** **28.7 dBV/m**	Grid 3 **M4** **29.21 dBV/m**
Grid 4 **M4** **23.74 dBV/m**	Grid 5 **M4** **28.56 dBV/m**	Grid 6 **M4** **29.2 dBV/m**
Grid 7 **M4** **24.58 dBV/m**	Grid 8 **M4** **27.4 dBV/m**	Grid 9 **M4** **28.24 dBV/m**

Cursor:
Total = 29.21 dBV/m
E Category: M4
Location: -15.5, -10.5, 8.7 mm

0 dB = 28.88 V/m = 29.21 dBV/m

#09_HAC_E_LTE Band 41_20M_QPSK_1_0_Ch39750

Communication System: LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK); Frequency: 2506 MHz;Duty Cycle: 1:8.33681

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 12.72 V/m; Power Drift = -0.00 dB

Applied MIF = -1.62 dB

RF audio interference level = 24.05 dBV/m

**Emission category: M4**

MIF scaled E-field

Grid 1 **M4** **22.23 dBV/m**	Grid 2 **M4** **21.4 dBV/m**	Grid 3 **M4** **22.68 dBV/m**
Grid 4 **M4** **22.99 dBV/m**	Grid 5 **M4** **22.57 dBV/m**	Grid 6 **M4** **23.32 dBV/m**
Grid 7 **M4** **24.05 dBV/m**	Grid 8 **M4** **23.94 dBV/m**	Grid 9 **M4** **23.94 dBV/m**

Cursor:
Total = 24.05 dBV/m
E Category: M4
Location: 25, 25, 8.7 mm

0 dB = 15.93 V/m = 24.04 dBV/m

#10_HAC_E_LTE Band 41_20M_QPSK_1_0_Ch40185

Communication System: LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK); Frequency: 2549.5 MHz;Duty Cycle: 1:8.33681

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 12.89 V/m; Power Drift = -0.06 dB

Applied MIF = -1.62 dB

RF audio interference level = 22.74 dBV/m

**Emission category: M4**

MIF scaled E-field

Grid 1 **M4** **20.1 dBV/m**	Grid 2 **M4** **21.44 dBV/m**	Grid 3 **M4** **22.18 dBV/m**
Grid 4 **M4** **20.94 dBV/m**	Grid 5 **M4** **22.03 dBV/m**	Grid 6 **M4** **22.56 dBV/m**
Grid 7 **M4** **22.41 dBV/m**	Grid 8 **M4** **22.74 dBV/m**	Grid 9 **M4** **22.67 dBV/m**

Cursor:
Total = 22.74 dBV/m
E Category: M4
Location: -6, 25, 8.7 mm

0 dB = 13.70 V/m = 22.73 dBV/m

#11_HAC_E_LTE Band 41_20M_QPSK_1_0_Ch40620

Communication System: LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK); Frequency: 2593 MHz;Duty Cycle: 1:8.33681

Medium: Air Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 0 kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 12.38 V/m; Power Drift = -0.09 dB

Applied MIF = -1.62 dB

RF audio interference level = 23.41 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** 20.4 dBV/m	Grid 2 **M4** 19.63 dBV/m	Grid 3 **M4** 20.33 dBV/m
Grid 4 **M4** 21 dBV/m	Grid 5 **M4** 21.25 dBV/m	Grid 6 **M4** 21.31 dBV/m
Grid 7 **M4** 21.63 dBV/m	Grid 8 **M4** 23.41 dBV/m	Grid 9 **M4** 23.29 dBV/m

Cursor:
Total = 23.41 dBV/m
E Category: M4
Location: -5.5, 25, 8.7 mm

0 dB = 14.80 V/m = 23.41 dBV/m

#12_HAC_E_LTE Band 41_20M_QPSK_1_0_Ch41055

Communication System: LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK); Frequency: 2636.5 MHz;Duty Cycle: 1:8.33681

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 12.71 V/m; Power Drift = -0.09 dB

Applied MIF = -1.62 dB

RF audio interference level = 22.32 dBV/m

**Emission category: M4**

MIF scaled E-field

Grid 1 **M4** **19.89 dBV/m**	Grid 2 **M4** **20.26 dBV/m**	Grid 3 **M4** **20.86 dBV/m**
Grid 4 **M4** **20.4 dBV/m**	Grid 5 **M4** **21.65 dBV/m**	Grid 6 **M4** **22.02 dBV/m**
Grid 7 **M4** **21.36 dBV/m**	Grid 8 **M4** **22.31 dBV/m**	Grid 9 **M4** **22.32 dBV/m**

Cursor:
Total = 22.32 dBV/m
E Category: M4
Location: -9.5, 25, 8.7 mm

0 dB = 13.06 V/m = 22.32 dBV/m

#13_HAC_E_LTE Band 41_20M_QPSK_1_0_Ch41490

Communication System: LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK); Frequency: 2680 MHz; Duty Cycle: 1:8.33681

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 0$ kg/m^3

Ambient Temperature：23.5 ℃

DASY5 Configuration:
- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2018/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn917; Calibrated: 2017/12/14
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (0);SEMCAD X Version 14.6.10 (7417)

E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 13.68 V/m; Power Drift = -0.01 dB

Applied MIF = -1.62 dB

RF audio interference level = 23.20 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4**	Grid 2 **M4**	Grid 3 **M4**
21.8 dBV/m	**21.09 dBV/m**	**21.47 dBV/m**
Grid 4 **M4**	Grid 5 **M4**	Grid 6 **M4**
22.1 dBV/m	**22.28 dBV/m**	**22.57 dBV/m**
Grid 7 **M4**	Grid 8 **M4**	Grid 9 **M4**
22.5 dBV/m	**23.17 dBV/m**	**23.2 dBV/m**

Cursor:
Total = 23.20 dBV/m
E Category: M4
Location: -10, 25, 8.7 mm

0 dB = 14.45 V/m = 23.20 dBV/m