

FCC RF Test Report

APPLICANT : Motorola Solutions, Inc.
EQUIPMENT : Touch Computer
BRAND NAME : Motorola
MODEL NAME : TC55CH
FCC ID : UZ7TC55CH
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Jan. 08, 2014 and testing was completed on Jan. 25, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Louis Wu

Reviewed by: Louis Wu / Manager

Jones Tsai

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Testing Site	6
1.7 Applied Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Descriptions of Test Mode	8
2.2 Test Mode	9
2.3 Connection Diagram of Test System	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example	11
3 TEST RESULT	12
3.1 Number of Channel Measurement	12
3.2 Hopping Channel Separation Measurement	14
3.3 Dwell Time Measurement	21
3.4 20dB Bandwidth Measurement	24
3.5 Peak Output Power Measurement	31
3.6 Conducted Band Edges Measurement	33
3.7 Conducted Spurious Emission Measurement	40
3.8 Radiated Band Edges and Spurious Emission Measurement	50
3.9 AC Conducted Emission Measurement	63
3.10 Antenna Requirements	67
4 LIST OF MEASURING EQUIPMENT	68
5 UNCERTAINTY OF EVALUATION	69
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR3O1108-01A	Rev. 01	Initial issue of report	Feb. 10, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 17.31 dB at 30.540 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 7.00 dB at 13.558 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Motorola Solutions, Inc.

One Motorola Plaza, Holtsville, NY 11742-1300 USA

1.2 Manufacturer

Motorola Solutions, Inc.

One Motorola Plaza, Holtsville, NY 11742-1300 USA

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Touch Computer
Brand Name	Motorola
Model Name	TC55CH
FCC ID	UZ7TC55CH
Sample 1	EUT with Scanner
Sample 2	EUT without Scanner
EUT supports Radios application	CDMA/EV-DO/LTE WLAN 11abgn / Bluetooth 2.1 / 3.0 / 4.0 / NFC
HW Version	DV2.2
SW Version	Android 4.1.2
FW Version	BSP 1.7
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 3.89 dBm (0.0024 W) Bluetooth EDR (2Mbps) : 4.22 dBm (0.0026 W) Bluetooth EDR (3Mbps) : 4.45 dBm (0.0028 W)
Antenna Type	PIFA Antenna type with gain 0.20 dBi (Battery 1) PIFA Antenna type with gain 0.08 dBi (Battery 2)
Type of Modulation	Bluetooth 2.1 BR (1Mbps) : GFSK Bluetooth 2.1 EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth 2.1 EDR (3Mbps) : 8-DPSK Bluetooth 3.0 BR (1Mbps) : GFSK Bluetooth 3.0 EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth 3.0 EDR (3Mbps) : 8-DPSK

The bluetooth antenna is not changed while using battery cover 1 or 2. The antenna gain difference is due to antenna gain measurement result by using different battery covers.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH02-HY	CO05-HY	03CH07-HY	722060

Note: The test site complies with ANSI C63.4 2003 requirement.

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	3.37 dBm	3.26 dBm	3.21 dBm
Ch39	2441MHz	3.89 dBm	3.74 dBm	3.86 dBm
Ch78	2480MHz	3.29 dBm	3.24 dBm	3.16 dBm

Channel	Frequency	Bluetooth RF Output Power		
		π /4-DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	3.78 dBm	3.64 dBm	3.59 dBm
Ch39	2441MHz	4.13 dBm	4.22 dBm	4.18 dBm
Ch78	2480MHz	3.53 dBm	3.46 dBm	3.42 dBm

Channel	Frequency	Bluetooth RF Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	3.82 dBm	3.65 dBm	3.63 dBm
Ch39	2441MHz	4.34 dBm	4.26 dBm	4.45 dBm
Ch78	2480MHz	3.74 dBm	3.61 dBm	3.56 dBm

Remark: The data rate was set in 3Mbps for all the test items due to the highest RF output power.

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Y plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :CDMA2000 BC0 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + Scanner + NFC active + USB Cable (Charging from Adapter) + Battery 2 for Sample 1		
Remark:			
1. For radiated test cases, the data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 3Mbps, and no other significantly frequencies found in conducted spurious emission.			
2. “Bluetooth Link” means EUT linked with Bluetooth headset.			
3. “WLAN Link” means EUT associated with AP at 2.4GHz band.			
4. ”Scanner” stands for scanning and decoding a barcode by scanner.			
5. “NFC active” means turning on NFC function of EUT.			
6. For radiated test cases, the test cases were performance with Battery 2 and Sample 1.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
6.	Earphone	Cotron	MAX-300	N/A	Unshielded, 1.2 m	N/A
7.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, "QRCT" installed in the notebook make the EUT provides functions like channel selection and power level for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW \geq 1% of the span; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78


Date: 17.JAN.2014 11:09:49



Date: 17.JAN.2014 11:13:42

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
 $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation


Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6213	Pass
39	2441	1.002	0.6240	Pass
78	2480	1.002	0.6267	Pass


Channel Separation Plot on Channel 00 - 01



Date: 17.JAN.2014 13:41:18

Channel Separation Plot on Channel 39 - 40


Date: 17.JAN.2014 13:43:05

Channel Separation Plot on Channel 77 - 78



Date: 17.JAN.2014 13:44:01




Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8640	Pass
39	2441	1.002	0.8640	Pass
78	2480	1.002	0.8640	Pass


Channel Separation Plot on Channel 00 - 01



Date: 17.JAN.2014 13:49:13

Channel Separation Plot on Channel 39 - 40


Date: 17.JAN.2014 13:48:10

Channel Separation Plot on Channel 77 - 78



Date: 17.JAN.2014 13:46:54




Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8720	Pass
39	2441	1.002	0.8720	Pass
78	2480	1.002	0.8720	Pass


Channel Separation Plot on Channel 00 - 01



Date: 17.JAN.2014 13:51:30

Channel Separation Plot on Channel 39 - 40


Date: 17.JAN.2014 13:53:04

Channel Separation Plot on Channel 77 - 78


Date: 17.JAN.2014 13:54:12

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Test Mode :	DH5	Temperature :	24~26℃
Test Engineer :	Rover Lee	Relative Humidity :	48~51%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

Remark:

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate $(1600 / 6 / 79)$ in Occupancy Time Limit (0.4×79) (s),
Hops Over Occupancy Time comes to $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67$ hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate $(800 / 6 / 20)$ in Occupancy Time Limit (0.4×20) (s),
Hops Over Occupancy Time comes to $(800 / 6 / 20) \times (0.4 \times 20) = 53.33$ hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 17.JAN.2014 10:00:17

3.4 20dB Bandwidth Measurement

3.4.1 Limit of 20dB Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth


Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.932
39	2441	0.936
78	2480	0.940


20 dB Bandwidth Plot on Channel 00



Date: 17.JAN.2014 10:52:04

20 dB Bandwidth Plot on Channel 39


Date: 17.JAN.2014 10:53:26

20 dB Bandwidth Plot on Channel 78



Date: 17.JAN.2014 10:55:13



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.296
39	2441	1.296
78	2480	1.296


20 dB Bandwidth Plot on Channel 00



Date: 17.JAN.2014 10:56:26




20 dB Bandwidth Plot on Channel 39



Date: 17.JAN.2014 10:57:45


20 dB Bandwidth Plot on Channel 78



Date: 17.JAN.2014 10:59:25

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.308
39	2441	1.308
78	2480	1.308

20 dB Bandwidth Plot on Channel 00


Date: 17.JAN.2014 11:00:26




20 dB Bandwidth Plot on Channel 39



Date: 17.JAN.2014 11:01:36

20 dB Bandwidth Plot on Channel 78



Date: 17.JAN.2014 11:02:43

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, 3Mbps and AFH are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	3.37	20.97	Pass
39	2441	3.89	20.97	Pass
78	2480	3.29	20.97	Pass

Note: For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	3.64	20.97	Pass
39	2441	4.22	20.97	Pass
78	2480	3.46	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~26℃
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	3.63	20.97	Pass
39	2441	4.45	20.97	Pass
78	2480	3.56	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz ($\geq 1\%$ span=10MHz), VBW = 300kHz (\geq RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup






Test Mode :	1Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee



Date: 17.JAN.2014 12:00:58



Date: 17.JAN.2014 12:00:16




Low Band Edge Plot on Channel 00




High Band Edge Plot on Channel 78



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee

Low Band Edge Plot on Channel 00



Date: 17.JAN.2014 11:56:05

High Band Edge Plot on Channel 78



Date: 17.JAN.2014 11:55:33

3.6.7 Test Result of Conducted Hopping Mode Band Edges

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%


1Mbps Hopping Mode Low Band Edge Plot


Date: 17.JAN.2014 11:20:24


1Mbps Hopping Mode High Band Edge Plot


Date: 17.JAN.2014 11:23:44

Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%


2Mbps Hopping Mode Low Band Edge Plot


Date: 17.JAN.2014 11:41:42


2Mbps Hopping Mode High Band Edge Plot


Date: 17.JAN.2014 11:36:19

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Rover Lee	Relative Humidity :	48~51%

3Mbps Hopping Mode Low Band Edge Plot


Date: 17.JAN.2014 11:50:39

3Mbps Hopping Mode High Band Edge Plot


Date: 17.JAN.2014 11:55:03

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 17.JAN.2014 14:08:42


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 17.JAN.2014 14:09:04



Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 17.JAN.2014 14:07:26

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 17.JAN.2014 14:07:48



Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 17.JAN.2014 14:06:06

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 17.JAN.2014 14:06:28



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 17.JAN.2014 14:09:35

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 17.JAN.2014 14:09:57



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 17.JAN.2014 14:10:48

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 17.JAN.2014 14:11:10



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 17.JAN.2014 14:11:41

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 17.JAN.2014 14:12:03



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee


3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz

Date: 17.JAN.2014 14:14:50


3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz

Date: 17.JAN.2014 14:15:11

Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Rover Lee

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 17.JAN.2014 14:13:39

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 17.JAN.2014 14:14:01

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.8.3 Test Procedures


1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
$$\text{On time} = N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$$

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.8.6 Duty cycle correction factor for average measurement

3DH5 on time (One Pulse) Plot on Channel 39



3DH5 on time (Count Pulses) Plot on Channel 39


Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.89 / 100 = 5.78 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.89 \text{ ms} \times 20 \text{ channels} = 57.8 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.89 \text{ ms} \times 2 = 5.78 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.78 \text{ ms}/100\text{ms}) = -24.76 \text{ dB}$$

3.8.7 Test Result of Radiated Spurious at Band Edges

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	00	Relative Humidity :	47~49%
		Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.93	46.38	-27.62	74	41.44	32.3	6.91	34.27	100	39	Peak
2388.93	21.62	-32.38	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2311.26	46.13	-27.87	74	41.31	32.21	6.8	34.19	134	314	Peak
2311.26	21.37	-32.63	54	-	-	-	-	-	-	Average

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	78	Relative Humidity :	47~49%
		Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.59	50.77	-23.23	74	45.76	32.38	7.06	34.43	121	37	Peak
2483.59	26.01	-27.99	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	46.79	-27.21	74	41.78	32.38	7.06	34.43	184	109	Peak
2483.5	22.03	-31.97	54	-	-	-	-	-	-	Average

Note: Average Emission Level = Peak Emission Level + duty cycle correction factor(-24.76dB)

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	00	Relative Humidity :	47~49%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	2402 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.54	22.69	-17.31	40	35.33	18.28	0.54	31.46	111	39	Peak
85.62	19.13	-20.87	40	41.22	8.1	0.91	31.1	-	-	Peak
137.46	24.85	-18.65	43.5	43.26	11.5	1.19	31.1	-	-	Peak
400.1	16.1	-29.9	46	28.93	15.93	2.14	30.9	-	-	Peak
569.5	22.35	-23.65	46	30.74	19.73	2.6	30.72	-	-	Peak
811	24.44	-21.56	46	29.36	22.23	3.17	30.32	-	-	Peak
2402	101.86	-	-	96.95	32.3	6.91	34.3	100	39	Peak
2402	77.1	-	-	-	-	-	-	-	-	Average
4803	40.25	-33.75	74	56.48	33.98	8.75	58.96	100	0	Peak
4803	15.49	-38.51	54	-	-	-	-	-	-	Average

Note: 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor(-24.76)

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	00	Relative Humidity :	47~49%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	2402 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
85.62	21.35	-18.65	40	43.44	8.1	0.91	31.1	138	61	Peak
137.46	19.83	-23.67	43.5	38.24	11.5	1.19	31.1	-	-	Peak
206.85	21.61	-21.89	43.5	42.2	9.16	1.35	31.1	-	-	Peak
420.4	17.29	-28.71	46	29.18	16.7	2.21	30.8	-	-	Peak
575.8	24.68	-21.32	46	33.12	19.64	2.62	30.7	-	-	Peak
837.6	25.13	-20.87	46	29.14	23.12	3.24	30.37	-	-	Peak
2402	91.25	-	-	86.34	32.3	6.91	34.3	134	314	Peak
2402	66.49	-	-	-	-	-	-	-	-	Average
4803	39.46	-34.54	74	55.69	33.98	8.75	58.96	100	0	Peak
4803	14.7	-39.3	54	-	-	-	-	-	-	Average

Note: 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor(-24.76)

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	39	Relative Humidity :	47~49%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	2442 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
85.62	19.59	-20.41	40	41.68	8.1	0.91	31.1	-	-	Peak
137.73	25.07	-18.43	43.5	43.48	11.5	1.19	31.1	132	40	Peak
156.36	22.04	-21.46	43.5	41.33	10.66	1.22	31.17	-	-	Peak
407.8	18.1	-27.9	46	30.67	16.12	2.17	30.86	-	-	Peak
635.3	22.23	-23.77	46	29.56	20.4	2.8	30.53	-	-	Peak
724.2	24.72	-21.28	46	30.45	21.67	3	30.4	-	-	Peak
2442	101.32	-	-	96.37	32.35	6.99	34.39	100	151	Peak
2442	76.56	-	-	-	-	-	-	-	-	Average
4881	39.75	-34.25	74	55.78	33.95	8.85	58.83	100	0	Peak
4881	14.99	-39.01	54	-	-	-	-	-	-	Average
7323	42.23	-31.77	74	53.53	35.53	10.91	57.74	100	0	Peak
7323	17.47	-36.53	54	-	-	-	-	-	-	Average

Note: 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor(-24.76)

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	39	Relative Humidity :	47~49%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	2442 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
84.81	22.03	-17.97	40	44.14	8.1	0.91	31.12	247	62	Peak
128.82	19.24	-24.26	43.5	37.28	11.92	1.14	31.1	-	-	Peak
207.93	22.67	-20.83	43.5	43.25	9.17	1.35	31.1	-	-	Peak
585.6	23.9	-22.1	46	32.37	19.54	2.65	30.66	-	-	Peak
725.6	24.43	-21.57	46	30.1	21.73	3	30.4	-	-	Peak
917.4	26.26	-19.74	46	29.35	23.86	3.38	30.33	-	-	Peak
2442	99.05	-	-	94.1	32.35	6.99	34.39	106	121	Peak
2442	74.29	-	-	-	-	-	-	-	-	Average
4881	39.41	-34.59	74	55.44	33.95	8.85	58.83	100	0	Peak
4881	14.65	-39.35	54	-	-	-	-	-	-	Average
7323	42.13	-31.87	74	53.43	35.53	10.91	57.74	100	0	Peak
7323	17.37	-36.63	54	-	-	-	-	-	-	Average

Note: 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor(-24.76)

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	78	Relative Humidity :	47~49%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	2480 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
85.62	15.02	-24.98	40	37.11	8.1	0.91	31.1	-	-	Peak
137.46	22.18	-21.32	43.5	40.59	11.5	1.19	31.1	144	28	Peak
156.36	20.13	-23.37	43.5	39.42	10.66	1.22	31.17	-	-	Peak
393.8	16.21	-29.79	46	29.35	15.66	2.13	30.93	-	-	Peak
580	20.82	-25.18	46	29.27	19.6	2.63	30.68	-	-	Peak
738.9	24.16	-21.84	46	29.35	22.18	3.03	30.4	-	-	Peak
2480	101.74	-	-	96.73	32.38	7.06	34.43	121	37	Peak
2480	76.98	-	-	-	-	-	-	-	-	Average
4959	39.82	-34.18	74	55.65	33.91	8.92	58.66	100	0	Peak
4959	15.06	-38.94	54	-	-	-	-	-	-	Average
7440	39.01	-34.99	74	50.31	35.51	11.04	57.85	100	0	Peak
7440	14.25	-39.75	54	-	-	-	-	-	-	Average

Note: 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor(-24.76)

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	78	Relative Humidity :	47~49%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	2480 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
84.81	22.33	-17.67	40	44.44	8.1	0.91	31.12	137	93	Peak
129.09	18.97	-24.53	43.5	37.01	11.92	1.14	31.1	-	-	Peak
214.68	21.96	-21.54	43.5	42.39	9.24	1.38	31.05	-	-	Peak
423.2	17.89	-28.11	46	29.7	16.76	2.22	30.79	-	-	Peak
585.6	24.82	-21.18	46	33.29	19.54	2.65	30.66	-	-	Peak
839	25.2	-20.8	46	29.18	23.16	3.24	30.38	-	-	Peak
2480	96.66	-	-	91.65	32.38	7.06	34.43	184	109	Peak
2480	71.9	-	-	-	-	-	-	-	-	Average
4959	39.42	-34.58	74	55.25	33.91	8.92	58.66	100	0	Peak
4959	14.66	-39.34	54	-	-	-	-	-	-	Average
7440	38.92	-35.08	74	50.22	35.51	11.04	57.85	100	0	Peak
7440	14.16	-39.84	54	-	-	-	-	-	-	Average

Note: 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor(-24.76)

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Cosmo Xu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + Scanner + NFC active + USB Cable (Charging from Adapter) + Battery 2 for Sample 1		




Final Result: Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.190000	41.4	Off	L1	19.4	22.6	64.0
0.246000	39.3	Off	L1	19.4	22.6	61.9
0.334000	39.5	Off	L1	19.4	19.9	59.4
1.110000	36.6	Off	L1	19.4	19.4	56.0
1.582000	34.4	Off	L1	19.4	21.6	56.0
3.046000	33.3	Off	L1	19.6	22.7	56.0
3.734000	32.3	Off	L1	19.6	23.7	56.0
13.558000	53.0	Off	L1	19.8	7.0	60.0
24.022000	30.9	Off	L1	19.9	29.1	60.0

Final Result: Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.190000	27.0	Off	L1	19.4	27.0	54.0
0.246000	24.4	Off	L1	19.4	27.5	51.9
0.334000	33.4	Off	L1	19.4	16.0	49.4
1.110000	27.0	Off	L1	19.4	19.0	46.0
1.582000	27.4	Off	L1	19.4	18.6	46.0
3.046000	25.0	Off	L1	19.6	21.0	46.0
3.734000	26.0	Off	L1	19.6	20.0	46.0
13.558000	43.0	Off	L1	19.8	7.0	50.0
24.022000	18.5	Off	L1	19.9	31.5	50.0

Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Cosmo Xu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + Scanner + NFC active + USB Cable (Charging from Adapter) + Battery 2 for Sample 1		


Final Result: Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	41.4	Off	N	19.4	23.8	65.2
0.334000	40.0	Off	N	19.4	19.4	59.4
0.870000	37.9	Off	N	19.5	18.1	56.0
1.038000	39.0	Off	N	19.5	17.0	56.0
1.158000	38.5	Off	N	19.5	17.5	56.0
1.230000	39.1	Off	N	19.5	16.9	56.0
13.558000	51.0	Off	N	19.9	9.0	60.0

Final Result: Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	27.2	Off	N	19.4	28.0	55.2
0.334000	34.0	Off	N	19.4	15.4	49.4
0.870000	30.5	Off	N	19.5	15.5	46.0
1.038000	31.9	Off	N	19.5	14.1	46.0
1.158000	31.6	Off	N	19.5	14.4	46.0
1.230000	31.5	Off	N	19.5	14.5	46.0
13.558000	41.0	Off	N	19.9	9.0	50.0



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 07, 2013	Jan. 17, 2014	Jun. 06, 2014	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Feb. 05, 2013	Jan. 17, 2014	Feb. 04, 2014	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Feb. 05, 2013	Jan. 17, 2014	Feb. 04, 2014	Conducted (TH02-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9 kHz~7 GHz	Sep. 06, 2013	Jan. 25, 2014	Sep. 05, 2014	Radiation (03CH07-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9 kHz~30 GHz	Nov. 20, 2013	Jan. 25, 2014	Nov. 19, 2014	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	860004/0001	9 kHz~30 MHz	Jul. 03, 2012	Jan. 25, 2014	Jul. 03, 2014	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30 MHz~1 GHz	Oct. 10, 2013	Jan. 25, 2014	Oct. 09, 2014	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1 GHz~18 GHz	Aug. 22, 2013	Jan. 25, 2014	Aug. 21, 2014	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15 GHz~40 GHz	Oct. 03, 2013	Jan. 25, 2014	Oct. 02, 2014	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	30 MHz~1 GHz	Feb. 26, 2013	Jan. 25, 2014	Feb. 25, 2014	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1 GHz~26.5 GHz	Nov. 29, 2013	Jan. 25, 2014	Nov. 28, 2014	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	159088	DC~18 G High Gain	Feb. 27, 2013	Jan. 25, 2014	Feb. 26, 2014	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Jan. 25, 2014	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	ChainTek 3000	N/A	N/A	N/A	Jan. 25, 2014	N/A	Radiation (03CH07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz~2.75GHz	Nov. 15, 2013	Jan. 16, 2014	Nov. 14, 2014	Conduction (CO05-HY)
Two-LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 12, 2013	Jan. 16, 2014	Dec. 11, 2014	Conduction (CO05-HY)
Two-LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 04, 2013	Jan. 16, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 16, 2014	N/A	Conduction (CO05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.50
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.10
---	------