FCC LABEL LOCATION

The label will be permanently affixed at a conspicuous location on the device.

Back Side:

Label Here

Safety Label Note:

1. Printing color: Black

2. 製造國家(MFG Country):

Decide by import and export country for example: 1. MADE IN TAIWAN

- 2. MADE IN CHINA

印刷廠商代號(Vender ID): (CSA 要求標示)


Decide by Vendor


製造工廠代號 (MFG Factory): (UL 要求標示)

視代工廠而定 (Decide by MFG Factory)

- 1.昊陽 / JoyTech (深圳/ ShenZhen) ----->None
- 2.Accton---->AC







Modification	Caro Paper / Top lineboard			Corrugate list	Cardboard Die Cut Legend	Unspecialized =+/-0.5mm	PE Bag	(A Degree)	Clear	Pink	Label list	(Total Thick	kness = mm±	<u>+</u> 10%)	Compl	y with	RoHs	٨٥	otoo		
1	Paper CCNE	SBS Double	Flu (A De	ute Single wall Double wall GSM g/mijReferance) Suresting Eregree) (Top lineboard/Medium/Bottom lineboard) Bursting Eregree Bursting Eregree	(CL) Cutting Line	- 0 16 0.05 0.1 0.15 0.2 0.2 0.5	Normal	Anti-Sta	tic ESD Value/of	Ω hm = 9-11	Material 8	Thickness	Adhesiv (Except all leds in FP	/e P label)		Others	;	AC	cton	TECHNOLO	OGY CORP.
2	250			A/C Taiwan 230 X 180 X 230 16 3	3.6 (C1) Crease Line _	16 — 63 0.05 0.15 0.2 0.3 0.3 0.8 ine 63 — 250 0.05 0.2 0.25 0.4 0.5 1.2	Anti-Static	Electron	nic ESD Value/of	Ω hm < 5	Art paper	0.025mm / 25# / 1mil	Acrylic	T=0.022mm	Material Spe	ec:		Dort No	0.400000000	0544	REV. 01
4	280			B China 250 X 100 X 250 14 2 Taiwan 230 X 100 X 230 14 2	6.2 (SO) Slit-Score Line	250 — 500 0.1 0.25 0.3 0.6 0.8 1.8 500 — 1000 0.3 0.5 0.8 1.2 30	Thickness/mm	0.04	0.06	0.08	✓ 3M7872 V	0.050mm / 50# / 2mil	✓ Acrylic UL approved	d T=0.046mm	IOC	Inspect C		Part No.	2460000009	954A	REV. 01
5	310		! '	AB Taiwan 230X100X100X230 AB Taiwan 230X100X100X100X230 BC China 250X100X100X100X230 18 3	7.1 (SL) Slit Line	Printing Tolerance = +/ -	Bubble Bag	layer	(By 1.5M / Width x 1	100M / Length)	Metalized White Polyester	0.076mm / 75# / 3mil	"R" Adhesive Water Adhesive	T=0.022mm	Please refer to		0.0/	Descripti	on:		
6	340 350			A/C Taiwan 230 X 100 X 238 16 China 205 X 140 X 230	26 Flute	Pulp Tray Recycle Kraft 80% + Newspaper 20%	(Ø=10mm)	layer	(By 1.5M/Width x 1	al >= 16 kg 100M/Length)	(PP)Pepa paper	0.254mm / 10mil	+	T=0.05mm / 2mil	Approve		MAY07.14	UL LAE	BEL WAP102	22A-FLF-	D8 US
This document and the technical data disclosed	Coated IIV	Mar Resistan	d	B Taiwan 220 X 100 X 200 14 2	8.5 Manufactory (MFG STAMP)	Weight/gs +/-5%	EPE F		White	Pink	PC 8B35	0.381mm / 15mil	3M 468 T	Γ=0.127mm / 5mil	Check	LIII	IVIATOT.14	UNIT	SCALE	1 / 1	SIZE A3
are proprietary to Accton Tech. Corp. and shall not be duplicated, used, released, or disclosed without expressed written permission.	PP Film LF	Varnish T=	-	E China 175 X 100 X 250 12 1 1 1 1 1 1 1 1	8.6 Stand	Thickness/mm 15 2.0 Draft Angle 3° Hydrous % 719	Density (k Lamina	· /	>=27 Non - lamir	Other nated	PC 8010	0.500mm / 20mil	3M 7945 T	Γ=0.127mm / 5mil	Design	Carry	MAY07.14	MM (1	N) Outside	View :	Sheet 1 of 1