

# FCC RF Test Report

**APPLICANT** : Zebra Technologies Corporation  
**EQUIPMENT** : Enterprise Tablet  
**BRAND NAME** : Zebra  
**MODEL NAME** : ET55BT  
**FCC ID** : UZ7ET55BT  
**STANDARD** : FCC Part 15 Subpart C §15.225  
**CLASSIFICATION** : (DXX) Low Power Communication Device Transmitter


The testing was completed on Jun. 30, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



---

Reviewed by: Joseph Lin / Supervisor



---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.**



## Table of Contents

<b>SUMMARY OF THE TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL INFORMATION.....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer.....	5
1.3 Product Details.....	5
1.4 Modification of EUT.....	5
1.5 Testing Location .....	6
1.6 Applicable Standards .....	6
1.7 Test Modes.....	6
1.8 Test Configurations.....	7
1.9 Table for Supporting Units .....	8
<b>2. CONDUCTED EMISSION TEST.....</b>	<b>9</b>
2.1 Measuring Instruments .....	9
2.2 Test setup .....	9
2.3 Test Result of Conducted Emission Test.....	9
2.4 AC Power Line Conducted Emissions Measurement .....	10
<b>3. CONDUCTED TEST ITEMS .....</b>	<b>11</b>
3.1 Measuring Instruments .....	11
3.2 Test Setup .....	11
3.3 Test Result of Conducted Test Items.....	11
3.4 20dB and 99% OBW Spectrum Bandwidth Measurement.....	12
3.5 Frequency Stability Measurement .....	12
<b>4. RADIATED TEST ITEMS.....</b>	<b>13</b>
4.1 Measuring Instruments .....	13
4.2 Test Setup .....	13
4.3 Test Result of Radiated Test Items .....	13
4.4 Field Strength of Fundamental Emissions and Mask Measurement .....	14
4.5 Radiated Emissions Measurement .....	15
<b>5. LIST OF MEASURING EQUIPMENT .....</b>	<b>17</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS OF EUT</b>	
<b>APPENDIX B. TEST RESULTS OF CONDUCTED EMISSION TEST</b>	
<b>APPENDIX C. TEST RESULTS OF CONDUCTED TEST ITEMS</b>	
C.1. Test Result of 20dB Spectrum Bandwidth	
C.2 Test Result of Frequency Stability	
<b>APPENDIX D. TEST RESULTS OF RADIATED TEST ITEMS</b>	
D.1 Test Result of Field Strength of Fundamental Emissions	
D.2 Results of Radiated Emissions (9 kHz~30MHz)	
D.3 Results of Radiated Emissions (30MHz~1GHz)	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR660115D	Rev. 01	Initial issue of report	Aug. 04, 2016



## SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	FCC Rule	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	14.60 dB at 0.198MHz
3.2	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	64.93 dB at 13.560 MHz
3.3	2.1049	20dB Spectrum Bandwidth	Complies	-
3.3	-	99% OBW Spectrum Bandwidth	Complies	-
3.4	15.225(d) 15.209	Radiated Emissions	Complies	9.64 dB at 102.090 MHz
3.5	15.225(e)	Frequency Stability	Complies	-
3.6	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.26dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±4.80dB	Confidence levels of 95%



## 1. GENERAL INFORMATION

### 1.1 Applicant

**Zebra Technologies Corporation**

1 Zebra Plaza, Holtsville, NY 11742

### 1.2 Manufacturer

**Zebra Technologies Corporation**

1 Zebra Plaza, Holtsville, NY 11742

### 1.3 Product Details

Items	Description
<b>Tx/Rx Frequency Range</b>	13.553 ~ 13.567MHz
<b>Channel Number</b>	1
<b>20dBW</b>	2.66 KHz
<b>99%OBW</b>	2.26 KHz
<b>HW Version</b>	DV1
<b>SW Version</b>	5.1.1
<b>FW Version</b>	8.1.24
<b>MFD</b>	31-Mar-16
<b>Antenna Type</b>	Loop Antenna
<b>Type of Modulation</b>	ASK

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.		
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		
	TH03-HY	CO05-HY	03CH07-HY
<b>Test Engineer</b>	Tommy Lee	Arthur Hsieh	Derreck Chen
<b>Temperature</b>	22~24°C	25~26°C	21~23°C
<b>Relative Humidity</b>	53~55%	54~55%	55~58%

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2013


## 1.7 Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.


Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz
<b>Note:</b> <ol style="list-style-type: none"> <li>1. The EUT was programmed to be in continuously transmitting mode.</li> <li>2. The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.</li> </ol>	

## 1.8 Test Configurations

### <AC Conducted Emissions>



### <For Fundamental Emissions and Mask and Radiated Emissions Measurement>



**1.9 Table for Supporting Units**

Support Unit	Manufacturer	Model	FCC ID
iPod Earphone	Apple	N/A	Verification
USB HD	WD	WDBAAR3200ABK-PESN	FCC DoC
SD Card	SanDisk	MicroSD HC	FCC DoC
NFC Card	Metro Taipei	Easy Card	N/A
Adapter	Delta	APP-10BWC	FCC DoC




## 2. CONDUCTED EMISSION TEST

### 2.1 Measuring Instruments

See list of measuring instruments of this test report.

### 2.2 Test setup



### 2.3 Test Result of Conducted Emission Test

Please refer to Appendix B.

## 2.4 AC Power Line Conducted Emissions Measurement

### 2.4.1 Limit

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 2.4.2 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3. CONDUCTED TEST ITEMS

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup

##### 3.2.1 20dB and 99% OBW Spectrum Bandwidth



##### 3.2.2 Frequency Stability



#### 3.3 Test Result of Conducted Test Items

Please refer to Appendix C.



### **3.4 20dB and 99% OBW Spectrum Bandwidth Measurement**

#### **3.4.1 Limit**

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

#### **3.4.2 Test Procedures**

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

### **3.5 Frequency Stability Measurement**

#### **3.5.1 Limit**

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

#### **3.5.2 Test Procedures**

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The  $f_c$  is declaring of channel frequency. Then the frequency error formula is  $(f_c - f)/f_c \times 10^6$  ppm and the limit is less than  $\pm 100$ ppm.
6. Extreme temperature rule is -20°C~50°C.


## 4. RADIATED TEST ITEMS

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

#### 4.2.1 For radiated emissions below 30MHz



#### 4.2.2 For radiated emissions above 30MHz



### 4.3 Test Result of Radiated Test Items

Please refer to Appendix D.

## 4.4 Field Strength of Fundamental Emissions and Mask Measurement

### 4.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
	IC RSS-210 A2.6			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength ( $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 10m	Field Strength (dB $\mu$ V/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

### 4.4.2 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
  2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
  3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
  4. For Fundamental emissions, use the receiver to measure QP reading.
  5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
  6. Compliance with the spectrum mask is tested with RBW set to 9kHz.
- Note: Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).

## 4.5 Radiated Emissions Measurement

### 4.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

**Note:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

#### **4.5.3 Test Procedures**

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

#### **4.5.4 Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

#### **4.5.5 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.






## 5. LIST OF MEASURING EQUIPMENT

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F104070011	50Hz~60Hz	Dec. 02, 2015	Jun. 30, 2016	Dec. 01, 2016	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 27, 2016	Jun. 30, 2016	Jun. 26, 2017	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30°C ~70°C	Nov. 20, 2015	Jun. 30, 2016	Nov. 19, 2016	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 13, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	Jun. 13, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Jun. 13, 2016	Dec. 01, 2016	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D	35419	30MHz to 1GHz	Jan. 13, 2016	Jun. 15, 2016	Jan. 12, 2017	Radiation (03CH07-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20Hz ~ 8.4GHz	Nov. 04, 2015	Jun. 15, 2016	Nov. 03, 2016	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Jun. 15, 2016	Sep. 01, 2016	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Feb. 27, 2016	Jun. 15, 2016	Feb. 26, 2017	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Jun. 15, 2016	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF780208368	Control Ant Mast	N/A	Jun. 15, 2016	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Jun. 15, 2016	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Jun. 15, 2016	N/A	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Mar. 18, 2016	Jun. 15, 2016	Mar. 17, 2017	Radiation (03CH07-HY)

## Appendix B. Test Results of Conducted Emission Test

< Original Test Result >


Test Mode :	NFC Tx	Test Voltage :	120Vac / 60Hz
Function Type :	USB Cable (Charging from Adapter) + NFC Tx + Battery + Earphone + USB HD		



**Final Result : Quasi-Peak**


Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	49.1	Off	L1	19.6	14.6	63.7
0.310000	36.3	Off	L1	19.6	23.7	60.0
0.390000	35.4	Off	L1	19.6	22.7	58.1
0.510000	32.0	Off	L1	19.6	24.0	56.0
0.598000	31.8	Off	L1	19.6	24.2	56.0
0.838000	31.9	Off	L1	19.6	24.1	56.0
1.054000	31.8	Off	L1	19.7	24.2	56.0
2.486000	28.2	Off	L1	19.7	27.8	56.0
4.374000	25.3	Off	L1	19.8	30.7	56.0
7.190000	32.9	Off	L1	19.9	27.1	60.0
13.558000	53.2	Off	L1	20.3	6.8	60.0
27.118000	22.6	Off	L1	21.0	37.4	60.0

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	USB Cable (Charging from Adapter) + NFC Tx + Battery + Earphone + USB HD		


**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	36.7	Off	L1	19.6	17.0	53.7
0.310000	23.2	Off	L1	19.6	26.8	50.0
0.390000	23.8	Off	L1	19.6	24.3	48.1
0.510000	21.8	Off	L1	19.6	24.2	46.0
0.598000	19.9	Off	L1	19.6	26.1	46.0
0.838000	19.5	Off	L1	19.6	26.5	46.0
1.054000	20.2	Off	L1	19.7	25.8	46.0
2.486000	20.1	Off	L1	19.7	25.9	46.0
4.374000	16.7	Off	L1	19.8	29.3	46.0
7.190000	19.6	Off	L1	19.9	30.4	50.0
13.558000	51.5	Off	L1	20.3	-1.5	50.0
27.118000	18.1	Off	L1	21.0	31.9	50.0

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	USB Cable (Charging from Adapter) + NFC Tx + Battery + Earphone + USB HD		


**Final Result : Quasi-Peak**


Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.198000	48.9	Off	N	19.6	14.8	63.7
0.302000	36.0	Off	N	19.6	24.2	60.2
0.390000	36.3	Off	N	19.6	21.8	58.1
0.606000	31.8	Off	N	19.6	24.2	56.0
0.790000	28.5	Off	N	19.6	27.5	56.0
0.950000	28.3	Off	N	19.6	27.7	56.0
2.334000	26.3	Off	N	19.6	29.7	56.0
7.614000	29.2	Off	N	20.0	30.8	60.0
13.558000	53.7	Off	N	20.3	6.3	60.0
27.118000	23.6	Off	N	21.2	36.4	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.198000	36.2	Off	N	19.6	17.5	53.7
0.302000	23.6	Off	N	19.6	26.6	50.2
0.390000	24.0	Off	N	19.6	24.1	48.1
0.606000	19.4	Off	N	19.6	26.6	46.0
0.790000	18.8	Off	N	19.6	27.2	46.0
0.950000	19.3	Off	N	19.6	26.7	46.0
2.334000	22.0	Off	N	19.6	24.0	46.0
7.614000	17.8	Off	N	20.0	32.2	50.0
13.558000	51.6	Off	N	20.3	-1.6	50.0
27.118000	18.9	Off	N	21.2	31.1	50.0

**< Terminal Test Result >**

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	USB Cable (Charging from Adapter) + NFC Tx + Battery + Earphone + USB HD		



**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	29.4	Off	L1	20.3	30.6	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	24.4	Off	L1	20.3	25.6	50.0

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	USB Cable (Charging from Adapter) + NFC Tx + Battery + Earphone + USB HD		


**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	29.1	Off	N	20.3	30.9	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	23.9	Off	N	20.3	26.1	50.0

(1) with antenna

Remark: 13.558MHz is the NFC RF fundamental signal.



(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.



## Appendix C. Test Results of Conducted Test Items

### C.1 Test Result of 20dB Spectrum Bandwidth

Test mode		NFC Tx		Test Frequency (MHz)	13.56
				<p>Date: 30.JUN.2016 17:24:59</p>	
20dB Bandwidth (kHz)	2.660	99% OccupiedBW(kHz)	2.260		
Frequency range (MHz)	$f_L > 13.553$	13.55896	Test Result		
	$f_H < 13.567$	13.56162	Complies		

**C.2 Test Result of Frequency Stability**

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
120	13.560300	-20	0	13.560360
102	13.560290		2	13.560360
138	13.560290		5	13.560360
			10	13.560360
		-10	0	13.560380
			2	13.560380
			5	13.560380
			10	13.560380
		0	0	13.560370
			2	13.558860
			5	13.560380
			10	13.560370
		10	0	13.560320
			2	13.560320
			5	13.560320
			10	13.560320
		20	0	13.560280
			2	13.560280
			5	13.560270
			10	13.560280
		30	0	13.560260
			2	13.560260
			5	13.560260
			10	13.560260
		40	0	13.560240
			2	13.560240
			5	13.560240
			10	13.560240






Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
		50	0	13.560240
			2	13.560240
			5	13.560240
			10	13.560240
Max.Deviation (MHz)	0.000300	Max.Deviation (MHz)		-0.001140
Max.Deviation (ppm)	22.1239	Max.Deviation (ppm)		-84.0708
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS



## Appendix D. Test Results of Radiated Test Items

### D.1 Test Result of Field Strength of Fundamental Emissions



**Note:** All NFC's spurious emissions are below 20dB of limits.

**D.2 Results of Radiated Emissions (9 kHz~30MHz)**

Test Mode :		NFC Tx			Polarization :		Horizontal		
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.01298	63.51	-61.83	125.34	42.25	20.24	1.02			Average
0.06462	63.49	-47.91	111.4	42.46	20.01	1.02			Average
0.10314	62.06	-45.28	107.34	41.08	19.96	1.02			QP
0.12924	55.9	-49.48	105.38	34.94	19.94	1.02			Average
0.19386	67.87	-33.98	101.85	46.94	19.91	1.02			Average
0.49751	58.6	-15.07	73.67	37.7	19.88	1.02	100	0	QP
13.352	38.35	-31.15	69.5	17.26	20.07	1.02			QP
13.56	56.66	-12.84	69.5	35.57	20.07	1.02			QP
19.627	38.04	-31.46	69.5	16.63	20.39	1.02			QP
25.555	38.2	-31.3	69.5	15.76	20.67	1.77			QP

Test Mode :		NFC Tx			Polarization :		Vertical		
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.01334	64.11	-60.99	125.1	42.85	20.24	1.02			Average
0.06462	61.23	-50.17	111.4	40.2	20.01	1.02			Average
0.0981	58.3	-49.47	107.77	37.32	19.96	1.02			QP
0.12924	53.78	-51.6	105.38	32.82	19.94	1.02			Average
0.19556	64.86	-36.92	101.78	43.93	19.91	1.02			Average
0.58012	55.12	-17.21	72.33	34.22	19.88	1.02	100	0	QP
8.064	37.45	-32.05	69.5	16.47	19.96	1.02			QP
13.56	54.63	-14.87	69.5	33.54	20.07	1.02			QP
21.301	38.26	-31.24	69.5	15.94	20.55	1.77			QP
27.495	37.98	-31.52	69.5	15.53	20.68	1.77			QP

**Note:**

1. 13.56 MHz is fundamental signal which can be ignored.
2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
4. Limit line = specific limits (dBμV) + distance extrapolation factor.

**D.3 Results of Radiated Emissions (30MHz~1GHz)**

<b>Test Mode :</b>		NFC Tx			<b>Polarization :</b>		Horizontal			
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
30.27	28.65	-11.35	40	32.93	26	1.07	31.35			Peak
102.09	33.86	-9.64	43.5	47.25	16.58	1.55	31.52	100	0	Peak
240.06	34.03	-11.97	46	45.27	18.09	2.07	31.4			Peak
424.6	27.25	-18.75	46	32.74	22.75	2.89	31.13			Peak
714.4	29.85	-16.15	46	30.17	26.64	3.74	30.7			Peak
942.6	33.81	-12.19	46	30.23	30.04	4.07	30.53			Peak

<b>Test Mode :</b>		NFC Tx			<b>Polarization :</b>		Vertical			
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
34.86	28.89	-11.11	40	35.93	23.3	1.07	31.41	100	0	Peak
63.21	26.97	-13.03	40	45.06	12.21	1.28	31.58			Peak
241.41	26.45	-19.55	46	37.59	18.18	2.07	31.39			Peak
424.6	26.01	-19.99	46	31.5	22.75	2.89	31.13			Peak
667.5	29.69	-16.31	46	30.72	26.07	3.65	30.75			Peak
949.6	34.48	-11.52	46	30.74	30.2	4.07	30.53			Peak

**Note:**

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.