

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com



# **TEST REPORT For FCC**

Test Report No.	:	2007050079

Date of Issue : May 30, 2007

FCC ID : UZCGFT-4000

Model/Type No. : GFT-4000

Kind of Product : FM Transmitter

Applicant : GT Telecom Co., Ltd.

Applicant Address : 848-16, Gupyeong-Dong, Gumi-City, Gyeongbuk, Korea

Manufacturer : GT Telecom Co., Ltd.

Manufacturer Address : 848-16, Gupyeong-Dong, Gumi-City, Gyeongbuk, Korea

Contact Person : LEE HYO JIN / Junior Engineer

Telephone : +82-54-474-2246

Received Date : May 16, 2007

Test Date : May 30, 2007

Test Results :  $\square$  In Compliance  $\square$  Not in Compliance

The test results presented in this report relate only to the object tested.

CTK Co., Ltd. is accredited by Korea Laboratory Accreditation Scheme (KOLAS) which signed the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Arrangement (MRA) for the above test item(s) and test method(s).

Tested by Reviewed by

Young-Joon, Park EMC Test Engineer Date: May 30, 2007 James Hong EMC Technical Manager Date: May 30, 2007

Test Report No.: 2007050079 Page 1 of 25 Date: May 30, 2007

This Report shall not be reproduced except in full without the written approval of CTK

Form No.: CTK-RF-EF-Part15(Rev.2.1)



386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com



## REPORT REVISION HISTORY

Date	Revision	Page No
May 30, 2007	Issued (2007050079)	All

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

Test Report No.: 2007050079
Date: May 30, 2007

This Report shall not be reproduced except in full without the written approval of CTK





# **TABLE OF CONTENTS**

REPORT	REVISION HISTORY	. 2
1.0	General Product Description	. 4
1.1	Model Differences	. 4
1.2	Device Modifications	. 4
1.3	EUT Configuration(s)	. 5
1.4	EUT Exercise	. 5
1.5	Test Software	. 5
1.6	EUT Operating Mode(s)	. 6
1.7	Configuration	
1.8	Calibration Details of Equipment Used for Measurement	. 8
1.9	Test Facility	
1.10	Measurement Procedure	. 8
1.11	Laboratory Accreditations and Listings	. 9
2.0	Emissions Test Regulations	
2.1	Radiated Electric Field Emissions - #1	11
2.2	Radiated Electric Field Emissions - #2	12
2.3	200kHz Bandwidth	13
2.4	Conducted Voltage Emissions – 15.207	15
	IX A – TEST DATA	
Radi	iated Electric Field Emissions - #1	16
APPEND	IX B - Test Setup Photos and Configuration	17
Radi	iated Electric Field Emissions	17
APPEND	IX C – EUT Photographs	18
EUT	External Photographs	19
EUT	Internal Photographs	21
PCB		22
Photogra	aphs related to Label	24
FCC ID I	abel location	25



386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com



# 1.0 General Product Description

Product : FM Transmitter

Equipment model name : GFT-4000

Serial number : Prototype

Antenna designation : Fixed Antenna, which is built in EUT

Antenna type : Wire antenna (UL1571 #30, 130mm)

Frequency Range : 88.1MHz - 107.9MHz

Number of channels : 199

Type of Modulation : F3E

Operating Voltage : DC 12V - 24V

Modulation Technique : FM

#### Note:

- 1. The product is a Transmitter. This submittal(s) (test report) is intended for FCC ID: UZCGFT-4000 filing to comply with Section 15.239 of the FCC Part 15 Subpart C Rules.
- 2. The composite system (digital device) is compliance with subpart B is authorized under a DOC procedure.
- 3. The lowest channel is 88.1MHz, and the highest channel is 107.9MHz. The tuning controls were manually adjusted to verify maximum tuning range.

#### 1.1 Model Differences

Not applicable

#### 1.2 Device Modifications

Not applicable

Test Report No.: 2007050079 Page 4 of 25



386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com



# 1.3 EUT Configuration(s)

The following peripheral devices and/or interface cables were connected during the measurement:

## Peripheral Devices

Device	Manufacturer	Model No.	Serial No.	FCC ID or DoC
MP3 Player	iRiver China Ltd.	N11MT 256MB	291370051101926	DoC
Bluetooth Headset	GT Telecom Co., Ltd.	GBH-100	-	UZCGBH-M100
Ciga Socket	-	-	-	-
Dual-Tracking DC	Topward Electric	6303D	711196	
Power Supply	Instruments Co.,Ltd.	0303D	/11196	-

## 

#	Description	Ferrite Core	Length (m)	Other Details
0	Audio In cable, Unshielded	-	0.4 m	Between the EUT and MP3 Player
1	Bluetooth Headset	-	-	Direct connect to the EUT
2	Ciga Socket	-	-	Direct connect to the EUT
3	Ciga Socket cable, Unshielded	-	1.0 m	Between the EUT and DC Power Supply
4	AC power cable, Unshielded	-	2.0 m	Connect to AC power

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

## 1.4 EUT Exercise

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

# 1.5 Test Software ☐ EMC Test V 1.0 ☐ Display Test Patterns – V1.5 ☐ Ping.exe ☐ Not applicable

Test Report No.: 2007050079 Page 5 of 25 Date: May 30, 2007



386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com

Equipment under test was operated during the measurement under the following



# 1.6 EUT Operating Mode(s)

the volume to Max.

artificial during test.)

conditions:	
<ul><li>☐ Standby</li><li>☐ Display circles pattern</li><li>☒ Practice operation</li></ul>	Scrolling 'H' Read / Write
<ol> <li>Bluetooth handsfree Mode</li> <li>Audio Mode</li> </ol>	anned during the preliminary test Mode(s): wing test mode was found to produce the
Mode 2) Audio Mode	
S S	configuration of the above highest emission ems. The MP3 Player played a music MP3 and set

There are 199 channels on EUT. All 199 channels are pre-tested and choose three channels, low (88.1MHz), middle (98.0MHz), high (107.9MHz), for final test.

(Note: The tuning range was checked by physically adjusting the tuning controls by


Test Report No.: 2007050079
Date: May 30, 2007
Page 6 of 25

This Report shall not be reproduced except in full without the written approval of CTK





#### Configuration 1.7



Page 7 of 25 Test Report No.: 2007050079



386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com



# 1.8 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

# 1.9 Test Facility

The measurement facility is located at 386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

#### 1.10 Measurement Procedure

Preliminary AC power line conducted emissions tests were performed shielded room. To find worst mode, several typical mode and typical cable position were tested. Final AC power line conducted emissions test was performed shielded room. (location is same as Preliminary test)

Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

Preliminary radiated emissions test were performed anechoic chamber (Distance of antenna and EUT was 3 m). To find worst mode, several typical mode and typical cable position were tested and peak level and frequency were recorded.

Final radiated emissions test was performed Open Area Test Site. Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

\* Measurement procedures was In accordance with ANSI C63.4-2003 7.2.3, 7.2.4, 8.3.1.1, 8.3.1.2

Test Report No.: 2007050079 Page 8 of 25





# 1.11 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	FC 93250
JAPAN	VCCI	10 meter Open Area Test Site and one conducted site.	<b>VCI</b> R-948, C-986
KOREA	MIC	EMI (10 meter Open Area Test Site and two conducted sites) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	No. 51, KR0025
International	KOLAS	EMC	KOLAS PROPERTING NO. 119 SHOW
Europe	GLAS	EMC EN 55011, EN 55022, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 50130-4, EN 55024, EN 61204-3, EN 60601-1-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11	<b>TÜV</b> No.13000796-02

Page 9 of 25 Test Report No.: 2007050079





#### **Emissions Test Regulations** 2.0

The emissions tests were performed according	to rollowing regulations	S:
☐ EN 61000-6-3:2001	☐ Class A	☐ Class B
☐ EN 61000-6-4:2001	☐ Class A	☐ Class B
☐ EN 50083-2:2001		
☐ EN 55011:1998 +A1:1999 +A2:2002	Group 1 Class A	Group 2 Class B
☐ EN 55013:2001 +A1:2003		
☐ EN 55014-1:2000 +A1:2001 +A2:2002		
☐ EN 55015:2000 +A1:2001 +A2:2002		
☐ EN 61204-3:2000	☐ Class A	☐ Class B
☐ EN 55022:1994 +A1:1995 +A2:1997 ☐ EN 55022:1998 ☐ EN 55022:1998 +A1:2000 ☐ EN 55022:1998 +A1:2000 +A2:2003	☐ Class A ☐ Class A ☐ Class A ☐ Class A	☐ Class B ☐ Class B ☐ Class B ☐ Class B
☐ EN 61000-3-2:2000		
☐ EN 61000-3-3:1995 +A1:2001		
☐ VCCI V-3/2004.04	☐ Class A	☐ Class B
☐ AS/NZS 3548:1995 +A1:1997 +A2:1997	☐ Class A	☐ Class B
☐ CISPR 22:1997 ☐ CISPR 22:1997 +A1:2000 The unit was tested to CISPR 22 and complied FCC under paragraphs 15.107 and 15.109.	☐ Class A ☐ Class A I with the alternate meth	Class B Class B class B

Page 10 of 25 Test Report No.: 2007050079



386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com



## 2.1 Radiated Electric Field Emissions - #1

#### **Reference Standard**

FCC Part 15.239

#### **Test Date**

May 27, 2007

#### **Test Location**

⋈ EMI-OATS: Testing was performed at a test distance of 3 m

#### **Test Equipment**

	Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
$\boxtimes$	Field Strength Meter	Rohde & Schwarz	ESVS30	829673/015	2008-01-12
$\boxtimes$	ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014	2008-06-12

## **Frequency Range of Measurement**

88.1 MHz to 107.9 MHz

# Instrument Settings

IF Band Width: 120 kHz

lest Results				
The requirements are:				
'				
⊠ MET				
NOT MET				
NOT APPLICABLE				

#### Remarks

We have tested three modes (X, Y, Z). The worst mode (Y axis) for final test.

See Appendix A for test data

Test Report No.: 2007050079 Page 11 of 25



386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com



## 2.2 Radiated Electric Field Emissions - #2

#### **Reference Standard**

FCC Part 15.239

#### **Test Date**

May 27, 2007

#### **Test Location**

⋈ EMI-OATS: Testing was performed at a test distance of 3 m

#### **Test Equipment**

	Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
$\boxtimes$	Field Strength Meter	Rohde & Schwarz	ESVS30	829673/015	2008-01-12
$\boxtimes$	ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014	2008-06-12

## **Frequency Range of Measurement**

30 MHz to 1000 MHz,

## Instrument Settings

IF Band Width: 120 kHz

Test	Resu	lts

The requirements are:

MET
NOT MET
NOT APPLICABLE

#### Remarks

See Appendix A for test data

Emissions 20dB's below the limit were not necessarily recorded.

Test Report No.: 2007050079 Page 12 of 25

Date: May 30, 2007

Form No.: CTK-RF-EF-Part15(Rev.2.1)





#### 2.3 200kHz Bandwidth

#### **Reference Standard**

FCC Part 15.239

#### **Test Date**

May 28, 2007

## **Test Equipment**

	Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
$\boxtimes$	Spectrum Analyzer	HP	8564E	3551A00410	2007-11-03
$\boxtimes$	Field Strength Meter	Rohde & Schwarz	ESVS30	829673/015	2008-01-12
$\boxtimes$	ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014	2008-06-12

#### **Test Results**

The requirements are:

**NOT MET** 

NOT APPLICABLE

[88.1 MHz]



Test Report No.: 2007050079 Page 13 of 25






#### [98.0 MHz]



[107.9 MHz]



Test Report No.: 2007050079





#### Conducted Voltage Emissions - 15.207 2.4

**Reference Standard** 

FCC Part 15.207

**Test Date Not Applicable** 

**Test Location** Shielded Room

#### **Test Equipment**

Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date	
Field Strength Meter	Rohde & Schwarz	ESHS30	828144/002	2008-02-15	
LISN	EMCO	3825/2	9607-2574	2007-09-01	
LISN	EMCO	3825/2	9409-2246	2007-09-01	
Field Strength Meter	Rohde & Schwarz	ESHS30	862024/001	2008-03-07	
LISN	Rohde & Schwarz	ESH3-Z5	100207	2007-12-15	
LISN	EMCO	3825/2	9206-1971	2007-12-15	

## **Frequency Range of Measurement**

150 kHz to 30 MHz

#### **Conducted Emission limits**

Frequency of Emission (MHz)	Conducted Limit (dBuV)				
Trequency of Emission (WHZ)	Quasi-peak	Average			
0.15-0.5	66 to 56	56 to 46			
0.5-5	56	46			
5-30	60	50			

Test Results					
The requirements are:					
☐ MET ☐ NOT MET ☑ NOT APPLICABLE					

Remarks

Test Report No.: 2007050079 Page 15 of 25 Date: May 30, 2007

Form No.: CTK-RF-EF-Part15(Rev.2.1)





# **APPENDIX A - TEST DATA**

#### Radiated Electric Field Emissions - #1

Frequency	Reading	Pol.	Detect	Correction Factor		Limits	Result	Margin
[MHz]	[dBuV/m]			Antenna	Cable	[dBuV/m]	[dBuV/m]	[dB]
88.10	28.3	Н	Peak	8.8	1.0	68.0	38.1	29.9
88.10	26.8	Н	Average	8.8	1.0	48.0	36.6	11.4
98.00	27.5	Н	Peak	9.5	0.9	68.0	37.9	30.1
98.00	25.2	Н	Average	9.5	0.9	48.0	35.6	12.4
107.90	26.0	Н	Peak	9.9	1.1	68.0	37.0	31.0
107.90	24.8	Н	Average	9.9	1.1	48.0	35.8	12.2

#### Radiated Electric Field Emissions - #2

Frequency	Reading	Pol.	Height	Correction Factor		Limits	Result	Margin
[MHz]	[dBuV/m]		[m]	Antenna	Cable	[dBuV/m]	[dBuV/m]	[dB]
36.00	7.4	V	1.0	17.4	0.5	40.0	25.3	14.7
41.47	10.6	Н	4.0	12.9	0.6	43.5	24.1	19.4
50.90	12.3	V	1.0	8.2	0.6	43.5	21.1	22.4
175.12	12.2	Н	4.0	7.0	1.6	46.0	20.8	25.2
204.82	11.9	V	1.0	7.7	1.7	40.0	21.3	18.7
239.92	18.1	Н	4.0	9.3	1.9	40.0	29.3	10.7

Page 16 of 25 Test Report No.: 2007050079