

### 9 kHz ~ 25 GHz Data (Modulation : $\pi/4$ DQPSK)

#### ▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2378.31	V	X	PK	48.90	0.70	N/A	N/A	49.60	74.00	24.40
2378.31	V	X	AV	48.90	0.70	-24.79	N/A	24.81	54.00	29.19
4803.14	H	Z	PK	45.15	4.77	N/A	N/A	49.92	74.00	24.08
4803.14	H	Z	AV	45.15	4.77	-24.79	N/A	25.13	54.00	28.87

#### ▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.45	H	Z	PK	45.99	5.11	N/A	N/A	51.10	74.00	22.90
4882.45	H	Z	AV	45.99	5.11	-24.79	N/A	26.31	54.00	27.69

#### ▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2486.72	V	X	PK	49.68	1.07	N/A	N/A	50.75	74.00	23.25
2486.72	V	X	AV	49.68	1.07	-24.79	N/A	25.96	54.00	28.04
4960.25	H	Z	PK	45.11	5.34	N/A	N/A	50.45	74.00	23.55
4960.25	H	Z	AV	45.11	5.34	-24.79	N/A	25.66	54.00	28.34

#### ▪ Note.

1. The radiated emissions were investigated up to 25GHz. And no other spurious and harmonic emissions were found above listed frequencies.

#### 2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor =  $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{\underline{-9.54 \text{ dB}}}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

#### 3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

- Time to cycle through all channels =  $\Delta t = T [\text{ms}] \times 20$  minimum hopping channels, where T = pulse width = **2.88 ms**

-  $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$  Round up to next highest integer, to account for worst case,  $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$

- The Worst Case Dwell Time =  $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$

- D.C.F =  $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = \underline{\underline{-24.79 \text{ dB}}}$

#### 4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

.

## 9 kHz ~ 25 GHz Data (Modulation : 8DPSK)

### ▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2387.43	V	X	PK	50.05	0.70	N/A	N/A	50.75	74.00	23.25
2387.43	V	X	AV	50.05	0.70	-24.79	N/A	25.96	54.00	28.04
4803.80	H	Z	PK	44.85	4.77	N/A	N/A	49.62	74.00	24.38
4803.80	H	Z	AV	44.85	4.77	-24.79	N/A	24.83	54.00	29.17

### ▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.89	H	Z	PK	45.33	5.11	N/A	N/A	50.44	74.00	23.56
4881.89	H	Z	AV	45.33	5.11	-24.79	N/A	25.65	54.00	28.35

### ▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2492.22	V	X	PK	49.88	1.07	N/A	N/A	50.95	74.00	23.05
2492.22	V	X	AV	49.88	1.07	-24.79	N/A	26.16	54.00	27.84
4960.43	H	Z	PK	44.78	5.34	N/A	N/A	50.12	74.00	23.88
4960.43	H	Z	AV	44.78	5.34	-24.79	N/A	25.33	54.00	28.67

### ▪ Note.

1. The radiated emissions were investigated up to 25GHz. And no other spurious and harmonic emissions were found above listed frequencies.

#### 2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor =  $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{\underline{-9.54 \text{ dB}}}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

#### 3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

- Time to cycle through all channels =  $\Delta t = T [\text{ms}] \times 20$  minimum hopping channels, where T = pulse width = **2.88 ms**

-  $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$  Round up to next highest integer, to account for worst case,  $H' = 100 / (2.88 \times 20) = 1.74 \approx 2$

- The Worst Case Dwell Time =  $T [\text{ms}] \times H' = 2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$

- D.C.F =  $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \log(5.76 / 100) = \underline{\underline{-24.79 \text{ dB}}}$

#### 4. Sample Calculation.


Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

### 7.4.3. Conducted Spurious Emissions


#### Low Band-edge

#### Lowest Channel & Modulation : GFSK





#### Low Band-edge

#### Hopping mode & Modulation : GFSK




## Conducted Spurious Emissions

## Lowest Channel & Modulation : GFSK



# Conducted Spurious Emissions *Lowest Channel & Modulation : GFSK*




## Reference for limit

## Middle Channel & Modulation : GFSK





## Conducted Spurious Emissions

## Middle Channel & Modulation : GFSK




# Conducted Spurious Emissions

## Middle Channel & Modulation : GFSK




## High Band-edge

## Highest Channel & Modulation : GFSK





## High Band-edge

## Hopping mode & Modulation : GFSK






# Conducted Spurious Emissions *Highest Channel & Modulation : GFSK*




# Conducted Spurious Emissions *Highest Channel & Modulation : GFSK*




## Low Band-edge

## Lowest Channel & Modulation : $\pi/4$ DQPSK





## Low Band-edge


## Hopping mode & Modulation : $\pi/4$ DQPSK



# Conducted Spurious Emissions *Lowest Channel & Modulation : $\pi/4$ DQPSK*




# Conducted Spurious Emissions Lowest Channel & Modulation : $\pi/4$ DQPSK




Reference for limit

***Middle Channel & Modulation :  $\pi/4$ DQPSK***





Conducted Spurious Emissions



***Middle Channel & Modulation :  $\pi/4$ DQPSK***



# Conducted Spurious Emissions

## Middle Channel & Modulation : $\pi/4$ DQPSK





**High Band-edge****Highest Channel & Modulation :  $\pi/4$ DQPSK****High Band-edge****Hopping mode & Modulation :  $\pi/4$ DQPSK**




# Conducted Spurious Emissions

## Highest Channel & Modulation : $\pi/4$ DQPSK




# Conducted Spurious Emissions

***Highest Channel & Modulation :  $\pi/4$ DQPSK***




## Low Band-edge

## Lowest Channel & Modulation : 8DPSK





## Low Band-edge

## Hopping mode & Modulation : 8DPSK




# Conducted Spurious Emissions

## Lowest Channel & Modulation : 8DPSK




# Conducted Spurious Emissions

## Lowest Channel & Modulation : 8DPSK




Reference for limit

Middle Channel & Modulation : 8DPSK





Conducted Spurious Emissions

Middle Channel & Modulation : 8DPSK




# Conducted Spurious Emissions

## Middle Channel & Modulation : 8DPSK



## High Band-edge

## Highest Channel & Modulation : 8DPSK



## High Band-edge



## Hopping mode & Modulation : 8DPSK






# Conducted Spurious Emissions

## Highest Channel & Modulation : 8DPSK



# Conducted Spurious Emissions

## Highest Channel & Modulation : 8DPSK



## 8. Transmitter AC Power Line Conducted Emission

### 8.1 Test Setup

See test photographs for the actual connections between EUT and support equipment.

### 8.2 Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

### 8.3 Test Procedures

Conducted emissions from the EUT were measured according to the ANSI C63.10.

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

## 8.4 Test Results

### AC Line Conducted Emissions (Graph) = Modulation : 8DPSK

#### Results of Conducted Emission

DT&C

Date 2017-06-23

Model  
Function  
Mode  
Test condition


PM70  
Bluetooth  
1Mbps\_Hopping\_0

Temp/Humi.  
Power Supply  
Operator

23 'C 48 %  
AC 120 V 60 Hz  
J.W.KIM

Memo

LIMIT : FCC P15.207 QP  
FCC P15.207 AV



## AC Line Conducted Emissions (List) = Modulation : 8DPSK

### Results of Conducted Emission

DT&amp;C

Date 2017-06-23

Model  
Function  
Mode  
Test condition

PM70  
Bluetooth  
1Mbps\_Hopping\_0

Temp/Humi.  
Power Supply  
Operator

23 'C 48 %  
AC 120 V 60 Hz  
J.W.KIM

Memo

LIMIT : FCC P15.207 QP  
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP	CAV		QP	CAV	QP	CAV	QP	CAV	
		[dBuV]	[dBuV]		[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	
1	0.15318	49.72	38.22	0.22	49.94	38.44	65.83	55.83	15.89	17.39	N
2	0.18755	47.45	38.09	0.20	47.65	38.29	64.14	54.14	16.49	15.85	N
3	0.41687	39.12	31.89	0.21	39.33	32.10	57.51	47.51	18.18	15.41	N
4	0.72363	30.31	22.07	0.23	30.54	22.30	56.00	46.00	25.46	23.70	N
5	2.25100	26.53	16.33	0.32	26.85	16.65	56.00	46.00	29.15	29.35	N
6	5.32460	24.60	15.50	0.45	25.05	15.95	60.00	50.00	34.95	34.05	N
7	9.77760	23.11	14.45	0.70	23.81	15.15	60.00	50.00	36.19	34.85	N
8	0.15166	50.87	31.27	0.18	51.05	31.45	65.91	55.91	14.86	24.46	L1
9	0.18704	48.38	30.09	0.18	48.56	30.27	64.17	54.17	15.61	23.90	L1
10	0.40186	33.49	25.63	0.20	33.69	25.83	57.81	47.81	24.12	21.98	L1
11	0.52245	24.39	14.54	0.20	24.59	14.74	56.00	46.00	31.41	31.26	L1
12	2.11840	23.95	15.32	0.29	24.24	15.61	56.00	46.00	31.76	30.39	L1
13	5.26640	19.42	11.67	0.46	19.88	12.13	60.00	50.00	40.12	37.87	L1
14	8.43780	18.98	13.50	0.69	19.67	14.19	60.00	50.00	40.33	35.81	L1

## 9. Antenna Requirement

Describe how the EUT complies with the requirement that either its antenna is permanently attached, or that it employs a unique antenna connector, for every antenna proposed for use with the EUT.

**Conclusion:** **Comply**

The internal antenna is attached on the main PCB using the special spring tension. (Refer to Internal Photo file.)

### - Minimum Standard :

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions.

## 10. Occupied Bandwidth (99 %)

### 10.1 Test Setup

Refer to the APPENDIX I.

### 10.2 Limit

Limit : Not Applicable

### 10.3 Test Procedure

The 99 % power bandwidth was measured with a calibrated spectrum analyzer.

The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately  $3 \times \text{RBW}$ .


Spectrum analyzer plots are included on the following pages.

### 10.4 Test Results

Modulation	Tested Channel	Test Results (MHz)
<b><u>GFSK</u></b>	Lowest	0.868
	Middle	0.880
	Highest	<b>0.883</b>
<b><u><math>\pi/4</math>DQPSK</u></b>	Lowest	1.173
	Middle	<b>1.180</b>
	Highest	1.177
<b><u>8DPSK</u></b>	Lowest	1.182
	Middle	<b>1.183</b>
	Highest	1.178


## Occupied Bandwidth (99 %)

## Lowest Channel & GFSK



## Occupied Bandwidth (99 %)

## Middle Channel & GFSK






## Occupied Bandwidth (99 %)

## Highest Channel & GFSK




## Occupied Bandwidth (99 %)

## Lowest Channel & $\pi/4$ DQPSK




## Occupied Bandwidth (99 %)

## Middle Channel & $\pi/4$ DQPSK




## Occupied Bandwidth (99 %)

## Highest Channel & $\pi/4$ DQPSK




## Occupied Bandwidth (99 %)

## Lowest Channel & 8DPSK




## Occupied Bandwidth (99 %)

## Middle Channel & 8DPSK



## Occupied Bandwidth (99 %)


## Highest Channel & 8DPSK




## APPENDIX I

### Test set up diagrams

#### ▪ Radiated Measurement



#### ▪ Conducted Measurement



Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	6.69	15	10.40
1	6.97	20	11.17
2.402 & 2.440 & 2.480	7.60	25	13.39
5	8.33	-	-
10	9.49	-	-


Note 1 : The path loss from EUT to Spectrum analyzer were measured and used for test.

Path loss ( S/A's Correction factor) = Cable A + Power splitter




$\pi$ /4DQPSK & Lowest & X & Ver

Detector Mode : PK



$\pi$ /4DQPSK & Highest & X & Ver


Detector Mode : PK






# 8DPSK & Lowest & X & Ver

Detector Mode : PK




# 8DPSK & Highest & X & Ver

Detector Mode : PK




## GFSK & Middle & Z & Hor

Detector Mode : PK



## $\pi/4$ DQPSK & Middle & Z & Hor

Detector Mode : PK



**8DPSK & Middle & Z & Hor**

**Detector Mode : PK**

