



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Applicant: Win Accord Ltd.

Address: 12F., No. 225, Sec. 5, Nanjing E. Rd., Songshan Dist, Taipei City
105, Taiwan

Product Name: Tablet PC

Model Name: PTT-826D, PT08002-51-XXX(X=a-z, 0-9, A-Z), IDxD8, IDxD8 3G

Brand Name: N/A

FCC ID: V37-PTT826D

Report No.: MTE/DAL/D12081189

Date of Issue: Oct. 13, 2012

Issued by: Most Technology Service Co., Ltd.

Address : No.5, Langshan 2nd Road, North District, Hi-tech Industrial Park,
Nanshan, Shenzhen, Guangdong, China

Tel : 86-755-8617 0306

Fax : 86-755-8617 0310

The report consists 49 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION.....	5
2.1 Product Information	5
2.2 Objective	6
2.3 Test Standards and Results	6
2.4 Environmental Conditions.....	6
2.5 MEASUREMENT UNCERTAINTY	6
3. TEST FACILITY	7
3.1 TEST FACILITY	7
3.2 Test Conditions	7
3.3 Channel List	8
3.4 Description of Test Modes	8
3.5 Table of Parameters of Text Software Setting.....	9
3.6 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	10
4. SETUP OF EQUIPMENT UNDER TEST.....	11
4.1 SUPPORT EQUIPMENT	11
4.2 TEST EQUIPMENT LIST	12
5. 47 CFR Part 15C 15.249 Requirements.....	13
5.1 Spurious Emission Test	13
5.1.1 Requirement.....	13
5.1.2 Test Description.....	14
5.1.3 Test Description.....	15
5.1.5 Test Result	16
5.2 Band Edge.....	30
5.2.1 Requirement.....	30
5.2.2 Test Description.....	30
5.2.3 Test Result.....	30
5.3 LINE CONDUCTED EMISSION TEST	36
5.3.1. LIMITS OF LINE CONDUCTED EMISSION TEST.....	36
5.3.2. BLOCK DIAGRAM OF TEST SETUP.....	36
5.3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	37
5.3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	37
5.3.5. Test result	37
5.3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	38

5.4 20 dB Bandwidth 42

5.4.1 Definition 42

5.4.2 Block Diagram Of Test Setup 42

5.4.3 Test Result..... 42

APPENDIX 1 47

PHOTOGRAPHS OF TEST SETUP..... 47

1. VERIFICATION OF CONFORMITY

Equipment Under Test: Tablet PC
Brand Name: N/A
Model Number: PTT-826D
Series Number: PT08002-51-XXX(X=a-z, 0-9, A-Z), IDxD8, IDxD8 3G
Description of Differences: The series numbers are different in model names with the same functions.
FCC ID: V37-PTT826D
Applicant: Win Accord Ltd.
12F., No. 225, Sec. 5, Nanjing E. Rd., Songshan Dist, Taipei City 105,
Taiwan
Manufacturer: Win Accord Ltd.
7F., Garden City Cyber Port, Nanhai Road A, No. 1079, Nanshan Dist.,
Shenzhen, China
Technical Standards: 47 CFR Part 15 Subpart C
File Number: MTE/DAL/D12081189
Date of test: Aug. 24-Oct. 13, 2012
Deviation: None
Condition of Test Sample: Normal
Test Result: PASS

The above equipment was tested by MOST for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Prepare by (+ signature):


Dona Liu

Sep. 10, 2012

Review by (+ signature):


Elva Wong

Oct. 13, 2012

Approved by (+ signature):


Yvette Zhou

Oct. 13, 2012



2. GENERAL INFORMATION

2.1 Product Information

Product:	Tablet PC
Trade Name:	N/A
Model Number:	PTT-826D
Series Number:	PT08002-51-XXX(X=a-z, 0-9, A-Z), IDxD8, IDxD8 3G
Description of Differences:	The series numbers are different in model names with the same functions.
Power Supply:	DC 5V by AC adapter 100~240V 50/60Hz DC 3.7V by battery
Frequency Range:	2402MHz -2480MHz
Modulation Type:	GFSK, π / 4-DQPSK, 8-DPSK
Modulation Technique:	FHSS
Antenna Type:	Internal Fixed
Antenna Gain:	3.0dBi
Channel Spacing:	1MHz
Channel Number:	79
Temperature Range:	0°C ~ +40°C

NOTE:

1. For a more detailed features description about the EUT, please refer to User's Manual.

2.2 Objective

Perform FCC Part 15 Subpart C tests for FCC Marking.

2.3 Test Standards and Results

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.249(a)	Spurious Emission	PASS	2012-09-03
2	15.249(a)	Band Edge	PASS	2012-09-03
3	15.207	Power Line Conducted Emission Test	PASS	2012-09-03
4	15.249	20dB Bandwidth	PASS	2012-09-03/ 2012-10-13

Note: 1. The test result judgment is decided by the limit of measurement standard
2. The information of measurement uncertainty is available upon the customer's request.

2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

2.5 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

The report uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, Providing a level of confidence of approximately 95%

- Uncertainty of Conducted Emission, $U_c = \pm 1.8\text{dB}$
- Uncertainty of Radiated Emission, $U_c = \pm 3.2\text{dB}$

3. TEST FACILITY

3.1 TEST FACILITY

Test Site:	Most Technology Service Co., Ltd.
Location:	No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan, Shenzhen, Guangdong, China
Description:	<p>There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009 and CISPR 16 requirements.</p> <p>The FCC Registration Number is 490827.</p> <p>The IC Registration Number is 46405-7103.</p> <p>The CNAS Registration Number is CNAS L3573.</p>
Site Filing:	The site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.
Instrument Tolerance:	All measuring equipment is in accord with ANSI C63.4:2009 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.
Ground Plane:	Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna.

3.2 Test Conditions

The EUT has been tested under normal operating (TX) and standby (RX) condition.

The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis).

The following data show only with the worst case setup.

The worst case of Y axis was reported.

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

3.3 Channel List

Channel List for GFSK, Pi/4-DQPSK, 8-DPSK Mode					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402MHz	28	2429MHz	55	2456MHz
02	2403MHz	29	2430MHz	56	2457MHz
03	2404MHz	30	2431MHz	57	2458MHz
04	2405MHz	31	2432MHz	58	2459MHz
05	2406MHz	32	2433MHz	59	2460MHz
06	2407MHz	33	2434MHz	60	2461MHz
07	2408MHz	34	2435MHz	61	2462MHz
08	2409MHz	35	2436MHz	62	2463MHz
09	2410MHz	36	2437MHz	63	2464MHz
10	2411MHz	37	2438MHz	64	2465MHz
11	2412MHz	38	2439MHz	65	2466MHz
12	2413MHz	39	2440MHz	66	2467MHz
13	2414MHz	40	2441MHz	67	2468MHz
14	2415MHz	41	2442MHz	68	2469MHz
15	2416MHz	42	2443MHz	69	2470MHz
16	2417MHz	43	2444MHz	70	2471MHz
17	2418MHz	44	2445MHz	71	2472MHz
18	2419MHz	45	2446MHz	72	2473MHz
19	2420MHz	46	2447MHz	73	2474MHz
20	2421MHz	47	2448MHz	74	2475MHz
21	2422MHz	48	2449MHz	75	2476MHz
22	2423MHz	49	2450MHz	76	2477MHz
23	2424MHz	50	2451MHz	77	2478MHz
24	2425MHz	51	2452MHz	78	2479MHz
25	2426MHz	52	2453MHz	79	2480MHz
26	2427MHz	53	2454MHz		
27	2428MHz	54	2455MHz		

3.4 Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level, Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively

Pre-test Mode	Description
Mode 1	GFSK CH01/CH41/CH79
Mode 2	Pi/4-DQPSK CH01/CH41/CH79
Mode 3	8-DPSK CH01/CH41/CH79

Note:

The measurements are performed at the highest, middle, lowest available channels.

The measurements are performed at all bit rate of transmitter, the worst data was reported.

3.5 Table of Parameters of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level, the RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth.

Test software Version	Test program:N/A		
GFSK Mode	2402MHz	2442MHz	2480MHz
π / 4-DQPSK	2402MHz	2442MHz	2480MHz
8-DPSK	2402MHz	2442MHz	2480MHz

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4:2009,Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4:2009.

3.6 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

4. SETUP OF EQUIPMENT UNDER TEST**4.1 SUPPORT EQUIPMENT**

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
---	---	---	---	---	---

Remark:

All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2 TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at Most for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

No.	Equipment	Manufacturer	Model No.	S/N	Calculator date	Calculator Interval
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14	1 Year
2	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2012/03/14	1 Year
3	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14	1 Year
4	Terminator	Hubersuhner	50Ω	No.1	2012/03/14	1 Year
5	RF Cable	SchwarzBeck	N/A	No.1	2012/03/14	1 Year
6	Test Receiver	Rohde & Schwarz	ESPI	101202	2012/03/14	1 Year
7	Bilog Antenna	SCHWARZBECK	BBHA9120D	D69250	2012/03/14	1 Year
8	Cable	Resenberger	N/A	NO.1	2012/03/14	1 Year
9	Cable	SchwarzBeck	N/A	NO.2	2012/03/14	1 Year
10	Cable	SchwarzBeck	N/A	NO.3	2012/03/14	1 Year
11	DC Power Filter	DuoJi	DL2×30B	N/A	2012/03/14	1 Year
12	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2012/03/14	1 Year
13	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2012/03/14	1 Year
14	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14	1 Year
15	Absorbing Clamp	Luthi	MDS21	3635	2012/03/14	1 Year
16	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14	1 Year
17	AC Power Source	Kikusui	AC40MA	LM003232	2012/03/14	1 Year
18	Test Analyzer	Kikusui	KHA1000	LM003720	2012/03/14	1 Year
19	Line Impedence Network	Kikusui	LIN40MA-PCR-L	LM002352	2012/03/14	1 Year
20	ESD Tester	Kikusui	KES4021	LM003537	2012/03/14	1 Year
21	EMC PRO System	EM Test	UCS-500-M4	V0648102026	2012/03/14	1 Year
22	Signal Generator	IFR	2032	203002/100	2012/03/14	1 Year
23	Amplifier	A&R	150W1000	301584	2012/03/14	1 Year
24	CDN	FCC	FCC-801-M2-25	47	2012/03/14	1 Year
25	CDN	FCC	FCC-801-M3-25	107	2012/03/14	1 Year
26	EM Injection Clamp	FCC	F-203I-23mm	403	2012/03/14	1 Year
27	RF Cable	MIYAZAKI	N/A	No.1/No.2	2012/03/14	1 Year
28	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2012/03/14	1 Year
29	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2012/03/14	1 Year
30	Telecommunication Test Equipment	R&S	CMU200	N/A	2012/03/14	1 Year
31	8 Loop Antenna	ARA	PLA-1030/B	1029	2012/02/19	1 Year

NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR Part 15C 15.249 Requirements

5.1 Spurious Emission Test

5.1.1 Requirement

According to FCC section 15.249(a):

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μ V/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

According to FCC section 15.109 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μ V/m)	Measurement Distance (m)
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μ V/m)	Measurement Distance (m)
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3


5.1.2 Test Description


Test Setup:

From 9KHz to 30MHz:



From 30MHz to 1GHz:



Above 1GHz:**5.1.3 Test Description**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO
Above 1GHz ☹ a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

5.1.4 Test Result

From 9 KHz to 30MHz:

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
N/A	H								>20
N/A	V								>20

-Note: No test data was detected in below 30MHz.

From 30MHz to 1GHz:

The following test mode(s) were scanned during the preliminary test:

Preliminary Radiated Emission Test				
Frequency Range Investigated		9KHz TO 26 GHz		
Mode of operation	Date	Report No.	Data#	Worst Mode
Bluetooth Mode	2012-09-27	MTE/DAL/D12081189	1_(V, H)	<input checked="" type="checkbox"/>
LINE INPUT Mode	2012-09-27	MTE/DAL/D12081189	1_(V, H)	<input type="checkbox"/>

Note:

The Bluetooth model was carried out for GFSK, π / 4-DQPSK and 8-DPSK modulation types with two adapters, GFSK Low channel modulation type was the worst case condition, The test data was shown on the summary data page.

From 30MHz to 1GHz



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Radiated Emission Measurement

File: PTT-826D

Data: #10

Date: 2012-8-27

Time: 15:01:05



Site: Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 5V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Tablet PC

Distance:

M/N: PTT-826D

Mode: BT Mode

Note: MPAS-U012050E

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	!	82.3800	24.01	11.35	35.36	40.00	-4.64	QP		
2		132.8199	18.24	17.56	35.80	43.50	-7.70	QP		
3		239.5200	18.03	17.17	35.20	46.00	-10.80	QP		
4		335.5500	19.78	17.06	36.84	46.00	-9.16	QP		
5	!	527.6100	20.23	22.08	42.31	46.00	-3.69	QP		
6	*	624.6100	19.00	23.59	42.59	46.00	-3.41	QP		

*:Maximum data x:Over limit !:over margin

Engineer Signature:

Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement


File: PTT-826D

Data: #11

Date: 2012-8-27

Time: 15:05:28

70.0 dBuV/m



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 5V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Tablet PC

Distance:

M/N: PTT-826D

Mode: BT Mode

Note: MPAS-U012050E

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		97.9000	19.88	12.72	32.60	43.50	-10.90	QP		
2		167.7400	15.33	17.20	32.53	43.50	-10.97	QP		
3		239.5200	21.25	17.17	38.42	46.00	-7.58	QP		
4	!	335.5500	24.05	17.06	41.11	46.00	-4.89	QP		
5		431.5800	15.92	20.32	36.24	46.00	-9.76	QP		
6	*	624.6100	17.85	23.59	41.44	46.00	-4.56	QP		

*:Maximum data x:Over limit !:over margin

Engineer Signature:

Allen



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement


File: PTT-826D

Data: #20

Date: 2012-8-27

Time: 15:53:22

70.0 dBuV/m



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 5V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Tablet PC

Distance:

M/N: PTT-826D

Mode: BT Mode

Note: GP302E-050-200

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	!	71.7100	23.20	11.68	34.88	40.00	-5.12	QP		
2	!	239.5200	22.94	17.17	40.11	46.00	-5.89	QP		
3	!	335.5500	22.96	17.06	40.02	46.00	-5.98	QP		
4	!	431.5800	20.56	20.32	40.88	46.00	-5.12	QP		
5	!	527.6100	18.86	22.08	40.94	46.00	-5.06	QP		
6	*	749.7400	16.24	25.80	42.04	46.00	-3.96	QP		

*:Maximum data x:Over limit !:over margin

Engineer Signature:

Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement


File: PTT-826D

Data: #21

Date: 2012-8-27

Time: 15:58:31

70.0 dBuV/m



Site Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 5V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Tablet PC

Distance:

M/N: PTT-826D

Mode: BT Mode

Note: GP302E-050-200

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	!	31.9400	11.95	23.31	35.26	40.00	-4.74	QP		
2		148.3400	15.67	16.63	32.30	43.50	-11.20	QP		
3		167.7400	16.68	17.20	33.88	43.50	-9.62	QP		
4		527.6100	14.90	22.08	36.98	46.00	-9.02	QP		
5		623.6399	15.84	23.57	39.41	46.00	-6.59	QP		
6	*	749.7400	16.49	25.80	42.29	46.00	-3.71	QP		

*:Maximum data x:Over limit !:over margin

Engineer Signature:

Allen

Above 1 GHz**Operation Mode:** GFSK Mode/CH Low**Test Date:** Aug. 27, 2012**Temperature:** 20°C**Tested by:** Sky Guo**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2402.00	H	70.52	64.32	16.25	86.77	80.57	114.00	94.00	-13.43
4804.00	H	45.23	21.71	20.18	65.41	41.89	74.00	54.00	-12.11
N/A									>20
2402.00	V	71.36	62.87	16.25	87.61	79.12	114.00	94.00	-14.88
4804.00	V	44.60	22.91	20.18	64.78	43.09	74.00	54.00	-10.91
N/A									>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: GFSK Mode/CH Mid**Test Date:** Aug. 27, 2012**Temperature:** 20°C**Tested by:** Sky Guo**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2441.00	H	72.53	67.26	17.01	89.54	84.27	114.00	94.00	-9.73
4882.00	H	45.17	23.75	21.57	66.74	45.32	74.00	54.00	-8.68
N/A									>20
2441.00	V	71.59	66.38	17.01	88.60	83.39	114.00	94.00	-10.61
4882.00	V	46.31	22.34	21.57	67.88	43.91	74.00	54.00	-10.09
N/A									>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: GFSK Mode/CH High**Test Date:** Aug. 27, 2012**Temperature:** 20°C**Tested by:** Sky Guo**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2480.00	H	67.38	60.71	17.24	84.62	77.95	114.00	94.00	-16.05
4960.00	H	44.98	23.04	21.57	66.55	44.61	74.00	54.00	-9.39
N/A									>20
2480.00	V	65.30	59.75	17.24	82.54	76.99	114.00	94.00	-17.01
4960.00	V	45.05	21.82	21.57	66.62	43.39	74.00	54.00	-10.61
N/A									>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: π / 4-DQPSK/CH Low**Test Date:** Aug. 27, 2012**Temperature:** 20°C**Tested by:** Sky Guo**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2402.00	H	68.26	60.31	16.25	84.51	76.56	114.00	94.00	-17.44
4804.00	H	45.23	21.71	20.18	65.41	41.89	74.00	54.00	-12.11
N/A									>20
2402.00	V	67.39	61.20	16.25	83.64	77.45	114.00	94.00	-16.55
4804.00	V	44.60	22.91	20.18	64.78	43.09	74.00	54.00	-10.91
N/A									>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: π / 4-DQPSK/CH Mid**Test Date:** Aug. 27, 2012**Temperature:** 20°C**Tested by:** Sky Guo**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2441.00	H	71.41	61.38	17.01	88.42	78.39	114.00	94.00	-15.61
4882.00	H	44.54	22.86	21.57	66.11	44.43	74.00	54.00	-9.57
N/A									>20
2441.00	V	70.98	62.74	17.01	87.99	79.75	114.00	94.00	-14.25
4882.00	V	44.91	21.50	21.57	66.48	43.07	74.00	54.00	-10.93
N/A									>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: π / 4-DQPSK Mode /CH High **Test Date:** Aug. 27, 2012
Temperature: 20°C **Tested by:** Sky Guo
Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2480.00	H	65.87	59.36	17.24	83.11	76.60	114.00	94.00	-17.40
4960.00	H	44.98	23.04	21.57	66.55	44.61	74.00	54.00	-9.39
N/A									>20
2480.00	V	67.02	60.31	17.24	84.26	77.55	114.00	94.00	-16.45
4960.00	V	45.05	21.82	21.57	66.62	43.39	74.00	54.00	-10.61
N/A									>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: 8-DPSK Mode /CH Low**Test Date:** Aug. 27, 2012**Temperature:** 20°C**Tested by:** Sky Guo**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2402.00	H	65.31	58.42	16.25	81.56	74.67	114.00	94.00	-19.33
4804.00	H	45.76	20.93	20.18	65.94	41.11	74.00	54.00	-12.89
N/A									>20
2402.00	V	67.95	61.25	16.25	84.20	77.50	114.00	94.00	-16.50
4804.00	V	45.69	19.94	20.18	65.87	40.12	74.00	54.00	-13.88
N/A									>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: 8-DPSK Mode /CH Mid**Test Date:** Aug. 27, 2012**Temperature:** 20°C**Tested by:** Sky Guo**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2441.00	H	66.95	60.2	17.01	83.96	77.21	114.00	94.00	-16.79
4882.00	H	46.95	19.97	21.57	68.52	41.54	74.00	54.00	-12.46
N/A									>20
2441.00	V	64.30	57.39	17.01	81.31	74.40	114.00	94.00	-19.60
4882.00	V	43.77	18.99	21.57	65.34	40.56	74.00	54.00	-13.44
N/A									>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: 8-DPSK Mode /CH High**Test Date:** Aug. 27, 2012**Temperature:** 20°C**Tested by:** Sky Guo**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2480.00	H	64.32	58.30	17.24	81.56	75.54	114.00	94.00	-18.46
4960.00	H	44.74	21.40	22.64	67.38	44.04	74.00	54.00	-9.96
N/A									>20
2480.00	V	63.75	57.96	17.24	80.99	75.20	114.00	94.00	-18.80
4960.00	V	44.20	22.07	22.64	66.84	44.71	74.00	54.00	-9.29
N/A									>20

Notes:


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

5.2 Band Edge

5.2.1 Requirement

According to FCC section 15.249(a), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2.2 Test Description




5.2.3 Test Result

The EUT operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.


GFSK Modulation Mode:

Test Mode		Channel Marked Frequency	Limit (dBuV/m)	Test Result Highest Emission (dBuV/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
Bluetooth	Low Channel	2390MHz	74(Peak) 54(Average)	49.38	28.07	49.48	27.95
		2400MHz		48.71	26.98	49.73	28.87
	High Channel	2483.5MHz		50.13	29.87	49.27	30.00
		2500MHz		49.52	28.91	48.93	27.25


Test Plot:




(CH Low, Horizontal, Peak)



(CH Low, Vertical, Peak)



(CH High, Horizontal, Peak)




(CH High, Vertical, Peak)


8DPSK Modulation Mode:

Test Mode		Channel Marked Frequency	Limit (dBuV/m)	Test Result Highest Emission (dBuV/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
Bluetooth	Low Channel	2390MHz	74(Peak) 54(Average)	49.99	30.02	49.48	28.83
		2400MHz		49.56	28.96	49.09	29.01
	High Channel	2483.5MHz		49.50	28.34	49.26	27.91
		2500MHz		49.05	27.67	49.12	27.84


Test Plot:




(CH Low, Horizontal, Peak)



(CH Low, Vertical, Peak)



(CH High, Horizontal, Peak)




(CH High, Vertical, Peak)

5.3 LINE CONDUCTED EMISSION TEST
5.3.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

****Note:** 1. the lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

5.3.2. BLOCK DIAGRAM OF TEST SETUP



5.3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per FCC Part 15 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per FCC Part 15.
- 3) All I/O cables were positioned to simulate typical actual usage as per FCC Part 15.
- 4) The EUT received DC 5V by Adapter which received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5) All support equipments received power from a second LISN supplying power of AC 120V/60Hz, if any.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.

5.3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

EUT and support equipment was set up on the test bench as per step 9 of the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

5.3.5. Test result

The following test mode(s) were scanned during the preliminary test:

Preliminary Conducted Emission Test				
Frequency Range Investigated		150KHz TO 30 MHz		
Mode of operation	Date	Report No.	Data#	Worst Mode
Bluetooth Mode	2012-08-24	MTE/DAL/D12081189	1_(V, H)	<input checked="" type="checkbox"/>
LINE INPUT Mode	2012-08-24	MTE/DAL/E12081189	1_(V, H)	<input type="checkbox"/>

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


Note:

The Bluetooth model was carried out for GFSK, π / 4-DQPSK and 8-DPSK modulation types with two adapters, GFSK Low channel modulation type was the worst case condition, The test data was shown on the summary data page.

5.3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310



Site Chamber #1 Phase: **L1** Temperature: 26
Limit: FCC Part15 B Class B QP Power: DC 5V Adapter AC 120V/60Hz Humidity: 60 %
EUT: Tablet PC
M/N: PTT-826D
Mode: BT Mode
Note: MPAS-U012050E

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.2316	38.00	11.79	49.79	62.39	-12.60	QP	
2		0.2316	27.49	11.79	39.28	52.39	-13.11	AVG	
3		0.5899	37.19	10.00	47.19	56.00	-8.81	QP	
4		0.5899	24.19	10.00	34.19	46.00	-11.81	AVG	
5		0.6460	35.76	10.00	45.76	56.00	-10.24	QP	
6		0.6460	20.45	10.00	30.45	46.00	-15.55	AVG	
7	*	0.7660	37.59	10.00	47.59	56.00	-8.41	QP	
8		0.7660	20.63	10.00	30.63	46.00	-15.37	AVG	
9		1.0540	34.18	9.95	44.13	56.00	-11.87	QP	
10		1.0540	19.50	9.95	29.45	46.00	-16.55	AVG	
11		3.2180	32.68	10.22	42.90	56.00	-13.10	QP	
12		3.2180	14.27	10.22	24.49	46.00	-21.51	AVG	


*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



Site Chamber #1

Phase: **N**

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 5V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Tablet PC

M/N: PTT-826D

Mode: BT Mode

Note: MPAS-U012050E

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.2701	35.13	11.53	46.66	61.11	-14.45	QP	
2		0.2701	26.22	11.53	37.75	51.11	-13.36	AVG	
3		0.5181	35.84	10.00	45.84	56.00	-10.16	QP	
4		0.5181	23.61	10.00	33.61	46.00	-12.39	AVG	
5		0.5820	33.76	10.00	43.76	56.00	-12.24	QP	
6	*	0.5820	26.24	10.00	36.24	46.00	-9.76	AVG	
7		2.1020	28.63	9.10	37.73	56.00	-18.27	QP	
8		2.1020	13.08	9.10	22.18	46.00	-23.82	AVG	
9		3.3300	31.45	10.33	41.78	56.00	-14.22	QP	
10		3.3300	17.58	10.33	27.91	46.00	-18.09	AVG	
11		4.7859	24.55	11.79	36.34	56.00	-19.66	QP	
12		4.7859	9.43	11.79	21.22	46.00	-24.78	AVG	


*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



Site Chamber #1 Phase: **N** Temperature: 26
Limit: FCC Part15 B Class B QP Power: DC 5V Adapter AC 120V/60Hz Humidity: 60 %
EUT: Tablet PC
M/N: PTT-826D
Mode: BT Mode
Note: GP302E-050-200

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.2429	39.71	11.71	51.42	61.99	-10.57	QP	
2		0.2429	28.40	11.71	40.11	51.99	-11.88	AVG	
3		0.4786	35.00	10.14	45.14	56.36	-11.22	QP	
4		0.4786	25.23	10.14	35.37	46.36	-10.99	AVG	
5		0.6380	33.44	10.00	43.44	56.00	-12.56	QP	
6		0.6380	21.74	10.00	31.74	46.00	-14.26	AVG	
7		2.8340	31.35	9.83	41.18	56.00	-14.82	QP	
8		2.8340	21.69	9.83	31.52	46.00	-14.48	AVG	
9		4.6779	30.77	11.68	42.45	56.00	-13.55	QP	
10		4.6779	20.85	11.68	32.53	46.00	-13.47	AVG	
11		5.4419	36.55	11.73	48.28	60.00	-11.72	QP	
12		5.4419	27.10	11.73	38.83	50.00	-11.17	AVG	


*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



Site Chamber #1

Phase: **L1**

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 5V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Tablet PC

M/N: PTT-826D

Mode: BT Mode

Note: GP302E-050-200

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1884	41.19	11.31	52.50	64.10	-11.60	QP	
2		0.1884	30.22	11.31	41.53	54.10	-12.57	AVG	
3		0.4994	36.86	10.00	46.86	56.01	-9.15	QP	
4	*	0.4994	29.38	10.00	39.38	46.01	-6.63	AVG	
5		0.5620	33.59	10.00	43.59	56.00	-12.41	QP	
6		0.5620	24.79	10.00	34.79	46.00	-11.21	AVG	
7		2.8220	34.34	9.82	44.16	56.00	-11.84	QP	
8		2.8220	27.27	9.82	37.09	46.00	-8.91	AVG	
9		4.4818	32.19	11.48	43.67	56.00	-12.33	QP	
10		4.4818	25.17	11.48	36.65	46.00	-9.35	AVG	
11		5.3899	39.73	11.77	51.50	60.00	-8.50	QP	
12		5.3899	28.53	11.77	40.30	50.00	-9.70	AVG	

*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen


5.4 20 dB Bandwidth

5.4.1 Definition

Intentional radiators operating under the alternative provisions to the general emission limits, as Contained in §§15.217 through 15.257 and in sub-part E of this part, must be designed to ensure that the 20 dB Bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific Rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


5.4.2 Block Diagram Of Test Setup

The EUT is powered by the Battery, is coupled to the Spectrum Analyzer (SA) through the Attenuator/DC Block. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power. The RF load attached to the EUT antenna terminal is 50Ohm.




5.4.3 Test Result


GFSK Modulation test result:



CH Low




CH MID




CH High


II / 4-DQPSK Modulation test result:



CH Low




CH MID




CH High


8DPSK Modulation test result:



CH Low



CH MID



CH High

APPENDIX 1
PHOTOGRAPHS OF TEST SETUP



CONDUCTED TEST SETUP



CE TEST SETUP



RE TEST SETUP



-----END OF REPORT-----