



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Bird Technologies

Model: DDRXXX

Description: 33dBm Cellular Remotes

Serial Number: N/A

FCC ID: V5FDDR003

To

FCC Part 1.1310

Date of Issue: October 17, 2016

On the behalf of the applicant:

**Bird Technologies
30303 Aurora Road
Cleveland, OH 44139**

Attention of:

**Tim O'Brien, Technical Product Manager
Ph: (440)519-2194
Email: tobrien@bird-technologies.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1620031**

**Greg Corbin
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	October 17, 2016	Greg Corbin	Original Document

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: DDRXXX

Description: 33dBm Cellular Remotes

Additional Information: N/A

EUT Operation during Tests

The EUT is classified as a Part 20 CMRS industrial DAS signal booster

Note: the UL is directly connected to a base station and therefore does not radiate.

The EUT was setup in an end to end configuration. Signals were injected into the head end unit and measured from the remote unit.

The signal booster uses the following frequency bands.

Frequency Band (MHz)	
Downlink	728-757

Per the user manual, the 700 MHz band uses an antenna with a maximum gain of 5.5 dBi.

The lowest frequency and highest measured power are used to calculate the power density.



Source Based Time Averaged Power Calculation

Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
728	2059	100	2059



MPE Evaluation

This is a Fixed device used in an **Uncontrolled** Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	728
Power, Conducted, mW (P)	2059
Antenna Gain Isotropic	5.5 dBi
Antenna Gain Numeric (G)	3.55
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) = 1.45 mw/cm ²
Limit =(from above table) = 0.485 mw/cm ²

EUT does not meet the power density requirements at 20 cm, so the minimum safe distance was calculated below.

$R = \sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
34.6	2059	3.55	0.485

The minimum safe distance is 34.6 cm

END OF TEST REPORT