

## FCC PART 15.225


### TEST REPORT

For

### Advanced Card Systems Limited

Units 4108 - 4110, 41st Floor, Manhattan Place, 23 Wang Tai Road, Kowloon Bay, Hong Kong

**FCC ID: V5MACR330**

<b>Report Type:</b> Original Report	<b>Product Type:</b> ACR330 Validator with QR Code Scanner
<b>Report Number:</b> RSZ180829001-00D	
<b>Report Date:</b> 2018-11-14	
Rocky Kang 	
<b>Reviewed By:</b> RF Engineer	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “\*”.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
MEASUREMENT UNCERTAINTY .....	3
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
JUSTIFICATION .....	5
EUT EXERCISE SOFTWARE .....	5
EQUIPMENT MODIFICATIONS .....	5
LOCAL SUPPORT EQUIPMENT .....	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP .....	5
<b>SUMMARY OF TEST RESULTS .....</b>	<b>6</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>7</b>
<b>FCC§15.203 - ANTENNA REQUIREMENT.....</b>	<b>8</b>
APPLICABLE STANDARD .....	8
ANTENNA CONNECTED CONSTRUCTION .....	8
<b>FCC§15.225, §15.205 &amp; §15.209 - RADIATED EMISSIONS TEST .....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
EUT SETUP .....	9
EMI TEST RECEIVER SETUP.....	9
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	10
TEST RESULTS SUMMARY .....	10
TEST DATA .....	10
<b>FCC§15.225(E) - FREQUENCY STABILITY.....</b>	<b>14</b>
APPLICABLE STANDARD .....	14
TEST PROCEDURE .....	14
TEST DATA .....	14
<b>FCC§15.215(C) - 20DB EMISSION BANDWIDTH .....</b>	<b>15</b>
REQUIREMENT .....	15
TEST PROCEDURE .....	15
TEST DATA .....	15

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

The *Advanced Card Systems Limited's* product, model number: *ACR330 (FCC ID: V5MACR330)* or the "EUT" in this report was an *ACR330 Validator with QR Code Scanner*, which was measured approximately: 91 mm (L) \* 135 mm (W) \* 243 mm (H), rated with input voltage: DC9V-36V.

*\*All measurement and test data in this report was gathered from production sample serial number: 180829001. (Assigned by BACL ,Shenzhen). The EUT supplied by the applicant was received on 2018-08-29.*

### Objective

This Type approval report is prepared on behalf of *Advanced Card Systems Limited* in accordance with Part 2- Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules, section 15.203, 15.205, 15.209 and 15.225.

### Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS & DTS submissions with FCC ID: V5MACR330.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	±5%
AC Power Lines Conducted Emissions	±1.95dB
Emissions, Radiated Below 1GHz	±4.75dB
Temperature	±3°C
Humidity	±6%
Supply voltages	±0.4%

### **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

## SYSTEM TEST CONFIGURATION

### Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

### EUT Exercise Software

No Exercise Software was used.

### Equipment Modifications

No modification on the EUT.


### Local Support Equipment

Manufacturer	Description	Model	Serial Number
N/A	N/A	N/A	N/A

### External I/O Cable

Cable Description	Length (m)	From Port	To
N/A	N/A	N/A	N/A

### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emission	Not Applicable
§15.225 §15.209 §15.205	Radiated Emission Test	Compliance
§15.225(e)	Frequency Stability	Compliance
§15.215(c)	20dB Emission Bandwidth	Compliance

Not Applicable: EUT power by battery and used on vehicle

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447E	1937A01046	2018-05-17	2018-11-19
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-08-01	2019-02-01
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
ETS	Passive Loop Antenna	6512	00029604	2018-03-07	2021-03-06
Sonoma instrument	Amplifier	310N	186238	2018-05-12	2018-11-12
Ducommun technologies	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-08-01	2019-02-01
Ducommun technologies	RF Cable	104PEA	218124002	2018-05-21	2018-11-19
Fluke	Digital Multimeter	287	19000011	2018-04-12	2019-04-12
Long Wei	DC Power Supply	TPR-6420D	398363	NCR	NCR
ESPEC	Temperature & Humidity Chamber	EL-10KA	9107726	2017-12-21	2018-12-21

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

---

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **Antenna Connected Construction**

The EUT has an internal antenna arrangement, which was permanently attached, fulfill the requirement of this section. Please refer to EUT photos for details.




## **FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST**

### **Applicable Standard**

As per FCC Part 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

### **EUT Setup**



Note: Antenna is set up at 1m during test for below 30MHz.

The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part Subpart C limits.

### **EMI Test Receiver Setup**

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	300 Hz	1 kHz	/	QP
150 kHz – 30 MHz	10 kHz	30 kHz	/	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	/	QP

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\begin{aligned}\text{Corrected Factor} &= \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain} \\ \text{Corrected Amplitude} &= \text{Meter Reading} + \text{Corrected Factor}\end{aligned}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.209.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

### Test Data

#### Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Tracy Hu on 2018-09-06.

Test mode: Transmitting

1) Spurious Emissions (9 kHz~30 MHz):


Indicated		Table Angle Degree	Antenna Height (m)	Detector	Correction Factor			FCC part 15.225	
Freq. (MHz)	Corrected Amplitude (dBμV/m) @3m				Ant. Factor (dB)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Limit (dBμV/m) @3m	Result
0.009	64.59	0	1	PK	20.0	0.2	30.2	128.25	Pass
0.15	74.55	0	1	PK	20.8	0.3	30.2	104.08	Pass

9 kHz~150 kHz




EUT  
Date: 6.SEP.2018    21:44:18

150 kHz~30 MHz



EUT  
Date: 6.SEP.2018    16:40:01

## 2) Spurious Emissions (30 MHz~1GHz):



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
199.875000	29.23	153.0	H	239.0	-13.8	43.50	14.27
207.768875	30.09	135.0	H	262.0	-13.9	43.50	13.41
359.640125	35.57	242.0	H	26.0	-10.7	46.00	10.43
528.594000	35.94	351.0	H	21.0	-6.2	46.00	10.06
624.073750	35.11	117.0	H	0.0	-2.5	46.00	10.89
912.396750	35.94	284.0	H	134.0	5.6	46.00	10.06

**Note:**

- 1) Correction Factor = Antenna factor(Rx) + Cable Loss – Amplifier factor
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

## 3) Inband:

Indicated			Table Angle Degree	Antenna Height (m)	Detector	Correction Factor			FCC part 15.225	
Frequency Range (MHz)	Mark Point (MHz)	Corrected Amplitude (dBμV/m) @3m				Ant. Factor (dB)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Limit	Result
									(dBμV/m) @3m	
13.110-13.410	13.396	72.31	0	1.6	QP	20.8	0.2	30.2	80.5	Pass
13.410-13.553	13.543	74.26	0	1.3	QP	20.9	0.2	30.2	90.5	Pass
13.553-13.567	13.554	74.87	0	1.1	QP	20.9	0.2	30.2	124	Pass
13.567-13.710	13.562	73.42	0	1.0	QP	21.1	0.2	30.2	90.5	Pass
13.710-14.010	13.878	71.67	0	1.2	QP	21.2	0.2	30.2	80.5	Pass

## FCC§15.225(e) - FREQUENCY STABILITY

### Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to PC, then to an external AC power supply and inductive antenna was connected to a Spectrum Analyzer. The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable AC power supply Source. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the end point. The output frequency was recorded for each voltage.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Tracy Hu on 2018-09-03.

Test Mode: Transmitting

Test Result: Pass

Voltage Supply (V <sub>DC</sub> )	Temperature (°C)	Measured Frequency (MHz)	Frequency Error	Part 15.225 Limit
12	-20	13.559460	-0.00398%	$\pm 0.01\%$
	-10	13.559647	-0.00260%	$\pm 0.01\%$
	0	13.559666	-0.00246%	$\pm 0.01\%$
	10	13.559732	-0.00198%	$\pm 0.01\%$
	20	13.559752	-0.00183%	$\pm 0.01\%$
	30	13.559828	-0.00127%	$\pm 0.01\%$
	40	13.559846	-0.00113%	$\pm 0.01\%$
	50	13.559999	-0.00001%	$\pm 0.01\%$
9.0	20	13.560144	0.00107%	$\pm 0.01\%$
36.0	20	13.559964	-0.00026%	$\pm 0.01\%$

**FCC§15.215(c) - 20dB EMISSION BANDWIDTH****Requirement**

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the table of the chamber, Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Tracy Hu on 2018-09-06.*

*Test Mode: Transmitting*

Test Result: Pass

20 dB Emission Bandwidth



EUT  
Date: 6.SEP.2018 16:30:26

\*\*\*\*\* END OF REPORT \*\*\*\*\*