

# FCC TEST REPORT

## (Part 15, Subpart C)



Applicant:	PAX Technology Limited
Address:	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

Manufacturer or Supplier	PAX Computer Technology (Shenzhen) Co., Ltd.
Address	4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.
Product	Mobile Payment Terminal
Brand Name	PAX
Model Name	S920
FCC ID	V5PS920LTE
Date of tests	Jul. 25, 2018 ~ Aug. 16, 2018

The tests have been carried out according to the requirements of the following standard:

- ☒ **FCC Part 15, Subpart C, Section 15.247**
- ☒ **ANSI C63.10-2013**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Roger Li Engineer / Mobile Department	Approved by Sam Tung Manager / Mobile Department
	
Date: Aug. 17, 2018	Date: Aug. 17, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>4</b>
<b>1 SUMMARY OF TEST RESULTS.....</b>	<b>5</b>
1.1 MEASUREMENT UNCERTAINTY .....	5
<b>2 GENERAL INFORMATION .....</b>	<b>6</b>
2.1 GENERAL DESCRIPTION OF EUT .....	6
2.2 DESCRIPTION OF TEST MODES .....	8
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	9
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
2.3 DUTY CYCLE OF TEST SIGNAL .....	12
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	13
2.5 DESCRIPTION OF SUPPORT UNITS .....	13
<b>3 TEST TYPES AND RESULTS.....</b>	<b>14</b>
3.1 CONDUCTED EMISSION MEASUREMENT .....	14
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	14
3.1.2 TEST INSTRUMENTS.....	14
3.1.3 TEST PROCEDURES .....	15
3.1.4 DEVIATION FROM TEST STANDARD .....	15
3.1.5 TEST SETUP .....	16
3.1.6 EUT OPERATING CONDITIONS .....	16
3.1.7 TEST RESULTS .....	17
3.2 RADIATED EMISSION MEASUREMENT .....	19
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	19
3.2.2 TEST INSTRUMENTS.....	20
3.2.3 TEST PROCEDURES .....	21
3.2.4 DEVIATION FROM TEST STANDARD .....	21
3.2.5 TEST SETUP .....	22
3.2.6 EUT OPERATING CONDITIONS .....	23
3.2.7 TEST RESULTS .....	24
3.3 6 DB BANDWIDTH MEASUREMENT .....	40
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT .....	40
3.3.2 TEST INSTRUMENTS.....	40
3.3.3 TEST PROCEDURE.....	40



3.3.4	DEVIATION FROM TEST STANDARD .....	41
3.3.5	TEST SETUP .....	41
3.3.6	EUT OPERATING CONDITIONS .....	41
3.3.7	TEST RESULTS .....	42
3.4	CONDUCTED OUTPUT POWER.....	46
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....	46
3.4.2	TEST SETUP .....	46
3.4.3	TEST INSTRUMENTS.....	46
3.4.4	TEST PROCEDURES .....	46
3.4.5	DEVIATION FROM TEST STANDARD .....	46
3.4.6	EUT OPERATING CONDITIONS .....	46
3.4.7	TEST RESULTS .....	47
3.4.7.1	MAXIMUM PEAK OUTPUT POWER .....	47
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	48
3.5	POWER SPECTRAL DENSITY MEASUREMENT .....	49
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	49
3.5.2	TEST SETUP .....	49
3.5.3	TEST INSTRUMENTS.....	49
3.5.4	TEST PROCEDURE.....	49
3.5.5	DEVIATION FROM TEST STANDARD .....	49
3.5.6	EUT OPERATING CONDITION .....	49
3.5.7	TEST RESULTS .....	50
3.6	OUT OF BAND EMISSION MEASUREMENT .....	54
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....	54
3.6.2	TEST SETUP .....	54
3.6.3	TEST INSTRUMENTS.....	54
3.6.4	TEST PROCEDURE.....	54
3.6.5	DEVIATION FROM TEST STANDARD .....	55
3.6.6	EUT OPERATING CONDITION .....	55
3.6.7	TEST RESULTS .....	55
4	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	64
5	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	65



**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF180724W016-2	Original release	Aug. 17, 2018



## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -10.49dB at 0.480000MHz.
15.205 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -6.08dB at 2390MHz.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

### 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in ETSI TR 100 028-2001:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.68dB
	30MHz ~ 1GMHz	3.26dB
	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Mobile Payment Terminal
<b>BRAND NAME</b>	PAX
<b>MODEL NAME</b>	S920
<b>POWER SUPPLY</b>	5.0Vdc (adapter or host equipment) 3.6Vdc (Li-ion, battery)
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM, DTS
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM BT-LE(GFSK) for DTS
<b>TRANSMISSION RATE</b>	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n: up to 65 Mbps BT_LE: 1 Mbps
<b>OPERATING FREQUENCY</b>	2412-2462MHz for 11b/g/n(HT20) 2402-2480MHz for BT-LE(GFSK)
<b>MAX. OUTPUT POWER</b>	WLAN: 164.816mW (Maximum) BT-LE: 4.276mW (Maximum)
<b>ANTENNA TYPE</b>	FPC Antenna with 0.6dBi gain
<b>HW VERSION</b>	S920-xxx-xxx-xxxx
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	N/A

**NOTE:**

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

<b>MODULATION MODE</b>	<b>TX/RX FUNCTION</b>
<b>802.11b</b>	1TX /1RX
<b>802.11g</b>	1TX /1RX
<b>802.11n (20MHz)</b>	1TX /1RX
<b>BT_LE</b>	1TX /1RX



3. The EUT was powered by the following adapter:

ADAPTER	
<b>BRAND:</b>	Shenzhen Sorghum red Electronics Technology Co., Ltd
<b>MODEL:</b>	GLH50D1000HW
<b>INPUT:</b>	AC 100-240V, 400mA
<b>OUTPUT:</b>	DC 5V, 1000mA

4. There were Sample A and B for this project, one carries a GPS module and the other removes it. The difference is as below, the sample A was worst and record in report.

SAMPLE	SW VERSION	GPS
<b>A</b>	V0.0.0.1	With GPS
<b>B</b>	V0.0.0.2	Without GPS

5. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



## 2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480





## 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

## 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

**RE≥1G**: Radiated Emission above 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**NOTE**: No need to concern of Conducted Emission due to the EUT is powered by battery.

**RADIATED EMISSION TEST (BELOW 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.1n HT20	1 to 11	11	OFDM	BPSK	6.5
BT-LE	0 to 39	39	DTS	GFSK	1

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
BT-LE	0 to 39	0,19, 39	DTS	GFSK	1

**POWER LINE CONDUCTED EMISSION TEST:**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n HT20	1 to 11	11	OFDM	BPSK	6.5

**BANDEDGE MEASUREMENT:**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
BT-LE	0 to 39	0, 39	DTS	GFSK	1

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5V from adaptor	Rose Ma
RE≥1G	22deg. C, 54%RH	DC 5V from adaptor	Rose Ma
PLC	24deg. C, 55%RH	DC 5V from adaptor	John
APCM	25deg. C, 60%RH	3.6Vdc from battery	Bert Ma



**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2


## 2.3 Duty Cycle of Test Signal

### WIFI 2.4GHz

**802.11b:** Duty cycle =  $12.45/12.65 = 0.984 > 98\%$ , Duty factor is not required;

**802.11g:** Duty cycle =  $2.061/2.365 = 0.871 < 98\%$ , Duty factor =  $10 * \log(1/0.871) = 0.598$

**802.11n (HT20):** Duty cycle =  $1.915/2.223 = 0.861 < 98\%$ , Duty factor =  $10 * \log(1/0.861) = 0.648$





## 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**KDB 558074 D01 DTS Meas Guidance v04**

**ANSI C63.10-2013**

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (SDoc). The test report has been issued separately.

## 2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m



### 3 TEST TYPES AND RESULTS

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

##### 3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Mar. 15,18	Mar. 14,19
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 18,17	Sep. 17,18

**NOTE:**

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



### 3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



### 3.1.5 TEST SETUP



**Note: 1.Support units were connected to second LISN.**

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.





**BUREAU  
VERITAS**

**Test Report No.: RF180724W016-2**

### 3.1.7 TEST RESULTS


#### CONDUCTED WORST-CASE DATA:

<b>Frequency Range</b>	150KHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>Input Power</b>	120Vac, 60Hz	<b>Environmental Conditions</b>	22deg. C, 43RH
<b>Tested By</b>	John	<b>TEST DATE</b>	2018/08/03

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154000	---	26.65	55.78	-29.13	L1	ON	9.6
0.154000	46.68	---	65.78	-19.10	L1	ON	9.6
0.236000	---	29.48	52.24	-22.76	L1	ON	9.7
0.236000	42.69	---	62.24	-19.55	L1	ON	9.7
0.504000	---	24.52	46.00	-21.48	L1	ON	9.7
0.504000	41.51	---	56.00	-14.49	L1	ON	9.7
0.832000	---	26.67	46.00	-19.33	L1	ON	9.7
0.832000	37.66	---	56.00	-18.34	L1	ON	9.7
1.304000	---	26.61	46.00	-19.39	L1	ON	9.7
1.304000	36.79	---	56.00	-19.21	L1	ON	9.7
12.396000	---	30.16	50.00	-19.84	L1	ON	9.9
12.396000	37.75	---	60.00	-22.25	L1	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





**BUREAU  
VERITAS**


**Test Report No.: RF180724W016-2**

<b>Frequency Range</b>	150KHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>Input Power</b>	120Vac, 60Hz	<b>Environmental Conditions</b>	22deg. C, 43RH
<b>Tested By</b>	John	<b>TEST DATE</b>	2018/08/03

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154000	---	27.07	55.78	-28.71	N	ON	9.9
0.154000	47.65	---	65.78	-18.13	N	ON	9.9
0.412000	---	26.23	47.61	-21.38	N	ON	10.1
0.412000	43.59	---	57.61	-14.02	N	ON	10.1
0.480000	---	30.71	46.34	-15.63	N	ON	10.1
<b>0.480000</b>	<b>45.85</b>	---	<b>56.34</b>	<b>-10.49</b>	<b>N</b>	<b>ON</b>	<b>10.1</b>
1.032000	---	27.68	46.00	-18.32	N	ON	9.9
1.032000	42.39	---	56.00	-13.61	N	ON	9.9
1.280000	---	28.17	46.00	-17.83	N	ON	9.9
1.280000	39.47	---	56.00	-16.53	N	ON	9.9
2.904000	---	26.08	46.00	-19.92	N	ON	9.8
2.904000	35.70	---	56.00	-20.30	N	ON	9.8

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Apr. 21,18	Apr. 20,19
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
Loop antenna	Daze	ZN30900A	0708	Nov. 20,17	Nov. 19,18
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Dec. 16,16	Dec. 15,18
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 09,18	Jul. 08,19
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 16,18	Mar. 15,19
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 09,18	Jul. 08,19
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 09,18	Jul. 08,19
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 09,18	Jul. 08,19

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 3m Chamber.
  3. The FCC Site Registration No. is 525120.



### 3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation




### 3.2.5 TEST SETUP

#### < Frequency Range below 30MHz >




#### < Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



## 3.2.7 TEST RESULTS

## BELOW 1GHz WORST-CASE DATA:

**9 KHz – 30 MHz data:** the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

**30 MHz – 1GHz data:**


**802.11n (20MHz)**

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
48.59	26.63	55.95	40	-13.37	7.02	1.06	37.4	200	0	QP
114.79	28.16	55.99	43.5	-15.34	7.48	1.64	36.95	200	0	QP
172.38	31.08	55.77	43.5	-12.42	10.01	2.01	36.71	200	0	QP
213.28	26.04	49.62	43.5	-17.46	10.71	2.24	36.53	200	0	QP
273	32.13	53.39	46	-13.87	12.68	2.57	36.51	200	0	QP
372.83	34.11	51.68	46	-11.89	16.06	3.03	36.66	200	0	QP

## REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.








<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
33.31	26.35	48.21	40	-13.65	14.82	0.85	37.53	100	0	QP
105	30.08	57.67	43.5	-13.42	7.82	1.57	36.98	100	0	QP
146.43	26.83	53.01	43.5	-16.67	8.77	1.86	36.81	100	0	QP
211.87	28.69	52.34	43.5	-14.81	10.65	2.24	36.54	100	0	QP
249.7	31.3	52.98	46	-14.7	12.39	2.45	36.52	100	0	QP
383.38	33.11	50.21	46	-12.89	16.5	3.08	36.68	100	0	QP

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.





## ABOVE 1GHz WORST-CASE DATA:

**Note:** For higher frequency, the emission is too low to be detected.

## 802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	45.27	53.44	54	-8.73	32.87	4.88	45.92	100	140	Average
2390	57.94	66.11	74	-16.06	32.87	4.88	45.92	100	140	Peak
2412	105.07	113.19			32.89	4.9	45.91	100	140	Average
2412	107.84	115.96			32.89	4.9	45.91	100	140	Peak
2483.5	43.25	51.18	54	-10.75	32.98	4.98	45.89	100	140	Average
2483.5	55.52	63.45	74	-18.48	32.98	4.98	45.89	100	140	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.59	52.76	54	-9.41	32.87	4.88	45.92	100	270	Average
2390	56.88	65.05	74	-17.12	32.87	4.88	45.92	100	270	Peak
2412	100.89	109.01			32.89	4.9	45.91	100	270	Average
2412	103.11	111.23			32.89	4.9	45.91	100	270	Peak
2483.5	42.8	50.73	54	-11.2	32.98	4.98	45.89	100	270	Average
2483.5	53.73	61.66	74	-20.27	32.98	4.98	45.89	100	270	Peak

## REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	40.94	49.69	54	-13.06	32.29	4.88	45.92	125	16	Average
2390	54.99	63.74	74	-19.01	32.29	4.88	45.92	125	16	Peak
2437	94.79	103.43			32.34	4.93	45.91	125	16	Average
2437	100	108.64			32.34	4.93	45.91	125	16	Peak
2483.5	39.84	48.37	54	-14.16	32.38	4.98	45.89	125	16	Average
2483.5	53.12	61.65	74	-20.88	32.38	4.98	45.89	125	16	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.26	52.01	54	-10.74	32.29	4.88	45.92	140	165	Average
2390	55.97	64.72	74	-18.03	32.29	4.88	45.92	140	165	Peak
2437	95.86	104.5			32.34	4.93	45.91	140	165	Average
2437	97.72	106.36			32.34	4.93	45.91	140	165	Peak
2483.5	43.6	52.13	54	-10.4	32.38	4.98	45.89	140	165	Average
2483.5	55.63	64.16	74	-18.37	32.38	4.98	45.89	140	165	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU  
VERITAS**

**Test Report No.: RF180724W016-2**

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.36	50.11	54	-12.64	32.29	4.88	45.92	172	70	Average
2390	53.61	62.36	74	-20.39	32.29	4.88	45.92	172	70	Peak
2462	93.17	101.75			32.36	4.96	45.9	172	70	Average
2462	103.37	111.95			32.36	4.96	45.9	172	70	Peak
2483.5	44.51	53.04	54	-9.49	32.38	4.98	45.89	172	70	Average
2483.5	59.04	67.57	74	-14.96	32.38	4.98	45.89	172	70	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	38.49	47.24	54	-15.51	32.29	4.88	45.92	140	160	Average
2390	54.19	62.94	74	-19.81	32.29	4.88	45.92	140	160	Peak
2462	92.75	101.33			32.36	4.96	45.9	140	160	Average
2462	102.16	110.74			32.36	4.96	45.9	140	160	Peak
2483.5	43.38	51.91	54	-10.62	32.38	4.98	45.89	140	160	Average
2483.5	59.51	68.04	74	-14.49	32.38	4.98	45.89	140	160	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2

### 802.11g

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.09	54.26	54	-7.91	32.87	4.88	45.92	100	150	Average
2390	59.38	67.55	74	-14.62	32.87	4.88	45.92	100	150	Peak
2412	99.94	108.06			32.89	4.9	45.91	100	150	Average
2412	108.25	116.37			32.89	4.9	45.91	100	150	Peak
2483.5	41.39	49.32	54	-12.61	32.98	4.98	45.89	100	150	Average
2483.5	56.52	64.45	74	-17.48	32.98	4.98	45.89	100	150	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.44	52.61	54	-9.56	32.87	4.88	45.92	142	341	Average
2390	56.86	65.03	74	-17.14	32.87	4.88	45.92	142	341	Peak
2412	93.23	101.35			32.89	4.9	45.91	142	341	Average
2412	100.95	109.07			32.89	4.9	45.91	142	341	Peak
2483.5	41.71	49.64	54	-12.29	32.98	4.98	45.89	142	341	Average
2483.5	52.28	60.21	74	-21.72	32.98	4.98	45.89	142	341	Peak

#### REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.49	52.24	54	-10.51	32.29	4.88	45.92	125	17	Average
2390	61.05	69.8	74	-12.95	32.29	4.88	45.92	125	17	Peak
2437	92.97	101.61			32.34	4.93	45.91	125	17	Average
2437	104.81	113.45			32.34	4.93	45.91	125	17	Peak
2483.5	42.45	50.98	54	-11.55	32.38	4.98	45.89	125	17	Average
2483.5	59.22	67.75	74	-14.78	32.38	4.98	45.89	125	17	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.68	53.43	54	-9.32	32.29	4.88	45.92	140	168	Average
2390	61.76	70.51	74	-12.24	32.29	4.88	45.92	140	168	Peak
2437	97.15	105.79			32.34	4.93	45.91	140	168	Average
2437	106.64	115.28			32.34	4.93	45.91	140	168	Peak
2483.5	42.79	51.32	54	-11.21	32.38	4.98	45.89	140	168	Average
2483.5	59.96	68.49	74	-14.04	32.38	4.98	45.89	140	168	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.38	50.13	54	-12.62	32.29	4.88	45.92	124	147	Average
2390	57.33	66.08	74	-16.67	32.29	4.88	45.92	124	147	Peak
2462	94.04	102.62			32.36	4.96	45.9	124	147	Average
2462	104.79	113.37			32.36	4.96	45.9	124	147	Peak
2483.5	44.49	53.02	54	-9.51	32.38	4.98	45.89	124	147	Average
2483.5	61.26	69.79	74	-12.74	32.38	4.98	45.89	124	147	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	39.4	48.15	54	-14.6	32.29	4.88	45.92	100	98	Average
2390	61.57	70.32	74	-12.43	32.29	4.88	45.92	100	98	Peak
2462	90.32	98.9			32.36	4.96	45.9	100	98	Average
2462	103.28	111.86			32.36	4.96	45.9	100	98	Peak
2483.5	45.93	54.46	54	-8.07	32.38	4.98	45.89	100	98	Average
2483.5	62.95	71.48	74	-11.05	32.38	4.98	45.89	100	98	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2

**802.11n (20MHz)**

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	47.92	56.09	54	-6.08	32.87	4.88	45.92	100	140	Average
2390	55.12	63.29	74	-18.88	32.87	4.88	45.92	100	140	Peak
2412	98.74	106.86			32.89	4.9	45.91	100	140	Average
2412	107.81	115.93			32.89	4.9	45.91	100	140	Peak
2483.5	43.85	51.78	54	-10.15	32.98	4.98	45.89	100	140	Average
2483.5	54.52	62.45	74	-19.48	32.98	4.98	45.89	100	140	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.09	52.26	54	-9.91	32.87	4.88	45.92	158	340	Average
2390	56.19	64.36	74	-17.81	32.87	4.88	45.92	158	340	Peak
2412	94.07	102.19			32.89	4.9	45.91	158	340	Average
2412	102.4	110.52			32.89	4.9	45.91	158	340	Peak
2483.5	41.79	49.72	54	-12.21	32.98	4.98	45.89	158	340	Average
2483.5	53.88	61.81	74	-20.12	32.98	4.98	45.89	158	340	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.





**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.44	52.19	54	-10.56	32.29	4.88	45.92	125	10	Average
2390	62.74	71.49	74	-11.26	32.29	4.88	45.92	125	10	Peak
2437	90.4	99.04			32.34	4.93	45.91	125	10	Average
2437	102.84	111.48			32.34	4.93	45.91	125	10	Peak
2483.5	44.62	53.15	54	-9.38	32.38	4.98	45.89	125	10	Average
2483.5	61.41	69.94	74	-12.59	32.38	4.98	45.89	125	10	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.77	52.52	54	-10.23	32.29	4.88	45.92	135	168	Average
2390	59.86	68.61	74	-14.14	32.29	4.88	45.92	135	168	Peak
2437	90.68	99.32			32.34	4.93	45.91	135	168	Average
2437	101.69	110.33			32.34	4.93	45.91	135	168	Peak
2483.5	43.45	51.98	54	-10.55	32.38	4.98	45.89	135	168	Average
2483.5	57.83	66.36	74	-16.17	32.38	4.98	45.89	135	168	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF180724W016-2

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.24	51.99	54	-10.76	32.29	4.88	45.92	100	98	Average
2390	57.66	66.41	74	-16.34	32.29	4.88	45.92	100	98	Peak
2462	98.18	106.76			32.36	4.96	45.9	100	98	Average
2462	107.08	115.66			32.36	4.96	45.9	100	98	Peak
2483.5	46.46	54.99	54	-7.54	32.38	4.98	45.89	100	98	Average
2483.5	62.34	70.87	74	-11.66	32.38	4.98	45.89	100	98	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.49	50.24	54	-12.51	32.29	4.88	45.92	100	98	Average
2390	56.03	64.78	74	-17.97	32.29	4.88	45.92	100	98	Peak
2462	92.96	101.54			32.36	4.96	45.9	100	98	Average
2462	102.84	111.42			32.36	4.96	45.9	100	98	Peak
2483.5	44.33	52.86	54	-9.67	32.38	4.98	45.89	100	98	Average
2483.5	63.01	71.54	74	-10.99	32.38	4.98	45.89	100	98	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.

**BELOW 1GHz WORST-CASE DATA:**

**9 KHz – 30 MHz data:** the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

**30 MHz – 1GHz data:**


**BT-LE (GFSK)**

<b>CHANNEL</b>	TX Channel 39	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
141.28	28.36	55.48	43.5	-15.14	8.15	1.56	36.83	100	360	QP
249.39	33.57	55.68	46	-12.43	12.37	2.04	36.52	100	360	QP
394.9	30.65	47.77	46	-15.35	16.99	2.6	36.71	100	360	QP
452.01	31.15	47.36	46	-14.85	17.82	2.81	36.84	100	360	QP
659.23	30.2	42.18	46	-15.8	21.96	3.38	37.32	100	360	QP
842.92	33.08	43.75	46	-12.92	23	3.95	37.62	100	360	QP

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





**BUREAU  
VERITAS**


Test Report No.: RF180724W016-2

<b>CHANNEL</b>	TX Channel 39	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
43.25	20.86	48.32	40	-19.14	9	0.99	37.45	100	0	QP
104.32	23.78	51.34	43.5	-19.72	7.85	1.57	36.98	100	0	QP
156.28	27.46	52.48	43.5	-16.04	9.83	1.91	36.76	100	0	QP
224.3	30.53	53.53	46	-15.47	11.22	2.31	36.53	100	0	QP
250	35.2	56.87	46	-10.8	12.4	2.45	36.52	100	0	QP
359	31.83	50.01	46	-14.17	15.48	2.97	36.63	100	0	QP

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





**BUREAU  
VERITAS**

**Test Report No.: RF180724W016-2**

### ABOVE 1GHz TEST DATA:

**Note:** For higher frequency, the emission is too low to be detected.

### BT-LE (GFSK)

<b>CHANNEL</b>	TX Channel 0	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	42.1	50.85	54	-11.9	32.29	4.88	45.92	100	60	Average
2390	52.47	61.22	74	-21.53	32.29	4.88	45.92	100	60	Peak
2402	98.99	107.72			32.3	4.89	45.92	100	60	Average
2402	104.54	113.27			32.3	4.89	45.92	100	60	Peak
2483.5	40.26	48.79	54	-13.74	32.38	4.98	45.89	100	60	Average
2483.5	52.55	61.08	74	-21.45	32.38	4.98	45.89	100	60	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	42.09	50.84	54	-11.91	32.29	4.88	45.92	100	290	Average
2390	53.01	61.76	74	-20.99	32.29	4.88	45.92	100	290	Peak
2402	94.01	102.74			32.3	4.89	45.92	100	290	Average
2402	101.02	109.75			32.3	4.89	45.92	100	290	Peak
2483.5	41.28	49.81	54	-12.72	32.38	4.98	45.89	100	290	Average
2483.5	53.85	62.38	74	-20.15	32.38	4.98	45.89	100	290	Peak

### REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.



**BUREAU  
VERITAS**

**Test Report No.: RF180724W016-2**

<b>CHANNEL</b>	TX Channel 19	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.15	49.9	54	-12.85	32.29	4.88	45.92	100	12	Average
2390	53.83	62.58	74	-20.17	32.29	4.88	45.92	100	12	Peak
2440	94.94	103.57			32.34	4.94	45.91	100	12	Average
2440	99.48	108.11			32.34	4.94	45.91	100	12	Peak
2483.5	40.21	48.74	54	-13.79	32.38	4.98	45.89	100	12	Average
2483.5	53.41	61.94	74	-20.59	32.38	4.98	45.89	100	12	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.13	49.88	54	-12.87	32.29	4.88	45.92	100	172	Average
2390	53.12	61.87	74	-20.88	32.29	4.88	45.92	100	172	Peak
2440	100.86	109.49			32.34	4.94	45.91	100	172	Average
2440	105.32	113.95			32.34	4.94	45.91	100	172	Peak
2483.5	42.25	50.78	54	-11.75	32.38	4.98	45.89	100	172	Average
2483.5	54.18	62.71	74	-19.82	32.38	4.98	45.89	100	172	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



**BUREAU  
VERITAS**

**Test Report No.: RF180724W016-2**

<b>CHANNEL</b>	TX Channel 39	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.37	50.12	54	-12.63	32.29	4.88	45.92	100	15	Average
2390	53.48	62.23	74	-20.52	32.29	4.88	45.92	100	15	Peak
2480	99.95	108.49			32.38	4.98	45.9	100	15	Average
2480	102.02	110.56			32.38	4.98	45.9	100	15	Peak
2483.5	45.12	53.65	54	-8.88	32.38	4.98	45.89	100	15	Average
2483.5	53.75	62.28	74	-20.25	32.38	4.98	45.89	100	15	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	42.31	51.06	54	-11.69	32.29	4.88	45.92	100	170	Average
2390	53.48	62.23	74	-20.52	32.29	4.88	45.92	100	170	Peak
2480	95.04	103.58			32.38	4.98	45.9	100	170	Average
2480	103.68	112.22			32.38	4.98	45.9	100	170	Peak
2483.5	44.73	53.26	54	-9.27	32.38	4.98	45.89	100	170	Average
2483.5	54.7	63.23	74	-19.3	32.38	4.98	45.89	100	170	Peak

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



### 3.3 6 dB BANDWIDTH MEASUREMENT

#### 3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Mar. 02,18	Mar. 01,19
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Mar. 16,18	Mar. 15,19
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	Mar. 16,18	Mar. 15,19
Power Sensor	ANRITSU	MA2411B	1339352	Mar. 16,18	Mar. 15,19

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

#### 3.3.3 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.






### 3.3.4 DEVIATION FROM TEST STANDARD

No deviation.

### 3.3.5 TEST SETUP



### 3.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




BUREAU  
VERITAS

Test Report No.: RF180724W016-2

### 3.3.7 TEST RESULTS

#### 802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.57	0.5	PASS
6	2437	8.55	0.5	PASS
11	2462	9.04	0.5	PASS






BUREAU  
VERITAS

Test Report No.: RF180724W016-2

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.28	0.5	PASS
6	2437	16.05	0.5	PASS
11	2462	16.01	0.5	PASS






BUREAU  
VERITAS

Test Report No.: RF180724W016-2

### 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.54	0.5	PASS
6	2437	17.53	0.5	PASS
11	2462	17.55	0.5	PASS






BUREAU  
VERITAS

Test Report No.: RF180724W016-2

### BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.68	0.5	PASS
19	2440	0.68	0.5	PASS
39	2480	0.70	0.5	PASS






### 3.4 CONDUCTED OUTPUT POWER

#### 3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

#### 3.4.2 TEST SETUP



#### 3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

#### 3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



## 3.4.7 TEST RESULTS

## 3.4.7.1 MAXIMUM PEAK OUTPUT POWER

## 802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	17.95	62.373	1	PASS
6	2437	18.20	66.069	1	PASS
11	2462	18.07	64.121	1	PASS

## 802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	21.46	139.959	1	PASS
6	2437	22.17	<b>164.816</b>	1	PASS
11	2462	21.65	146.218	1	PASS

## 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	20.18	104.232	1	PASS
6	2437	20.56	113.763	1	PASS
11	2462	20.23	105.439	1	PASS

## BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	6.31	<b>4.276</b>	1	PASS
19	2440	5.77	3.776	1	PASS
39	2480	5.10	3.236	1	PASS



### 3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

#### 802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	15.66	N/A
6	2437	15.91	N/A
11	2462	15.87	N/A

#### 802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	14.83	N/A
6	2437	15.07	N/A
11	2462	14.90	N/A

#### 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.74	N/A
6	2437	13.81	N/A
11	2462	13.77	N/A

#### BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	6.17	N/A
19	2440	5.66	N/A
39	2480	4.98	N/A






### 3.5 POWER SPECTRAL DENSITY MEASUREMENT

#### 3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

#### 3.5.2 TEST SETUP



#### 3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW  $\geq 3 \times$  RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

#### 3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




BUREAU  
VERITAS

Test Report No.: RF180724W016-2

### 3.5.7 TEST RESULTS

#### 802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-7.35	8	PASS
6	2437	-6.39	8	PASS
11	2462	-5.62	8	PASS






BUREAU  
VERITAS

## Test Report No.: RF180724W016-2

802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-10.08	8	PASS
6	2437	-10.56	8	PASS
11	2462	-10.46	8	PASS






BUREAU  
VERITAS

Test Report No.: RF180724W016-2

802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-11.75	8	PASS
6	2437	-11.60	8	PASS
11	2462	-12.07	8	PASS






BUREAU  
VERITAS

Test Report No.: RF180724W016-2

### BT-LE (GFSK)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-3.77	8	PASS
19	2440	-4.80	8	PASS
39	2480	-6.19	8	PASS






### 3.6 OUT OF BAND EMISSION MEASUREMENT

#### 3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

#### 3.6.2 TEST SETUP



#### 3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.6.4 TEST PROCEDURE

##### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



## **MEASUREMENT PROCEDURE OOB**

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

### **3.6.5 DEVIATION FROM TEST STANDARD**

No deviation.

### **3.6.6 EUT OPERATING CONDITION**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### **3.6.7 TEST RESULTS**

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




BUREAU  
VERITAS


Test Report No.: RF180724W016-2

802.11b


### CH 1



### CH 6



### CH 11









BUREAU  
VERITAS

Test Report No.: RF180724W016-2

### CH 1 Band Edge



### CH 11 Band Edge






BUREAU  
VERITAS


Test Report No.: RF180724W016-2

802.11g


CH 1



CH 6



CH 11







BUREAU  
VERITAS

Test Report No.: RF180724W016-2

### CH 1 Band Edge



### CH 11 Band Edge







BUREAU  
VERITAS



Test Report No.: RF180724W016-2

## 802.11n (20MHz)



### CH 1



### CH 6




### CH 11





BUREAU  
VERITAS

Test Report No.: RF180724W016-2






BUREAU  
VERITAS


Test Report No.: RF180724W016-2

## BT-LE (GFSK)


### CH 0



### CH 19



### CH 39







BUREAU  
VERITAS

Test Report No.: RF180724W016-2

### CH 0 Band Edge



### CH 39 Band Edge





Test Report No.: RF180724W016-2

## 4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).





Test Report No.: RF180724W016-2

## 5 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---