

FCC RF Test Report

APPLICANT : PAX Technology Limited
EQUIPMENT : Smart Tablet
BRAND NAME : PAX
MODEL NAME : Aries6
FCC ID : V5PAR6LITE
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Nov. 06, 2019 and testing was completed on Nov. 29, 2019. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.



Reviewed by: Derreck Chen / Supervisor



Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Re-use of Measured Data	6
1.7 Testing Location	8
1.8 Test Software.....	8
1.9 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency and Channel	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
3 TEST RESULT	13
3.1 Radiated Band Edges and Spurious Emission Measurement	13
3.2 AC Conducted Emission Measurement.....	17
3.3 Antenna Requirements	19
4 LIST OF MEASURING EQUIPMENT	20
5 UNCERTAINTY OF EVALUATION	21
APPENDIX A. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	
APPENDIX E. REFERENCE REPORT	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR941109-01C	Rev. 01	Initial issue of report	Dec. 19, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
-	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	1
-	-	99% Bandwidth	-	Pass	1
-	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	1
-	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	1
-	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	1
		Conducted Spurious Emission		Pass	1
3.1	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.90 dB at 2483.680 MHz
3.2	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.83 dB at 9.200 MHz
3.3	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-
Remark 1: Test items are performed on original report which can be referred to Sporton report number FR941109C.					

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

PAX Technology Limited

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

1.2 Manufacturer

PAX Computer Technology (Shenzhen) Co., Ltd.

4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Tablet
Brand Name	PAX
Model Name	Aries6
FCC ID	V5PAR6LITE
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR / EDR / LE NFC
HW Version	N/A
SW Version	N/A
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Antenna Type / Gain	Internal Antenna with gain 1.50 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Re-use of Measured Data

1.6.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: Aries6, FCC ID: V5PAR6LITE) is electrically identical to the reference device (Model: Aries6, FCC ID: V5PAR6) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 484596 D01.

1.6.2 Difference Section

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., please refer to the Product Equality Declaration.

The re-used RF data includes the following bands provided in Appendix E (Sporton RF Report No. FR941109C for the reference device Model: Aries6, FCC ID: V5PAR6).

1.6.3 Reference detail Section:

Equipment Class	Reference FCC ID	Folder Test	Report Title/Section
DSS (BR/EDR)	V5PAR6	Part15C(FR941109A)	All sections applicable except AC Conducted Emission and RSE
DTS (BLE)	V5PAR6	Part15C(FR941109B)	All sections applicable except AC Conducted Emission and RSE
DTS (WLAN)	V5PAR6	Part15C(FR941109C)	All sections applicable except AC Conducted Emission and RSE
DXX(NFC)	V5PAR6	Part15C(FR941109D)	All sections applicable except AC Conducted Emission and RSE

1.6.4 Spot Check Verification Data Section

In order to confirm hardware similarity of the subject device with the reference device, spot check measurements were performed on the subject device for the following test items, the test result were consistent with FCC ID: V5PAR6.

Assertions concerning the similarity of these devices are based on representations by the applicant. The applicant accepts full responsibility for the validity of the similarity claim, and for the determination that verification test data are sufficient to support it.

Test Item	Mode	V5PAR6 Worst Result	V5PAR6LITE Worst Result	Difference (dB)
Peak Conducted Power (dBm)	Bluetooth BR	9.90	7.77	-2.13
	Bluetooth LE	3.70	3.50	-0.20
	WLAN 802.11b	16.10	15.50	-0.60
	WLAN 802.11a	13.80	13.42	-0.38
Radiated Spurious Emission (Band Edge. Harmonic) (dBuV/m)	NFC	36.99	37.13	0.14



1.7 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan Shenzhen, 518055 People's Republic of China TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a
2.	CO01-SZ	AUDIX	E3	6.120613b

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0


Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN Link (2.4G) + USB Cable(Charging from Adapter) + Earphone
Remark: For Radiated Test Cases, The tests were performance with Adapter , Earphone and USB Cable.	

2.3 Connection Diagram of Test System

For Radiation



For Conducted Emission





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-link	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8m
2.	Notebook	FCC DoC	FCC DoC	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

3 Test Result

3.1 Radiated Band Edges and Spurious Emission Measurement

3.1.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.1.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.1.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.1.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.1.7 Duty Cycle

Please refer to Appendix C.

3.1.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.2 AC Conducted Emission Measurement

3.2.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.2.4 Test Setup



3.2.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



3.3 Antenna Requirements

3.3.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.3.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.3.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Apr. 19, 2019	Nov. 29, 2019	Apr. 18, 2020	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 29, 2018	Nov. 29, 2019	May 28, 2020	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Jul. 19, 2019	Nov. 29, 2019	Jul. 18, 2020	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 07, 2019	Nov. 29, 2019	Jan. 06, 2020	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 22, 2019	Nov. 29, 2019	Jul. 21, 2020	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 18, 2019	Nov. 29, 2019	Apr. 17, 2020	Radiation (03CH02-SZ)
LF Amplifier	Burgeon	BPA-530	102211	0.01~3000Mhz	Oct. 18, 2019	Nov. 29, 2019	Oct. 17, 2020	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 18, 2019	Nov. 29, 2019	Oct. 17, 2020	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5GHz	Oct. 18, 2019	Nov. 29, 2019	Oct. 17, 2020	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010002470	N/A	NCR	Nov. 29, 2019	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Nov. 29, 2019	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Nov. 29, 2019	NCR	Radiation (03CH02-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 23, 2018	Nov. 21, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Oct. 17, 2019	Nov. 21, 2019	Oct. 16, 2020	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Dec. 23, 2018	Nov. 21, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 23, 2019	Nov. 21, 2019	Jul. 22, 2020	Conduction (CO01-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.6dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)


Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.4dB
---	-------




Appendix A. AC Conducted Emission Test Results





Test Engineer :	Dalin Liu	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
Condition: FCC 15C_QP LISN_20190719_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.48	28.67	-17.65	46.32	18.60	0.02	10.05	Average
2	0.48	37.37	-18.95	56.32	27.30	0.02	10.05	QP
3	0.58	34.38	-11.62	46.00	24.30	0.02	10.06	Average
4 *	0.58	44.78	-11.22	56.00	34.70	0.02	10.06	QP
5	1.03	21.10	-24.90	46.00	11.00	0.05	10.05	Average
6	1.03	33.10	-22.90	56.00	23.00	0.05	10.05	QP
7	9.30	34.58	-15.42	50.00	24.20	0.14	10.24	Average
8	9.30	48.48	-11.52	60.00	38.10	0.14	10.24	QP
9	10.51	32.64	-17.36	50.00	22.21	0.18	10.25	Average
10	10.51	45.44	-14.56	60.00	35.01	0.18	10.25	QP
11	12.19	32.51	-17.49	50.00	22.00	0.24	10.27	Average
12	12.19	42.31	-17.69	60.00	31.80	0.24	10.27	QP

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2347.48	46.95	-27.05	74	44.36	27.9	7.51	32.82	320	293	P	H
		2389.17	36.37	-17.63	54	33.93	27.7	7.54	32.8	320	293	A	H
	*	2412	92.52	-	-	90.09	27.67	7.54	32.78	320	293	P	H
	*	2412	90.2	-	-	87.77	27.67	7.54	32.78	320	293	A	H
		2334.04	47.9	-26.1	74	45.33	27.93	7.48	32.84	100	248	P	V
		2389.38	36.99	-17.01	54	34.55	27.7	7.54	32.8	100	248	A	V
	*	2412	97.21	-	-	94.78	27.67	7.54	32.78	100	248	P	V
	*	2412	94.99	-	-	92.56	27.67	7.54	32.78	100	248	A	V
802.11b CH 06 2437MHz		2359.42	47.83	-26.17	74	45.31	27.83	7.51	32.82	307	283	P	H
		2357.32	36.27	-17.73	54	33.75	27.83	7.51	32.82	307	283	A	H
	*	2437	93.51	-	-	91.13	27.6	7.54	32.76	307	283	P	H
	*	2437	90.74	-	-	88.36	27.6	7.54	32.76	307	283	A	H
		2498.39	47.24	-26.76	74	45.01	27.4	7.53	32.7	307	283	P	H
		2483.69	36.15	-17.85	54	33.87	27.47	7.53	32.72	307	283	A	H
		2361.8	47	-27	74	44.48	27.83	7.51	32.82	100	248	P	V
		2389.8	36.45	-17.55	54	33.99	27.7	7.54	32.78	100	248	A	V
	*	2437	97.85	-	-	95.47	27.6	7.54	32.76	100	248	P	V
	*	2437	94.12	-	-	91.74	27.6	7.54	32.76	100	248	A	V
		2491.32	46.82	-27.18	74	44.61	27.4	7.53	32.72	100	248	P	V
		2485.23	36.4	-17.6	54	34.12	27.47	7.53	32.72	100	248	A	V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 11 2462MHz	*	2462	93.82	-	-	91.49	27.53	7.54	32.74	306	284	P	H
	*	2462	91.44	-	-	89.11	27.53	7.54	32.74	306	284	A	H
		2499	47.4	-26.6	74	45.17	27.4	7.53	32.7	306	284	P	H
		2483.52	36.61	-17.39	54	34.33	27.47	7.53	32.72	306	284	A	H
	*	2462	97.92	-	-	95.59	27.53	7.54	32.74	100	247	P	V
	*	2462	95.52	-	-	93.19	27.53	7.54	32.74	100	247	A	V
		2486.92	48.72	-25.28	74	46.44	27.47	7.53	32.72	100	247	P	V
		2483.52	37.63	-16.37	54	35.35	27.47	7.53	32.72	100	247	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	38.9	-35.1	74	57.93	31.15	9.86	60.04	185	255	P	H
		4824	37.8	-36.2	74	56.83	31.15	9.86	60.04	185	255	P	V
802.11b CH 06 2437MHz		4874	39.3	-34.7	74	58.32	31.13	9.88	60.03	165	106	P	H
		7311	44.76	-29.24	74	56.99	36.4	11.88	60.51	174	100	P	H
		4874	37.66	-36.34	74	56.68	31.13	9.88	60.03	165	106	P	V
		7311	45.91	-28.09	74	58.14	36.4	11.88	60.51	174	100	P	V
802.11b CH 11 2462MHz		4924	40.22	-33.78	74	59.1	31.23	9.91	60.02	150	285	P	H
		7386	44.73	-29.27	74	56.95	36.3	12.01	60.53	155	274	P	H
		4924	37.78	-36.22	74	56.66	31.23	9.91	60.02	150	285	P	V
		7386	45.86	-28.14	74	58.08	36.3	12.01	60.53	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2387.28	53.48	-20.52	74	51.04	27.7	7.54	32.8	313	291	P	H
		2389.90	40.87	-13.13	54	38.41	27.7	7.54	32.78	313	291	A	H
	*	2412	94.94	-	-	92.51	27.67	7.54	32.78	313	291	P	H
	*	2412	87.95	-	-	85.52	27.67	7.54	32.78	313	291	A	H
		2387.07	60.6	-13.4	74	58.16	27.7	7.54	32.8	101	226	P	V
		2389.90	47.48	-6.52	54	45.02	27.7	7.54	32.78	101	226	A	V
	*	2412	101.6	-	-	99.17	27.67	7.54	32.78	101	226	P	V
	*	2412	92.91	-	-	90.48	27.67	7.54	32.78	101	226	A	V
802.11g CH 06 2437MHz		2349.48	47.33	-26.67	74	44.74	27.9	7.51	32.82	312	276	P	H
		2311.96	37.26	-16.74	54	34.67	27.97	7.48	32.86	312	276	A	H
	*	2437	94.83	-	-	92.45	27.6	7.54	32.76	312	276	P	H
	*	2437	87.7	-	-	85.32	27.6	7.54	32.76	312	276	A	H
		2497.62	47.53	-26.47	74	45.3	27.4	7.53	32.7	312	276	P	H
		2496.99	37.18	-16.82	54	34.95	27.4	7.53	32.7	312	276	A	H
		2323.02	47.55	-26.45	74	44.98	27.93	7.48	32.84	100	228	P	V
		2389.94	37.59	-16.41	54	35.13	27.7	7.54	32.78	100	228	A	V
	*	2437	101.48	-	-	99.1	27.6	7.54	32.76	100	228	P	V
	*	2437	94.07	-	-	91.69	27.6	7.54	32.76	100	228	A	V
		2491.18	48.67	-25.33	74	46.46	27.4	7.53	32.72	100	228	P	V
		2484.74	38.58	-15.42	54	36.3	27.47	7.53	32.72	100	228	A	V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 11 2462MHz	*	2462	94.91	-	-	92.58	27.53	7.54	32.74	312	276	P	H
	*	2462	87.69	-	-	85.36	27.53	7.54	32.74	312	276	A	H
		2483.52	52.59	-21.41	74	50.31	27.47	7.53	32.72	312	276	P	H
		2483.6	39.84	-14.16	54	37.56	27.47	7.53	32.72	312	276	A	H
	*	2462	102.32	-	-	99.99	27.53	7.54	32.74	100	226	P	V
	*	2462	94.94	-	-	92.61	27.53	7.54	32.74	100	226	A	V
		2483.92	61.49	-12.51	74	59.21	27.47	7.53	32.72	100	226	P	V
		2483.68	49.1	-4.9	54	46.82	27.47	7.53	32.72	100	226	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	38.67	-35.33	74	57.7	31.15	9.86	60.04	185	255	P	H
		4824	37.12	-36.88	74	56.15	31.15	9.86	60.04	185	255	P	V
802.11g CH 06 2437MHz		4874	38.64	-35.36	74	57.66	31.13	9.88	60.03	165	106	P	H
		7311	45.21	-28.79	74	57.44	36.4	11.88	60.51	174	100	P	H
		4874	38.89	-35.11	74	57.91	31.13	9.88	60.03	165	106	P	V
		7311	44.83	-29.17	74	57.06	36.4	11.88	60.51	174	100	P	V
802.11g CH 11 2462MHz		4924	37.32	-36.68	74	56.2	31.23	9.91	60.02	150	285	P	H
		7386	45.48	-28.52	74	57.7	36.3	12.01	60.53	155	274	P	H
		4924	38.26	-35.74	74	57.14	31.23	9.91	60.02	150	285	P	V
		7386	45.25	-28.75	74	57.47	36.3	12.01	60.53	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.27	50.56	-23.44	74	48.12	27.7	7.54	32.8	102	245	P	H
		2389.48	39.83	-14.17	54	37.39	27.7	7.54	32.8	102	245	A	H
	*	2412	92.49	-	-	90.06	27.67	7.54	32.78	102	245	P	H
	*	2412	85.72	-	-	83.29	27.67	7.54	32.78	102	245	A	H
		2389.69	57.23	-16.77	74	54.79	27.7	7.54	32.8	100	226	P	V
		2389.90	43.95	-10.05	54	41.49	27.7	7.54	32.78	100	226	A	V
	*	2412	99.36	-	-	96.93	27.67	7.54	32.78	100	226	P	V
	*	2412	90.94	-	-	88.51	27.67	7.54	32.78	100	226	A	V
802.11n HT20 CH 06 2437MHz		2373.28	47.18	-26.82	74	44.7	27.77	7.51	32.8	102	245	P	H
		2310.84	37.15	-16.85	54	34.56	27.97	7.48	32.86	102	245	A	H
	*	2437	92.61	-	-	90.23	27.6	7.54	32.76	102	245	P	H
	*	2437	84.63	-	-	82.25	27.6	7.54	32.76	102	245	A	H
		2495.1	46.51	-27.49	74	44.28	27.4	7.53	32.7	102	245	P	H
		2487.61	37.18	-16.82	54	34.97	27.4	7.53	32.72	102	245	A	H
		2336.88	47.58	-26.42	74	45.04	27.9	7.48	32.84	100	227	P	V
		2315.74	38.35	-15.65	54	35.74	27.97	7.48	32.84	100	227	A	V
	*	2437	100.1	-	-	97.72	27.6	7.54	32.76	100	227	P	V
	*	2437	92.23	-	-	89.85	27.6	7.54	32.76	100	227	A	V
		2494.05	47.76	-26.24	74	45.53	27.4	7.53	32.7	100	227	P	V
		2483.97	37.95	-16.05	54	35.67	27.47	7.53	32.72	100	227	A	V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 11 2462MHz	*	2462	92.46	-	-	90.13	27.53	7.54	32.74	100	92	P	H
	*	2462	85.88	-	-	83.55	27.53	7.54	32.74	100	92	A	H
		2485.92	50.58	-23.42	74	48.3	27.47	7.53	32.72	100	92	P	H
		2483.72	39.08	-14.92	54	36.8	27.47	7.53	32.72	100	92	A	H
	*	2462	99.31	-	-	96.98	27.53	7.54	32.74	100	225	P	V
	*	2462	92.77	-	-	90.44	27.53	7.54	32.74	100	225	A	V
		2484.68	59.57	-14.43	74	57.29	27.47	7.53	32.72	100	225	P	V
		2483.6	45.01	-8.99	54	42.73	27.47	7.53	32.72	100	225	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	37.93	-36.07	74	56.96	31.15	9.86	60.04	185	255	P	H
		4824	37.8	-36.2	74	56.83	31.15	9.86	60.04	185	255	P	V
802.11n HT20 CH 06 2437MHz		4874	39.05	-34.95	74	58.07	31.13	9.88	60.03	165	106	P	H
		7311	45.38	-28.62	74	57.61	36.4	11.88	60.51	174	100	P	H
		4874	39.48	-34.52	74	58.5	31.13	9.88	60.03	165	106	P	V
		7311	45.94	-28.06	74	58.17	36.4	11.88	60.51	174	100	P	V
802.11n HT20 CH 11 2462MHz		4924	38.49	-35.51	74	57.37	31.23	9.91	60.02	150	285	P	H
		7386	44.5	-29.5	74	56.72	36.3	12.01	60.53	155	274	P	H
		4924	37.76	-36.24	74	56.64	31.23	9.91	60.02	150	285	P	V
		7386	44.24	-29.76	74	56.46	36.3	12.01	60.53	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		30	22.77	-17.23	40	28.71	24.8	0.56	31.3	100	222	P	H
		107.6	21.73	-21.77	43.5	35.64	16.6	1.07	31.58	-	-	P	H
		127	21.88	-21.62	43.5	34.78	17.43	1.16	31.49	-	-	P	H
		404.42	24.55	-21.45	46	31.93	21.9	2.13	31.41	-	-	P	H
		515.97	26.8	-19.2	46	31.4	24.2	2.44	31.24	-	-	P	H
		965.08	29.51	-24.49	54	27.32	30.04	3.42	31.27	-	-	P	H
		30	30.79	-9.21	40	36.73	24.8	0.56	31.3	100	159	P	V
		61.04	24.91	-15.09	40	43.83	11.88	0.8	31.6	-	-	P	V
		130.88	22.88	-20.62	43.5	35.72	17.45	1.19	31.48	-	-	P	V
		276.38	20.24	-25.76	46	30.77	19.27	1.74	31.54	-	-	P	V
		618.79	27.12	-18.88	46	29.97	25.97	2.71	31.53	-	-	P	V
		899.12	29.24	-16.76	46	28.42	29	3.32	31.5	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	98.55	-	-	10Hz
802.11g	93.24	1.399	0.715	1kHz
802.11n HT20	92.78	1.304	0.767	1kHz

802.11b




Date: 18.NOV.2019 12:19:48

802.11g



Date: 18.NOV.2019 12:18:11

802.11n HT20



Date: 18.NOV.2019 12:16:12



Appendix E. Reference Report

Please refer to Sporton report number FR941109A which is issued separately.