

FCC RF Test Report


APPLICANT : PAX Technology Limited
EQUIPMENT : Wireless POS Terminal
BRAND NAME : PAX
MODEL NAME : D210
MARKETING NAME : D210
FCC ID : V5PD210WCDMA
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Jul. 07, 2015 and testing was completed on Aug. 25, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard.....	6
1.5 Modification of EUT	7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	8
1.8 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	12
3 TEST RESULT	13
3.1 Conducted Output Power Measurement.....	13
3.2 Peak-to-Average Ratio	15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	29
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	33
3.5 Band Edge Measurement.....	53
3.6 Conducted Spurious Emission Measurement	60
3.7 Field Strength of Spurious Radiation Measurement	79
3.8 Frequency Stability Measurement.....	99
4 LIST OF MEASURING EQUIPMENT	104
5 UNCERTAINTY OF EVALUATION	105
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG570701	Rev. 01	Initial issue of report	Sep. 01, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	RSS-132 (5.4) RSS-133 (6.4)	Conducted Output Power	N/A	PASS	-
0	§24.232(d)	RSS-132 (5.4) RSS-133(6.4)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049	RSS-GEN(6.6) RSS-133(2.3)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Conducted Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.4	§2.1053 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 19.41 dB at 1697.600 MHz
3.8	§2.1055 §22.355	RSS-GEN(6.11) RSS-132 (5.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22 Within Authorized Band	PASS	-
	§2.1055 §24.235	RSS-GEN(6.11) RSS-133 (6.3)				

1 General Description

1.1 Applicant

PAX Technology Limited

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

1.2 Manufacturer

PAX Computer Technology (Shenzhen) Co., Ltd.

4/F, No. 3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P. R. C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wireless POS Terminal
Brand Name	PAX
Model Name	D210
Marketing Name	D210
FCC ID	V5PD210WCDMA
EUT supports Radios application	GPRS/EGPRS/WCDMA/HSPA/NFC WLAN2.4GHz 802.11b/g/n HT20 Bluetooth v2.1+EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: N/A Radiation: 866174010240956 ERP/EIRP: 866174010240956
HW Version	D210-xxx-xxx-xxxx
SW Version	4.00.xx
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.60 dBm GSM1900 : 29.34 dBm WCDMA Band V : 22.62 dBm WCDMA Band II : 22.31 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.5808	0.0143 ppm	243KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.1442	0.0311 ppm	247KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0624	0.0096 ppm	4M08F9W
Part 24	GSM1900 GPRS class 8	GMSK	0.7962	0.0080 ppm	242KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.1932	0.0324 ppm	247KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.0798	0.0027 ppm	4M08F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.
Test Site Location	1F & 2F,Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595
Test Site No.	Sporton Site No.
	TH01-SZ

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC/IC Registration No.
	03CH02-SZ	566869/4086F

Note: The test site complies with ANSI C63.4 2009 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- ♦ IC RSS-132 Issue 3
- ♦ IC RSS-133 Issue 6
- ♦ IC RSS-Gen Issue 4

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Frequency range investigated for radiated emission: 30MHz to 10th harmonic.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:


Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Conducted Power Measurement Results:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	32.27	32.38	32.60	29.19	29.34	29.20
GPRS class 10	29.70	29.82	29.87	26.68	26.83	26.69
GPRS class 11	28.34	28.36	28.43	25.34	25.51	25.35
GPRS class 12	27.24	27.36	27.44	24.36	24.52	24.40
EGPRS class 8	26.75	26.88	26.91	25.40	25.50	25.43
EGPRS class 10	24.12	24.22	24.30	23.10	23.29	23.14
EGPRS class 11	22.83	22.96	23.01	21.79	21.97	21.80
EGPRS class 12	22.70	22.90	22.92	21.75	21.98	21.82

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	22.26	22.62	22.44	22.24	22.25	22.31
HSDPA Subtest-1	22.13	22.33	22.33	21.92	21.92	22.08
HSDPA Subtest-2	21.85	22.09	22.10	21.67	21.71	21.89
HSDPA Subtest-3	21.60	21.84	21.85	21.46	21.51	21.62
HSDPA Subtest-4	21.40	21.60	21.60	21.24	21.26	21.41
HSUPA Subtest-1	20.64	20.83	20.85	20.64	20.38	20.62
HSUPA Subtest-2	19.89	20.10	20.10	19.71	19.68	19.91
HSUPA Subtest-3	20.68	21.07	21.06	20.72	20.58	20.87
HSUPA Subtest-4	20.13	20.10	20.12	19.72	19.95	20.27
HSUPA Subtest-5	22.00	22.20	22.10	21.80	21.80	21.90

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTRON	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.27	32.38	32.60	26.75	26.88	26.91	22.26	22.62	22.44

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.19	29.34	29.20	25.40	25.50	25.43	22.24	22.25	22.31

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For GPRS/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
4. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Peak-to-Average Ratio (dB)	0.30	0.31	0.30	2.41	2.15	2.62	2.55	2.58	2.58


PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.28	0.28	0.28	2.81	2.55	2.60	2.52	2.52	2.49




3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)




Peak-to-Average Ratio on Channel 189 (836.4 MHz)






Peak-to-Average Ratio on Channel 251 (848.8 MHz)






Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)




Peak-to-Average Ratio on Channel 189 (836.4 MHz)






Peak-to-Average Ratio on Channel 251 (848.8 MHz)






Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)






Peak-to-Average Ratio on Channel 810 (1909.8 MHz)






Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)







Peak-to-Average Ratio on Channel 810 (1909.8 MHz)






Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	--------------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 4132 (826.4 MHz)**Peak-to-Average Ratio on Channel 4182 (836.4 MHz)**




Peak-to-Average Ratio on Channel 4233 (846.6 MHz)






Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)


Date: 10.JUL.2015 20:01:03

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)

Date: 10.JUL.2015 20:02:21



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 10.JUL.2015 20:03:15

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

3.3.4 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	824.2	26.36	0.4325	22.91	0.1954
Middle	836.4	27.64	0.5808	23.89	0.2449
Highest	848.8	27.61	0.5768	24.28	0.2679
Limit	ERP < 7W	Result		PASS	

GSM850 (EDGE class 8) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	824.2	21.03	0.1268	16.38	0.0435
Middle	836.4	21.59	0.1442	18.27	0.0671
Highest	848.8	21.40	0.1380	18.79	0.0757
Limit	ERP < 7W	Result		PASS	

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	826.4	17.11	0.0514	15.24	0.0334
Middle	836.4	17.95	0.0624	15.26	0.0336
Highest	846.6	17.87	0.0612	14.59	0.0288
Limit	ERP < 7W	Result		PASS	

3.3.5 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	26.10	0.4074	29.01	0.7962
Middle	1880.0	25.64	0.3664	27.83	0.6067
Highest	1909.8	24.95	0.3126	27.97	0.6266
Limit	EIRP < 2W	Result		PASS	

GSM1900 (EDGE class 8) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	22.43	0.1750	20.80	0.1202
Middle	1880.0	22.86	0.1932	20.41	0.1099
Highest	1909.8	20.48	0.1117	21.35	0.1365
Limit	EIRP < 2W	Result		PASS	

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1852.4	18.88	0.0773	17.93	0.0621
Middle	1880.0	19.02	0.0798	18.87	0.0771
Highest	1907.6	17.90	0.0617	17.20	0.0525
Limit	EIRP < 2W	Result		PASS	

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, peak detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	241.68	241.68	243.13	246.02	247.47	247.47
26dB BW (kHz)	318.40	316.90	318.40	302.50	311.10	311.10

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	241.68	241.68	241.68	247.47	243.13	246.02
26dB BW (kHz)	315.50	316.90	318.40	314.00	312.60	314.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.07	4.08	4.07
26dB BW (MHz)	4.66	4.65	4.66


PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.07	4.08	4.07
26dB BW (MHz)	4.66	4.66	4.66



3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 9.JUL.2015 23:12:28


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 9.JUL.2015 23:22:48




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 9.JUL.2015 23:14:20


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 9.JUL.2015 23:24:53

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 9.JUL.2015 23:16:02


26dB Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 9.JUL.2015 23:38:26




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




26dB Bandwidth Plot on Channel 128 (824.2 MHz)






99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 10.JUL.2015 00:18:44


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 10.JUL.2015 00:21:25




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 10.JUL.2015 00:17:49

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 10.JUL.2015 00:22:02




Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 10.JUL.2015 19:19:06


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 10.JUL.2015 19:07:14




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 10.JUL.2015 19:16:21


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 10.JUL.2015 19:09:53




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 10.JUL.2015 19:14:20

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 10.JUL.2015 19:11:48




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




26dB Bandwidth Plot on Channel 512 (1850.2 MHz)






99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 10.JUL.2015 01:28:52


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 10.JUL.2015 01:28:23



99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)




26dB Bandwidth Plot on Channel 810 (1909.8 MHz)






Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 10.JUL.2015 20:43:51


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 10.JUL.2015 20:23:19



99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)




26dB Bandwidth Plot on Channel 4182 (836.4 MHz)






99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)




26dB Bandwidth Plot on Channel 4233 (846.6 MHz)






Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 10.JUL.2015 20:20:09


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 10.JUL.2015 20:06:16




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 10.JUL.2015 20:16:55


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 10.JUL.2015 20:07:23



99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

6. The testing follows FCC KDB 971168 v02r02 Section 6.0.
7. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
8. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
9. The band edges of low and high channels for the highest RF powers were measured.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.5.4 Test Setup







3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Higher Band Edge Plot on Channel 251 (848.8 MHz)






Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Higher Band Edge Plot on Channel 251 (848.8 MHz)






Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 10.JUL.2015 19:26:23

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 10.JUL.2015 19:33:03




Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Higher Band Edge Plot on Channel 810 (1909.8 MHz)






Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Higher Band Edge Plot on Channel 4233 (846.6 MHz)





Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


12. The testing follows FCC KDB 971168 v02r02 Section 6.0.
13. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
14. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
15. The middle channel for the highest RF power within the transmitting frequency was measured.
16. The conducted spurious emission for the whole frequency range was taken.
17. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
18. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.6.4 Test Setup



**3.6.5 Test Result (Plots) of Conducted Spurious Emission**


Band :	GSM850	Channel :	CH128
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 10.JUL.2015 00:11:19




Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 10.JUL.2015 00:09:51




Band :	GSM850	Channel :	CH251
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 10.JUL.2015 00:07:48




Band :	GSM850	Channel :	CH128
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 10.JUL.2015 00:13:23



Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 10.JUL.2015 00:14:10



Band :	GSM850	Channel :	CH251
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 10.JUL.2015 00:14:54



Band :	GSM1900	Channel :	CH512
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1850.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 10.JUL.2015 19:38:15



Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Date: 10.JUL.2015 19:36:49



Band :	GSM1900	Channel :	CH810
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1909.8 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 10.JUL.2015 19:35:42



Band :	GSM1900	Channel :	CH512
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1850.2 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Date: 10.JUL.2015 01:31:51




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 10.JUL.2015 01:34:23




Band :	GSM1900	Channel :	CH810
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1909.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 10.JUL.2015 01:35:06



Band :	WCDMA Band V	Channel :	CH4132
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	826.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 10.JUL.2015 20:38:29



Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Date: 10.JUL.2015 20:37:17




Band :	WCDMA Band V	Channel :	CH4233
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	846.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 10.JUL.2015 22:18:13



Band :	WCDMA Band II	Channel :	CH9262
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1852.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 10.JUL.2015 19:51:48



Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Date: 10.JUL.2015 19:53:49



Band :	WCDMA Band II	Channel :	CH9538
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1907.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 10.JUL.2015 19:54:51

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850 for CH128					Temperature :	22~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1648.4	-38.22	-13	-25.22	-41.93	-44.91	0.56	9.40	H	Pass
2472.6	-49.74	-13	-36.74	-54.52	-57.44	0.75	10.60	H	Pass
3296.8	-57.15	-13	-44.15	-66.45	-66.75	0.85	12.60	H	Pass

Band :	GSM850 for CH128					Temperature :	22~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-38.96	-13	-25.96	-44.53	-45.65	0.56	9.40	V	Pass
2472.6	-47.47	-13	-34.47	-53.97	-55.17	0.75	10.60	V	Pass
3296.8	-57.40	-13	-44.40	-64.26	-67.00	0.85	12.60	V	Pass



Band :	GSM850 for CH189	Temperature :	22~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-37.45	-13	-24.45	-41.12	-44.14	0.56	9.40	H	Pass
2510	-52.96	-13	-39.96	-56.86	-60.66	0.75	10.60	H	Pass
3346	-57.91	-13	-44.91	-67.21	-67.51	0.85	12.60	H	Pass

Band :	GSM850 for CH189					Temperature :	22~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-34.57	-13	-21.57	-40.52	-41.26	0.56	9.40	V	Pass
2510	-43.38	-13	-30.38	-50.74	-51.08	0.75	10.60	V	Pass
3346	-56.48	-13	-43.48	-63.34	-66.08	0.85	12.60	V	Pass



Band :	GSM850 for CH251					Temperature :	22~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-32.41	-13	-19.41	-36.16	-39.10	0.56	9.40	H	Pass
2546.4	-47.14	-13	-34.14	-52.51	-54.84	0.75	10.60	H	Pass
3395.2	-57.36	-13	-44.36	-66.66	-66.96	0.85	12.60	H	Pass

Band :	GSM850 for CH251					Temperature :	22~24℃		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-34.98	-13	-21.98	-40.92	-41.67	0.56	9.40	V	Pass
2546.4	-42.80	-13	-29.80	-50.28	-50.50	0.75	10.60	V	Pass
3395.2	-57.38	-13	-44.38	-64.24	-66.98	0.85	12.60	V	Pass



Band :	GSM850 for CH128					Temperature :	22~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-47.24	-13	-34.24	-50.07	-53.93	0.56	9.40	H	Pass
2472.6	-61.91	-13	-48.91	-65.81	-69.61	0.75	10.60	H	Pass
3296.8	-58.01	-13	-45.01	-67.31	-67.61	0.85	12.60	H	Pass

Band :	GSM850 for CH128	Temperature :	22~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-45.21	-13	-32.21	-50.13	-51.90	0.56	9.40	V	Pass
2472.6	-59.55	-13	-46.55	-63.93	-67.25	0.75	10.60	V	Pass
3296.8	-60.45	-13	-47.45	-67.31	-70.05	0.85	12.60	V	Pass



Band :	GSM850 for CH189					Temperature :	22~24℃		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-43.93	-13	-30.93	-47.27	-50.62	0.56	9.40	H	Pass
2510	-61.18	-13	-48.18	-65.08	-68.88	0.75	10.60	H	Pass
3346	-56.92	-13	-43.92	-66.22	-66.52	0.85	12.60	H	Pass

Band :	GSM850 for CH189					Temperature :	22~24℃		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-43.90	-13	-30.90	-48.95	-50.59	0.56	9.40	V	Pass
2510	-57.20	-13	-44.20	-61.58	-64.90	0.75	10.60	V	Pass
3346	-60.20	-13	-47.20	-67.06	-69.80	0.85	12.60	V	Pass



Band :	GSM850 for CH251					Temperature :	22~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-39.78	-13	-26.78	-43.40	-46.47	0.56	9.40	H	Pass
2510	-58.83	-13	-45.83	-62.73	-66.53	0.75	10.60	H	Pass
3346	-56.89	-13	-43.89	-66.19	-66.49	0.85	12.60	H	Pass

Band :	GSM850 for CH251					Temperature :	22~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-42.38	-13	-29.38	-47.72	-49.07	0.56	9.40	V	Pass
2510	-56.92	-13	-43.92	-61.30	-64.62	0.75	10.60	V	Pass
3346	-60.69	-13	-47.69	-67.55	-70.29	0.85	12.60	V	Pass



Band :	GSM1900 for CH512					Temperature :	22~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-50.27	-13	-37.27	-63.04	-57.46	0.81	8.00	H	Pass
5550.6	-49.87	-13	-36.87	-68.62	-59.86	1.01	11.00	H	Pass
7400.8	-47.16	-13	-34.16	-69.33	-59.40	1.46	13.70	H	Pass

Band :	GSM1900 for CH512					Temperature :	22~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-44.99	-13	-31.99	-58.06	-52.18	0.81	8	V	Pass
5550.6	-48.45	-13	-35.45	-67.51	-58.44	1.01	11	V	Pass
7400.8	-46.64	-13	-33.64	-69.13	-58.88	1.46	13.7	V	Pass



Band :	GSM1900 for CH661	Temperature :	22~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-47.62	-13	-34.62	-60.39	-54.81	0.81	8.00	H	Pass
5640	-49.02	-13	-36.02	-67.77	-59.01	1.01	11.00	H	Pass
7520	-47.59	-13	-34.59	-69.76	-59.83	1.46	13.70	H	Pass

Band :	GSM1900 for CH661	Temperature :	22~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-43.52	-13	-30.52	-56.59	-50.71	0.81	8	V	Pass
5640	-49.30	-13	-36.30	-68.36	-59.29	1.01	11	V	Pass
7520	-47.30	-13	-34.30	-69.79	-59.54	1.46	13.7	V	Pass



Band :	GSM1900 for CH810					Temperature :	22~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-52.08	-13	-39.08	-64.85	-59.27	0.81	8.00	H	Pass
5729.4	-49.88	-13	-36.88	-68.63	-59.87	1.01	11.00	H	Pass
7639.2	-47.23	-13	-34.23	-69.40	-59.47	1.46	13.70	H	Pass

Band :	GSM1900 for CH810					Temperature :	22~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-49.56	-13	-36.56	-62.63	-56.75	0.81	8	V	Pass
5729.4	-49.56	-13	-36.56	-68.62	-59.55	1.01	11	V	Pass
7639.2	-46.62	-13	-33.62	-69.11	-58.86	1.46	13.7	V	Pass



Band :	GSM1900 for CH512					Temperature :	22~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3700.4	-51.01	-13	-38.01	-63.78	-58.20	0.81	8.00	H	Pass
5550.6	-49.54	-13	-36.54	-68.29	-59.53	1.01	11.00	H	Pass
7400.8	-47.26	-13	-34.26	-69.43	-59.50	1.46	13.70	H	Pass

Band :	GSM1900 for CH512					Temperature :	22~24℃		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3700.4	-48.00	-13	-35.00	-61.07	-55.19	0.81	8	V	Pass
5550.6	-48.55	-13	-35.55	-67.61	-58.54	1.01	11	V	Pass
7400.8	-47.33	-13	-34.33	-69.82	-59.57	1.46	13.7	V	Pass



Band :	GSM1900 for CH661					Temperature :	22~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-53.12	-13	-40.12	-65.89	-60.31	0.81	8.00	H	Pass
5640	-46.58	-13	-33.58	-65.33	-56.57	1.01	11.00	H	Pass
7520	-47.83	-13	-34.83	-70.00	-60.07	1.46	13.70	H	Pass

Band :	GSM1900 for CH661	Temperature :	22~24℃						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-50.23	-13	-37.23	-63.3	-57.42	0.81	8	V	Pass
5640	-45.83	-13	-32.83	-64.89	-55.82	1.01	11	V	Pass
7520	-47.12	-13	-34.12	-69.61	-59.36	1.46	13.7	V	Pass



Band :	GSM1900 for CH810					Temperature :	22~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3819.6	-54.60	-13	-41.60	-67.37	-61.79	0.81	8.00	H	Pass
5729.4	-50.10	-13	-37.10	-68.85	-60.09	1.01	11.00	H	Pass
7639.2	-47.37	-13	-34.37	-69.54	-59.61	1.46	13.70	H	Pass

Band :	GSM1900 for CH810					Temperature :	22~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-53.81	-13	-40.81	-66.88	-61.00	0.81	8	V	Pass
5729.4	-49.54	-13	-36.54	-68.6	-59.53	1.01	11	V	Pass
7639.2	-47.22	-13	-34.22	-69.71	-59.46	1.46	13.7	V	Pass



Band :	WCDMA Band V for CH4132	Temperature :	22~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1649.4	-57.16	-13	-44.16	-58.77	-63.85	0.56	9.40	H	Pass
2474.1	-62.44	-13	-49.44	-66.34	-70.14	0.75	10.60	H	Pass
3298.8	-57.75	-13	-44.75	-67.05	-67.35	0.85	12.60	H	Pass

Band :	WCDMA Band V for CH4132	Temperature :	22~24℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1649.4	-56.84	-13	-43.84	-59.29	-63.53	0.56	9.40	V	Pass
2474.1	-61.90	-13	-48.90	-66.28	-69.60	0.75	10.60	V	Pass
3298.8	-60.29	-13	-47.29	-67.15	-69.89	0.85	12.60	V	Pass



Band :	WCDMA Band V for CH4182	Temperature :	22~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-55.60	-13	-42.60	-57.21	-62.29	0.56	9.40	H	Pass
2510	-61.68	-13	-48.68	-65.58	-69.38	0.75	10.60	H	Pass
3346	-57.74	-13	-44.74	-67.04	-67.34	0.85	12.60	H	Pass

Band :	WCDMA Band V for CH4182	Temperature :	22~24℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-55.27	-13	-42.27	-57.72	-61.96	0.56	9.40	V	Pass
2510	-61.86	-13	-48.86	-66.24	-69.56	0.75	10.60	V	Pass
3346	-60.11	-13	-47.11	-66.97	-69.71	0.85	12.60	V	Pass



Band :	WCDMA Band V for CH4233	Temperature :	22~24℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1696.62	-54.36	-13	-41.36	-55.97	-61.05	0.56	9.40	H	Pass
2544.93	-63.02	-13	-50.02	-66.92	-70.72	0.75	10.60	H	Pass
3393.24	-58.20	-13	-45.20	-67.50	-67.80	0.85	12.60	H	Pass

Band :	WCDMA Band V for CH4233	Temperature :	22~24℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1696.62	-55.50	-13	-42.50	-57.95	-62.19	0.56	9.40	V	Pass
2544.93	-61.72	-13	-48.72	-66.10	-69.42	0.75	10.60	V	Pass
3393.24	-60.23	-13	-47.23	-67.09	-69.83	0.85	12.60	V	Pass



Band :	WCDMA Band II for CH9262					Temperature :	22~24°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	42~48%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3704.8	-50.57	-13	-37.57	-63.34	-57.76	0.81	8.00	H	Pass
5557.2	-49.69	-13	-36.69	-68.44	-59.68	1.01	11.00	H	Pass
7409.6	-46.74	-13	-33.74	-68.91	-58.98	1.46	13.70	H	Pass

Band :	WCDMA Band II for CH9262	Temperature :	22~24℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3704.8	-50.42	-13	-37.42	-63.49	-57.61	0.81	8	V	Pass
5557.2	-49.36	-13	-36.36	-68.42	-59.35	1.01	11	V	Pass
7409.6	-46.73	-13	-33.73	-69.22	-58.97	1.46	13.7	V	Pass



Band :	WCDMA Band II for CH9400	Temperature :	22~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-53.12	-13	-40.12	-65.89	-60.31	0.81	8.00	H	Pass
5640	-49.55	-13	-36.55	-68.30	-59.54	1.01	11.00	H	Pass
7520	-47.58	-13	-34.58	-69.75	-59.82	1.46	13.70	H	Pass

Band :	WCDMA Band II for CH9400	Temperature :	22~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-50.97	-13	-37.97	-64.04	-58.16	0.81	8	V	Pass
5640	-49.27	-13	-36.27	-68.33	-59.26	1.01	11	V	Pass
7520	-47.20	-13	-34.20	-69.69	-59.44	1.46	13.7	V	Pass



Band :	WCDMA Band II for CH9538	Temperature :	22~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3815.2	-54.20	-13	-41.20	-66.97	-61.39	0.81	8.00	H	Pass
5722.8	-50.52	-13	-37.52	-69.27	-60.51	1.01	11.00	H	Pass
7630.4	-47.26	-13	-34.26	-69.43	-59.50	1.46	13.70	H	Pass

Band :	WCDMA Band II for CH9538	Temperature :	22~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~48%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3815.2	-52.79	-13	-39.79	-65.86	-59.98	0.81	8	V	Pass
5722.8	-49.99	-13	-36.99	-69.05	-59.98	1.01	11	V	Pass
7630.4	-47.03	-13	-34.03	-69.52	-59.27	1.46	13.7	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0096	0.0060	PASS
40	0.0060	0.0036	
30	0.0024	0.0012	
20(Ref.)	0.0000	0.0000	
10	0.0024	0.0012	
0	0.0048	0.0227	
-10	0.0084	0.0251	
-20	0.0108	0.0275	
-30	0.0143	0.0311	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0048	0.0053	PASS
40	0.0032	0.0032	
30	0.0016	0.0016	
20(Ref.)	0.0000	0.0000	
10	0.0011	0.0011	
0	0.0027	0.0027	
-10	0.0043	0.0287	
-20	0.0059	0.0309	
-30	0.0080	0.0324	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0072	PASS
40	0.0060	
30	0.0036	
20(Ref.)	0.0000	
10	0.0024	
0	0.0012	
-10	0.0024	
-20	0.0048	
-30	0.0096	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0027	PASS
40	0.0011	
30	0.0005	
20(Ref.)	0.0000	
10	0.0011	
0	0.0005	
-10	0.0005	
-20	0.0016	
-30	0.0011	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	9.90	0.0012	2.5	PASS
		9.00	0.0000		
		BEP	0.0012		
	EDGE class 8	9.90	0.0012		
		9.00	0.0000		
		BEP	0.0012		
GSM 1900 CH661	GPRS class 8	9.90	0.0011	(Note 3.)	
		9.00	0.0000		
		BEP	0.0005		
	EDGE class 8	9.90	0.0011		
		9.00	0.0000		
		BEP	0.0005		
WCDMA Band V CH4182	RMC 12.2Kbps	9.90	0.0012	2.5	
		9.00	0.0000		
		BEP	0.0012		
WCDMA Band II CH9400	RMC 12.2Kbps	9.90	0.0011	(Note 3.)	
		9.00	0.0000		
		BEP	0.0005		

Note:

1. Normal Voltage = 9.00V.
2. Battery End Point (BEP) = 8.50 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	May 05, 2015	Jul. 09, 2015~ Jul. 10, 2015	May 04, 2016	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Jul. 09, 2015~ Jul. 10, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion	LP-150U	H2014081803	-40~+150°C	Aug. 07, 2014	Jul. 09, 2015~ Jul. 10, 2015	Aug. 06, 2015	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz; Max 30dBm	Oct. 14, 2014	Aug. 25, 2015	Oct. 13, 2015	Radiation (03CH02-SZ)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz;Ma x 30dBm	Oct. 15, 2014	Aug. 25, 2015	Oct. 14, 2015	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Nov. 07, 2014	Aug. 25, 2015	Nov. 06, 2015	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 20, 2015	Aug. 25, 2015	Jan. 19, 2016	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Sep. 04, 2014	Aug. 25, 2015	Sep. 03, 2015	Radiation (03CH02-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz / 30 dB	Jan. 28, 2015	Aug. 25, 2015	Jan. 27, 2016	Radiation (03CH02-SZ)
Amplifier	Agilent	8449B	3008A01023	1GHz~26.5GHz	Oct. 29, 2014	Aug. 25, 2015	Oct. 28, 2015	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	61601000247 0	N/A	NCR	Aug. 25, 2015	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Aug. 25, 2015	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Aug. 25, 2015	NCR	Radiation (03CH02-SZ)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------