EXHIBIT 9 APPENDIX B1: SAR DISTRIBUTION PLOTS (HEAD)

CDMA 800 (CELL)

Test Laboratory: Comptest/KWC   Date: 12/1/2009

FCC M6000 CDMA-800 Left, 120109

Communication System: CDMA-800, Frequency: 824.7 MHz, Duty Cycle: 1:1
Medium: Head 835 MHz,Medium parameters used (interpolated): f = 824.7 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ES3DV3 - SN3035, ConvF(6.12, 6.12, 6.12), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE3 Sn494,Calibrated: 4/22/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch1013 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (interpolated) = 0.882 mW/g

CDMA-800 Ch1013 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.1 V/m; Power Drift = 0.127 dB
Peak SAR (extrapolated) = 1.06 W/kg
SAR(1 g) = 0.837 mW/g; SAR(10 g) = 0.620 mW/g
Maximum value of SAR (measured) = 0.888 mW/g

0 dB = 0.888mW/g

Test Laboratory: Comptest/KWC

Date: 12/1/2009

FCC M6000 CDMA-800 Left, 120109

Communication System: CDMA-800, Frequency: 836.49 MHz, Duty Cycle: 1:1
Medium: Head 835 MHz,Medium parameters used (interpolated): f = 836.49 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ES3DV3 - SN3035, ConvF(6.12, 6.12, 6.12), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE3 Sn494,Calibrated: 4/22/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch383 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.19 mW/g

CDMA-800 Ch383 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.1 V/m; Power Drift = 0.006 dB
Peak SAR (extrapolated) = 1.35 W/kg
**SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.784 mW/g**
Maximum value of SAR (measured) = 1.15 mW/g

0 dB = 1.15mW/g

Interpolated SAR(x,y,z,f0)
SAR; Z Scan: Value Along Z, X=0, Y=0

Test Laboratory: Comptest/KWC

Date: 12/1/2009

FCC M6000 CDMA-800 Left, 120109

Communication System: CDMA-800, Frequency: 848.31 MHz, Duty Cycle: 1:1
Medium: Head 835 MHz,Medium parameters used (interpolated): f = 848.31 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ES3DV3 - SN3035, ConvF(6.12, 6.12, 6.12), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE3 Sn494,Calibrated: 4/22/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch777 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.695 mW/g

CDMA-800 Ch777 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.68 V/m; Power Drift = 0.097 dB
Peak SAR (extrapolated) = 0.836 W/kg
SAR(1 g) = 0.663 mW/g; SAR(10 g) = 0.488 mW/g
Maximum value of SAR (measured) = 0.696 mW/g

0 dB = 0.695mW/g

Test Laboratory: Comptest/KWC

Date: 12/1/2009

FCC M6000 CDMA-800 Left, 120109

Communication System: CDMA-800, Frequency: 836.49 MHz, Duty Cycle: 1:1
Medium: Head 835 MHz,Medium parameters used (interpolated): f = 836.49 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ES3DV3 - SN3035, ConvF(6.12, 6.12, 6.12), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE3 Sn494,Calibrated: 4/22/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch383 LT/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.542 mW/g

CDMA-800 Ch383 LT/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 15.9 V/m; Power Drift = -0.119 dB
Peak SAR (extrapolated) = 0.629 W/kg
SAR(1 g) = 0.511 mW/g; SAR(10 g) = 0.387 mW/g
Maximum value of SAR (measured) = 0.533 mW/g

0 dB = 0.542mW/g

Test Laboratory: Comptest/KWC

Date: 12/1/2009

FCC M6000 CDMA-800 Right, 120109

Communication System: CDMA-800, Frequency: 824.7 MHz, Duty Cycle: 1:1
Medium: Head 835 MHz,Medium parameters used (interpolated): f = 824.7 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ES3DV3 - SN3035, ConvF(6.12, 6.12, 6.12), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE3 Sn494,Calibrated: 4/22/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch1013 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.05 mW/g

CDMA-800 Ch1013 RC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 12.8 V/m; Power Drift = -0.196 dB
Peak SAR (extrapolated) = 1.32 W/kg
SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.741 mW/g
Maximum value of SAR (measured) = 1.10 mW/g

0 dB = 1.10mW/g

This report shall not be reproduced except in full, without the written consent of CompTest Services LLC.

Test Laboratory: Comptest/KWC

Date: 12/1/2009

FCC M6000 CDMA-800 Right, 120109

Communication System: CDMA-800, Frequency: 836.49 MHz, Duty Cycle: 1:1
Medium: Head 835 MHz,Medium parameters used (interpolated): f = 836.49 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ES3DV3 - SN3035, ConvF(6.12, 6.12, 6.12), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE3 Sn494,Calibrated: 4/22/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch383 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.30 mW/g

CDMA-800 Ch383 RC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.6 V/m; Power Drift = 0.123 dB
Peak SAR (extrapolated) = 1.57 W/kg
SAR(1 g) = 1.24 mW/g; SAR(10 g) = 0.914 mW/g
Maximum value of SAR (measured) = 1.32 mW/g

0 dB = 1.32mW/g

COMPTEST
Services LLC

Interpolated SAR(x,y,z,f0)
SAR; Z Scan:Value Along Z, X=0, Y=0

Test Laboratory: Comptest/KWC

Date: 12/1/2009

FCC M6000 CDMA-800 Right, 120109

Communication System: CDMA-800, Frequency: 848.31 MHz, Duty Cycle: 1:1
Medium: Head 835 MHz,Medium parameters used (interpolated): f = 848.31 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ES3DV3 - SN3035, ConvF(6.12, 6.12, 6.12), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE3 Sn494,Calibrated: 4/22/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch777 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.760 mW/g

CDMA-800 Ch777 RC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.70 V/m; Power Drift = -0.136 dB
Peak SAR (extrapolated) = 0.936 W/kg
SAR(1 g) = 0.719 mW/g; SAR(10 g) = 0.526 mW/g
Maximum value of SAR (measured) = 0.784 mW/g

0 dB = 0.760mW/g

Test Laboratory: Comptest/KWC

Date: 12/1/2009

FCC M6000 CDMA-800 Right, 120109

Communication System: CDMA-800, Frequency: 836.49 MHz, Duty Cycle: 1:1
Medium: Head 835 MHz,Medium parameters used (interpolated): f = 836.49 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ES3DV3 - SN3035, ConvF(6.12, 6.12, 6.12), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE3 Sn494,Calibrated: 4/22/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch383 RT/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.550 mW/g

CDMA-800 Ch383 RT/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 16.1 V/m; Power Drift = -0.124 dB
Peak SAR (extrapolated) = 0.668 W/kg
SAR(1 g) = 0.523 mW/g; SAR(10 g) = 0.394 mW/g
Maximum value of SAR (measured) = 0.547 mW/g

0 dB = 0.547mW/g

CDMA 1900 (PCS)

Test Laboratory: Comptest/KWC

Date: 12/3/2009

FCC M6000 CDMA-1900 Left, 120309

Communication System: CDMA-1900, Frequency: 1851.25 MHz, Duty Cycle: 1:1
Medium: HSL1900,Medium parameters used (interpolated): f = 1851.25 MHz; σ = 1.4 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ES3DV3 - SN3036, ConvF(4.92, 4.92, 4.92), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn527,Calibrated: 7/9/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900_Ch25 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.591 mW/g

CDMA-1900_Ch25 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.55 V/m; Power Drift = -0.042 dB
Peak SAR (extrapolated) = 0.766 W/kg
SAR(1 g) = 0.529 mW/g; SAR(10 g) = 0.353 mW/g
Maximum value of SAR (measured) = 0.563 mW/g

CDMA-1900_Ch25 LC/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.55 V/m; Power Drift = -0.042 dB
Peak SAR (extrapolated) = 0.657 W/kg
SAR(1 g) = 0.444 mW/g; SAR(10 g) = 0.281 mW/g
Maximum value of SAR (measured) = 0.526 mW/g

0 dB = 0.526mW/g

This report shall not be reproduced except in full, without the written consent of CompTest Services LLC.

Test Laboratory: Comptest/KWC   Date: 12/3/2009

FCC M6000 CDMA-1900 Left, 120309

Communication System: CDMA-1900, Frequency: 1880 MHz, Duty Cycle: 1:1
Medium: HSL1900,Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ES3DV3 - SN3036, ConvF(4.92, 4.92, 4.92), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn527,Calibrated: 7/9/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900_CH600 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.879 mW/g

CDMA-1900_CH600 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.6 V/m; Power Drift = -0.077 dB
Peak SAR (extrapolated) = 1.15 W/kg
SAR(1 g) = 0.805 mW/g; SAR(10 g) = 0.531 mW/g
Maximum value of SAR (measured) = 0.864 mW/g

CDMA-1900_CH600 LC/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.6 V/m; Power Drift = -0.077 dB
Peak SAR (extrapolated) = 1.02 W/kg
SAR(1 g) = 0.680 mW/g; SAR(10 g) = 0.426 mW/g
Maximum value of SAR (measured) = 0.796 mW/g

0 dB = 0.796mW/g

Test Laboratory: Comptest/KWC

Date: 12/3/2009

FCC M6000 CDMA-1900 Left, 120309

Communication System: CDMA-1900, Frequency: 1908.75 MHz, Duty Cycle: 1:1
Medium: HSL1900,Medium parameters used (interpolated): f = 1908.75 MHz; σ = 1.4 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ES3DV3 - SN3036, ConvF(4.92, 4.92, 4.92), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn527,Calibrated: 7/9/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900_Ch 1175 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.533 mW/g

CDMA-1900_Ch 1175 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.55 V/m; Power Drift = -0.149 dB
Peak SAR (extrapolated) = 0.653 W/kg
SAR(1 g) = 0.464 mW/g; SAR(10 g) = 0.306 mW/g
Maximum value of SAR (measured) = 0.496 mW/g

0 dB = 0.496mW/g

Test Laboratory: Comptest/KWC

Date: 12/3/2009

FCC M6000 CDMA-1900 Left, 120309

Communication System: CDMA-1900, Frequency: 1880 MHz, Duty Cycle: 1:1
Medium: HSL1900,Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ES3DV3 - SN3036, ConvF(4.92, 4.92, 4.92), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn527,Calibrated: 7/9/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900_CH600 LT/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.630 mW/g

**CDMA-1900_CH600 LT/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 16.8 V/m; Power Drift = -0.164 dB
Peak SAR (extrapolated) = 0.800 W/kg
SAR(1 g) = 0.547 mW/g; SAR(10 g) = 0.341 mW/g
Maximum value of SAR (measured) = 0.591 mW/g

0 dB = 0.591mW/g

Test Laboratory: Comptest/KWC

Date: 12/3/2009

FCC M6000 CDMA-1900 Right, 120309

Communication System: CDMA-1900, Frequency: 1851.25 MHz, Duty Cycle: 1:1
Medium: HSL1900,Medium parameters used (interpolated): f = 1851.25 MHz; σ = 1.4 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ES3DV3 - SN3036, ConvF(4.92, 4.92, 4.92), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn527,Calibrated: 7/9/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900_Ch25 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.03 mW/g

CDMA-1900_Ch25 RC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.82 V/m; Power Drift = 0.061 dB
Peak SAR (extrapolated) = 1.37 W/kg
SAR(1 g) = 0.947 mW/g; SAR(10 g) = 0.583 mW/g
Maximum value of SAR (measured) = 1.06 mW/g

0 dB = 1.06mW/g

Test Laboratory: Comptest/KWC

Date: 12/3/2009

FCC M6000 CDMA-1900 Right, 120309

Communication System: CDMA-1900, Frequency: 1880 MHz, Duty Cycle: 1:1
Medium: HSL1900,Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; $ε_r$ = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ES3DV3 - SN3036, ConvF(4.92, 4.92, 4.92), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn527,Calibrated: 7/9/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900_CH600 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.47 mW/g

CDMA-1900_CH600 RC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.4 V/m; Power Drift = -0.144 dB
Peak SAR (extrapolated) = 1.97 W/kg
SAR(1 g) = 1.35 mW/g; SAR(10 g) = 0.828 mW/g
Maximum value of SAR (measured) = 1.48 mW/g

0 dB = 1.48mW/g

COMPTEST
Services LLC

Interpolated SAR(x,y,z,f0)
SAR; Z Scan:Value Along Z, X=0, Y=0

Test Laboratory: Comptest/KWC

FCC M6000 CDMA-1900 Right, 120309

Communication System: CDMA-1900, Frequency: 1908.75 MHz, Duty Cycle: 1:1
Medium: HSL1900,Medium parameters used (interpolated): f = 1908.75 MHz; σ = 1.4 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ES3DV3 - SN3036, ConvF(4.92, 4.92, 4.92), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn527,Calibrated: 7/9/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900_Ch 1175 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.758 mW/g

**CDMA-1900_Ch 1175 RC/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.55 V/m; Power Drift = -0.095 dB
Peak SAR (extrapolated) = 1.05 W/kg
SAR(1 g) = 0.699 mW/g; SAR(10 g) = 0.429 mW/g
Maximum value of SAR (measured) = 0.775 mW/g

0 dB = 0.775mW/g

Test Laboratory: Comptest/KWC

Date: 12/3/2009

FCC M6000 CDMA-1900 Right, 120309

Communication System: CDMA-1900, Frequency: 1880 MHz, Duty Cycle: 1:1
Medium: HSL1900,Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; $ε_r$ = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ES3DV3 - SN3036, ConvF(4.92, 4.92, 4.92), Calibrated: 8/20/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn527,Calibrated: 7/9/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900_CH600 RT/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.514 mW/g

CDMA-1900_CH600 RT/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 15.5 V/m; Power Drift = 0.062 dB
Peak SAR (extrapolated) = 0.689 W/kg
SAR(1 g) = 0.454 mW/g; SAR(10 g) = 0.278 mW/g
Maximum value of SAR (measured) = 0.496 mW/g

0 dB = 0.496mW/g

CDMA 1700 (AWS)

Test Laboratory: Comptest/KWC   Date: 12/2/2009

FCC M6000 CDMA-1700 Left 12-02-09

Communication System: AWS-1700, Frequency: 1711.25 MHz, Duty Cycle: 1:1
Medium: HSL 1700,Medium parameters used (interpolated): f = 1711.25 MHz; σ = 1.36 mho/m; $ε_r$ = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ET3DV6 - SN1664, ConvF(5.46, 5.46, 5.46), Calibrated: 6/22/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn603,Calibrated: 9/15/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1700 Ch25 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.746 mW/g

CDMA-1700 Ch25 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.40 V/m; Power Drift = -0.152 dB
Peak SAR (extrapolated) = 0.940 W/kg
SAR(1 g) = 0.671 mW/g; SAR(10 g) = 0.466 mW/g
Maximum value of SAR (measured) = 0.735 mW/g

CDMA-1700 Ch25 LC/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.40 V/m; Power Drift = -0.152 dB
Peak SAR (extrapolated) = 0.816 W/kg
SAR(1 g) = 0.608 mW/g; SAR(10 g) = 0.398 mW/g
Maximum value of SAR (measured) = 0.713 mW/g

0 dB = 0.713mW/g

Test Laboratory: Comptest/KWC   Date: 12/2/2009

FCC M6000 CDMA-1700 Left 12-02-09

Communication System: AWS-1700, Frequency: 1732.5 MHz, Duty Cycle: 1:1
Medium: HSL 1700,Medium parameters used (interpolated): f = 1732.5 MHz; σ = 1.36 mho/m; $ε_r$ = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ET3DV6 - SN1664, ConvF(5.46, 5.46, 5.46), Calibrated: 6/22/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn603,Calibrated: 9/15/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1700 Ch450 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.954 mW/g

CDMA-1700 Ch450 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.9 V/m; Power Drift = 0.034 dB
Peak SAR (extrapolated) = 1.16 W/kg
SAR(1 g) = 0.851 mW/g; SAR(10 g) = 0.581 mW/g
Maximum value of SAR (measured) = 0.913 mW/g

CDMA-1700 Ch450 LC/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.9 V/m; Power Drift = 0.034 dB
Peak SAR (extrapolated) = 0.987 W/kg
SAR(1 g) = 0.750 mW/g; SAR(10 g) = 0.479 mW/g
Maximum value of SAR (measured) = 0.869 mW/g

0 dB = 0.869mW/g

Interpolated SAR(x,y,z,f0)
SAR; Z Scan:Value Along Z, X=0, Y=0

Test Laboratory: Comptest/KWC   Date/: 12/2/2009

FCC M6000 CDMA-1700 Left 12-02-09

Communication System: AWS-1700, Frequency: 1753.75 MHz, Duty Cycle: 1:1
Medium: HSL 1700,Medium parameters used (extrapolated): f = 1753.75 MHz; σ = 1.36 mho/m; $ε_r$ = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ET3DV6 - SN1664, ConvF(5.46, 5.46, 5.46), Calibrated: 6/22/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn603,Calibrated: 9/15/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1700 Ch875 LC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.996 mW/g

CDMA-1700 Ch875 LC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.3 V/m; Power Drift = 0.091 dB
Peak SAR (extrapolated) = 1.18 W/kg
SAR(1 g) = 0.867 mW/g; SAR(10 g) = 0.585 mW/g
Maximum value of SAR (measured) = 0.942 mW/g

CDMA-1700 Ch875 LC/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.3 V/m; Power Drift = 0.091 dB
Peak SAR (extrapolated) = 1.02 W/kg
SAR(1 g) = 0.752 mW/g; SAR(10 g) = 0.476 mW/g
Maximum value of SAR (measured) = 0.890 mW/g

0 dB = 0.890mW/g

This report shall not be reproduced except in full, without the written consent of CompTest Services LLC.

Test Laboratory: Comptest/KWC

Date: 12/2/2009

FCC M6000 CDMA-1700 Left 12-02-09

Communication System: AWS-1700, Frequency: 1732.5 MHz, Duty Cycle: 1:1
Medium: HSL 1700,Medium parameters used (interpolated): f = 1732.5 MHz; σ = 1.36 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Left Section
DASY4 Configuration:
Probe: ET3DV6 - SN1664, ConvF(5.46, 5.46, 5.46), Calibrated: 6/22/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn603,Calibrated: 9/15/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1700 Ch450 LT/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.573 mW/g

CDMA-1700 Ch450 LT/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 15.4 V/m; Power Drift = -0.100 dB
Peak SAR (extrapolated) = 0.677 W/kg
SAR(1 g) = 0.499 mW/g; SAR(10 g) = 0.321 mW/g
Maximum value of SAR (measured) = 0.544 mW/g

0 dB = 0.544mW/g

Test Laboratory: Comptest/KWC

Date: 12/2/2009

FCC M6000 CDMA-1700 Right 12-02-09

Communication System: AWS-1700, Frequency: 1711.25 MHz, Duty Cycle: 1:1
Medium: HSL 1700,Medium parameters used (interpolated): f = 1711.25 MHz; σ = 1.36 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ET3DV6 - SN1664, ConvF(5.46, 5.46, 5.46), Calibrated: 6/22/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn603,Calibrated: 9/15/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1700 Ch25 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.882 mW/g

CDMA-1700 Ch25 RC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.8 V/m; Power Drift = 0.014 dB
Peak SAR (extrapolated) = 1.09 W/kg
SAR(1 g) = 0.817 mW/g; SAR(10 g) = 0.521 mW/g
Maximum value of SAR (measured) = 0.907 mW/g

0 dB = 0.907mW/g

Test Laboratory: Comptest/KWC

Date: 12/2/2009

FCC M6000 CDMA-1700 Right 12-02-09

Communication System: AWS-1700, Frequency: 1732.5 MHz, Duty Cycle: 1:1
Medium: HSL 1700,Medium parameters used (interpolated): f = 1732.5 MHz; σ = 1.36 mho/m; $ε_r$ = 39.2; ρ = 1000 kg/m³
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ET3DV6 - SN1664, ConvF(5.46, 5.46, 5.46), Calibrated: 6/22/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn603,Calibrated: 9/15/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1700 Ch450 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.22 mW/g

**CDMA-1700 Ch450 RC/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.9 V/m; Power Drift = 0.126 dB
Peak SAR (extrapolated) = 1.51 W/kg
SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.700 mW/g
Maximum value of SAR (measured) = 1.19 mW/g

0 dB = 1.19mW/g

Test Laboratory: Comptest/KWC

Date: 12/2/2009

FCC M6000 CDMA-1700 Right 12-02-09

Communication System: AWS-1700, Frequency: 1753.75 MHz, Duty Cycle: 1:1
Medium: HSL 1700,Medium parameters used (extrapolated): f = 1753.75 MHz; σ = 1.36 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ET3DV6 - SN1664, ConvF(5.46, 5.46, 5.46), Calibrated: 6/22/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn603,Calibrated: 9/15/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1700 Ch875 RC/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.14 mW/g

CDMA-1700 Ch875 RC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.7 V/m; Power Drift = -0.062 dB
Peak SAR (extrapolated) = 1.37 W/kg
SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.636 mW/g
Maximum value of SAR (measured) = 1.10 mW/g

0 dB = 1.10mW/g

Test Laboratory: Comptest/KWC

Date: 12/2/2009

FCC M6000 CDMA-1700 Right 12-02-09

Communication System: AWS-1700, Frequency: 1732.5 MHz, Duty Cycle: 1:1
Medium: HSL 1700,Medium parameters used (interpolated): f = 1732.5 MHz; σ = 1.36 mho/m; ε_r = 39.2; ρ = 1000 kg/m^3
Phantom: SAM 12,Phantom section: Right Section
DASY4 Configuration:
Probe: ET3DV6 - SN1664, ConvF(5.46, 5.46, 5.46), Calibrated: 6/22/2009
Sensor-Surface: 4mm (Mechanical Surface Detection),
Electronics: DAE4 Sn603,Calibrated: 9/15/2009
Measurement SW: DASY4, V4.7 Build 80
Postprocessing SW: SEMCAD, V1.8 Build 186
Temperature: Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1700 Ch450 RT/Area Scan (111x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.562 mW/g

CDMA-1700 Ch450 RT/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 16.8 V/m; Power Drift = 0.093 dB
Peak SAR (extrapolated) = 0.660 W/kg
SAR(1 g) = 0.473 mW/g; SAR(10 g) = 0.294 mW/g
Maximum value of SAR (measured) = 0.520 mW/g

0 dB = 0.520mW/g

This report shall not be reproduced except in full, without the written consent of CompTest Services LLC.