

## FCC Test Report

### (PART 90S)

**Report No.:** RF151222C07-3

**FCC ID:** V65C6743

**Test Model:** C6743

**Received Date:** Dec. 22, 2015

**Test Date:** Dec. 29, 2015 ~ Jan. 03, 2016

**Issued Date:** Jan. 15, 2016

**Applicant:** Kyocera Corporation c/o Kyocera Communications, Inc.

**Address:** 9520 Towne Centre Drive, Suite 200, San Diego, CA 92121

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
( R.O.C )

**Test Location (1):** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan  
Hsien 333, Taiwan, R.O.C.

**Test Location (2):** No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,  
R.O.C

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency

## Table of Contents

<b>Release Control Record .....</b>	<b>3</b>
<b>1 Certificate of Conformity .....</b>	<b>4</b>
<b>2 Summary of Test Results.....</b>	<b>5</b>
2.1 Measurement Uncertainty.....	5
2.2 Test Site and Instruments .....	6
<b>3 General Information .....</b>	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Configuration of System under Test.....	8
3.2.1 Description of Support Units .....	8
3.3 Test Mode Applicability and Tested Channel Detail .....	9
3.4 EUT Operating Conditions .....	11
3.5 General Description of Applied Standards.....	11
<b>4 Test Types and Results .....</b>	<b>12</b>
4.1 Output Power Measurement.....	12
4.1.1 Limits of Output Power Measurement .....	12
4.1.2 Test Procedures.....	12
4.1.3 Test Setup.....	13
4.1.4 Test Results .....	14
4.2 Frequency Stability Measurement .....	19
4.2.1 Limits of Frequency Stability Measurement.....	19
4.2.2 Test Procedure .....	19
4.2.3 Test Setup.....	19
4.2.4 Test Results .....	20
4.3 Occupied Bandwidth Measurement.....	21
4.3.1 Test Procedure .....	21
4.3.2 Test Setup.....	21
4.3.3 Test Result .....	22
4.4 Emission Mask Measurement.....	25
4.4.1 Limits of Band Edge Measurement .....	25
4.4.2 Test Setup.....	25
4.4.3 Test Procedures.....	25
4.4.4 Test Results .....	26
4.5 Conducted Spurious Emissions.....	30
4.5.1 Limits of Conducted Spurious Emissions Measurement.....	30
4.5.2 Test Setup.....	30
4.5.3 Test Procedure .....	30
4.5.4 Test Results .....	31
4.6 Radiated Emission Measurement.....	33
4.6.1 Limits of Radiated Emission Measurement .....	33
4.6.2 Test Procedure .....	33
4.6.3 Deviation from Test Standard .....	33
4.6.4 Test Setup.....	33
4.6.5 Test Results .....	34
<b>5 Pictures of Test Arrangements.....</b>	<b>38</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>39</b>



A D T

### Release Control Record

Issue No.	Description	Date Issued
RF151222C07-3	Original Release	Jan. 15, 2016

## 1 Certificate of Conformity

**Product:** preface

**Brand:** Kyocera

**Test Model:** C6743

**Sample Status:** Identical Prototype

**Applicant:** Kyocera Corporation c/o Kyocera Communications, Inc.

**Test Date:** Dec. 29, 2015 ~ Jan. 03, 2016

**Standards:** FCC Part 90, Subpart S

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Evonne Liu, **Date:** Jan. 15, 2016  
Evonne Liu / Specialist

**Approved by :** Stanley Wu, **Date:** Jan. 15, 2016  
Stanley Wu / Assistant Manager

## 2 Summary of Test Results

Applied Standard: FCC Part 90 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 90.635 (b)	Effective Radiated Power	Pass	Meet the requirement of limit.
2.1055 90.213	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 90.209	Occupied Bandwidth (*)	Pass	Meet the requirement of limit.
2.1051 90.209	Emission Masks	Pass	Meet the requirement of limit.
2.1051 90.691	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 90.691	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -36.04 dB at 118.29 MHz.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

## 2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	May 19, 2015	May 18, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2015	Dec. 16, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna ETS-Lindgren	3117	00143293	Jan. 05, 2015	Jan. 04, 2016
Bluetooth Tester	CBT	100980	Apr. 27, 2015	Apr. 26, 2017
Loop Antenna	EM-6879	269	Jul. 31, 2015	Jul. 30, 2016
Agilent Communications Tester-Wireless	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Preamplifier Agilent	310N	187226	Jun. 29, 2015	Jun. 28, 2016
Preamplifier Agilent	83017A	MY39501357	Jun. 29, 2015	Jun. 28, 2016
Power Meter Anritsu	ML2495A	1232002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor Anritsu	MA2411B	1207325	Sep. 21, 2015	Sep. 20, 2016
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 27, 2015	Jun. 26, 2016
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 27, 2015	Jun. 26, 2016
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Radio Communication Analyzer Anritsu	MT8820C	6201240432	Jul. 06, 2015	Jul. 05, 2017

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The FCC Site Registration No. is 149147.
5. The IC Site Registration No. is IC7450I-1.

### 3 General Information

#### 3.1 General Description of EUT

<b>Product</b>	preface	
<b>Brand</b>	Kyocera	
<b>Test Model</b>	C6743	
<b>Status of EUT</b>	Identical Prototype	
<b>Power Supply Rating</b>	5.0Vdc (adapter or host equipment) 3.8Vdc (Li-ion battery)	
<b>Modulation Type</b>	CDMA	QPSK, OQPSK, HPSK
	LTE	QPSK, 16QAM
<b>Frequency Range</b>	CDMA BC10	817.9 ~ 823.1 MHz
	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	814.7 ~ 823.3 MHz
	LTE Band 26 (Channel Bandwidth: 3 MHz)	815.5 ~ 822.5 MHz
	LTE Band 26 (Channel Bandwidth: 5 MHz)	816.5 ~ 821.5 MHz
	LTE Band 26 (Channel Bandwidth: 10 MHz)	819 MHz
<b>Emission Designator</b>	CDMA BC10	1M27F9W
	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	1M09G7D
	LTE Band 26 (Channel Bandwidth: 3 MHz)	2M73G7D
	LTE Band 26 (Channel Bandwidth: 5 MHz)	4M50G7D
	LTE Band 26 (Channel Bandwidth: 10 MHz)	9M90G7D
<b>Max. ERP Power</b>	CDMA BC10	103.75 mW
	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	116.14 mW
	LTE Band 26 (Channel Bandwidth: 3 MHz)	122.46 mW
	LTE Band 26 (Channel Bandwidth: 5 MHz)	123.37 mW
	LTE Band 26 (Channel Bandwidth: 10 MHz)	100.46 mW
<b>Antenna Type</b>	Fixed Internal Antenna	
<b>Accessory Device</b>	Refer to Note as below	
<b>Data Cable Supplied</b>	Refer to Note as below	

Note:


1. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	KYOCERA	SCP-47ADT	I/P: 100-240Vac, 50/60Hz, 0.2A O/P: 5Vdc, 1A
USB Cable	KYOCERA	SCP-19SDC	0.5m shielded cable w/o core


2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Configuration of System under Test

#### <Radiated Emission Test>



#### <E.R.P. Test>



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.



### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP	Radiated Emission
CDMA	Y-plane	X-axis
LTE Band 26	Y-plane	Z-axis

#### CDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	ERP	476 to 684	476, 580, 684	1xRTT
-	Frequency Stability	476 to 684	580	1xRTT
-	Occupied Bandwidth	476 to 684	476, 580, 684	1xRTT
-	Emission Mask	476 to 684	476, 580, 684	1xRTT
-	Conducted Emission	476 to 684	580	1xRTT
-	Radiated Emission	476 to 684	580	1xRTT

## LTE Band 26

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	26697 to 26783	26697, 26740, 26783	1.4 MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		26705 to 26775	26705, 26740, 26775	3 MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		26715 to 26765	26715, 26740, 26765	5 MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		26740	26740	10 MHz	QPSK, 16QAM	1 RB / 24 RB Offset
-	Frequency Stability	26697 to 26783	26740	1.4 MHz	QPSK	1 RB / 2 RB Offset
		26705 to 26775	26740	3 MHz	QPSK	1 RB / 7 RB Offset
		26715 to 26765	26740	5 MHz	QPSK	1 RB / 12 RB Offset
		26740	26740	10 MHz	QPSK	1 RB / 24 RB Offset
-	Occupied Bandwidth	26697 to 26783	26697, 26740, 26783	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		26740	26740	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Emission Mask	26697 to 26783	26697, 26740, 26783	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		26740	26740	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Conducted Emission	26697 to 26783	26740	1.4 MHz	QPSK	1 RB / 2 RB Offset
		26705 to 26775	26740	3 MHz	QPSK	1 RB / 7 RB Offset
		26715 to 26765	26740	5 MHz	QPSK	1 RB / 12 RB Offset
		26740	26740	10 MHz	QPSK	1 RB / 24 RB Offset
-	Radiated Emission	26740	26740	10 MHz	QPSK	1 RB / 49 RB Offset

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

### Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP	25 deg. C, 65 % RH	3.8 Vdc	Howard Kao
Frequency Stability	25 deg. C, 65 % RH	3.8 Vdc	Howard Kao
Occupied Bandwidth	25 deg. C, 65 % RH	3.8 Vdc	Howard Kao
Band Edge	25 deg. C, 65 % RH	3.8 Vdc	Howard Kao
Peak to Average Ratio	25 deg. C, 65 % RH	3.8 Vdc	Howard Kao
Condcudeted Emission	25 deg. C, 65 % RH	3.8 Vdc	Howard Kao
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao

### 3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 90**

**ANSI/TIA/EIA-603-C 2004**

**NOTE:** All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 100 watts e.r.p.

#### 4.1.2 Test Procedures

##### **EIRP / ERP Measurement:**


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5 MHz for CDMA and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ . E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$ .

##### **Conducted Power Measurement:**

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

#### 4.1.3 Test Setup

##### EIRP / ERP Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

##### Conducted Power Measurement:



#### 4.1.4 Test Results

##### Conducted Output Power (dBm)

Band	CDMA		
Channel	476	580	684
Frequency (MHz)	817.9	820.5	823.1
RC1+SO55	24.19	24.24	24.18
RC3+SO55	24.24	24.29	24.22
RC3+SO32(+ F-SCH)	24.18	24.22	24.16
RC3+SO32(+SCH)	24.16	24.21	24.15
RC1+SO3, 1/8 Rate	24.23	24.26	24.19
RTAP 153.6	24.07	24.11	24.05
RETAP 4096	24.10	24.14	24.08

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 26697	Mid Ch 26740	High Ch 26783		Low Ch 26697	Mid Ch 26740	High Ch 26783	
			814.7 MHz	819.0 MHz	823.3 MHz		814.7 MHz	819.0 MHz	823.3 MHz	
26 / 1.4M	1	0	22.76	23.18	22.79	0	21.70	22.10	21.71	1
	1	2	23.04	22.99	22.60	0	21.98	21.91	21.52	1
	1	5	22.81	22.91	22.52	0	21.75	21.83	21.44	1
	3	0	21.97	22.13	21.74	0	20.91	21.05	20.66	1
	3	1	21.84	22.16	21.77	0	20.88	21.08	20.69	1
	3	3	21.90	22.03	21.64	0	20.84	20.95	20.56	1
	6	0	21.93	22.13	21.74	1	20.87	21.05	20.66	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 26705	Mid Ch 26740	High Ch 26775		Low Ch 26705	Mid Ch 26740	High Ch 26775	
			815.5 MHz	819.0 MHz	822.5 MHz		815.5 MHz	819.0 MHz	822.5 MHz	
26 / 3M	1	0	22.87	23.28	22.89	0	21.81	22.20	21.81	1
	1	7	23.15	23.09	22.70	0	22.09	22.01	21.62	1
	1	14	22.92	23.01	22.62	0	21.86	21.93	21.54	1
	8	0	22.08	22.23	21.84	1	21.02	21.15	20.76	2
	8	3	21.95	22.26	21.87	1	20.89	21.18	20.79	2
	8	7	21.91	22.13	21.74	1	20.85	21.05	20.66	2
	15	0	22.04	22.23	21.84	1	20.98	21.15	20.76	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 26715	Mid Ch 26740	High Ch 26765		Low Ch 26715	Mid Ch 26740	High Ch 26765	
			816.5 MHz	819.0 MHz	821.5 MHz		816.5 MHz	819.0 MHz	821.5 MHz	
26 / 5M	1	0	22.93	23.37	22.98	0	21.87	22.29	21.90	1
	1	12	23.21	23.18	22.79	0	22.15	22.10	21.71	1
	1	24	22.98	23.10	22.71	0	21.92	22.02	21.63	1
	12	0	22.14	22.32	21.93	1	21.08	21.24	20.85	2
	12	6	22.01	22.35	21.96	1	20.95	21.27	20.88	2
	12	13	21.97	22.22	21.83	1	20.91	21.14	20.75	2
	25	0	22.10	22.32	21.93	1	21.04	21.24	20.85	2

Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)
			Mid Ch 26740		Mid Ch 26740	
			819.0 MHz		819.0 MHz	
26 / 10M	1	0	23.03	0	21.97	1
	1	24	23.31	0	22.25	1
	1	49	23.08	0	22.02	1
	25	0	22.24	1	21.18	2
	25	12	22.11	1	21.05	2
	25	25	22.07	1	21.01	2
	50	0	22.20	1	21.14	2

## ERP Power (dBm)

CDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	476	817.9	-8.97	31.208	20.09	102.05	H
	580	820.5	-8.99	31.3	20.16	103.75	
	684	823.1	-8.99	31.222	20.08	101.91	
	476	817.9	-19.11	31.504	10.24	10.58	V
	580	820.5	-18.14	31.117	10.83	12.10	
	684	823.1	-19.20	31.922	10.57	11.41	

LTE Band 26							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	26697	814.7	-9.03	31.208	20.03	100.65	H
	26740	819.0	-8.50	31.3	20.65	116.14	
	26783	823.3	-8.46	31.222	20.61	115.13	
	26697	814.7	-19.11	31.504	10.24	10.58	V
	26740	819.0	-17.99	31.117	10.98	12.52	
	26783	823.3	-18.88	31.922	10.89	12.28	
Channel Bandwidth: 1.4 MHz / 16QAM							
Y	26697	814.7	-9.40	31.208	19.66	92.43	H
	26740	819.0	-9.46	31.3	19.69	93.11	
	26783	823.3	-9.23	31.222	19.84	96.43	
	26697	814.7	-19.99	31.504	9.36	8.64	V
	26740	819.0	-19.88	31.117	9.09	8.10	
	26783	823.3	-19.85	31.922	9.92	9.82	



LTE Band 26							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	26705	815.5	-8.60	31.208	20.46	111.12	H
	26740	819.0	-8.27	31.3	20.88	122.46	
	26775	822.5	-8.25	31.222	20.82	120.84	
	26705	815.5	-18.90	31.504	10.45	11.10	V
	26740	819.0	-18.67	31.117	10.30	10.71	
	26775	822.5	-19.46	31.922	10.31	10.74	
Channel Bandwidth: 3 MHz / 16QAM							
Y	26705	815.5	-9.72	31.208	19.34	85.86	H
	26740	819.0	-9.47	31.3	19.68	92.90	
	26775	822.5	-9.10	31.222	19.97	99.36	
	26705	815.5	-20.03	31.504	9.32	8.56	V
	26740	819.0	-19.28	31.117	9.69	9.30	
	26775	822.5	-20.49	31.922	9.28	8.48	

LTE Band 26							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	26715	816.5	-8.85	31.208	20.21	104.91	H
	26740	819.0	-8.39	31.3	20.76	119.12	
	26765	821.5	-8.16	31.222	20.91	123.37	
	26715	816.5	-18.92	31.504	10.43	11.05	V
	26740	819.0	-18.78	31.117	10.19	10.44	
	26765	821.5	-19.38	31.922	10.39	10.94	
Channel Bandwidth: 5 MHz / 16QAM							
Y	26715	816.5	-9.95	31.208	19.11	81.43	H
	26740	819.0	-9.33	31.3	19.82	95.94	
	26765	821.5	-9.12	31.222	19.95	98.90	
	26715	816.5	-19.97	31.504	9.38	8.68	V
	26740	819.0	-19.54	31.117	9.43	8.76	
	26765	821.5	-20.41	31.922	9.36	8.63	

LTE Band 26							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	26740	819.0	-9.13	31.3	20.02	100.46	H
	26740	819.0	-18.70	31.117	10.27	10.63	V
Channel Bandwidth: 10 MHz / 16QAM							
Y	26740	819.0	-9.44	31.3	19.71	93.54	H
	26740	819.0	-19.49	31.117	9.48	8.87	V

## 4.2 Frequency Stability Measurement

### 4.2.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

### 4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5$  °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 4.2.3 Test Setup



#### 4.2.4 Test Results

##### Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)					Limit (ppm)
	CDMA	LTE Band 26				
		1.4 MHz	3 MHz	5 MHz	10 MHz	
3.8	-0.004	0.004	0.002	0.003	0.003	2.5
3.3	-0.002	0.002	0.004	0.001	0.004	2.5
4.35	0.003	-0.004	0.004	0.005	0.001	2.5

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3 Vdc to 4.35 Vdc.

##### Frequency Error vs. Temperature


Temp. (°C)	Frequency Error (ppm)					Limit (ppm)
	CDMA	LTE Band 26				
		1.4 MHz	3 MHz	5 MHz	10 MHz	
-30	-0.004	0.003	0.003	0.003	0.004	2.5
-20	-0.002	0.002	0.002	0.002	0.001	2.5
-10	-0.003	0.004	0.005	0.005	0.005	2.5
0	0.002	0.005	0.007	0.004	0.007	2.5
10	0.004	-0.001	0.001	-0.004	0.001	2.5
20	0.005	-0.004	-0.004	-0.007	-0.004	2.5
30	0.003	-0.003	-0.007	-0.006	-0.003	2.5
40	0.002	-0.002	-0.005	-0.001	-0.007	2.5
50	-0.003	0.003	-0.001	-0.003	-0.002	2.5

### 4.3 Occupied Bandwidth Measurement

#### 4.3.1 Test Procedure


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

#### 4.3.2 Test Setup



### 4.3.3 Test Result

CDMA		
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)
476	817.9	1.2740
580	820.5	1.2788
684	823.1	1.2788



# LTE Band 26


## Channel Bandwidth: 1.4 MHz

## Channel Bandwidth: 3 MHz


Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
26697	814.7	1.0961	1.0913	26705	815.5	2.7300	2.7300
26740	819.0	1.0961	1.0913	26740	819.0	2.7300	2.7300
26783	823.3	1.0961	1.0913	26775	822.5	2.7300	2.7300

## Spectrum Plot of Worst Value


### 1.4 MHz / QPSK




### 1.4 MHz / 16QAM



### 3 MHz / QPSK



### 3 MHz / 16QAM



# LTE Band 26


## Channel Bandwidth: 5 MHz

## Channel Bandwidth: 10 MHz

Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
26715	816.5	4.5000	4.5000	26740	819.0	9.006	8.9743
26740	819.0	4.5000	4.5000				
26765	821.5	4.5000	4.5000				


## Spectrum Plot of Worst Value

### 5 MHz / QPSK




Date: 30.DEC.2015 17:00:07

### 5 MHz / 16QAM




Date: 30.DEC.2015 16:59:25

### 10 MHz / QPSK



Date: 30.DEC.2015 17:06:42

### 10 MHz / 16QAM



Date: 30.DEC.2015 17:06:29




## 4.4 Emission Mask Measurement

### 4.4.1 Limits of Band Edge Measurement

According to FCC part 90.691 shall be tested the emission mask. For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116 \log_{10}(f/6.1)$  decibels or  $50 + 10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.




### 4.4.2 Test Setup




### 4.4.3 Test Procedures

- The measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Record the test plot.

#### 4.4.4 Test Results






# LTE Band 26

Channel Bandwidth: 5 MHz / QPSK



Channel Bandwidth: 5 MHz / 16QAM






## 4.5 Conducted Spurious Emissions

### 4.5.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission is equal to -13dBm.

### 4.5.2 Test Setup




### 4.5.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 9 GHz. 10 dB attenuation pad is connected with spectrum. RBW=1 MHz and VBW=3 MHz are used for conducted emission measurement.


#### 4.5.4 Test Results

Frequency Range: 30 MHz ~ 8 GHz




# LTE Band 26 Channel 26740

## Channel Bandwidth: 1.4 MHz




Date: 30.DEC.2015 16:35:58

## Channel Bandwidth: 3 MHz




Date: 30.DEC.2015 16:51:15

## Channel Bandwidth: 5 MHz



Date: 30.DEC.2015 17:01:33

## Channel Bandwidth: 10 MHz



Date: 30.DEC.2015 17:07:54



## 4.6 Radiated Emission Measurement

### 4.6.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission is equal to -13 dBm.

### 4.6.2 Test Procedure


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}.$

**NOTE:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

### 4.6.3 Deviation from Test Standard

No deviation.

### 4.6.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.6.5 Test Results


##### CDMA:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1  
Condition: PART 90 3m Horizontal  
Remark : BC 10\_Link\_CH580  
Tested by: Charles Hsiao  
Plane : X


			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	119.10	-49.82	-41.50	-13.00	-36.82	-8.32	Peak
2	158.52	-56.98	-49.26	-13.00	-43.98	-7.72	Peak
3	213.87	-50.30	-44.31	-13.00	-37.30	-5.99	Peak
4	302.10	-58.84	-52.91	-13.00	-45.84	-5.93	Peak
5	388.20	-64.70	-61.34	-13.00	-51.70	-3.36	Peak
6	660.50	-68.06	-67.87	-13.00	-55.06	-0.19	Peak
7	1641.00	-57.67	-65.40	-13.00	-44.67	7.73	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1  
Condition: PART 90 3m Vertical  
Remark : BC 10\_Link\_CH580  
Tested by: Charles Hsiao  
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	35.67	-53.36	-42.64	-13.00	-40.36	-10.72	Peak
2	119.64	-56.15	-47.83	-13.00	-43.15	-8.32	Peak
3	280.02	-56.51	-50.73	-13.00	-43.51	-5.78	Peak
4	321.70	-64.39	-58.69	-13.00	-51.39	-5.70	Peak
5	388.20	-67.17	-63.81	-13.00	-54.17	-3.36	Peak
6	659.80	-68.62	-68.44	-13.00	-55.62	-0.18	Peak
7	1641.00	-57.77	-65.50	-13.00	-44.77	7.73	Peak

# LTE Band 26

Channel Bandwidth: 10 MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2015-12-29



Site : 966 chamber 1  
Condition: PART 90 3m Horizontal  
Remark : LTE\_Band 26\_QPSK(1,24)\_10M\_CH26740  
Tested by: Charles Hsiao  
Plane : Z

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	pp	118.29	-49.04	-40.66	-13.00	-36.04	-8.38 Peak
2		152.31	-57.13	-49.24	-13.00	-44.13	-7.89 Peak
3		207.66	-50.09	-44.01	-13.00	-37.09	-6.08 Peak
4		318.90	-64.01	-58.27	-13.00	-51.01	-5.74 Peak
5		547.10	-70.91	-69.04	-13.00	-57.91	-1.87 Peak
6		684.30	-68.60	-68.30	-13.00	-55.60	-0.30 Peak
7		1638.00	-56.58	-64.14	-13.00	-43.58	7.56 Peak




# Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-12-29



Site : 966 chamber 1  
 Condition: PART 90 3m Vertical  
 Remark : LTE\_Band 26\_QPSK(1,24)\_10M\_CH26740  
 Tested by: Charles Hsiao  
 Plane : Z

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	37.29	-50.51	-40.54	-13.00	-37.51	-9.97	Peak
2	118.56	-53.87	-45.49	-13.00	-40.87	-8.38	Peak
3	277.32	-54.91	-49.15	-13.00	-41.91	-5.76	Peak
4	307.70	-63.49	-57.62	-13.00	-50.49	-5.87	Peak
5	367.20	-65.94	-61.49	-13.00	-52.94	-4.45	Peak
6	589.80	-68.99	-68.98	-13.00	-55.99	-0.01	Peak
7	1638.00	-57.57	-65.13	-13.00	-44.57	7.56	Peak

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---